

CETECOM™

CETECOM ICT Services
consulting - testing - certification >>>

TEST REPORT

Test report no.: 1-4254/12-04-05



Deutsche
Akkreditierungsstelle
D-PL-12076-01-01

Testing laboratory

CETECOM ICT Services GmbH
Untertuerkheimer Strasse 6 – 10
66117 Saarbruecken / Germany
Phone: + 49 681 5 98 - 0
Fax: + 49 681 5 98 - 9075
Internet: <http://www.cetecom.com>
e-mail: ict@cetecom.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2005) by the Deutsche Akkreditierungsstelle GmbH (DAkkS). The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12076-01-01
Area of Testing: Radio/Satellite Communications

Applicant

Sony Ericsson Mobile Communications AB
Nya Vattentornet
22188 Lund / SWEDEN
Phone: +46 46 19 30 00
Fax: +46 46 19 32 95
Contact: Håkan Sjöberg
e-mail: hakan.sjoberg@sonyericsson.com
Phone: +46 46 19 35 59

Manufacturer

Sony Ericsson Mobile Communications AB
Nya Vattentornet
22188 Lund / SWEDEN

Test standard/s

47 CFR Part 27 Title 47 of the Code of Federal Regulations; Chapter I
Part 27 - Miscellaneous Wireless Communications Service
RSS - 139 Issue 2 Advanced Wireless Services Equipment Operating in the Bands 1710-1755 MHz
and 2110-2155 MHz

For further applied test standards please refer to section 3 of this test report.


Test Item

Kind of test item: GSM Mobile Phone 850/900/1800/1900; GPRS/EGPRS; UMTS FDDI/FDDII/FDDV; HSPA; LTE Band 4/17; BT EDR; WLAN b/g/n; ANT+; GPS; HDMI; RFID
Model name: AAL-8880001-BV
FCC ID: PY7A8880001
IC: 4170B-A8880001
Frequency [MHz]: LTE: 706.50 MHz – 713.50 MHz
Technology tested: LTE
Antenna: Integrated antenna
Power Supply: 3.70 V DC by Li-Ion Battery and Power Supply
Temperature Range: -30°C to +60 °C

Test report authorised:


2012-01-26 Stefan Bös
Senior Testing Manager

Test performed:


2012-01-26 Jakob Reschke
Testing Manager

1 Table of contents	
1	Table of contents2
2	General information3
2.1	Notes and disclaimer3
2.2	Application details.....3
3	Test standard/s3
4	Test environment.....4
5	Test item4
6	Test laboratories sub-contracted4
7	Additional comments4
8	Summary of measurement results5
8.1	LTE – Band 175
8.2	Receiver.....5
9	RF measurements6
9.1	Description of test setup6
9.1.1	Radiated measurements.....6
9.1.2	Conducted measurements.....7
9.2	RSP100 test report cover sheet / performance test data8
9.3	LTE technologies supported by EUT9
9.4	Results LTE – Band 1710
9.4.1	RF output power10
9.4.2	Frequency stability.....13
9.4.3	Spurious emissions radiated16
9.4.4	Spurious emissions conducted.....23
9.4.5	Block edge compliance.....34
9.4.6	Occupied bandwidth39
9.5	Results receiver mode45
9.5.1	Spurious emissions radiated – receiver mode45
10	Test equipment and ancillaries used for tests50
11	Observations51
Annex A	Document history52
Annex B	Further information.....52
Annex C	Accreditation Certificate53

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM ICT Services GmbH.

The testing service provided by CETECOM ICT Services GmbH has been rendered under the current "General Terms and Conditions for CETECOM ICT Services GmbH".

CETECOM ICT Services GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CETECOM ICT Services GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CETECOM ICT Services GmbH test report include or imply any product or service warranties from CETECOM ICT Services GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CETECOM ICT Services GmbH.

All rights and remedies regarding vendor's products and services for which CETECOM ICT Services GmbH has prepared this test report shall be provided by the party offering such products or services and not by CETECOM ICT Services GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

2.2 Application details

Date of receipt of order:	2012-01-10
Date of receipt of test item:	2012-01-02
Start of test:	2012-01-02
End of test:	2012-01-19
Person(s) present during the test:	-/-

3 Test standard/s

Test standard	Date	Test standard description
47 CFR Part 27	2010-10	Title 47 of the Code of Federal Regulations; Chapter I Part 27 - Miscellaneous Wireless Communications Service
RSS - 139 Issue 2	2009-02	Advanced Wireless Services Equipment Operating in the Bands 1710-1755 MHz and 2110-2155 MHz

4 Test environment

Temperature:	T_{nom}	+22 °C during room temperature tests
	T_{max}	+60 °C during high temperature tests
	T_{min}	-30 °C during low temperature tests
Relative humidity content:		49 %
Barometric pressure:		not relevant for this kind of testing
Power supply:	V_{nom}	3.70 V DC by Li-Ion Battery and Power Supply
	V_{max}	4.40 V
	V_{min}	3.30 V

5 Test item

Kind of test item	:	GSM Mobile Phone 850/900/1800/1900; GPRS/EGPRS; UMTS FDDI/FDDII/FDDV; HSPA; LTE Band 4/17; BT EDR; WLAN b/g/n; ANT+; GPS; HDMI; RFID
Type identification	:	AAL-8880001-BV
S/N serial number	:	Rad. CB5A1JE2R3 Cond. CB5A1JE2S3
HW hardware status	:	AP2
SW software status	:	6.0.C.0.257, 6.0.C.0.243 s_atp_aoba_0_0_22
Frequency band [MHz]	:	LTE: 706.50 MHz – 713.50 MHz
Type of modulation	:	QPSK; 16-QAM
Antenna	:	Integrated antenna
Power supply	:	3.70 V DC by Li-Ion Battery and Power Supply
Temperature range	:	-30°C to +60 °C

6 Test laboratories sub-contracted

None

7 Additional comments

Conducted tests performed by Jakob Reschke
Radiated tests performed by Andreas Luckenbill

8 Summary of measurement results

- No deviations from the technical specifications were ascertained
- There were deviations from the technical specifications ascertained

TC identifier	Description	verdict	date	Remark
RF-Testing	CFR Part 27 RSS 139	passed	2012-01-26	-/-

8.1 LTE – Band 17

Test Case	temperature conditions	power source voltages	Pass	Fail	NA	NP	Remark
RF Output Power	Nominal	Nominal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Not rated
Frequency Stability	Nominal	Nominal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Not rated
Spurious Emissions Radiated	Nominal	Nominal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Not rated
Spurious Emissions Conducted	Nominal	Nominal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Not rated
Block Edge Compliance	Nominal	Nominal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Not rated
Occupied Bandwidth	Nominal	Nominal	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Not rated

Note:

NA = Not applicable; NP = Not performed

8.2 Receiver

Test Case	temperature conditions	power source voltages	Pass	Fail	NA	NP	Remark
Spurious Emissions Radiated	Nominal	Nominal	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	

Note:

NA = Not applicable; NP = Not performed

9 RF measurements


9.1 Description of test setup

For the spurious measurements we use the substitution method according TIA/EIA 603.

9.1.1 Radiated measurements

The radiated emissions from the EUT are performed in a semi anechoic chamber. The EUT is placed on a conductive turntable and powered with nominal voltage. The signalling is performed either from outside the chamber with a signalling unit (AP or other) by air link using a signalling antenna or directly by special test software from the customer.

Semi anechoic chamber




Picture 1: Diagram radiated measurements

9 kHz - 30 MHz:	active loop antenna
30 MHz – 1 GHz:	tri-log antenna
> 1 GHz:	horn antenna

9.1.2 Conducted measurements

The EUT's RF signal is coupled out by the antenna connector which is supplied by the manufacturer. The signal is first 10dB attenuated before it is power divided (~6dB loss per branch). One of the signal paths is connected to the signalling unit (AP or other), the other one is connected to the spectrum analyzer. The specific losses for both signal paths are first checked within a calibration. The measurement readings on the signalling unit/spectrum analyzer are corrected by the specific test set-up loss. The attenuator, power divider, signalling unit and the spectrum analyzer are impedance matched on 50 Ohm. If special software is used, there is no power divider necessary.



Picture 2: Diagram conducted measurements

The term measuring receiver refers to either a selective voltmeter or a spectrum analyser.

Frequency being measured f	Measuring receiver bandwidth 6 dB	Spectrum analyser bandwidth 3dB
$f < 150 \text{ kHz}$	200 Hz or	300 Hz
$150 \text{ kHz} \leq f < 25 \text{ MHz}$	9 kHz or	10 kHz
$25 \text{ MHz} \leq f < 1000 \text{ MHz}$	120 kHz or	100 kHz
$1000 \text{ MHz} \leq f$		1 MHz
NOTE: Specific requirements in CEPT/ERC/Recommendation 70-03 [2] shall be applied where applicable.		

9.2 RSP100 test report cover sheet / performance test data

Test Report Number	:	1-4254/12-04-05				
Equipment Model Number	:	AAL-8880001-BV				
Certification Number	:	4170B-A8880001				
Manufacturer (complete Address)	:	Sony Ericsson Mobile Communications AB Nya Vattentornet 22188 Lund / SWEDEN				
Tested to radio standards specification no.	:	RSS - 139 Issue 2				
Open Area Test Site IC No.	:	IC 3462C-1				
Frequency Range	:	LTE: 706.50 MHz – 713.50 MHz				
GPS receiver turned	:	On				
RF-power [dBm] (max.)	:	Band	Channel bandwidth	Conducted [dBm]	ERP / EIRP [dBm]	Mode
				24.0		QPSK
		LTE – Band 17	5	23.0		16-QAM
				22.9		QPSK
Occupied bandwidth (99%-BW) [kHz]	:	Band	Channel bandwidth	Conducted [dBm]	ERP / EIRP [dBm]	Mode
				23.1		16-QAM
		LTE – Band 17	5	4489		QPSK
				4489		16-QAM
10	8958		QPSK			
	8928		16-QAM			
Type of modulation	:	QPSK; 16-QAM				
Emission Designator (TRC-43)	:	Band	Channel bandwidth	Conducted [dBm]	ERP / EIRP [dBm]	Mode
				4M49G7D		QPSK
		LTE – Band 17	5	4M49W7D		16-QAM
				8M96G7D		QPSK
10	8M93W7D		16-QAM			
	Antenna Information	:	integrated antenna			
Transmitter Spurious (worst case) [dBm]	:	-45 dBm (noise floor)				
Receiver Spurious (worst case) [μ V/m @ 10m]	:	25.4 μ V/m @ 265.51 MHz				

ATTESTATION:

DECLARATION OF COMPLIANCE:

I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned Industry Canada standard(s); and that the equipment identified in this application has been subjected to all the applicable test conditions specified in the Industry Canada standards and all of the requirements of the standard have been met.

Laboratory Manager:

2012-01-26
Date

Jakob Reschke
Name



Signature

9.3 LTE technologies supported by EUT

Channel bandwidth

	Band 17
[MHz]	
1.4	<input type="checkbox"/>
3	<input type="checkbox"/>
5	<input checked="" type="checkbox"/>
10	<input checked="" type="checkbox"/>
15	<input type="checkbox"/>
20	<input type="checkbox"/>

Antenna

SISO	<input checked="" type="checkbox"/>
SIMO	<input type="checkbox"/>
MISO	<input type="checkbox"/>
MIMO	<input type="checkbox"/>

9.4 Results LTE – Band 17

The EUT was set to transmit the maximum power.

9.4.1 RF output power

Description:

This paragraph contains average power, peak output power and EIRP measurements for the mobile station. In all cases, the peak output power is within the required mask (this mask is specified in the JTC standards, TIA PN3389 Vol. 1 Chap 7, and is no FCC requirement).

Measurement:

The mobile was set up for the maximum output power with pseudo random data modulation.

To determine the Peak-To-Average Power Ratio (PAPR) the measurement was performed with the Power Complementary Cumulative Distribution Function (CCDF).

Measurement parameters	
Detector:	Peak and RMS (Power in Burst)
Sweep time:	Auto
Video bandwidth:	Depends on Channel Bandwidth
Resolution bandwidth:	Depends on Channel Bandwidth
Span:	Zero Span
Trace-Mode:	Max Hold

Limits:

FCC	IC
CFR Part 27.53 CFR Part 2.1046	RSS 139, Issue 2, Section 6.4
Nominal Peak Output Power	
+33.00 dBm	
In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	

Results:

Output Power (conducted)						
Bandwidth (MHz)	Frequency (MHz)	Resource block allocation	Average Output Power (dBm)	Peak to Average Ratio (dB)	Average Output Power (dBm)	Peak to Average Ratio (dB)
			QPSK		16-QAM	
5	706.5	1 RB low	23.9	4.6	22.9	5.7
		1 RB high	24.0	4.0	22.9	5.1
		50% RB mid	22.8	5.3	21.8	6.6
		100% RB	22.9	5.6	22.4	6.3
	710.0	1 RB low	24.0	4.1	23.0	5.1
		1 RB high	24.0	4.4	22.9	5.5
		50% RB mid	22.9	5.1	21.8	6.4
		100% RB	22.9	5.8	22.4	6.5
	713.5	1 RB low	22.4	5.1	22.6	5.6
		1 RB high	22.8	5.0	22.5	5.7
		50% RB mid	22.8	5.9	21.6	7.0
		100% RB	22.7	6.0	22.2	7.1
10	709.0	1 RB low	22.8	4.7	22.6	6.0
		1 RB high	22.9	4.6	22.5	5.9
		50% RB mid	22.8	5.3	22.1	6.2
		100% RB	22.8	6.0	22.1	6.8
	710.0	1 RB low	22.4	3.6	22.5	5.8
		1 RB high	22.6	4.7	22.6	5.9
		50% RB mid	22.8	5.4	22.1	6.3
		100% RB	22.7	6.1	22.0	6.8
	711.0	1 RB low	23.0	2.3	23.1	5.0
		1 RB high	22.5	5.2	23.0	5.4
		50% RB mid	22.8	5.5	21.9	6.4
		100% RB	22.8	6.0	21.9	6.9
Measurement uncertainty			± 0.5 dB			

The output power was measured with the lowest supported channel bandwidth and with the number of resource blocks where the highest output power conducted was found.

All other bandwidths were calculated with the corresponding antenna gain (with full resource blocks).

Output Power (radiated)			
Bandwidth (MHz)	Frequency (MHz)	Average Output Power (dBm)	Average Output Power (dBm)
		QPSK	16-QAM
5	706.5	21.82	20.72
	710.0	21.60	20.60
	713.5	20.62	20.52
10	709.0	20.72*	20.42*
	710.0	20.40*	20.20*
	711.0	20.92*	21.02*
Measurement uncertainty		± 3.0 dB	

*) calculated with antenna gain

Result: The result of the measurement is passed.

9.4.2 Frequency stability

Description:

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the mobile station in a “call mode”. This is accomplished with the use of a R&S CMU200 DIGITAL RADIOCOMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the mobile station to overnight soak at -30 C.
3. With the mobile station, powered with V_{nom} , connected to the CMU200 and in a simulated call on channel 1412 (centre channel), measure the carrier frequency. These measurements should be made within two minutes of powering up the mobile station, to prevent significant self warming.
4. Repeat the above measurements at 10°C increments from -30°C to +60°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with V_{nom} . Vary supply voltage from V_{min} to V_{max} , in 0.1 Volt steps remeasuring carrier frequency at each voltage. Pause at V_{nom} for 1.5 hours unpowered, to allow any self heating to stabilize, before continuing.
6. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

This measurement was performed with the highest channel bandwidth supported from the EUT on the middle channel

Measurement:

Measurement parameters	
Detector:	Measured with CMU200
Sweep time:	
Video bandwidth:	
Resolution bandwidth:	
Span:	
Trace-Mode:	

Limits:



FCC	IC
CFR Part 27.54 CFR Part 2.1055	RSS 139, Issue 2, Section 6.3
Frequency Stability	
< 2.5 ppm	

Results:**FREQ ERROR versus VOLTAGE**

Voltage (V)	Frequency Error (Hz)	Frequency Error (%)	Frequency Error (ppm)
3.3	8	0.00000113	0.0113
3.4	7	0.00000099	0.0099
3.5	7	0.00000099	0.0099
3.6	6	0.00000085	0.0085
3.7	4	0.00000056	0.0056
3.8	3	0.00000042	0.0042
3.9	4	0.00000056	0.0056
4.0	6	0.00000085	0.0085
4.1	5	0.00000070	0.0070
4.2	5	0.00000070	0.0070
4.3	4	0.00000056	0.0056
4.4	5	0.00000070	0.0070

FREQ ERROR versus TEMPERATURE

Temperature (°C)	Frequency Error (Hz)	Frequency Error (%)	Frequency Error (ppm)
-30	9	0.00000127	0.0127
-20	7	0.00000099	0.0099
-10	8	0.00000113	0.0113
± 0	6	0.00000085	0.0085
10	5	0.00000070	0.0070
20	4	0.00000056	0.0056
30	6	0.00000085	0.0085
40	6	0.00000085	0.0085
50	8	0.00000113	0.0113
60	10	0.00000141	0.0141



Result: The result of the measurement is passed.

9.4.3 Spurious emissions radiated

Description:

The following steps outline the procedure used to measure the radiated emissions from the mobile station. The site is constructed in accordance with ANSI C63.4:2009 requirements and is recognized by the FCC to be in compliance for a 3 and a 10 meter site. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 746 MHz. This was rounded up to 12 GHz. The resolution bandwidth is set as outlined in Part 27.53. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE band 4.

The final open field emission (here 10m semi-anechoic chamber listed by FCC) test procedure is as follows:

- a) The test item was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna.
- b) The antenna output was terminated in a 50 ohm load (if possible).
- c) A double ridged wave guide antenna was placed on an adjustable height antenna mast 3 meters from the test item for emission measurements.
- d) Detected emissions were maximized at each frequency by rotating the test item and adjusting the receive antenna height and polarization. The maximum meter reading was recorded. The radiated emission measurements of the harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1 MHz bandwidth. If the harmonic could not be detected above the noise floor, the ambient level was recorded. The equivalent power into a dipole antenna was calculated from the field intensity levels measured at 3 meters.
- e) Now each detected emissions were substituted by the substitution method, in accordance with the TIA/EIA 603 .

Measurement:

Measurement parameters	
Detector:	Peak
Sweep time:	2 sec.
Video bandwidth:	Below 1 GHz: 100 kHz Above 1 GHz: 1 MHz
Resolution bandwidth:	Below 1 GHz: 100 kHz Above 1 GHz: 1 MHz
Span:	100 MHz Steps
Trace-Mode:	Max Hold

Limits:

FCC	IC
CFR Part 27.53(g) CFR Part 2.1053	RSS 139, Issue 2, Section 6.5
Spurious Emissions Radiated	
Attenuation $\geq 43 + 10\log(P)$ (P, Power in Watts)	
-13 dBm	

Results:

Radiated emissions measurements were made only at the upper, center, and lower carrier frequencies of the LTE band 17 (706.5 MHz, 710.0 MHz and 713.5 MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the LTE band 17 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

The final open field radiated levels are presented on the next pages. All measurements were done in horizontal and vertical polarization; the plots show the worst case. The plots show only the middle channel at the channel bandwidth and resource blocks with the highest output power. If spurious were detected, the lowest and highest channel and all supported channel bandwidths were checked, too.

As can be seen from this data, the emissions from the test item were within the specification limit.

QPSK

SPURIOUS EMISSION LEVEL [dBm]								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1413.0	-	2	1420.0	-	2	1427.0	-
3	2119.5	-	3	2130.0	-	3	2140.5	-
4	2826.0	-	4	2840.0	-	4	2854.0	-
5	3532.5	-	5	3550.0	-	5	3567.5	-
6	4239.0	-	6	4260.0	-	6	4281.0	-
7	4945.5	-	7	4970.0	-	7	4994.5	-
8	5652.0	-	8	5680.0	-	8	5708.0	-
9	6358.5	-	9	6390.0	-	9	6421.5	-
10	7065.0	-	10	7100.0	-	10	7135.0	-
Measurement uncertainty					± 3dB			


16-QAM

SPURIOUS EMISSION LEVEL [dBm]								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1413.0	-	2	1420.0	-	2	1427.0	-
3	2119.5	-	3	2130.0	-	3	2140.5	-
4	2826.0	-	4	2840.0	-	4	2854.0	-
5	3532.5	-	5	3550.0	-	5	3567.5	-
6	4239.0	-	6	4260.0	-	6	4281.0	-
7	4945.5	-	7	4970.0	-	7	4994.5	-
8	5652.0	-	8	5680.0	-	8	5708.0	-
9	6358.5	-	9	6390.0	-	9	6421.5	-
10	7065.0	-	10	7100.0	-	10	7135.0	-
Measurement uncertainty					± 3dB			


Result: The result of the measurement is passed.

QPSK with 5 MHz channel bandwidth


Plot 1: Channel 23790 (Traffic mode up to 30 MHz)



Plot 2: Channel 23790 (30 MHz - 1 GHz)




Plot 3: Channel 23790 (1 GHz – 12.75 GHz)




16-QAM with 5 MHz channel bandwidth


Plot 4: Channel 23790 (Traffic mode up to 30 MHz)



Plot 5: Channel 23790 (30 MHz - 1 GHz)



Plot 6: Channel 23790 (1 GHz – 12.75 GHz)



9.4.4 Spurious emissions conducted

Description:

The following steps outline the procedure used to measure the conducted emissions from the mobile station.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 7460 MHz, data taken from 10 MHz to 12 GHz.
2. Determine mobile station transmits frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

Measurement:

Measurement parameters	
Detector:	Peak
Sweep time:	Auto
Video bandwidth:	Pre-measurement with 1 MHz On spurious detection re-measurement below 1 GHz with 100 kHz Above 1 GHz with 1 MHz
Resolution bandwidth:	Pre-measurement with 1 MHz On spurious detection re-measurement below 1 GHz with 100 kHz Above 1 GHz with 1 MHz
Span:	10 MHz – 12 GHz
Trace-Mode:	Max Hold

Limits:

FCC	IC
CFR Part 27.53(g) CFR Part 2.1053	RSS 139, Issue 2, Section 6.5
Spurious Emissions Conducted	
Attenuation $\geq 43 + 10\log(P)$ (P, Power in Watts)	
-13 dBm	

Results: for 5 MHz channel bandwidth

QPSK

SPURIOUS EMISSION LEVEL [dBm]								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1413.0	-	2	1420.0	-	2	1427.0	-
3	2119.5	-	3	2130.0	-	3	2140.5	-
4	2826.0	-	4	2840.0	-	4	2854.0	-
5	3532.5	-	5	3550.0	-	5	3567.5	-
6	4239.0	-	6	4260.0	-	6	4281.0	-
7	4945.5	-	7	4970.0	-	7	4994.5	-
8	5652.0	-	8	5680.0	-	8	5708.0	-
9	6358.5	-	9	6390.0	-	9	6421.5	-
10	7065.0	-	10	7100.0	-	10	7135.0	-
Measurement uncertainty					± 0.5dB			

16-QAM

SPURIOUS EMISSION LEVEL [dBm]								
Harmonic	Ch. 23755 Freq. (MHz)	Level [dBm]	Harmonic	Ch. 23790 Freq. (MHz)	Level [dBm]	Harmonic	Ch. 23825 Freq. (MHz)	Level [dBm]
2	1413.0	-	2	1420.0	-	2	1427.0	-
3	2119.5	-	3	2130.0	-	3	2140.5	-
4	2826.0	-	4	2840.0	-	4	2854.0	-
5	3532.5	-	5	3550.0	-	5	3567.5	-
6	4239.0	-	6	4260.0	-	6	4281.0	-
7	4945.5	-	7	4970.0	-	7	4994.5	-
8	5652.0	-	8	5680.0	-	8	5708.0	-
9	6358.5	-	9	6390.0	-	9	6421.5	-
10	7065.0	-	10	7100.0	-	10	7135.0	-
Measurement uncertainty					± 0.5dB			

Results: for 10 MHz channel bandwidth

QPSK

SPURIOUS EMISSION LEVEL [dBm]								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1418.0	-	2	1420.0	-	2	1422.0	-
3	2127.0	-	3	2130.0	-	3	2133.0	-
4	2836.0	-	4	2840.0	-	4	2844.0	-
5	3545.0	-	5	3550.0	-	5	3555.0	-
6	4254.0	-	6	4260.0	-	6	4266.0	-
7	4963.0	-	7	4970.0	-	7	4977.0	-
8	5672.0	-	8	5680.0	-	8	5688.0	-
9	6381.0	-	9	6390.0	-	6	6399.0	-
10	7090.0	-	10	7100.0	-	10	7110	-
Measurement uncertainty					± 0.5dB			

16-QAM


SPURIOUS EMISSION LEVEL [dBm]								
Harmonic	Lowest channel Freq. (MHz)	Level [dBm]	Harmonic	Middle channel Freq. (MHz)	Level [dBm]	Harmonic	Highest channel Freq. (MHz)	Level [dBm]
2	1418.0	-	2	1420.0	-	2	1422.0	-
3	2127.0	-	3	2130.0	-	3	2133.0	-
4	2836.0	-	4	2840.0	-	4	2844.0	-
5	3545.0	-	5	3550.0	-	5	3555.0	-
6	4254.0	-	6	4260.0	-	6	4266.0	-
7	4963.0	-	7	4970.0	-	7	4977.0	-
8	5672.0	-	8	5680.0	-	8	5688.0	-
9	6381.0	-	9	6390.0	-	6	6399.0	-
10	7090.0	-	10	7100.0	-	10	7110	-
Measurement uncertainty					± 0.5dB			

Result: The result of the measurement is passed.


Results: for 5 MHz channel bandwidth

QPSK


Plot 1: Lowest Channel (10 MHz - 12 GHz)



Plot 2: Middle Channel (10 MHz - 12 GHz)




Plot 3: Highest Channel (10 MHz - 12 GHz)




16-QAM


Plot 4: Lowest Channel (10 MHz - 12 GHz)



Plot 5: Middle Channel (10 MHz - 12 GHz)




Plot 6: Highest Channel (10 MHz - 12 GHz)




Results: for 10 MHz channel bandwidth

QPSK


Plot 1: Lowest Channel (10 MHz - 12 GHz)



Plot 2: Middle Channel (10 MHz - 12 GHz)




Plot 3: Highest Channel (10 MHz - 12 GHz)




16-QAM


Plot 4: Lowest Channel (10 MHz - 12 GHz)



Plot 5: Middle Channel (10 MHz - 12 GHz)



Plot 6: Highest Channel (10 MHz - 12 GHz)



9.4.5 Block edge compliance

Description:

The spectrum at the band edges must comply with the spurious emissions limits.

Measurement:

Measurement parameters	
Detector:	RMS
Sweep time:	20 sec.
Video bandwidth:	30 kHz
Resolution bandwidth:	30 kHz
Span:	1 MHz
Trace-Mode:	Max Hold


Limits:

FCC	IC
CFR Part 27.53(h) CFR Part 2.1053	RSS 139, Issue 2, Section 6.5
Block Edge Compliance	
<p>Part 27.53 specifies that “the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.”</p> <p>However, in publication number 890810, The FCC Office of Engineering and Technology specified the following correction to the limits when a resolution bandwidth smaller than 1% of the emission bandwidth is used:</p> <p>“An alternative is to add an additional correction factor of 10 Log (RBW1/ RBW2) to the 43 +10 log(P) limit. RBW1 is the narrower measurement resolution bandwidth and RBW2 is either the 1% emissions bandwidth or 1 MHz.”</p> <p>When using a 30 kHz bandwidth, this yields a -2.2185 adjustment to the limit [10 log(30kHz/50kHz) = -2.2185]. When this adjustment is applied to the limit, the limit becomes -15.2185.</p>	
-15.22 dBm	


Result: The result of the measurement is passed.

Results: 5 MHz channel bandwidth


Plot 1: Lowest Channel- QPSK




Plot 2: Highest Channel- QPSK



Plot 3: Lowest Channel- 16-QAM




Plot 4: Highest Channel- 16-QAM




Results: 10 MHz channel bandwidth


Plot 1: Lowest Channel- QPSK




Plot 2: Highest Channel- QPSK



Plot 3: Lowest Channel– 16-QAM



Plot 4: Highest Channel– 16-QAM



9.4.6 Occupied bandwidth

Description:

Measurement of the occupied bandwidth of the transmitted signal.

Measurement:

Similar to conducted emissions, occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the mid frequencies of the LTE band 17 frequency band. The table below lists the measured 99% power and -26dBc occupied bandwidths. Spectrum analyzer plots are included on the following pages.

Part 27.53 requires a measurement bandwidth of at least 1% of the occupied bandwidth.

Measurement parameters	
Detector:	Peak
Sweep time:	Auto
Video bandwidth:	Depends on Channel Bandwidth
Resolution bandwidth:	Depends on Channel Bandwidth
Span:	Depends on Channel Bandwidth
Trace-Mode:	Max Hold

Limits:

FCC	IC
CFR Part 27.53(h) CFR Part 2.1049	RSS 139, Issue 2, Section 6.5
Occupied Bandwidth	
Spectrum must fall completely in the specified band	

Results:


Occupied Bandwidth - QPSK		
Bandwidth [MHz]	99% OBW (kHz)	-26 dBc BW (kHz)
5	4489	4910
10	8958	9439
Measurement uncertainty	± 100 kHz	

Occupied Bandwidth – 16-QAM		
Bandwidth [MHz]	99% OBW (kHz)	-26 dBc BW (kHz)
5	4489	4890
10	8928	9619
Measurement uncertainty	± 100 kHz	


Result: [The result of the measurement is passed.](#)

QPSK


Plot 1: 5 MHz (99% - OBW)




Plot 2: 5 MHz (-26 dBc BW)



Plot 3: 10 MHz (99% - OBW)




Plot 4: 10 MHz (-26 dBc BW)




16-QAM


Plot 1: 5 MHz (99% - OBW)




Plot 2: 5 MHz (-26 dBc BW)



Plot 3: 10 MHz (99% - OBW)



Plot 4: 10 MHz (-26 dBc BW)



9.5 Results receiver mode

9.5.1 Spurious emissions radiated – receiver mode

Description:

The measurement was performed in worst case. The EUT was not connected to the CMU 200. So the EUT performs a network search. In this mode all oscillators are active.

Measurement:

Measurement parameters	
Detector:	Below 1 GHz Peak / QuasiPeak Above 1 GHz Peak / Average
Sweep time:	2 sec
Video bandwidth:	Below 1 GHz 100 kHz Above 1 GHz 1 MHz
Resolution bandwidth:	1 MHz
Span:	100 MHz Steps
Trace-Mode:	Max Hold

Limits:


FCC		IC	
CFR Part 15.109 CFR Part 2.1053		RSS Gen, Issue 2, Section 4.10	
Spurious Emissions Radiated – Receiver Mode			
Frequency (MHz)	Field Strength (dB μ V/m)	Measurement distance (m)	
30 – 88	30.0	10	
88 - 216	33.5	10	
216 – 960	36.0	10	
Above 960	54.0	3	

Results:

SPURIOUS EMISSION LEVEL (dB μ V/m)		
Frequency (MHz)	Detector	Level (dB μ V/m)
No critical peaks found		
Measurement uncertainty		± 3 dB

Result: [The result of the measurement is passed.](#)

Plot 1: Receiver mode up to 30 MHz



Plot 2: Receiver mode (30 MHz - 1 GHz)


Common Information

EUT: AAL-8880001-BV
 Serial Number: CB5A1JE2PV
 Test Description: FCC part 15 B class B @ 10 m
 Operating Conditions: GSM idle, camera mode with HDMI out + charging
 Operator Name: Wolsdorfer
 Comment: AC: 115 V / 60 Hz

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
 Receiver: [ESCI 3]
 Level Unit: dBµV/m


Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB




Final Result 1

Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)	Comment
30.261172	23.4	1000.0	120.000	98.0	V	11.0	12.5	6.6	30.0	
102.166200	17.1	1000.0	120.000	113.0	V	283.0	11.7	16.4	33.5	
265.510350	28.1	1000.0	120.000	98.0	V	283.0	13.7	7.9	36.0	
519.230250	20.4	1000.0	120.000	170.0	H	-1.0	19.0	15.6	36.0	
709.742700	19.8	1000.0	120.000	98.0	H	11.0	22.7	16.2	36.0	
892.880850	22.6	1000.0	120.000	170.0	H	-2.0	25.1	13.4	36.0	

Plot 3: Receiver mode (1 GHz – 12.75 GHz)



Plot 4: Receiver mode (12 GHz – 25 GHz)



10 Test equipment and ancillaries used for tests

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, rf-generating and signalling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Labor/Item).

No.	Lab / Item	Equipment	Type	Manufact.	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	19	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	9107-3697	300001605	Ve	19.10.2010	19.10.2012
2	n. a.	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP Meßtechnik	2920A04590	300001041	Ve	12.01.2012	12.01.2015
3	n. a.	Temperature Test Chamber	VT 4002	Heraeus Voetsch	521/83761	300002326	Ve	20.09.2011	20.09.2013
4	n. a.	Signal Analyzer 20Hz-26,5GHz-150 to + 30 DBM	FSiQ26	R&S	835111/0004	300002678	Ve	04.11.2010	04.11.2012
5	n. a.	Wideband Radio Communication Tester	CMW500	R&S	102375	300004187_0		04.01.2011	
6	45	Switch-Unit	3488A	HP Meßtechnik	2719A14505	300000368	g		
7	50	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP Meßtechnik	2920A04466	300000580	ne		
8	n. a.	software	SPS_PHE 1.4f	Spitzberger & Spieß	B5981; 5D1081;B5979	300000210	ne		
9	n. a.	EMI Test Receiver	ESCI 1166.5950.03	R&S	100083	300003312	k	05.01.2011	05.01.2013
10	n. a.	Analyzer-Reference-System (Harmonics and Flicker)	ARS 16/1	SPS	A3509 07/0 0205	300003314	k	14.07.2011	14.07.2013
11	n. a.	Amplifier	JS42-00502650-28-5A	MITEQ	1084532	300003379	ev		
12	n. a.	Antenna Tower	Model 2175	ETS-LINDGREN	64762	300003745	izw		
13	n. a.	Positioning Controller	Model 2090	ETS-LINDGREN	64672	300003746	izw		
14	n. a.	Turntable Interface-Box	Model 105637	ETS-LINDGREN	44583	300003747	izw		
15	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	295	300003787	k	01.04.2010	01.04.2012
16	n. a.	Spectrum-Analyzer	FSU26	R&S	200809	300003874	k	10.01.2011	10.01.2013
17	n. a.	Isolating Transformer	RT5A	Grundig	8041	300001626	g		
18	n. a.	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP Meßtechnik	2818A03450	300001040	Ve	12.01.2012	12.01.2015
19	n. a.	Coaxial Attenuator 30dB/500W	8325	Bird	1530	300001595	ev		
20	n. a.	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	8812-3088	300001032	vik!	11.05.2011	11.05.2013
21	n. a.	Active Loop Antenna	6502	EMCO	2210	300001015	ne		
22	n. a.	Anechoic	FAC 3/5m	MWB / TDK	87400/02	300000996		23.03.2009	

		chamber							
23	Spec.A. 2_2e	System rack for EMI measurement solution	85900	HP I.V.	*	300000222	ne		
24	9	Artificial Mains 9 kHz to 30 MHz	ESH3-Z5	R&S	828576/020	300001210	Ve	06.01.2012	06.01.2014
25	n. a.	Relais Matrix	3488A	HP Meßtechnik	2719A15013	300001156	ne		
26	n. a.	Relais Matrix	PSU	R&S	890167/024	300001168	ne		
27	n. a.	Isolating Transformer	RT5A	Grundig	9242	300001263	ne		
28	n. a.	Three-Way Power Splitter, 50 Ohm	11850C	HP Meßtechnik		300000997	ne		
29	n. a.	Switch / Control Unit	3488A	HP	2605e08770	300001443	ne		
30	n. a.	Amplifier	js42-00502650-28-5a	Parzich GMBH	928979	300003143	ne		
31	n. a.	Band Reject filter	WRCG1855/1910-1835/1925-40/8SS	Wainwright	7	300003350	ev		
32	n. a.	Band Reject filter	WRCG2400/2483-2375/2505-50/10SS	Wainwright	11	300003351	ev		
33	n. a.	TILE-Software Emission	Quantum Change, Modell TILE-ICS/FULL	EMCO	none	300003451	ne		
34	n. a.	Highpass Filter	WHKX2.9/18G-12SS	Wainwright	1	300003492	ev		
35	n. a.	Highpass Filter	WHK1.1/15G-10SS	Wainwright	3	300003255	ev		
36	n. a.	Highpass Filter	WHKX7.0/18G-8SS	Wainwright	18	300003789	ne		
37	n. a.	PSA Spectrum Analyzer 3 Hz - 26.5 GHz	E4440A	Agilent Technologies	MY48250080	300003812	k	08.09.2010	08.09.2012
38	n. a.	MXG Microwave Analog Signal Generator	N5183A	Agilent Technologies	MY47420220	300003813	k	13.09.2010	13.09.2012
39	n. a.	RF Filter Section 9kHz - 1GHz	N9039A	Agilent Technologies	MY48260003	300003825	vkI!	08.09.2010	08.09.2012
40	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	371	300003854	vkI!	14.10.2011	14.10.2014

Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vkI!	Attention: extended calibration interval	*)	next calibration ordered / currently in progress
NK!	Attention: not calibrated		

11 Observations

No observations exceeding those reported with the single test cases have been made.

Annex A Document history

Version	Applied changes	Date of release
1.0	Initial release	2012-01-26

Annex B Further information**Glossary**

AVG	-	Average
DUT	-	Device under test
EMC	-	Electromagnetic Compatibility
EN	-	European Standard
EUT	-	Equipment under test
ETSI	-	European Telecommunications Standard Institute
FCC	-	Federal Communication Commission
FCC ID	-	Company Identifier at FCC
HW	-	Hardware
IC	-	Industry Canada
Inv. No.	-	Inventory number
N/A	-	Not applicable
PP	-	Positive peak
QP	-	Quasi peak
S/N	-	Serial number
SW	-	Software

Annex C Accreditation Certificate



Deutsche Akkreditierungsstelle GmbH
German Accreditation Body

Entrusted according to Section 8 subsection 1 AkkStelleG in connection with Section 1 subsection 1 AkkStelleGBV
Signatory to the Multilateral Agreements of EA, ILAC and IAF for Mutual Recognition



Accreditation

The Deutsche Akkreditierungsstelle GmbH (German Accreditation Body) attests that the testing laboratory

CETECOM ICT Services GmbH
Untertürkheimer Straße 6-10
66117 Saarbrücken

is competent under the terms of DIN EN ISO/IEC 17025:2005 to carry out tests in the following fields:

- Wired communications and DECT
- Acoustic
- Radio
- Short Range Devices (SRD)
- RFID
- WiMax and Richtfunk
- Mobile radio (GSM / DCS), Over the Air (OTA) Performance
- Electromagnetic Compatibility (EMC) incl. Automotive
- Product safety
- SAR and Hearing Aid Compatibility (HAC)
- Environmental simulation
- Smart Card Terminals
- Bluetooth
- Wi-Fi-Services

The accreditation certificate shall only apply in connection with the notice of accreditation of 13.04.2011 with the accreditation number D-PL-12076-01 and is valid until 03.09.2014. It comprises the cover sheet, the reverse side of the cover sheet and the following annex with a total of 82 pages.

Registration number of the certificate: D-PL-12076-01-01

Frankfurt am Main, 13.04.2011

[Signature]
Dipl.-Ing. (FH) J. Egner
Head of Division 2

This document is a translation. The definitive version is the original German accreditation certificate.
See notes on back.

Front side of certificate

Deutsche Akkreditierungsstelle GmbH

Office Berlin
Spittelmarkt 10
10117 Berlin

Office Frankfurt am Main
Gartenstraße 6
60594 Frankfurt am Main

Office Braunschweig
Bundesallee 100
38116 Braunschweig

The publication of extracts of the accreditation certificate is subject to the prior written approval by Deutsche Akkreditierungsstelle GmbH (DAkkS). Exempted is the unchanged form of separate disseminations of the cover sheet by the conformity assessment body mentioned overleaf.

No impression shall be made that the accreditation also extends to fields beyond the scope of accreditation attested by DAkkS.

The accreditation was granted pursuant to the Act on the Accreditation Body (AkkStelleG) of 31 July 2009 (Federal Law Gazette I p. 2625) and the Regulation (EC) No 765/2008 of the European Parliament and of the Council of 9 July 2008 setting out the requirements for accreditation and market surveillance relating to the marketing of products [Official Journal of the European Union L 218 of 9 July 2008, p. 30]. DAkkS is a signatory to the Multilateral Agreements for Mutual Recognition of the European co-operation for Accreditation (EA), International Accreditation Forum (IAF) and International Laboratory Accreditation Cooperation (ILAC). The signatories to these agreements recognise each other's accreditations.

The up-to-date state of membership can be retrieved from the following websites:
EA: www.european-accreditation.org
ILAC: www.ilac.org
IAF: www.iaf.eu

Back side of certificate

Note:
The current certificate including annex is published on our website (see link below) or may be received from CETECOM ICT Services on request.

http://www.cetecom.com/fileadmin/de/CETECOM_D_Saarbruecken/accreditations_Jan_2010/DAKKS_Akkredi_Urk_EN17025-En_incl_Annex.pdf