

Confidential MARKING DRAWING 1(3)

Prepared		Date	Rev	Doc no.
RT/SEM/CA/KA Sandy Smith		2005-07-06	С	1/151 86-DPY 101 1464 Uen
Approved	Checked			File
CA/KA (Lance Workman)				I:\2)Product_Information\3)Product_Specific_Information\Zc
				TA\FCC and TA\Z520a_Zoe850_15186_Marking_Drawing.c

1/151 86-DPY 101 1464 Marking Drawing For Z520a

Note: This marking drawing is applicable for both the 1464 and 1486 DPY's.

Type AAC-1052012-BV = Z520a

Label #1

The Label used for marking is defined in the Manufacturing Specification 1301-SVF 930 2389.


Label #2 (CE Logo)

The label used for marking is defined in the manufacturing specification 1301-SVF 9301427.

Placing Labels

The labels shall be placed on the back of the telephone according to the Assembly Drawing (151 88 KRH 101 220) for the KRH.

Print Layout (Label #1)



*Note: representative samples, text in image may not match required information for this product defined in table below.

Print Layout Label #2

CE Marking

C €0682



Confidential MARKING DRAWING 2(3)

				· · ·
Prepared		Date	Rev	Doc no.
RT/SEM/CA/KA Sandy Smith		2005-07-06	С	1/151 86-DPY 101 1464 Uen
Approved	Checked			File
CA/KA (Lance Workman)				l:\2)Product_Information\3)Product_Specific_Information\Zc
,				TA\FCC and TA\Z520a_Zoe850_15186_Marking_Drawing.c

Line	Text
1.	Sony Ericsson Trademark, Model Number
2.	Type Number, GHY1 Fields, 7 Digit Repair Code
3.	Country Approval Mark 1, Country Approval Mark 2
4.	IMEI-Numbers as Barcode
5.	IMEI-Numbers as characters
6.	Serial number as barecode
7.	Serial number as characters
8.	Prod/Repair wk as characters & Prod wk as barcode
9.	UPC numbers as barcode & UPC number as characters
10.	Reduced DPY number & r-state
11.	Marking of Origin
12.	CE Marking

Definitions

Sony Ericsson trademark	Sony Ericsson trademark shall be according to the corporate		
Soffy Effessor trademark	standard 190 89-EN/LZT 108 5347.		
Model number	The model number is Z520a and shall be printed " Z520a "		
Type number	The type number is AAC-1052012-BV and shall be printed		
	"Type AAC-1052012-BV"		
G-field	R-state identification of the CXC module according to the G-		
	Field section of 1/151 86- KRH 101 220.		
H-field	R-state identification of the KRH according to the H-Field		
	section of 1/151 86- KRH 101 220.		
Y ¹ -field	R-state identification of the ROA according to the Y-Field		
	section of 1/151 86- KRH 101 220.		
Country approval mark 1	Consist of text: FCC ID: PY7AC052012		
	Within a frame with height > 1,5 mm.		
Country approval mark 2	Consist of text: IC: 4170B-AC052012		
,	Within a frame with height > 1,5 mm.		
IMEI number as barcode	See below for definition of IMEI-number. The bar code shall		
	only contain the digits of the IMEI number (no -).		
IMEI number as characters	See the 1/151 86-KRH 101 220 (latest revision).		
	The text 'IMEI:' shall come before the IMEI number.		
	Therefore the format shall be		
	IMEI: 01AAAAAA-BBBBBB-C		
	AAAAAA = TAC		
	BBBBBB = assigned serial number		
	C = A check digit, from 0-9, calculated according to the Luhn		
	formula (ISO/IEC 7812), GSM 02.16.		
Serial number as barcode	According to Ericsson corporate standard 102 01 - 109.		
Serial number as characters	According to Ericsson group standard 0012-101.		
	Ericsson group factory number system according the		
	Ericsson corporate standard 1120-101		
	The text 'MSN:' shall come before the Serial number.		
	THE LEXT MOIN. SHAII COINE DEIDIE THE SEHAI HUITIDEL.		



Confidential MARKING DRAWING 3(3)

				()
Prepared		Date	Rev	Doc no.
RT/SEM/CA/KA Sandy Smith		2005-07-06	С	1/151 86-DPY 101 1464 Uen
Approved	Checked			File
CA/KA (Lance Workman)				I:\2)Product_Information\3)Product_Specific_Information\Zc TA\FCC and TA\Z520a Zoe850 15186 Marking Drawing.c

UPC Code as Barcode	See below for definition of UPC-number. The UPC code shall only contain the digits of the UPC number		
UPC Code as Characters	The text 'UPC:' shall come before the UPC number. Therefore the format shall be UPC: 095673 XXXXX, where XXXXX indicates the last five digits of the UPC number for the specific DPY.		
Production week (Prod wk)	The production week shall be given as yyWww (yy = year, ww = week) according to the ISO 8601 standard.		
Production week as barcode	According to Ericsson corporate standard 102 01 - 109.		
Repair week	The field shall be left blank unless a repair centre repairs the unit. The repair week shall then be given as Rywwxx (R = repair, y = year, ww = week, xx = Revision eg. 1A)		
Reduced DPY	The reduced product number of the DPY leaves out the 3 digit number prefix (ex: DPY 101 1464/1 R2A would be printed DPY 1464/1 R2A).		
Marking of origin	"Made in" statement should reflect the country of origin of the KRC (i.e. Made in China).		
CE Marking	1. According to 1424 - SVF 930 52		
	2. The notified body number from the type approval certificate, 0682. The print size (height) for the notified body number (e.g. 0682) and the corresponding approval marks shall be minimum 5 mm. This is a regulatory requirement.		

Print guidelines/regulations

The printing shall be well readable and permanent.

Typeface OCR-B
Type size min 1.1 mm
Line spacing min 1.5 mm
Trademark min 1mm (required)

Approval Marks min 5.0 mm

Product Listing

In the event that this marking drawing is to be used for the production of DPA units please use the following chart for cross-referencing the DPA number to the reduced DPY number that shall appear on the KRH label.

Product Number	Associated DPA	Customer

Revision History

Revision	Reason	Originator
PA1	Initial Release	Lance Workman
PA2	Added Sony Ericsson back to KRH label	Lance Workman
PA3	Added part number for CE label, updated label	Lance Workman
	pictures to reflect correct manufacturing week	



Confidential MARKING DRAWING 4(3)

				• •
Prepared		Date	Rev	Doc no.
RT/SEM/CA/KA Sandy Smith		2005-07-06	С	1/151 86-DPY 101 1464 Uen
Approved Check	ed			File
CA/KA (Lance Workman)				I:\2)Product_Information\3)Product_Specific_Information\Zc
,				TA\FCC and TA\Z520a_Zoe850_15186_Marking_Drawing.c

	text and barcode orientation, and added CXC 112 2391 to G field.	
PA4	Change layout of KRH labels	Lance Workman
Α	Released to rev. A to support FP build.	Lance Workman
В	Changed Type Number, FCC ID, & IC ID due to product changing from EDGE to Bluetooth.	Sandy Smith
С	Changed Type Number, FCC ID, & IC ID to 850 variant. Replaced "Zoe" w/ "Z520a". Added table to identify lines on label. Deleted_ on type number. Removed Cingular specific references. Replaced "CXC 112 2931" with "CXC".	Sandy Smith