



Prepared (also subject responsible if other)

SEM/BGURDBB, Niklas Lövberg

Approved

SEM/BGURDBB (Niklas Lövberg)

Checked

Company Internal  
MARKING DRAWING  
No.

151 86–SVV 107 304/1 Uen

Date

2005-04-25

Rev

A

Reference

2

Approved according to 000 21–LXE 107 42/1

## K600i, KRH-label, TYPE: AAD-3021021-BV, Made in...

### 1 General information

The format of the label is based on a label SVF 930 2406 (40,4 x 31,4 mm).

If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.

All bar codes, when applicable, are according to Ericsson corporate standard 102 01–109 Uen. All bar codes shall fulfil minimum print quality C according to ANSI X3.182-1990 as stated in Ericsson corporate standard 102 01–1003 Uen. No bar codes are allowed to be closer to a label edge than 2 mm! (quiet zone).

“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

The label shall be placed on the back of the telephone according to the Assembly Drawing (151 88-) for the KRH.

### 2 Printing information

|                        | Content   | Format  |
|------------------------|---|---|
| Line 1<br>(1,0/29,0)   | SIM-card logo   | Graphics, height 7,3 mm.<br>According to 1424-SVF 930 1418.<br>Rotated 90° Clockwise. |
| Line 2a<br>(20,7/1,0)  | Sony Ericsson stylized name.  | Graphics, height 2,0 mm.<br>According to 190 89–EN/LZT 108 5347                       |
| Line 2b<br>(20,2/18,0) | Model name, “K600i”   | Text, height 1,2 mm.  |
| Line 2c<br>(20,2/23,0) | Product number of the DPY kit in which the phone is packed. Printed without “DPY 101” and R-state, “0000/000” | Text, height 1,2 mm.  |
| Line 3a<br>(22,2/1,0)  | Type number of the phone (KRH), “Type: AAD-3021021-BV”.   | Text, height 1,2 mm.  |
| Line 3b<br>(22,2/18,0) | ROA and R-state identification field, “GHY <sub>1</sub> Y <sub>2</sub> Y <sub>3</sub> ”                       | Text, height 1,2 mm.<br>According to the 3/151 86- document in the 1095- for the SVV. |
| Line 3c<br>(22,2/24,0) | Location code of where the phone is flashed, if applicable, “FFF”   | Text, height 1,2 mm.  |



Prepared (also subject responsible if other)

SEM/BGURDBB, Niklas Lövberg

Approved

SEM/BGURDBB (Niklas Lövberg)

Checked

Company Internal  
MARKING DRAWING  
No.

151 86–SVV 107 304/1 Uen

Date

Rev

Reference

2005-04-25

A

2

| Content                | Format  |  |
|------------------------|---|--|
| Line 3d<br>(22,2/27,5) | Production week (flash), “yy’W’ww”<br>(yy = year, ww = week)  | Text, height 1,2 mm.   |
| Line 3e<br>(22,2/34,0) | Repair week, if applicable.<br>“Ry’W’ww”<br>(y = year, ww = week)   | Text, height 1,2 mm.   |
| Line 4a<br>(24,0/1,0)  | Country approval mark 1<br>“FCC ID: PY7AD021021”  | Text, height 1,2 mm.   |
| Line 4b<br>(24,0/15,0) | Country approval mark 2<br>“IC: 4170B-AD021021”   | Text, height 1,2 mm.   |
| Line 5<br>(26,5/1,0)   | Line 6a in bar code.<br>As desired by supplier (e.g. only<br>actual number).  | Bar code, height 2,0 mm.<br>As desired by supplier (e.g. Code 128<br>symbology).   |
| Line 6a<br>(28,0/1,0)  | Supplier’s identification for trace-<br>ability of the telephone, as desired<br>by supplier (e.g. “S/N: nnn....” for<br>serial number). | Text, height 1,2 mm.<br>Defined by supplier.   |
| Line 6b<br>(28,0/13,0) | Actual electronic serial number<br>(IMEI) of the phone (KRH),<br>“00000000-000000-0”  | Text, height 2,0 mm.<br>In the format TAC-SNR-CD.<br>TAC and SNR derived from the<br>3/151 86- document in the 1095- for the<br>SVV.<br>CD = check digit according to the Luhn<br>formula (ISO/IEC 7812), GSM 02.16. |
| Line 6c<br>(28,0/28,5) | CE approval symbol.   | Graphics, height 5 mm.<br>According to 1424-SVF 930 52.  |
| Line 6d<br>(28,0/35,3) | The Notified body number.<br>“0682”   | Text, height 2,0 mm.   |
| Line 7a<br>(30,2/1,0)  | Line 6b in bar code (only actual<br>number, without data identifier).   | Bar code, height 2,0 mm.<br>Code 128 symbology, code C subset. If<br>uneven number of digits, code B subset<br>shall be used for the last digit.   |
| Line 7b<br>(30,2/27,0) | Marking of origin.<br>The line shall be printed as stated<br>in chapter 3 in this document.   | Text, height 1,2 mm.   |



Prepared (also subject responsible if other)

SEM/BGURDBB, Niklas Lövberg

Approved

SEM/BGURDBB (Niklas Lövberg)

Checked

Company Internal  
MARKING DRAWING  
No.

151 86–SVV 107 304/1 Uen

Date

Rev

Reference

2005-04-25

A

2

## 3 Marking of Origin

### 3.1 Content


“Made in Xxx”;

“Xxx” = actual country of production of the included telephone, in English

## 4 Layout

The conceptual picture (for Zebra 90Xill printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

### 4.1 Conceptual picture



double underlined = major changes since last revision.