



**Prediction of MPE at given distance**

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density  
P = Power input to the antenna  
G = Antenna gain  
R = Distance to the center of radiation of the antenna

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Based on the above table the limits are for  
Part 24 device: 1 mW/cm<sup>2</sup>  
Part 22 device: 0.567 mW/cm<sup>2</sup>

**Prediction for Part 24:**

P	Max measured radiated power:	366 mW EIRP
R	Distance:	20 cm
Pmax1	Limit where no routine evaluation is required:	3 W EIRP
Pmax2	Peak power limit according to §24.232(b):	2 W
Smax	MPE limit for uncontrolled exposure:	1 mW/cm <sup>2</sup>
	Calculated power density:	0.073 mW/cm <sup>2</sup>

**Result: Configuration complies with rules.**

**Prediction for Part 22:**

P	Max measured radiated power:	1.33 W ERP
R	Distance:	20 cm
Pmax1	Limit where no routine evaluation is required:	1.5 W ERP
Pmax2	power limit according to §22.913(a):	7 W
Smax	MPE limit for uncontrolled exposure:	0.567 mW/cm <sup>2</sup>
	Calculated power density:	0.434 mW/cm <sup>2</sup>

**Result: Configuration complies with rules.**

**Date: 2006-06-19**  
**Name: Michael Grings**  
**Company: Cetecom Inc.**  
**Address: 411 Dixon Landing Rd,**  
**Milpitas, CA 95035, USA**  
**Phone: +1 408 586 6200**  
**Email: [michael.grings@cetecomusa.com](mailto:michael.grings@cetecomusa.com)**