



## Accredited testing-laboratory

**DAR registration number: DAT-P-176/94-D1**

**Federal Motor Transport Authority (KBA)  
DAR registration number: KBA-P 00070-97**

**Recognized by the Federal Communications Commission**

**Anechoic chamber registration no.: 90462 (FCC)**

**Anechoic chamber registration no.: 3462C-1 (IC)**

**Certification ID: DE 0001**

**Accreditation ID: DE 0002**

**Accredited Bluetooth® Test Facility (BQTF)**

*The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Cetecom ICT is under license*

**Test report no. : 1-1065-40-02/09-A**  
**Type identification : DDA-0002025**  
**Applicant : Sony Ericsson Mobile Communications AB**  
**FCC ID : PY7DDA-2025**  
**IC Certification No : 4170B-DDA2025**  
**Test standards : 47 CFR Part 15**  
**RSS - 210 Issue 7**

## Table of contents


<b>1</b>	<b>General information.....</b>	<b>3</b>
1.1	Notes .....	3
1.2	Testing laboratory .....	4
1.3	Details of applicant .....	4
1.4	Application details .....	4
<b>2</b>	<b>Test standard/s:.....</b>	<b>5</b>
<b>3</b>	<b>Technical tests .....</b>	<b>6</b>
3.1	Details of manufacturer.....	6
3.1.1	Test item.....	6
3.1.2	Additional EUT information For IC Canada (appendix 2).....	7
3.1.3	RF Technical Brief Cover Sheet acc. To RSS-102 .....	8
3.1.4	EUT operating modes.....	9
3.1.5	Extreme conditions testing values.....	9
<b>4</b>	<b>Summary of Measurement Results and list of all performed test cases .....</b>	<b>10</b>
<b>5</b>	<b>RF measurement testing .....</b>	<b>11</b>
5.1	Description of test set-up.....	11
5.1.1	Radiated measurements.....	11
5.1.2	Conducted measurements.....	11
5.2	Referenced documents .....	12
5.3	Additional comments .....	12
5.4	Antenna gain .....	12
5.5	Carrier frequency separation §15.247(a)(1) .....	13
5.6	Number of hopping channels §15.247(a)(1) .....	14
5.7	Time of occupancy (dwell time) §15.247(a)(1)(iii).....	15
5.8	Power Spectral density (Hybrid system in Inquiry mode/Page scan) §15.247(e) .....	16
5.9	Spectrum Bandwidth of a FHSS System / 20dB Bandwidth §15.247(a)(1).....	17
5.10	Maximum output power (conducted) § 15.247 (b)(1).....	19
5.11	Max. peak output power (radiated) § 15.247 (b)(1) .....	21
5.12	Band-edge compliance of conducted emissions §15.247 (d) .....	22
5.13	Band-edge compliance of radiated emissions §15.205 .....	25
5.14	Spurious Emissions - conducted (Transmitter) § 15.247 (c)(1) .....	26
5.15	Spurious Emissions > 30 MHz- radiated (Transmitter) § 15.247 (c)(1).....	28
5.16	Spurious Emissions - radiated (Receiver) § 15.109 .....	36
5.17	Spurious Emissions < 30 MHz - Transmitter radiated § 15.209 .....	39
5.18	Conducted Emissions <30 MHz § 15.107/207.....	40
<b>6</b>	<b>Test equipment and ancillaries used for tests.....</b>	<b>41</b>
<b>7</b>	<b>Photographs of the Test Set-up.....</b>	<b>44</b>
<b>8</b>	<b>Photographs of the EUT .....</b>	<b>46</b>


## 1 General information

### 1.1 Notes

The test results of this test report relate exclusively to the test item specified in 3.1.1. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

**Test laboratory manager:**

<b>2009-08-03</b>	<b>Meheza Kpelou Walla</b>	
Date	Name	Signature

<b>2009-08-03</b>	<b>Joerg Warken</b>	
Date	Name	Signature

**Technical responsibility for area of testing:**

<b>2009-08-03</b>	<b>Stefan Bös</b>	
Date	Name	Signature

## 1.2 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6 - 10

66117 Saarbrücken

Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

e-mail: info@ICT.cetecom.de

Internet: http://www.cetecom-ict.de

**State of accreditation:** The test laboratory (area of testing) is accredited according to  
DIN EN ISO/IEC 17025  
DAR registration number: DAT-P-176/94-D1

**Accredited by:** Federal Motor Transport Authority (KBA)  
DAR registration number: KBA-P 00070-97

**Testing location, if different from CETECOM ICT Services GmbH:**

Name :  
Street :  
Town :  
Country :  
Phone :  
Fax :

## 1.3 Details of applicant

<b>Name:</b>	Sony Ericsson Mobile Communications AB
<b>Street:</b>	Mobilvägen 10
<b>Town:</b>	22188 Lund
<b>Country:</b>	Sweden
<b>Telephone:</b>	+46-46-19-3000
<b>Fax:</b>	+46-10-800-2441
<b>Contact:</b>	Mr. Peter Lindeborg
<b>E-mail:</b>	peter.lindeborg@sonyericsson.com
<b>Telephone:</b>	+46-10-802-43 68

## 1.4 Application details

<b>Date of receipt of order:</b>	2009-06-22
<b>Date of receipt of test item:</b>	2009-06-23
<b>Date of start test:</b>	2009-06-23
<b>Date of end test:</b>	2009-06-30
<b>Persons(s) who have been present during the test:</b>	-/-

## 2 Test standard/s:

47 CFR Part 15	2008-07	Title 47 of the Code of Federal Regulations; Chapter I- Federal Communications Commission subchapter A - general, Part 15-Radio frequency devices
RSS - 210 Issue 7	2007-06	Spectrum Management and Telecommunications - Radio Standards Specification Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

### 3 Technical tests

#### 3.1 Details of manufacturer

Name:	Sony Ericsson Mobile Communications AB
Street:	Mobilvägen 10
Town:	22188 Lund
Country:	Sweden

##### 3.1.1 Test item

Kind of test item	:	BT headset BT2.1
Type identification	:	DDA-0002025
S/N serial number	:	Sample #1 (conducted sample) EUT Sample #2 (conducted sample)  # 15495 (radiated sample) # 15496 (radiated sample) EUT
HW hardware status	:	AP1
SW software status	:	01:0P
Frequency Band [MHz]	:	ISM band 2400,0 – 2483,5
Type of Modulation	:	GFSK
Number of channels	:	79
Antenna	:	Integrated antenna
Power Supply	:	3.80 V DC from power supply
Temperature Range	:	-20 °C to +55 °C

Max. power radiated: 4.56 dBm  
Max. power conducted: 5.25 dBm

FCC ID: PY7DDA-2025  
IC: 4170B-DDA2025

**3.1.2 Additional EUT information For IC Canada (appendix 2)**

IC Registration Number:	<b>4170B-DDA2025</b>
Model Name:	<b>DDA-0002025</b>
Manufacturer (complete Address):	<b>Sony Ericsson Mobile Communications AB Mobilvägen 10 22188 Lund Sweden</b>
Tested to Radio Standards Specification (RSS) No.:	<b>RSS-210 Issue 7</b>
Open Area Test Site Industry Canada Number:	<b>IC 3462C-1</b>
Frequency Range (or fixed frequency) [MHz]:	<b>ISM band 2400 – 2483.5</b>
RF: Power [W] (max):	<b><u>GFSK:</u> Rad. EIRP: 2.86 mW Conducted : 3.35 mW</b>
Antenna Type:	<b>Integrated antenna</b>
Occupied Bandwidth (99% BW) [kHz]:	<b>920</b>
Type of Modulation:	<b>GFSK</b>
Emission Designator (TRC-43):	<b>920KFXD</b>
Transmitter Spurious (worst case) [dBµV/m]:	<b>39.17</b>
Receiver Spurious (worst case) [dBµV/m]:	<b>39.94</b>

**ATTESTATION:**

I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned departmental standard(s), and that the radio equipment identified in this application has been subject to all applicable test conditions specified in the departmental standards and all of the requirements of the standards have been met.

Signature:



Test engineer: Meheza Kpelou Walla

Date: 2009-06-30

### 3.1.3 RF Technical Brief Cover Sheet acc. To RSS-102

All Fields must be completed with the requested information or the following codes: N/A for Not Applicable, N/P for Not Performed or N/V for Not Available. Where applicable, check appropriate box.

1. COMPANY NUMBER:           **4170B**
2. MODEL NUMBER:           **DDA-0002025**
3. MANUFACTURER:           **Sony Ericsson Mobile Communications AB**
4. TYPE OF EVALUATION:      **© RF Evaluation**

- Evaluated against exposure limits: General Public Use  Controlled Use
- Duty cycle used in evaluation: 99 %
- Standard used for evaluation: RSS-102 Issue 2 (2005-11)
- Measurement distance: 0.20 m
- RF value: 0.0011 V/m  A/m  W/m<sup>2</sup>
- Measured  Computed  Calculated

#### Declaration of RF Exposure Compliance

#### ATTESTATION:

I attest that the information provided in this test report are correct; that a Technical Brief was prepared and the information it contains is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed and that the device meets the SAR and/or RF exposure limits of RSS-102.

Name:           Meheza Kpelou Meheza  
Title:           Engineer  
Company:       Cetecom ICT Services GmbH



### 3.1.4 EUT operating modes

EUT operating mode no. *)	Description of operating modes	Additional information
Op. 0	Normal mode	Normal temperature and power source conditions
Op. 1		low temperature, low power source conditions
Op. 2		low temperature, high power source conditions
Op. 3		high temperature, low power source conditions
Op. 4		high temperature, high power source conditions

\*) EUT operating mode no. is used to simplify the test plan

### 3.1.5 Extreme conditions testing values

Description	Shortcut	Unit	Value
Nominal Temperature	T <sub>nom</sub>	°C	<b>+20</b>
Nominal Humidity	H <sub>nom</sub>	%	<b>50</b>
Nominal Power Source	V <sub>nom</sub>	V	<b>3.80</b>

Type of power source: **DC from power supply**

Deviations from these values are reported in chapter 2

#### 4 Summary of Measurement Results and list of all performed test cases

- No deviations from the technical specifications were ascertained  
 There were deviations from the technical specifications ascertained

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC Part 15 §15.247 - CANADA RSS-210	PASS	2009-06-30	-/-

Test Specification Clause	Test Case	Modulation	Pass	Fail	N/A	Not performed
None	Antenna Gain	GFSK	Yes			
§15.247(a1)	Carrier frequency separation	GFSK	Yes			
§15.247(a1)	Number of hopping channels	GFSK	Yes			
§15.247(a)(1)(iii)	Time of occupancy (dwell time)	--	Yes			
§15.247(e)	Power Spectral density (Hybrid system in Inquiry mode/Page scan)	--			Yes	
§15.247(a)(1)	Spectrum Bandwidth of a FHSS System / 20dB Bandwith	GFSK	Yes			
§ 15.247 (b)(1)	Maximum output power (conducted)	GFSK	Yes			
§ 15.247 (b)(1)	Max. peak output power (radiated)	GFSK	Yes			
§ 15.247 (d)	Band-edge compliance of conducted emissions	GFSK	Yes			
§ 15.205	Band-edge compliance of radiated emissions	GFSK	Yes			
§ 15.247 (d)	Spurious Emission - conducted (Transmitter)	GFSK	Yes			
§ 15.247 (d)	Spurious Emission - radiated (Transmitter) >30 MHz	GFSK	Yes			
§ 15.109	Spurious Emissions - radiated (Receiver)	GFSK	Yes			
§ 15.209	Spurious Emissions - radiated (Transmitter) <30 MHz	GFSK	Yes			
§ 15.107/207	Conducted Emissions <30 MHz	GFSK	Yes			

## 5 RF measurement testing

### 5.1 Description of test set-up

#### 5.1.1 Radiated measurements

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 25 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63.2-1996 clause 15 and ANSI C63.4-2003 clause 4.1.5. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63-4-2003 clause 4.2. Antennas are confirmed with ANSI C63.2-1996 item 15.


- 9 kHz - 150 kHz: Quasi Peak measurement, 200 Hz Bandwidth, passive loop antenna.
- 150 kHz - 30 MHz: Quasi Peak measurement, 9 kHz Bandwidth, passive loop antenna.
- 30 MHz - 200 MHz: Quasi Peak measurement, 120 kHz Bandwidth, bi-conical antenna
- 200MHz - 1GHz: Quasi Peak measurement, 120 kHz Bandwidth, log periodic antenna
- >1GHz: Average, RBW 1MHz, VBW 10 Hz, waveguide horn

All measurements are done in accordance with the Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems DA 00-705 and Appendix A “BLUETOOTH APPROVALS”

The EUT is powered by an external power supply with nominal voltage. The signalling is performed from outside the chamber with a signalling unit (CMU200 or other) by air link using signalling antenna.

#### 5.1.2 Conducted measurements

The EUT’s RF signal is coupled out by the antenna connector which is supplied by the manufacturer. The signal is first 10dB attenuated before it is power divided (~6dB loss per branch). One of the signal paths is connected to the communication base Station (CMU200 or other), the other one is connected to the spectrum analyzer. The specific losses for both signal paths are first checked within a calibration. The measurement readings on the signalling unit/spectrum analyzer are corrected by the specific test set-up loss. The attenuator, power divider, signalling unit and the spectrum analyzer are impedance matched on 50 Ohm.



## 5.2 Referenced documents

None

## 5.3 Additional comments

None

## 5.4 Antenna gain


The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

	low channel 2402 MHz	mid channel 2441 MHz	high channel 2480 MHz
Conducted power [dBm] Measured, GFSK modulation	5.25	5.04	4.54
Radiated power [dBm] Measured, GFSK modulation	4.56	4.33	4.01
Gain [dBi] Calculated	-0.69	-0.71	-0.53

**5.5 Carrier frequency separation §15.247(a)(1)**

Modulation: GFSK

Plot 1 of 1:



Result: Channel separation is: ~ 1 MHz


Limits:

Under normal test conditions only	Minimum 25 kHz or 20 dB Bandwidth of the hopping system
-----------------------------------	---


**5.6 Number of hopping channels §15.247(a)(1)**

Modulation: GFSK

Plot 1 of 2:



Plot 2 of 2:



Result: The number of hopping channels is: 79

Limits:

Under normal test conditions only	at least 15 non-overlapping channels
-----------------------------------	--------------------------------------

---

## 5.7 Time of occupancy (dwell time) §15.247(a)(1)(iii)

### For Bluetooth devices:

The dwell time of 0.4 s within a 31.6 second period in data mode is independent from the packet type (packet length). The calculation for a 31.6 second period is as follows:

Dwell time = time slot length \* hop rate / number of hopping channels \* 31.6 s

Example for a DH1 packet (with a maximum length of one time slot)

Dwell time =  $625 \mu\text{s} * 1600 \text{ 1/s} / 79 * 31.6 \text{ s} = 0.4 \text{ s}$  (in a 31.6 s period)

For multi-slot packet the hopping is reduced according to the length of the packet.

Example for a DH5 packet (with a maximum length of five time slots)

Dwell time =  $5 * 625 \mu\text{s} * 1600 * 1/5 * 1/s / 79 * 31.6 \text{ s} = 0.4 \text{ s}$  (in a 31.6 s period)

This is according to the Bluetooth Core Specification V 1.1 & V 1.2 & V2.0 (+ critical errata) for all Bluetooth devices.

Therefore, all Bluetooth devices comply with the FCC dwell time requirement in the data mode.

This was checked during the Bluetooth Qualification tests.

The Dwell time in hybrid mode is approximately 2.6 ms (in a 12.8s period)

**5.8 Power Spectral density (Hybrid system in Inquiry mode/Page scan)  
§15.247(e)**

**Not applicable!**

Plot 1 of 1:

Result: Power density: - dBm/Hz = - dBm / 3 kHz  
Correction factor from dBm/Hz to dBm / 3 kHz is +34.8 dB


Limits:

Under normal test conditions only	For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission
-----------------------------------	---




### 5.9 Spectrum Bandwidth of a FHSS System / 20dB Bandwidth §15.247(a)(1)


Plot 1: GFSK



Plot 2: GFSK



Plot 3: GFSK



Result:

Modulation	20 dB BANDWIDTH [kHz]		
	2402	2441	2480
Frequency [MHz]			
GFSK	920	920	920
Measurement uncertainty	±1kHz		

RBW / VBW as provided in the „Measurement Guidelines“ (DA 00-705, March 30, 2000)


RBW: 10 kHz / VBW 10 kHz

Limits:


Under normal test conditions only	GFSK < 1000 kHz Pi/4 DQPSK < 1500 8DPSK < 1500
-----------------------------------	--

**5.10 Maximum output power (conducted) § 15.247 (b)(1)**


Plot 1: GFSK



Plot 2: GFSK



Plot 3: GFSK



Results:

Modulation	Max. peak output power [dBm]		
	2402	2441	2480
Frequency [MHz]			
<i>GFSK</i>	5.25	5.04	4.54
Measurement uncertainty	±2dB		

RBW / VBW: 3 MHz

Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
--	---------------

**5.11 Max. peak output power (radiated) § 15.247 (b)(1)**

Modulation: GFSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2402	2442	2480
T <sub>nom</sub>	V <sub>nom</sub>	4.56	4.33	4.01
Measurement uncertainty		±3dB		

RBW / VBW: 3 MHz

Measured at a distance of 3m


Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
--	---------------


**5.12 Band-edge compliance of conducted emissions §15.247 (d)**

Modulation: GFSK

Plot 1 of 4 (hopping off, lowest frequency):




Plot 2 of 4 (hopping on, lowest frequency):






Plot 3 of 4 (hopping off, highest frequency):



Plot 4 of 4 (hopping on, highest frequency):



Results:

SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB

Limits:


Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).
-----------------------------------	--




### 5.13 Band-edge compliance of radiated emissions §15.205

Modulation: GFSK

Plot 1: Band edge compliance at the highest channel with far away emissions



Plot 2: Band edge compliance at the lowest channel with far away emissions




Final verdict: Passed


**5.14 Spurious Emissions - conducted (Transmitter) § 15.247 (c)(1)**

*Modulation: GFSK*


Plot 1 of 3: lowest channel



Plot 2 of 3: middle channel



Plot 3 of 3: highest channel



Result & Limits:

Emission Limitation					
Frequency [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402		5.38	30 dBm		Operating frequency
			-20 dBc		
2441		5.06	30 dBm		Operating frequency
			-20 dBc		
2480		4.58	30 dBm		Operating frequency
			-20 dBc		
Measurement uncertainty			± 3dB		

F < 1 GHz: RBW: 100 kHz VBW: 100 kHz  
 F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Note: For emissions that fall into restricted bands you find the radiated emissions later in the report.

### 5.15 Spurious Emissions > 30 MHz- radiated (Transmitter) § 15.247 (c)(1)

Plot 1: 0.03 - 1 GHz vertical/horizontal (lowest channel)


#### Information

EUT:	DDA-0002025
Serial Number:	091606480004066
Test Description:	FCC part 15 @ 10 m
Operating Conditions:	BT TX Ch. 00 + charging
Operator Name:	Hennemann
Comment:	AC: 115 V / 60 Hz

#### Scan Setup: STAN\_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)
Level Unit:	dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver




Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
35.068600	9.2	15000.000	120.000	348.0	V	261.0	13.2	20.8	30.0
40.156300	9.3	15000.000	120.000	400.0	H	166.0	13.6	20.7	30.0
50.520350	10.5	15000.000	120.000	98.0	V	72.0	13.5	19.5	30.0
693.126950	20.0	15000.000	120.000	337.0	V	184.0	22.8	16.0	36.0
708.497650	20.4	15000.000	120.000	310.0	V	233.0	23.2	15.6	36.0
833.872200	21.9	15000.000	120.000	198.0	H	231.0	24.8	14.1	36.0
924.578650	23.0	15000.000	120.000	303.0	V	272.0	25.8	13.0	36.0

**Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]**

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0109)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 2: 1 - 12 GHz vertical/horizontal (lowest channel)



Carrier suppressed with a rejection filter



Plot 4: 0.03 - 1 GHz vertical/horizontal (middle channel)


### Information

EUT:	DDA-0002025
Serial Number:	091606480004066
Test Description:	FCC part 15 @ 10 m
Operating Conditions:	BT TX Ch. 39 + charging
Operator Name:	Hennemann
Comment:	AC: 115 V / 60 Hz

### Scan Setup: STAN\_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)
Level Unit:	dB $\mu$ V/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver




Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
591.174950	17.7	15000.000	120.000	204.0	V	142.0	21.1	18.3	36.0
687.292550	19.9	15000.000	120.000	173.0	V	224.0	22.7	16.1	36.0
751.434600	21.3	15000.000	120.000	220.0	V	47.0	24.2	14.7	36.0
946.173700	23.2	15000.000	120.000	220.0	H	151.0	25.8	12.8	36.0

**Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]**

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0109)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 5: 1 - 12 GHz vertical/horizontal (middle channel)



Carrier suppressed with a rejection filter



Plot 6: 0.03 - 1 GHz vertical/horizontal (highest channel)


### Information

EUT:	DDA-0002025
Serial Number:	091606480004066
Test Description:	FCC part 15 @ 10 m
Operating Conditions:	BT TX Ch. 78 + charging
Operator Name:	Hennemann
Comment:	AC: 115 V / 60 Hz

### Scan Setup: STAN\_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)
Level Unit:	dB $\mu$ V/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver




Frequency (MHz)	QuasiPeak (dB $\mu$ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V/m)
44.109150	9.9	15000.000	120.000	165.0	H	146.0	13.4	20.1	30.0
55.824000	9.2	15000.000	120.000	220.0	V	57.0	12.9	20.8	30.0
97.434700	7.9	15000.000	120.000	166.0	H	19.0	12.0	25.6	33.5
702.499850	20.3	15000.000	120.000	169.0	V	51.0	23.1	15.7	36.0
803.530050	21.4	15000.000	120.000	220.0	V	11.0	24.4	14.6	36.0
946.865450	23.1	15000.000	120.000	174.0	H	231.0	25.8	12.9	36.0

## Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0109)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 7: 1 - 12 GHz vertical/horizontal (highest channel)



Carrier suppressed with a rejection filter

Results:

SPURIOUS EMISSIONS LEVEL (dB $\mu$ V/m)								
2402 MHz			2441 MHz			2480 MHz		
Frequency [MHz]	Detector	Level [dB $\mu$ V/m]	Frequency [MHz]	Detector	Level [dB $\mu$ V/m]	Frequency [MHz]	Detector	Level [dB $\mu$ V/m]
7206	Average	52.78	7323	Average	52.95	7440	Average	53.65
						9920	Average	53.78
Measurement uncertainty			±3 dB					

f < 1 GHz : RBW/VBW: 100 kHz

f ≥ 1GHz : RBW/VBW: 1 MHz

Limits: § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limits: § 15.209

Frequency [MHz]	Field strength [ $\mu$ V/m]	Measurement distance (m)
30 - 88	100 (40 dB $\mu$ V/m)	3
88 - 216	150 (43.5 dB $\mu$ V/m)	3
216 - 960	200 (46 dB $\mu$ V/m)	3
above 960	500 (54 dB $\mu$ V/m)	3

**5.16 Spurious Emissions - radiated (Receiver) § 15.109**

Plot 1: 0.03 - 1 GHz vertical/horizontal (receiver)


**Information**

EUT:	DDA-0002025
Serial Number:	091606480004066
Test Description:	FCC part 15 @ 10 m
Operating Conditions:	Idle mode + charging
Operator Name:	Hennemann
Comment:	AC: 115 V / 60 Hz

**Scan Setup: STAN\_Fin [EMI radiated]**

Hardware Setup:	Electric Field (NOS)
Level Unit:	dBµV/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1 GHz	QuasiPeak	120 kHz	15 s	Receiver




Frequency (MHz)	QuasiPeak (dBµV/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dBµV/m)
43.012850	12.6	15000.000	120.000	120.0	V	78.0	13.5	17.4	30.0
48.883850	9.7	15000.000	120.000	220.0	H	276.0	13.5	20.3	30.0
103.715000	11.2	15000.000	120.000	153.0	V	217.0	11.9	22.3	33.5
701.064100	20.4	15000.000	120.000	176.0	V	192.0	23.0	15.6	36.0
863.364550	22.5	15000.000	120.000	141.0	H	6.0	25.2	13.5	36.0
929.520300	23.0	15000.000	120.000	121.0	V	278.0	25.8	13.0	36.0


**Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]**

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0109)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

Plot 2: 1 - 12 GHz vertical/horizontal (receiver)



Plot 3: 12 - 25 GHz vertical/horizontal (receiver)



**Results:**

Spurious Emissions level [dBµV/m]		
f[MHz]	Detector	Level [dBµV/m]
No critical peaks found!		
Measurement uncertainty		±3 dB

f < 1 GHz: RBW/VBW: 100 kHz      f ≥ 1GHz : RBW/VBW: 1 MHz  
 See above plots

Measurement distance see table


Limits: § 15.109

Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
30 - 88	100 (40 dBµV/m)	3
88 - 216	150 (43.5 dBµV/m)	3
216 - 960	200 (46 dBµV/m)	3
above 960	500 (54 dBµV/m)	3

### 5.17 Spurious Emissions < 30 MHz - Transmitter radiated § 15.209

Measured at 3 m distance.  
 Values recalculated with 40 dB/decade according to FCC rules.

Plot 1:




Limits:


Frequency (MHz)	Field strength (µV/m)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30 / 29.5 dBµV/m	30

5.18 Conducted Emissions <30 MHz § 15.107/207

Plot 1: Neutral Line



Plot 2: Phase Line



Limits:

Under normal test conditions only	See plots
-----------------------------------	-----------



## 6 Test equipment and ancillaries used for tests

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

All reported calibration intervals are calibrations according to the EN/ISO/IEC 17025 standard. These calibrations were performed from an accredited external calibration laboratory.

Additional to these calibrations the laboratory performed comparison measurements with other calibrated systems and performed a weekly chamber inspection.

All used devices are connected with a 10 MHz external reference.

According to the manufacturers' instruction is it possible to establish a calibration interval for the FSP unit of 24 month, if the device has an external 10 MHz reference.

### *Anechoic chamber C:*

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Anechoic chamber	MWB	87400/02	300000996	Monthly verification		
2	System-Rack 85900	HP I.V.	*	300000222	n.a.		
3	Measurement System 1						
4	PSA-Spektrumanalysator 3 Hz - 26.5 GHz (E4440A)	Agilent	MY48250080	300003812	05.08.2008	24	05.08.2010
5	EMI Preselector 9 kHz - 1 GHz (N9039A)	Agilent	MY48260003	300003825	19.08.2008	24	19.08.2010
6	Microwave Analog Signal Generator (N5183A)	Agilent	MY47420220	300003813	06.08.2008	24	06.08.2010
7	PC	F+W			n.a.		
8	TILE	TILE			n.a.		
9	TRILOG Super Broadband Antenna (VULB9163)	Schwarzbeck	371	300003854	Monthly verification (System cal.)		
10	Double Ridged Antenna 3115	EMCO	3088	300001032	Monthly verification (System cal.)		
11	Active Loop Antenna 6502	EMCO	2210	300001015	Monthly verification (System cal.)		
12	Switch / Control Unit 3488A	HP	2719A15013	300001156	n.a.		
13	Power Supply 6032A	HP	2818A03450	300001040	08.01.2009	36	08.01.2012
14	Busisolator	Kontron		300001056	n.a.		
15	Leitungsteiler 11850C	HP		300000997	Monthly verification (System cal.)		
16	Power attenuator 8325	Byrd	1530	300001595	Monthly verification (System cal.)		
17	Band reject filter WRCG1855/1910	Wainwright	7	300003350	Monthly verification (System cal.)		
18	Band reject filter WRCG2400/2483	Wainwright	11	300003351	Monthly verification (System cal.)		
19	Hochpassfilter WHK1.1/15G-10SS	Wainwright	3	300003255	Monthly verification (System cal.)		
20	Hochpassfilter WHKX2.9/18G-12SS	Wainwright	1	300003492	Monthly verification (System cal.)		
21	Hochpassfilter WHKX7.0/18G-8SS	Wainwright	18	300003789	Monthly verification (System cal.)		
22	Switch / Control Unit 3488A	HP	2605e08770	300001443	n.a.		
23	Trenntrafo RT5A	Grundig	9242	300001263	n.a.		
24	Relais Matrix PSU	R&S	890167/024	300001168	n.a.		
25	Netznachbildung ESH3-Z5	R&S	828576/020	300001210	n.a.		

**System Rack Room 005 :**

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	FSP 30	R&S	100886	300003575	25.08.2008	24	25.08.2010
2	CBT	R&S	100313	300003516	03.09.2008	24	03.09.2010
3	Switch Matrix	HP		300000929	n.a.		
4	Power Supply	HP	3041A00544	300002270	13.05.2007	36	13.05.2010
5	Signal Generator	R&S	836206/0092	300002680	30.05.2007	36	30.05.2010

**SRD Laboratory Room 002:**

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	System Controller PSM 12	R&S	835259/007	3000002681-00xx	n.a.		
2	Memory Extension PSM-K10	R&S	To 1	3000002681	n.a.		
3	Operating Software PSM-B2	R&S	To 1	3000002681	n.a.		
4	19" Monitor		22759020-ED	3000002681	n.a.		
5	Mouse		LZE 0095/6639	3000002681	n.a.		
6	Keyboard		G00013834L461	3000002681	n.a.		
7	Spectrum Analyser FSIQ 26	R&S	835540/018	3000002681-0005	10.01.2008	24	10.01.2010
8	Tracking Generator FSIQ-B10	R&S	835107/015	3000002681	s.No.7		
10	RF-Generator SMIQ03 (B1 Signal)	R&S	835541/056	3000002681-0002	26.08.2008	36	26.08.2011
11	Modulation Coder SMIQ-B20	R&S	To 10	3000002681	s.No.10		
12	Data Generator SMIQ-B11	R&S	To 10	3000002681	s.No.10		
13	RF Rear Connection SMIQ-B19	R&S	To 10	3000002681	s.No.10		
14	Broadband horn antenna (1-18 GHz)	EMCO	9107-3696	300001604	16.04.2008	24	16.04.2010
15	Broadband horn antenna (1-18 GHz)	EMCO	9107-3697	300001605	21.08.2008	24	21.08.2010
16	Std gain horn antenna (18-26.5 GHz)	Narda	Model no. 638	3000000486	n.a.		
17	Std gain horn antenna (18-26.5 GHz)	Narda	Model no. 638	3000000487	n.a.		
18	Sleeve dipole antenna Model 3126-880	ETS-Lindgren	00040887	3000000	n.a.		
19	Fast CPU SM-B50	R&S	To 10	3000002681	s.No.10		
20	FM Modulator SM-B5	R&S	835676/033	3000002681	s.No.10		
21	RF-Generator SMIQ03 (B2 Signal)	R&S	835541/055	3000002681-0001	25.08.2008	36	25.08.2011
22	Modulation Coder SMIQ-B20	R&S	To 16	3000002681	s.No.16		
23	Data Generator SMIQ-B11	R&S	To 16	3000002681	s.No.16		
24	RF Rear Connection SMIQ-B19	R&S	To 16	3000002681	s.No.16		
25	Fast CPU SM-B50	R&S	To 16	3000002681	s.No.16		
26	FM Modulator SM-B5	R&S	836061/022	3000002681	s.No.16		
27	RF-Generator SMP03 (B3 Signal)	R&S	835133/011	3000002681-0003	26.08.2008	36	26.08.2011
28	Attenuator SMP-B15	R&S	835136/014	3000002681	S.No.22		
29	RF Rear Connection SMP-B19	R&S	834745/007	3000002681	S.No.22		
30	Power Meter NRVD	R&S	835430/044	3000002681-0004	26.08.2008	24	26.08.2010
31	Power Sensor NRVD-Z1	R&S	833894/012	3000002681-0013	26.08.2008	24	26.08.2010
32	Power Sensor NRVD-Z1	R&S	833894/011	3000002681-0010	26.08.2008	24	26.08.2010
33	Rubidium Standard RUB	R&S		3000002681-0009	27.08.2008	24	27.08.2010
34	Switching and Signal Conditioning Unit SSCU	R&S	338864/003	3000002681-0006	Verified with path compensation		
35	Laser Printer HP Deskjet 2100	HP	N/A	3000002681-0011	n.a.		
36	19" Rack	R&S	11138363000004	3000002681	n.a.		
37	RF-cable set	R&S	N/A	3000002681	n.a.		

39	IEEE-cables	R&S	N/A	3000002681	n.a.		
40	Sampling System FSIQ-B70	R&S	835355/009	3000002681	s.No.7		
41	RSP programmable attenuator	R&S	834500/010	3000002681-0007	26.08.2008	24	26.08.2010
42	Signalling Unit	R&S	838312/011	3000002681	n.a.		
43	NGPE programmable Power Supply for EUT	R&S	192.033.41	3000002681			
44	Power Splitter 6005-3	Inmet Corp.	none	300002841	23.12.2006	24	23.12.2008
45	SMA Cables SPS-1151-985-SPS	Insulated Wire	different	different	n.a.		
46	CBT32 with EDR Signaling Unit	R&S					
47	Coupling unit	Narda	N/A	--	n.a.		
48	2xSwitch Matrix PSU	R&S	872584/021	300001329	n.a.		
49	RF-cable set	R&S	N/A	different	n.a.		
50	IEEE-cables	R&S	N/A	--	n.a.		

Note: 3000002681-00xx inventoried as a system

**Anechoic chamber F:**

No	Equipment/Type	Manuf.	Serial Nr.	Inv. No. Cetecom	Last Calibration	Frequency (months)	Next Calibration
1	Control Computer	F+W	FW0502032	300003303	-/-	-/-	-/-
2	Trilog Antenna VULB 9163	Schwarzbeck	295	300003787	01.04.2008	24	01.04.2010
3	Amplifier - 0518C-138	Veritech Micro-wave Inc.	-/-	-/-	-/-	-/-	-/-
4	Switch - 3488A	HP		300000368	-/-	-/-	-/-
5	EMI Test receiver - ESCI	R&S	100083	300003312	31.01.2009	24	31.01.2011
6	Turntable Controller - 1061 3M	EMCO	1218	300000661	-/-	-/-	-/-
7	Tower Controller 1051 Controller	EMCO	1262	300000625	-/-	-/-	-/-
8	Tower - 1051	EMCO	1262	300000625	-/-	-/-	-/-
10	Ultra Notch-Filter Rejected band Ch. 62	WRCD	9	-/-	-/-	-/-	-/-