



Prepared (also subject responsible if other)  
SEM/BGODD Mats Hörlin  
Approved

Company Internal  
MARKING DRAWING  
No.

Checked Date Rev Reference  
2008-06-27 PA1

## Mobile Phone label content, FAD-3880001-BV, (SG) Made in...iDA

### 1 General information

<b>Core Unit label part no</b>	1206-6118
<b>Bar code</b>	<ul style="list-style-type: none"> <li>• <b>Standard:</b> according to Ericsson corporate standard 102 01–109 Uen</li> <li>• <b>Print quality:</b> C, according to ANSI X3.182-1990 as stated in Ericsson corporate standard 102 01–1003 Uen</li> <li>• <b>Quiet zone:</b> No bar codes are allowed to be closer to a label edge than 2 mm!</li> </ul>
<b>Text</b>	If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.
<b>Coordinates</b>	"(x/y)" under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

### MLCI= Main Label Content Information-document

### 2 Printing information

	Content	Format
<b>Line 1</b> (2,5/19,0)	Sony Ericsson stylized name.	Graphics, height 1,5 mm. According to 1200-1925.
<b>Line 2a</b> (4,5/19,0)	Model Name "X000x"	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
<b>Line 2b</b> (4,5/23,4)	Business Edition	Text, height 1,2 mm.
<b>Line 3</b> (6,0/19,0)	Production week (flash), "yy'W'ww" (yy = year, ww = week)	Text, height 1,2 mm.
<b>Line 4</b> (8,0/19,5)	Product number without revision of the Sales Item in which the phone is packed, if applicable. "SI: XXXX-XXXX"	Text, height 1,2 mm.
<b>Line 5a</b> (10,5/1,0)	"TYPE: XXX-0000000-BV"	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
<b>Line 5b</b> (10,5/21,0)	PBA and R-state identification field, "G <sub>1</sub> G <sub>2</sub> G <sub>3</sub> HY <sub>1</sub> Y <sub>2</sub> Y <sub>3</sub> "	Text, height 1,2 mm. According to Type-testing report in the Product Model's Specifying Documents.
<b>Line 5c</b> (10,5/31,5)	Location code of where the phone is flashed, if applicable, "FFF"	Text, height 1,2 mm.
<b>Line 6a</b> (12,5/1,0)	"IC:0000X-X0000000"	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
<b>Line 6b</b> (12,5/17,5)	"FCC ID: XX0X0000000"	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI.</i>
<b>Line 7</b> (14,3/2,0)	Line 8a in bar code. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
<b>Line 8a</b> (16,3/1,0)	Supplier's identification for trace-ability of the telephone, as desired by supplier (e.g. "S/N: nnn...." for serial number).	Text, height 1,2 mm. Defined by supplier.



Prepared (also subject responsible if other)  
SEM/BGODD Mats Hörlin  
Approved

Checked

Date  
2008-06-27

Rev  
PA1

Reference

	Content	Format
<b>Line 8b</b> (16,3/20,0)	Actual electronic serial number (IMEI) of the Mobile Phone, "00000000-000000-0"	Text, height 1,2 mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
<b>Line 9a</b> (18,2/2,0)	Line 8b in bar code (only actual number, without data identifier).	Bar code, height 2,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.
<b>Line 9b</b> (18,2/29,0)	Repair week, if applicable. "Ry'W'ww" (y = year, ww = week)	Text, height 1,2 mm.
<b>Line 11</b> (23,0/1,5)	Marking of origin: The line shall be printed as stated in chapter 3 in this document.	Text, height 1,2 mm.
<b>Line 12a</b> (29,0/1,0)	CE approval symbol	Graphics, height 5 mm. According to 1202-5482.
<b>Line 12b</b> (29,0/10,0)	The notified body number "0682", rotated 90° counter clockwise.	Text, height 1,2 mm.
<b>Line 12c</b> (28,5/11,0)	iDA symbol	Graphics, height 4 mm According to 1202-5623
<b>Line 12d</b> (29,0/32,5)	SIM symbol	Graphics, height 5 mm. <i>According to Chapter 1 in MLCI.</i>

### 3 Marking of origin

#### 3.1 Content

"Made in Xxxxx"

"Xxxxx"= actual country of production of the included telephone, in English.

### 4 Layout

The conceptual picture (for Zebra 90Xill printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

#### 4.1 Conceptual picture

Scale 2:1

Company Internal  
MARKING DRAWING  
No.

Prepared (also subject responsible if other)  
SEM/BGODD Mats Hörlin  
Approved





Checked

Date  
2008-06-27

Rev  
PA1

Reference

6

No print area	<b>Sony Ericsson</b>
	G700 Business Edition yyWww SI: XXXX-XXXX
TYPE: FAD-3880001-BV GGGHYYY FFF IC:4170B-F3880001 FCC ID: PY7F3880001	
	
S/N: XXXABC1234 00000000-000000-0  RyWww	
Made in Xxxxx	
	 Complies with IDA Standards DB101365
	

## Position of label

The view below is taken from the back side of the mobile telephone. The label is located below the battery lid.

