

Company Internal
MARKING DRAWING

Prepared (also subject responsible if other)

SEM/BGURKLD Arne Rahm

Approved

SEM/BGURKLD Arne Rahm

Checked

No.

151 86-SVV 104 335/1 Uen

Date

Rev

Reference

2004-06-30

B

Type FAB-102 1012-BV

Smartphone P910i

1. Label

The label used for marking is defined in the Manufacturing Specification on the SVF 930 863.


2. Placing

The label shall be placed on the back of the telephone according to the Assembly Drawing (151 88-) for the KRH.

3. Print layout

Printing area 31.6 x 18.5 mm.

Line nbr



Line	Text	Text height
1.	Reduced DPY-number, R-state, Repair week, Model name, Additional field (if necessary)	min 1.2 mm
2.	Type number, G1,G2, G3, H, Y1, Y2, Y3 field, Additional field	min 1.2 mm
3.	IMEI number as bar code	min 3.5 mm
4.	IMEI number as characters	min 1.2 mm
5.	Serial number as bar code	min 3.5 mm
6.	Serial number as characters, production week, CDA number , R-state.	min 1.2 mm
7.	Country approval mark 1	min 1.2 mm
8.	Country approval mark 2	min 1.5 mm
9.	Approval mark, angled 90° clw	Min 5.0 mm
10.	Sony Ericsson trademark, angled 90° clw	min 2.0 mm
11.	Marking of origin, angled 90° clw	min 1.2 mm



Prepared (also subject responsible if other)

SEM/BGURKLD Arne Rahm

Approved

SEM/BGURKLD Arne Rahm

Checked

No.

151 86-SVV 104 335/1 Uen

Date

Rev

Reference

2004-06-30

B

4. Definitions:

1.	Reduced DPY-number	The DPY number, according to 1095- for the produced product, without "DPY 101" e.g. if DPY 101 2541/1 is produced the printing should be "2541/1". (6 pos)
	R-state	The R-state for the DPY according to the 1095- for the DPY. (3 pos)
	Repair week	The field shall be left blank unless a repair centre repairs the unit. The repair week shall then be given as Rywwxx. (R = repair, y = year, ww = week, xx = R-state e.g. 1A). (6 pos)
	Model name	The model name P910i .
	Additional field (if necessary)	The field shall be left blank unless otherwise stated in a separate 2/151 86-SVV according to 1095- of the actual SVV. Some fields might need two lines.
2.	Ericsson Type number	The type number shall be printed "Type FAB-1021012-BV" (19 pos)
	G1-field	R-state of the CXC-phone sw according to the Type approval report 17452-SVV104 335/1.
	G2-field	R-state of the CXC-organizer sw according to the Type approval report 17452-SVV104 335/1.
	G3-field	R-state of the CXC-BT sw according to the Type approval report 17452-SVV104 335/1.
	H-field	R-state of the type approved hardware according to the Type approval report 17452-SVV104 335/1.
	Y1-field	R-state of the KRH according to the Marking drawing 1/151 86-SVV104 335/1.
	Y2-field	ROA identification according to the Marking drawing 1/151 86-SVV104 335/1.
	Y3-field	R-state of the ROA according to the Marking drawing 1/151 86-SVV104 335/1.
	Additional field	The field shall be left blank unless otherwise stated in a separate 2/151 86-SVV according to 1095- of the actual SVV.
3.	IMEI number as bar code	See below for definition of IMEI-number. The bar code shall only contain the digits of the IMEI number (no dash). Acc. to Ericsson corporate standard 102 01-109. Code 128.
4.	IMEI number as characters	The IMEI number has format: TAC-SNR-CD (17 pos) TAC = 35423500 (type approval code) (8 pos) SNR = Serial number see 1301-FAD 109 0091/1 (6 pos) CD = A check digit, from 0-9, calculated according to the Luhn formula (1 pos) (ISO/IEC 7812), GSM 02.16.



Prepared (also subject responsible if other)

SEM/BGURKLD Arne Rahm

Approved

Checked

No.

151 86-SVV 104 335/1 Uen

Date

Rev

Reference

SEM/BGURKLD Arne Rahm

2004-06-30

B

5.	Serial number as bar code	According to Ericsson corporate standard 102 01 - 109. Code 128
6.	Serial number as characters	According to Ericsson group standard (10 pos) 0012-101. Ericsson group factory number system according the Ericsson corporate standard 1120-101 Factory codes: Flextronics Linköping A61 Ericsson Beijing CB5 Sony Alsace AL
	Production week	The production week shall be given as yyWww (yy = year, ww = week) according to the ISO 8601 standard. (5 pos)
	CDA number, R-state	The CDA number and the R-state according to 13132- for the produced DPY. (16 pos)
7.	Country approval mark 1	Consist of text: "IC 4170B-FB021012"
8.	Country approval mark 2	Consist of text: "FCC ID: PY7FB021012" in a frame with height > 1,5 mm
9.	Approval marks	According to 1424 - SVF 930 52
		The notified body number 0682 according to the RTTE directive. The print height for the notified body number and approval mark CE is a regulatory requirement.
10.	Sony Ericsson Trademark	According to corporate standard 190 89-EN/LZT 108 5347.
11.	Marking of origin	The field shall be left blank unless otherwise stated in a separate 3/151 86-SVV document according to 1095- of the actual SVV.