## **Application: PY7FF031021**



## **Prediction of MPE limit at given distance**

Equation from page 18 of OET Bulletin 65, Edition 97-01

 $S = PG / 4\pi R^2$ 

where: S = Power density

P = Power input to the antenna

G = Antenna gain

R = Distance to the center of radiation of the antenna

Solving this equation for G

 $G = S (4\pi R^2) / P$ 

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Based on the above table the limits are for

Part 24 device: 1 mW/cm<sup>2</sup> Part 22 device: 0.567 mW/cm<sup>2</sup>

## **Prediction for Part 24:**

P Max power input to the antenna: 29.2 dBm / 0.832 W

R Distance: 20 cm S MPE limit for uncontrolled exposure: 1 mW/cm<sup>2</sup>

G Antenna gain: 6.04 numerical G Antenna gain: 7.81 dBi

EIRP peak power limit according to §24.232(b): 2 W / 33 dBm

Therefore the maximum antenna gain for part 24 shall not exceed 3.8 dBi

## **Prediction for Part 22:**

P Max power input to the antenna: 32.4 dBm / 1.862 W

R Distance: 20 cm

S MPE limit for uncontrolled exposure: 0.567 mW/cm<sup>2</sup>

G Antenna gain: 1.53 numerical
G Antenna gain: 1.84 dBi / -0.3 dBd

ERP power limit according to §22.913(a): 7 W

Therefore the maximum antenna gain for part 22 shall not exceed -0.3 dBd