


CDMA SOL21 Mobile Phone label

1 General information



Core Unit label part no	1262-0653
Bar code	<ul style="list-style-type: none"> • Print quality: according to COSMETIC GUIDELINE – Bar code labels document 1222-6072 Uen • Quiet zone: No bar codes are allowed to be closer to a label edge than 2 mm!
Text	If applicable, or nothing else specified, Zebra printer Scalable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.
Coordinates	“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

MLCI= Main Label Content Information Document

2 Printing information

	Content	Format
Line 1 (3,0/36,0)	Model Name “CDMA SOL21”	Text, height 1,2 mm. <i>According to Chapter 1 in MLCI</i>
Line 2 (8,0/23,5)	 SONY® logo	Graphics, height 6,5 mm, width 11,4 mm According to 1267-8979.
Line 3a (9,0/3,0)	Two card-slot aw in Japanese	Graphics, height 8 mm. According to 1267-8982
Line 3b (9,0/36,0)	ARIB STD-T71-logo	Graphics height 6,0mm According to 1267-8998
Line 4a (12,0/3,0)	Sentence in Japanese: “商品コード”	Graphics, height 1,2 mm. According to 1248-3733

<p>Line 4b (12,0/10,0)</p>	<p>Colour info of the included phone "SOL21XXX"</p>	<p>Text, height 1,2 mm. "SOL21XXX" "XXX" = different for each phone unit color. "Pink", use "MPA" "White", use "MWA" "Black", use "MKA" "Blue", use "MLA"</p>
<p>Line 5a (14,5/3,0)</p>	<p>Type number of the phone, "TYPE: PM-0050-BV".</p>	<p>Text, height 1,2 mm. <i>According to Chapter 1 in MLCI</i></p>
<p>Line 5b (14,5/16,0)</p>	<p>HW & SW identification field, if applicable; "EFF"</p>	<p>Text, height 1,2 mm. <i>According to Type-testing report under Product Model Specifying Documents</i></p>
<p>Line 5c (14,5/210)</p>	<p>"FCC ID: PY7PM-0050"</p>	<p>Text, height 1,2 mm. <i>According to Chapter 1 in MLCI</i></p>
<p>Line 5d (14,5/35,0)</p>	<p>Production date in Japanese (eg: year / month : 製造年月 201X/XX</p>	<p>Text, height 1,5 mm. Graphics, height 1,5 mm. According to 1234-3763</p>
<p>Line 6a (15,2/3,0)</p>	<p>Product number of the Sales Item in which the phone is packed, if applicable. "SI XXXX-XXXX"</p>	<p>Text, height 1,2 mm</p>
<p>Line 6b (15,2/16,0)</p>	<p>Production week (flash), "yyWww" (yy = year, ww = week)</p>	<p>Text, height 1,2 mm.</p>
<p>Line 7a (19,0/3,2)</p>	<p>"Caution symbol"</p>	<p>Graphics, height 2.5 mm. According to 1234-3774</p>
<p>Line 7b (19,0/6,0)</p>	<p>"Caution" in Japanese</p>	<p>Graphics, height 2.0 mm. According to 1234-3790</p>
<p>Line 8 (20,2/10,0)</p>	<p>"Do not remove this label" statement in Japanese, on two rows. "航空機内・病院内では電源を切ってください" "このシールを剥がさないでください"</p>	<p>Graphics, height 1,5 mm. According to 1250-5471</p>
<p>Line 9 (25,2/4,0)</p>	<p>Line 9 in bar code, according to line 10 (ie IMEI number, only actual number, without data identifier).</p>	<p>Bar code, height 4,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.</p>

Line 10 (15,2/38,5)	Actual electronic serial number (IMEI) of the Mobile Phone, "IMEI: 00000000-000000-0"	Text, height 1,2 mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.
Line 11 (29,0/4,0)	Line 11 in bar code, according to line 12. As desired by supplier (e.g. only actual number).	Bar code, height 2,0 mm. As desired by supplier (e.g. Code 128 symbology).
Line 12 (31,0/4,0)	Supplier's identification for trace-ability of the telephone, as desired by supplier (e.g. "S/N: nnn...." for serial number).	Text, height 1.2 mm. Defined by supplier
Line 13a (36,5/3,0)	"CE approval symbol, The notified body number 0682 and Alert Symbol"	Graphics, height 5 mm. According to 1242-7470
Line 13b (36,5/33,5)	WEE trashcan without bar symbol	Graphics, min. height 5mm, according to 1202-5537
Line 13c (36,5/39,0)	"Li-ion 00 Symbol"	Graphics, min. height 5mm, according to 1235-2267
Line 14 (40,2/36,0)	Local Type Approval Number: T ADXX-XXXXXXX	Text, height 1,2 mm
Line 15 (41,0/35,7)	Square around T, see Line 14 	Width 1,5 x Height 2,0 mm
Line 16 (42,0/4,0)	Text within the frame; "2.4 FH1/XX8/DS4/OF4" Three bars under the text, each bar is 1 mm high and 3 mm long	Bluetooth value with frame measurements; 13x 4,4 mm Text height 1,2 mm
Line 17 (42,6/36,0)	Local Type Approval Number: R XXX-XXXXXX	Text, height 1,2 mm.
Line 18 (42,4/36,0)	Square around R, see Line 17 	Width 1,5 x Height 2,0 mm

Sony Mobile Communications AB
Prepared by
CGOVDPLG, Anna Englund
Contents responsible if other than preparer

Date
2012-07-06
Remarks

Approved by
CGOVDPLG, Anna Englund

Line 19 (44,0/28,0)	"JATE" logo	Graphics, height 5 mm. According to 1234-3837
Line 20 (47,0/2,0)	Sentence in Japanese, 2 rows; 発売元 KDDI(株)・沖縄セルラー電話(株) 製造元 ソニーモバイルコミュニケーションズ株式会社	Graphics height 3,5 acc to aw 1267-8983
Line 21 (51,5/2,0)	5,2 Ghz WLAN text, two rows	Graphics height 3,5 acc to aw 1267-8977
Line 22 (52,0/35,0)	Marking of origin. "Made in Xxx"; "Xxx" = actual country of production of the included telephone, in English	Text, height 1,2 mm.
Line 23 (60,2/11,7)	Line 23 in bar code, according to line 24 (ie IMEI number, only actual number, without data identifier).	Bar code, height 10,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.
Line 25 (68,0/11,7)	Actual electronic serial number (IMEI) of the Mobile Phone, "IMEI: 00000000-000000-0"	Text, height 2,5 mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.

3 Layout

The conceptual picture (for Zebra 90Xill printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

3.1 Conceptual picture

挿入方向に注意してください。

上段
micro SD
micro SDHC

下段
au Micro IC Card
(トレイ)

au

SONY®

CDMA SOL21

IEEE802.11b/g/n

IEEE802.11a/n

W52 W53 W56

商品コード SOL21XXX
TYPE: PM-0050-BV EFF FCC ID: PY7PM-0050 製造年月 201X/XX
SI XXXX-XXXX yyWww

⚠ 警告 航空機内・病院内では電源を切ってください
このシールを剥がさないでください



IMEI: 00000000-000000-0



S/N: XXXABC1234

CE 0682

2.4 FH1/XX8/DS4/OF4

Li-ion 00

ADXX-XXXXXXX
XXX-XXXXXXX

発売元 (株)・沖縄セルラー電話(株)
製造元 ソニーモバイルコミュニケーションズ株式会社
電波法により 5.2GHz 帯および 5.3GHz 帯 (W52/W53) の
屋外利用は禁止されています。 Made in Xxx



IMEI: 00000000-000000-0

double underlined = major changes since last revision.