

Sony Mobile Communications
Prepared by
SEM/CGQBAD RAZVAN BUJILA
Contents responsible if other than preparer

Document number
17/0061-LXE 110 0790 Uen
Date
2013-03-15
Remarks
This document is managed in metaDoc.

Revision
A

Approved by
SEM/CGQBAD (RAZVAN BUJILA)

Receiver
Federal Communications Commission &
Certification and Engineering Bureau

Dual Cell HSDPA Declaration Letter - PY7PM-0350

Applies to:

Product	Typenumber	FCC ID	IC ID
C5303	PM-0350-BV	PY7PM-0350	4170B-PM0350

There is no difference between uplink with DC-HSDPA configured and the normal HSDPA case. For the reporting format used on HS-DPCCH for CQI and ACK/NACK reporting please see 3GPP 25.212 4.7.3A.

The RF chain remains unchanged. This implementation described above does not affect uplink modulation, spurious emission, bandwidths and temperature behavior. Output power in DC-HSDPA mode is equal or lower than output power in RMC 12.2kbps mode, as demonstrated in this filing.

Secondary carrier share uplink HS-DPCCH according to document 3GPP TS 25.212 s4.7 with the first carrier. Uplink will be power controlled as normal by one stream of TPC commands received on DL DPCH i.e. E-DPDCH, E-DPCCH, DPDCH, DPCCH and HS-DPCCH will all be power controlled jointly.

Based on this the DC-HSDPA mode has been excluded from the testing performed in the EMC test reports.

Yours sincerely



Razvan Bujila
Global Type Approval

Sony Mobile Communications
Tel: +46 10 801 53 23
Mobilvägen 10, SE-221 88 Lund, Sweden
razvan.bujila@sonymobile.com