

**#01\_HAC\_E\_GSM850\_GSM Voice\_Ch128**

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 824.2 MHz; Duty Cycle: 1:8.6896  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.2 °C

**DASY5 Configuration:**

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2014/1/30;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1279; Calibrated: 2014/1/30
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (6); SEMCAD X Version 14.6.9 (7117)

**Ch128/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid**

**Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 77.87 V/m; Power Drift = -0.07 dB

Applied MIF = 3.63 dB

RF audio interference level = 38.86 dBV/m

**Emission category: M4**

MIF scaled E-field

<b>Grid 1 M4</b> <b>36.82 dBV/m</b>	<b>Grid 2 M4</b> <b>38.39 dBV/m</b>	<b>Grid 3 M4</b> <b>38.24 dBV/m</b>
<b>Grid 4 M4</b> <b>37.28 dBV/m</b>	<b>Grid 5 M4</b> <b>38.86 dBV/m</b>	<b>Grid 6 M4</b> <b>38.7 dBV/m</b>
<b>Grid 7 M4</b> <b>37.13 dBV/m</b>	<b>Grid 8 M4</b> <b>38.73 dBV/m</b>	<b>Grid 9 M4</b> <b>38.56 dBV/m</b>

**Cursor:**

Total = 38.86 dBV/m

E Category: M4

Location: -5, 2, 8.7 mm



0 dB = 87.66 V/m = 38.86 dBV/m

**#02\_HAC\_E\_GSM850\_GSM Voice\_Ch189**

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 836.6 MHz; Duty Cycle: 1:8.6896  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.2 °C

**DASY5 Configuration:**

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2014/1/30;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1279; Calibrated: 2014/1/30
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (6); SEMCAD X Version 14.6.9 (7117)

**Ch189/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm  
 Reference Value = 90.82 V/m; Power Drift = -0.07 dB  
 Applied MIF = 3.63 dB  
 RF audio interference level = 40.15 dBV/m


**Emission category: M3**

MIF scaled E-field

<b>Grid 1 M4</b> <b>37.73 dBV/m</b>	<b>Grid 2 M4</b> <b>39.58 dBV/m</b>	<b>Grid 3 M4</b> <b>39.43 dBV/m</b>
<b>Grid 4 M4</b> <b>38.21 dBV/m</b>	<b>Grid 5 M3</b> <b>40.15 dBV/m</b>	<b>Grid 6 M3</b> <b>40 dBV/m</b>
<b>Grid 7 M4</b> <b>38.09 dBV/m</b>	<b>Grid 8 M3</b> <b>40.02 dBV/m</b>	<b>Grid 9 M4</b> <b>39.88 dBV/m</b>

**Cursor:**

Total = 40.15 dBV/m  
 E Category: M3  
 Location: -5, 2.5, 8.7 mm



0 dB = 101.7 V/m = 40.15 dBV/m

**#03\_HAC\_E\_GSM850\_GSM Voice\_Ch251**

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 848.6 MHz; Duty Cycle: 1:8.6896  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.2 °C

**DASY5 Configuration:**

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2014/1/30;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1279; Calibrated: 2014/1/30
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (6); SEMCAD X Version 14.6.9 (7117)

**Ch251/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid**

**Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 94.05 V/m; Power Drift = -0.12 dB

Applied MIF = 3.63 dB

RF audio interference level = 40.35 dBV/m

**Emission category: M3**

MIF scaled E-field


<b>Grid 1 M4</b> <b>36.96 dBV/m</b>	<b>Grid 2 M4</b> <b>39.63 dBV/m</b>	<b>Grid 3 M4</b> <b>39.59 dBV/m</b>
<b>Grid 4 M4</b> <b>37.7 dBV/m</b>	<b>Grid 5 M3</b> <b>40.35 dBV/m</b>	<b>Grid 6 M3</b> <b>40.3 dBV/m</b>
<b>Grid 7 M4</b> <b>37.58 dBV/m</b>	<b>Grid 8 M3</b> <b>40.23 dBV/m</b>	<b>Grid 9 M3</b> <b>40.17 dBV/m</b>

**Cursor:**

Total = 40.35 dBV/m

E Category: M3

Location: -6.5, 3, 8.7 mm



0 dB = 104.2 V/m = 40.36 dBV/m

**#04\_HAC\_E\_GSM1900\_GSM Voice\_Ch512**

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1850.2 MHz; Duty Cycle: 1:8.6896  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.2 °C

**DASY5 Configuration:**

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2014/1/30;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1279; Calibrated: 2014/1/30
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (6); SEMCAD X Version 14.6.9 (7117)

**Ch512/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid**

**Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 21.77 V/m; Power Drift = 0.17 dB

Applied MIF = 3.63 dB

RF audio interference level = 32.15 dBV/m

**Emission category: M3**

MIF scaled E-field


Grid 1 <b>M3</b> <b>32.15 dBV/m</b>	Grid 2 <b>M3</b> <b>31.73 dBV/m</b>	Grid 3 <b>M4</b> <b>29.26 dBV/m</b>
Grid 4 <b>M4</b> <b>29.09 dBV/m</b>	Grid 5 <b>M3</b> <b>31.33 dBV/m</b>	Grid 6 <b>M3</b> <b>31.3 dBV/m</b>
Grid 7 <b>M3</b> <b>32.87 dBV/m</b>	Grid 8 <b>M3</b> <b>34.13 dBV/m</b>	Grid 9 <b>M3</b> <b>33.74 dBV/m</b>

**Cursor:**

Total = 34.13 dBV/m

E Category: M3

Location: -1.5, 25, 8.7 mm



0 dB = 50.90 V/m = 34.13 dBV/m

## #05\_HAC\_E\_GSM1900\_GSM Voice\_Ch661

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1880 MHz; Duty Cycle: 1:8.6896  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.2 °C

### DASY5 Configuration:

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2014/1/30;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1279; Calibrated: 2014/1/30
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (6); SEMCAD X Version 14.6.9 (7117)

### Ch661/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid

**Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 22.49 V/m; Power Drift = 0.14 dB

Applied MIF = 3.63 dB

RF audio interference level = 31.94 dBV/m

**Emission category: M3**

MIF scaled E-field


Grid 1 <b>M3</b> <b>31.94 dBV/m</b>	Grid 2 <b>M3</b> <b>31.65 dBV/m</b>	Grid 3 <b>M4</b> <b>29.55 dBV/m</b>
Grid 4 <b>M4</b> <b>29.24 dBV/m</b>	Grid 5 <b>M3</b> <b>31.55 dBV/m</b>	Grid 6 <b>M3</b> <b>31.52 dBV/m</b>
Grid 7 <b>M3</b> <b>32.53 dBV/m</b>	Grid 8 <b>M3</b> <b>33.92 dBV/m</b>	Grid 9 <b>M3</b> <b>33.59 dBV/m</b>

**Cursor:**

Total = 33.92 dBV/m

E Category: M3

Location: -1.5, 25, 8.7 mm



**#06\_HAC\_E\_GSM1900\_GSM Voice\_Ch810**

Communication System: GSM-FDD (TDMA, GMSK); Frequency: 1909.8 MHz; Duty Cycle: 1:8.6896  
 Medium: Air Medium parameters used:  $\sigma = 0$  S/m,  $\epsilon_r = 1$ ;  $\rho = 1000$  kg/m<sup>3</sup>  
 Ambient Temperature : 23.2 °C

**DASY5 Configuration:**

- Probe: ER3DV6 - SN2358; ConvF(1, 1, 1); Calibrated: 2014/1/30;
- Sensor-Surface: (Fix Surface)
- Electronics: DAE4 Sn1279; Calibrated: 2014/1/30
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (6); SEMCAD X Version 14.6.9 (7117)

**Ch810/E Scan - ER3D: 15 mm from Probe Center to the Device/Hearing Aid Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm  
 Reference Value = 22.06 V/m; Power Drift = 0.19 dB  
 Applied MIF = 3.63 dB  
 RF audio interference level = 31.65 dBV/m


**Emission category: M3**

MIF scaled E-field

<b>Grid 1 M3</b> <b>31.65 dBV/m</b>	<b>Grid 2 M3</b> <b>31.48 dBV/m</b>	<b>Grid 3 M4</b> <b>29.63 dBV/m</b>
<b>Grid 4 M4</b> <b>28.44 dBV/m</b>	<b>Grid 5 M3</b> <b>31.25 dBV/m</b>	<b>Grid 6 M3</b> <b>31.24 dBV/m</b>
<b>Grid 7 M3</b> <b>31.43 dBV/m</b>	<b>Grid 8 M3</b> <b>33.24 dBV/m</b>	<b>Grid 9 M3</b> <b>33.04 dBV/m</b>

**Cursor:**

Total = 33.24 dBV/m  
 E Category: M3  
 Location: -2.5, 25, 8.7 mm



0 dB = 45.94 V/m = 33.24 dBV/m