

## Appendix 5. System Check

Prior to the assessment, the system was verified in the flat region of the phantom, 900 MHz, 1800 MHz, 1900 MHz, 2450 MHz, 2600 MHz and 5.0 GHz dipoles were used. A forward power of 250 mW was applied to the 900 MHz, 1800 MHz, 1900 MHz, 2450 MHz, 2600 MHz dipoles and 100 mW was applied to 5.0 GHz dipole and the system was verified to a tolerance of  $\pm 5\%$  for the 900MHz, 1800MHz, 1900MHz, 2450 MHz and 5.0 GHz dipoles.

The applicable verification normalised to 1 Watt.

### System Check 900 Head

Date: 17/06/2013

Validation Dipole and Serial Number: D900V2; SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	900	23.0 °C	21.6 °C	$\epsilon_r$	41.50	40.95	-1.33	5.00
				$\sigma$	0.97	0.95	-1.80	5.00
				1g SAR	10.50	10.16	-3.24	5.00
				10g SAR	6.74	6.60	-2.08	5.00

Date: 21/06/2013

Validation Dipole and Serial Number: D900V2; SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	900	23.0 °C	21.8 °C	$\epsilon_r$	41.50	41.20	-0.72	5.00
				$\sigma$	0.97	0.98	1.03	5.00
				1g SAR	10.50	10.72	2.10	5.00
				10g SAR	6.74	6.96	3.26	5.00

Date: 24/06/2013

Validation Dipole and Serial Number: D900V2; SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	900	23.0 °C	22.5 °C	$\epsilon_r$	41.50	40.40	-2.65	5.00
				$\sigma$	0.97	0.97	-0.36	5.00
				1g SAR	10.50	10.80	2.86	5.00
				10g SAR	6.74	7.04	4.45	5.00

**System Check 900 Head (Continued):**

Date: 25/06/2013

Validation Dipole and Serial Number: D900V2; SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	900	23.0°C	22.5°C	$\epsilon_r$	41.50	40.40	-2.65	5.00
				$\sigma$	0.97	0.97	-0.36	5.00
				1g SAR	10.50	10.52	0.19	5.00
				10g SAR	6.74	6.84	-1.48	5.00

**System Check 900 Body**

Date: 18/06/2013

Validation Dipole and Serial Number: D900V2; SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	900	23.0°C	21.5°C	$\epsilon_r$	55.00	53.46	-2.80	5.00
				$\sigma$	1.05	1.04	-1.33	5.00
				1g SAR	10.80	10.68	-1.11	5.00
				10g SAR	6.96	7.04	1.15	5.00

Date: 18/06/2013

Validation Dipole and Serial Number: D900V2; SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	900	23.0°C	21.7°C	$\epsilon_r$	55.00	53.75	-2.27	5.00
				$\sigma$	1.05	1.04	-1.43	5.00
				1g SAR	10.80	11.04	2.22	5.00
				10g SAR	6.96	7.20	3.45	5.00

Date: 19/06/2013

Validation Dipole and Serial Number: D900V2; SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	900	23.0 °C	21.5 °C	$\epsilon_r$	55.00	53.46	-2.80	5.00
				$\sigma$	1.05	1.04	-1.33	5.00
				1g SAR	10.80	10.44	-3.33	5.00
				10g SAR	6.96	6.84	-1.72	5.00

Date: 26/06/2013

Validation Dipole and Serial Number: D900V2; SN: 035

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	900	24.0°C	22.0 °C	$\epsilon_r$	55.00	53.80	-2.18	5.00
				$\sigma$	1.05	1.04	-1.10	5.00
				1g SAR	10.80	10.68	-1.11	5.00
				10g SAR	6.96	7.00	0.57	5.00

**System Check 1800 Head**  
**Date: 19/06/2013**  
**Validation Dipole and Serial Number: D1800V2; SN: 264**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	1800	23.0°C	22.2°C	$\epsilon_r$	40.00	38.61	-3.48	5.00
				$\sigma$	1.40	1.41	0.57	5.00
				<b>1g SAR</b>	37.20	35.52	-4.52	5.00
				<b>10g SAR</b>	19.60	19.00	-3.06	5.00

**Date: 20/06/2013**  
**Validation Dipole and Serial Number: D1800V2; SN: 264**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	1800	23.0°C	22.2°C	$\epsilon_r$	40.00	39.18	-2.05	5.00
				$\sigma$	1.40	1.44	2.79	5.00
				<b>1g SAR</b>	37.20	37.60	-1.08	5.00
				<b>10g SAR</b>	19.60	19.72	0.61	5.00

**System Check 1800 Body**

Date: 17/06/2013

Validation Dipole and Serial Number: D1800V2; SN: 264

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1800	23.0 °C	22.2 °C	$\epsilon_r$	53.30	51.84	-2.74	5.00
				$\sigma$	1.52	1.56	2.70	5.00
				1g SAR	37.80	37.32	-1.27	5.00
				10g SAR	20.10	20.16	0.30	5.00

Date: 18/06/2013

Validation Dipole and Serial Number: D1800V2; SN: 264

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1800	23.0 °C	22.2 °C	$\epsilon_r$	53.30	51.84	-2.74	5.00
				$\sigma$	1.52	1.56	2.70	5.00
				1g SAR	37.80	37.04	-2.01	5.00
				10g SAR	20.10	19.92	-0.90	5.00

Date: 19/06/2013

Validation Dipole and Serial Number: D1800V2; SN: 264

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1800	23.0 °C	23.7 °C	$\epsilon_r$	53.30	52.61	-1.29	5.00
				$\sigma$	1.52	1.49	-1.71	5.00
				1g SAR	37.80	37.96	0.42	5.00
				10g SAR	20.10	20.40	1.49	5.00

**System Check 1900 Head**

Date: 20/06/2013

Validation Dipole and Serial Number: D1900V2; SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	1900	24.0°C	23.0°C	$\epsilon_r$	40.00	38.50	-3.75	5.00
				$\sigma$	1.40	1.45	3.60	5.00
				1g SAR	39.40	39.72	0.81	5.00
				10g SAR	20.70	20.84	0.68	5.00

Date: 20/06/2013

Validation Dipole and Serial Number: D1900V2; SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	1900	24.0°C	23.0°C	$\epsilon_r$	40.00	39.36	-1.60	5.00
				$\sigma$	1.40	1.45	3.22	5.00
				1g SAR	39.40	40.80	3.55	5.00
				10g SAR	20.70	20.60	-0.48	5.00

Date: 21/06/2013

Validation Dipole and Serial Number: D1900V2; SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	1900	24.0°C	23.0°C	$\epsilon_r$	40.00	38.50	-3.75	5.00
				$\sigma$	1.40	1.45	3.60	5.00
				1g SAR	39.40	39.56	0.41	5.00
				10g SAR	20.70	20.80	0.48	5.00

Date: 24/06/2013

Validation Dipole and Serial Number: D1900V2; SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	1900	24.0 °C	23.0 °C	$\epsilon_r$	40.00	38.82	-2.95	5.00
				$\sigma$	1.40	1.41	0.43	5.00
				1g SAR	39.40	38.80	-1.52	5.00
				10g SAR	20.70	20.80	0.48	5.00

**System Check 1900 Body**

Date: 20/06/2013

Validation Dipole and Serial Number: D1900V2; SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1900	23.0 °C	22.5 °C	$\epsilon_r$	53.30	54.13	1.56	5.00
				$\sigma$	1.52	1.53	0.63	5.00
				1g SAR	40.50	39.28	-3.01	5.00
				10g SAR	21.40	21.04	-1.68	5.00

Date: 21/06/2013

Validation Dipole and Serial Number: D1900V2; SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1900	23.0 °C	22.5 °C	$\epsilon_r$	53.30	54.13	1.56	5.00
				$\sigma$	1.52	1.53	0.63	5.00
				1g SAR	40.50	39.40	-2.72	5.00
				10g SAR	21.40	21.16	-1.12	5.00

Date: 21/06/2013

Validation Dipole and Serial Number: D1900V2; SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1900	24.0 °C	23.5 °C	$\epsilon_r$	53.30	52.17	-2.12	5.00
				$\sigma$	1.52	1.57	3.33	5.00
				1g SAR	40.50	40.00	-1.23	5.00
				10g SAR	21.40	21.08	-1.50	5.00

Date: 22/06/2013

Validation Dipole and Serial Number: D1900V2; SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1900	24.0 °C	23.5 °C	$\epsilon_r$	53.30	52.17	-2.12	5.00
				$\sigma$	1.52	1.57	3.33	5.00
				1g SAR	40.50	40.00	-1.23	5.00
				10g SAR	21.40	21.16	-1.12	5.00

**System Check 1900 Body (Continued):**

Date: 24/06/2013

Validation Dipole and Serial Number: D1900V2; SN: 537

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	1900	24.0 °C	23.8 °C	$\epsilon_r$	53.30	50.90	-4.50	5.00
				$\sigma$	1.52	1.57	3.33	5.00
				1g SAR	40.50	38.72	-4.40	5.00
				10g SAR	21.40	20.56	-3.93	5.00

**System Check 2450 Head****Date: 17/06/2013****Validation Dipole and Serial Number: D2440V2; SN: 701**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	2450	24.0 °C	24.0 °C	$\epsilon_r$	39.20	40.06	2.19	5.00
				$\sigma$	1.80	1.85	2.54	5.00
				<b>1g SAR</b>	52.30	50.80	-2.87	5.00
				<b>10g SAR</b>	24.20	23.88	-1.32	5.00

**Date: 18/06/2013****Validation Dipole and Serial Number: D2440V2; SN: 701**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	2450	24.0 °C	24.0 °C	$\epsilon_r$	39.20	40.06	2.19	5.00
				$\sigma$	1.80	1.85	2.54	5.00
				<b>1g SAR</b>	52.30	50.80	-2.87	5.00
				<b>10g SAR</b>	24.20	23.72	-1.98	5.00

**System Check 2450 Body**

**Date: 18/06/2013**

**Validation Dipole and Serial Number: D2440V2; SN: 701**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	2450	24.0 °C	22.8 °C	$\epsilon_r$	52.70	52.55	-0.28	5.00
				$\sigma$	1.95	2.00	2.61	5.00
				1g SAR	52.00	52.40	0.77	5.00
				10g SAR	24.10	24.00	-0.41	5.00

**Date: 19/06/2013**

**Validation Dipole and Serial Number: D2440V2; SN: 701**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	2450	24.0°C	22.8°C	$\epsilon_r$	52.70	52.55	-0.28	5.00
				$\sigma$	1.95	2.00	2.61	5.00
				1g SAR	52.00	52.80	1.54	5.00
				10g SAR	24.10	24.12	0.08	5.00

**System Check 2600 Head**

Date: 27/06/2013

Validation Dipole and Serial Number: D26000V2; SN: 1046

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	2600	24.0 °C	22.9 °C	$\epsilon_r$	39.00	38.96	-0.10	5.00
				$\sigma$	1.96	2.04	4.06	5.00
				1g SAR	58.20	60.40	3.78	5.00
				10g SAR	26.20	26.48	1.07	5.00

**System Check 2600 Body**

Date: 27/06/2013

Validation Dipole and Serial Number: D26000V2; SN: 1046

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	2600	24.0 °C	23.5 °C	$\epsilon_r$	52.50	52.77	0.51	5.00
				$\sigma$	2.16	2.18	0.71	5.00
				1g SAR	55.50	56.00	0.90	5.00
				10g SAR	25.00	24.36	-2.56	5.00

**System Check 5200/5500/5800 Head****Date: 20/06/2013****Validation Dipole and Serial Number: D5GHzV2; SN: 1016**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	5200	24.0 °C	24.0 °C	$\epsilon_r$	36.00	34.81	-3.31	5.00
				$\sigma$	4.66	4.65	2.10	5.00
				1g SAR	78.10	75.00	-3.97	5.00
				10g SAR	23.00	21.90	-1.79	5.00

**Date: 21/06/2013****Validation Dipole and Serial Number: D5GHzV2; SN: 1016**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	5200	24.0 °C	24.0 °C	$\epsilon_r$	36.00	34.81	-3.31	5.00
				$\sigma$	4.66	4.65	2.10	5.00
				1g SAR	78.10	80.30	2.82	5.00
				10g SAR	23.00	23.10	3.59	5.00

**Date: 21/06/2013****Validation Dipole and Serial Number: D5GHzV2; SN: 1016**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	5500	24.0 °C	24.0 °C	$\epsilon_r$	35.60	34.23	-3.85	5.00
				$\sigma$	4.96	5.06	2.02	5.00
				1g SAR	82.50	86.20	4.48	5.00
				10g SAR	23.50	24.20	2.98	5.00

**Date: 21/06/2013****Validation Dipole and Serial Number: D5GHzV2; SN: 1016**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Head	5800	24.0 °C	24.0 °C	$\epsilon_r$	35.30	33.77	-4.33	5.00
				$\sigma$	5.27	5.38	2.11	5.00
				1g SAR	77.00	80.40	4.42	5.00
				10g SAR	21.90	22.60	3.20	5.00

**System Check 5200/5500/5800 Body****Date: 24/06/2013****Validation Dipole and Serial Number: D5GHzV2; SN: 1016**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	5200	24.0 °C	24.0 °C	$\epsilon_r$	49.00	47.89	-2.27	5.00
				$\sigma$	5.30	5.42	2.20	5.00
				1g SAR	75.10	78.00	3.86	5.00
				10g SAR	21.10	20.10	-4.74	5.00

**Date: 25/06/2013****Validation Dipole and Serial Number: D5GHzV2; SN: 1016**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	5200	24.0 °C	24.0 °C	$\epsilon_r$	49.00	47.89	-2.27	5.00
				$\sigma$	5.30	5.42	2.20	5.00
				1g SAR	75.10	74.40	-0.93	5.00
				10g SAR	21.10	20.50	-2.84	5.00

**Date: 25/06/2013****Validation Dipole and Serial Number: D5GHzV2; SN: 1016**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	5500	24.0 °C	24.0 °C	$\epsilon_r$	48.60	47.36	-2.55	5.00
				$\sigma$	5.65	5.80	2.59	5.00
				1g SAR	79.00	82.90	4.94	5.00
				10g SAR	22.00	21.50	-2.27	5.00

**Date: 25/06/2013****Validation Dipole and Serial Number: D5GHzV2; SN: 1016**

Simulant	Frequency (MHz)	Room Temp	Liquid Temp	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	5800	24.0 °C	24.0 °C	$\epsilon_r$	48.20	46.86	-2.78	5.00
				$\sigma$	6.00	6.19	3.11	5.00
				1g SAR	74.40	72.10	-3.09	5.00
				10g SAR	20.60	19.80	-3.88	5.00

## Appendix 6. Simulated Tissues

The body mixture consists of water, Polysorbate (Tween 20) and salt. Visual inspection is made to ensure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue.

Ingredient (% by weight)	Frequency 750/835/850/900 MHz	
	Head	Body
De-Ionized Water	52.87	71.30
Polysorbate 20	46.10	28.00
Salt	1.03	0.70

Ingredient (% by weight)	Frequency 1800/1900 MHz	
	Head	Body
De-Ionized Water	55.40	71.50
Polysorbate 20	44.22	28.00
Salt	0.38	0.50

Ingredient (% by weight)	Frequency 2450/2600 MHz	
	Head	Body
De-Ionized Water	55.75 <sup>(1)</sup>	71.70
Polysorbate 20	45.25 <sup>(1)</sup>	28.00
Salt	0.00	0.30

Stimulating Liquid for 3700 MHz to 5800 MHz are supplied and manufactured by SPEAG

Ingredient (% by weight)	Frequency
	3700 - 5800 MHz Head / Body
De-Ionized Water	~78.00
Mineral Oil	~11.00
Emulsifiers	~9.00
Additives and Salt	~2.00

### Note(s):

- As per the recipe provided by National Physical Laboratory, the 2450 MHz Head Fluid recipe is mixed to the total percentage of weight is by 101.0 %.

## Appendix 7. DASY4 System Details

### A.7.1. DASY4 SAR Measurement System

UL, SAR measurement facility utilises the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 system is comprised of the robot controller, computer, near-field probe, probe alignment sensor, and the SAM phantom containing brain or muscle equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller; teach pendant (Joystick), and remote control. This is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. The data acquisition electronics (DAE) performs signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection etc. The DAE is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card. The DAE3 utilises a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

### A.7.2. DASY4 SAR System Specifications

#### Robot System

Positioner:	Stäubli Unimation Corp. Robot Model: RX90L
Repeatability:	0.025 mm
No. of Axis:	6
Serial Number:	F00/SD89A1/A/01
Reach:	1185 mm
Payload:	3.5 kg
Control Unit:	CS7
Programming Language:	V+

#### Robot System

Positioner:	Stäubli Unimation Corp. Robot Model: RX90L
Repeatability:	0.025 mm
No. of Axis:	6
Serial Number:	F01/5J86A1/A/01
Reach:	1185 mm
Payload:	3.5 kg
Control Unit:	CS7
Programming Language:	V+

#### Robot System

Positioner:	Stäubli Unimation Corp. Robot Model: TX60L
Repeatability:	±0.030 mm
No. of Axis:	6
Serial Number:	F12/5MZ7A1/A/01
Reach:	920 mm
Payload:	2.0 kg
Control Unit:	CS8C
Programming Language:	V+

#### Data Acquisition Electronic (DAE) System

Serial Number:	DAE3 SN:417
Serial Number:	DAE3 SN:431
Serial Number:	DAE3 SN:450

<b>DASY4 SAR System Specifications (Continued)</b>	
<b>PC Controller</b>	
<b>PC:</b>	Dell Precision 340
<b>Operating System:</b>	Windows 2000
<b>Data Card:</b>	DASY4 Measurement Server
<b>Serial Number:</b>	1080
<b>Data Converter</b>	
<b>Features:</b>	Signal Amplifier, multiplexer, A/D converted and control logic.
<b>Software:</b>	DASY4 Software
<b>Connecting Lines:</b>	Optical downlink for data and status info. Optical uplink for commands and clock.
<b>PC Interface Card</b>	
<b>Function:</b>	24 bit (64 MHz) DSP for real time processing Link to DAE3 16 nit A/D converter for surface detection system serial link to robot direct emergency stop output for robot.
<b>E-Field Probe</b>	
<b>Model:</b>	EX3DV4
<b>Serial No:</b>	3814
<b>Construction:</b>	Triangular core
<b>Frequency:</b>	10 MHz to >6 GHz
<b>Linearity:</b>	±0.2 dB (30 MHz to 6 GHz)
<b>Probe Length (mm):</b>	337
<b>Probe Diameter (mm):</b>	10
<b>Tip Length (mm):</b>	9
<b>Tip Diameter (mm):</b>	2.5
<b>Sensor X Offset (mm):</b>	1
<b>Sensor Y Offset (mm):</b>	1
<b>Sensor Z Offset (mm):</b>	1
<b>E-Field Probe</b>	
<b>Model:</b>	ES3DV3
<b>Serial No:</b>	3304
<b>Construction:</b>	Triangular core
<b>Frequency:</b>	10 MHz to >4 GHz
<b>Linearity:</b>	±0.2 dB (30 MHz to 4 GHz)
<b>Probe Length (mm):</b>	337
<b>Probe Diameter (mm):</b>	10
<b>Tip Length (mm):</b>	10
<b>Tip Diameter (mm):</b>	4
<b>Sensor X Offset (mm):</b>	2
<b>Sensor Y Offset (mm):</b>	2
<b>Sensor Z Offset (mm):</b>	2

<b>DASY4 SAR System Specifications (Continued)</b>	
<b>E-Field Probe</b>	
<b>Model:</b>	ET3DV6
<b>Serial No:</b>	1528;1529
<b>Construction:</b>	Triangular core
<b>Frequency:</b>	10 MHz to 2.55GHz
<b>Linearity:</b>	±0.2 dB (30 MHz to 2.55GHz)
<b>Probe Length (mm):</b>	337
<b>Probe Diameter (mm):</b>	10
<b>Tip Length (mm):</b>	10
<b>Tip Diameter (mm):</b>	6.8
<b>Sensor X Offset (mm):</b>	2.7
<b>Sensor Y Offset (mm):</b>	2.7
<b>Sensor Z Offset (mm):</b>	2.7
<b>Phantom</b>	
<b>Phantom:</b>	SAM Phantom, Eli Phantom
<b>Shell Material:</b>	Fibreglass
<b>Thickness:</b>	2.0 ±0.1 mm

## Appendix 8. 3G Test set-up

### 3G (12.K RMC / HSDPA / HSUPA) setup

To switch from 2G to 3G, on the system config screen choose Format Switch and select WCDMA. The Call Setup Screen as shown in figure 1 pops up.

Call Setup Screen																													
Call Control	Active Cell Operating Mode						Call Parms																						
Operating Mode	<table border="1"> <thead> <tr> <th colspan="2">UE Information</th> </tr> </thead> <tbody> <tr> <td>INSI:</td> <td></td> </tr> <tr> <td>INEL(SU):</td> <td>(--)</td> </tr> <tr> <td>Power Class:</td> <td></td> </tr> </tbody> </table>						UE Information		INSI:		INEL(SU):	(--)	Power Class:		Cell Power														
UE Information																													
INSI:																													
INEL(SU):	(--)																												
Power Class:																													
Active Cell							-35.00																						
							dBm/3.84 MHz																						
							Channel Type																						
							12.2k RMC																						
							Paging Service																						
Originate Call	<table border="1"> <thead> <tr> <th colspan="2">UE Expected Open Loop Transmit Power</th> </tr> </thead> <tbody> <tr> <td>Initial PRACH TX Power:</td> <td>-60.00 dBm</td> </tr> <tr> <td>Initial DPCCCH TX Power:</td> <td>-11.55 dBm</td> </tr> </tbody> </table>						UE Expected Open Loop Transmit Power		Initial PRACH TX Power:	-60.00 dBm	Initial DPCCCH TX Power:	-11.55 dBm	RB Test Mode																
UE Expected Open Loop Transmit Power																													
Initial PRACH TX Power:	-60.00 dBm																												
Initial DPCCCH TX Power:	-11.55 dBm																												
Paging Parameters	<table border="1"> <thead> <tr> <th colspan="2">Call Processing Status</th> </tr> </thead> <tbody> <tr> <td>Current Service Type:</td> <td>None</td> </tr> <tr> <td>MM Status:</td> <td>None</td> </tr> <tr> <td>GMN State:</td> <td>None</td> </tr> <tr> <td>Current DPCH Offset:</td> <td>0 chips</td> </tr> </tbody> </table>						Call Processing Status		Current Service Type:	None	MM Status:	None	GMN State:	None	Current DPCH Offset:	0 chips	HSPA Parameters												
Call Processing Status																													
Current Service Type:	None																												
MM Status:	None																												
GMN State:	None																												
Current DPCH Offset:	0 chips																												
Handovers	<table border="1"> <thead> <tr> <th colspan="2">HSUPA Information</th> </tr> </thead> <tbody> <tr> <td>Rep EDCH Cat/Ext:</td> <td>Unrep/Unrep</td> </tr> <tr> <td>Last received E-TFCI:</td> <td>----</td> </tr> <tr> <td>Throughput:</td> <td>---- kbps</td> </tr> <tr> <td>Acks Transmitted:</td> <td>----</td> </tr> </tbody> </table>			HSUPA Information		Rep EDCH Cat/Ext:	Unrep/Unrep	Last received E-TFCI:	----	Throughput:	---- kbps	Acks Transmitted:	----	<table border="1"> <thead> <tr> <th colspan="2">HSDPA Information</th> </tr> </thead> <tbody> <tr> <td>Cur UE HS-DSCH Cat:</td> <td>----</td> </tr> <tr> <td>Block Error Ratio:</td> <td>---- %</td> </tr> <tr> <td>Throughput:</td> <td>---- kbps</td> </tr> <tr> <td>Blocks Transmitted:</td> <td>----</td> </tr> </tbody> </table>			HSDPA Information		Cur UE HS-DSCH Cat:	----	Block Error Ratio:	---- %	Throughput:	---- kbps	Blocks Transmitted:	----	34,121 Preset Call Configs		
HSUPA Information																													
Rep EDCH Cat/Ext:	Unrep/Unrep																												
Last received E-TFCI:	----																												
Throughput:	---- kbps																												
Acks Transmitted:	----																												
HSDPA Information																													
Cur UE HS-DSCH Cat:	----																												
Block Error Ratio:	---- %																												
Throughput:	---- kbps																												
Blocks Transmitted:	----																												
Clear UE Info							Channel (UARFCN) Parms																						
	Active Cell						Sys Type: UTRA FDD																						
	Idle																												
1 of 5	IntRef						1 of 3																						

Figure 1: 3G Call Setup Screen

For a 12.2k RMC call follow the steps below.

#### 8.1. Steps for 12.2k RMC

1. Ensure that the Operating Mode of the cell is off before setting up the instrument.
2. On the Call Setup Screen, under Call Parameters, press the button against Cell Power. The Cell Power value is set to about -35dBm to account for all the losses and ensure sufficient signal strength to the EUT.
3. The Channel Type is selected to 12.2k RMC. Press button against Channel (UARFCN) Parms select the correct Downlink Channel for the required UMTS FDD Band.
4. On the Call Setup Screen, under Call Parameters, press the button against HSPA Parameters. Under HSDPA Parameters on page 1, press HSDPA Uplink parameters and set the Delta ACK, Delta NACK, Delta CQI values to 8. Under HSDPA Parms itself, press HSDPA RB Test Mode Setup button and then the HSDPA RB Test Mode Settings and change HS-DSCH Data Pattern to All Ones.

Call Setup Screen									
Call Control	Active Cell Operating Mode						HSDPA Parm		
Close Menu	UE Information						HSDPA RB Test Node Setup		
	INSI: IMEI(SU): (---) Power Class:								
	UE Expected Open Loop Transmit Power						UE Category Parameters ▾		
	Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -11.55 dBm								
	HSDPA Uplink Parameters				Value		MAC-(e)hs Parameters ▾		
	DeltaACK				8				
	DeltaNACK				8				
	DeltaCQI				8				
	Ack-Nack Repetition Factor				1		HSDPA Uplink Parameters ▾		
	CQI Feedback Cycle (k)				2 ms				
CQI Repetition Factor				1					
						Return			
Active Cell Idle						Sys Type: UTRA FDD			
IntRef						1 of 2			

Figure 2: HSDPA Parameters

- On the Call Setup Screen, under Call Parameters, on page 2, check if the DL DTCH Data is set to All Ones. On page 3, ensure that the Receiver is set to Manual. On page 3 itself, under UL CL Power Ctrl Parameters, UL CL Power Ctrl Mode is set to All Up Bits.

Call Setup Screen									
Call Control	Active Cell Operating Mode						Call Parm		
Operating Mode	UE Information						DL DTCH Data		
Active Cell	INSI: IMEI(SU): (---) Power Class:						All Ones		
Originate Call	UE Expected Open Loop Transmit Power						RLC Reestablish		
	Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -11.55 dBm						Auto		
Paging Parameters ▾	Call Processing Status						Call Limit State		
	Current Service Type: None						Off		
	MM Status: None								
	GMM State: None						Call Drop Timer		
Handovers	Current DPCH Offset: 0 chips						On		
	HSUPA Information			HSDPA Information			SRB Parameters ▾		
Clear UE Info	Rep EDCH Cat/Ext: Unrep/Unrep			Cur UE HS-DSCH Cat: ----					
	Last received E-TFCI: ----			Block Error Ratio: ---- %					
	Throughput: ---- kbps			Throughput: ---- kbps					
1 of 5	Acks Transmitted: ----			Blocks Transmitted: ----					
	Active Cell Idle						Sys Type: UTRA FDD		
IntRef						2 of 3			

Figure 3: DL DTCH Data Parm



Call Setup Screen										
Call Control	Active Cell Operating Mode						Call Parm			
Additional Screens	UE Information						Cell Power	-35.00		
	INSI: INEI(SU): (--) Power Class:						dBm/3.84 MHz	Channel Type		
Cell Parameters	UE Expected Open Loop Transmit Power						12.2k RNC			
Generator Info	Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -11.55 dBm						Paging Service			
							RB Test Mode			
Uplink Parameters	Uplink Parameters					Value	HSPA Parameters  34,121 Preset Call Configs			
	PRACH Preambles					64				
	PRACH Ramping Cycles(MMAX)					2				
	Available Subchannels (Bit Mask)					000000000001				
	Uplink DPCH Scrambling Code					0				
UE Rep Neas	Uplink DPCH Bc/Bd Control					Auto	Channel (UARFCH) Parm			
	Manual Uplink DPCH Bc					8				
Close Menu	Manual Uplink DPCH Bd					15	1 of 3			
	Maximum Uplink Transmit Power Level					24 dBm				
		Active Cell			Sys Type: UTRA FDD					
		Idle								
2 of 5				IntRef						

Figure 6: Uplink Parameters

- On page 3 under Call Control, for the RB Test Mode setup, Asymmetric RMC CN Domain is ensured to be in CS Domain for RMC call.

Call Setup Screen										
Call Control	Active Cell Operating Mode						Call Parm			
	UE Information						Cell Power	-35.00		
	INSI: INEI(SU): (--) Power Class:						dBm/3.84 MHz	Channel Type		
	UE Expected Open Loop Transmit Power						12.2k RNC			
	Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -11.55 dBm						Paging Service			
Voice Call	RB Test Mode Settings					Value	RB Test Mode			
	Uplink DTCH RNC CRC Presence					Present	HSPA Parameters  34,121 Preset Call Configs			
	Uplink Dummy DCCH Data					Off				
	UE Loopback Type					Type 1				
	Asymmetric RNC Loopback Messaging					Close/Open				
Asymmetric RNC CN Domain					CS Domain					
Close Menu							Channel (UARFCH) Parm			
		Active Cell			Sys Type: UTRA FDD					
		Idle								
3 of 5				IntRef						

Figure 7: RB Test Mode Settings

- After the test set has been set up, change the cell Operating Mode to Active Cell and originate a call.

**8.2. Steps for 12.2k RMC + HSDPA/HSUPA**

1. Most of the steps to be followed are as in the case of 12.2k RMC however, some of the settings need to be changed. The Channel Type is changed to 12.2k RMC+HSDPA or 12.2k RMC+HSUPA as required.
2. For HSDPA and HSUPA, the settings remain same as the case for RMC but the PS Domain is made Present for Cell Parameters (Figure 5) and RB Test Mode Setup (Figure 7).
3. The following tables taken from FCC 3G SAR procedures (KDB 941225 D01 SAR test for 3G devices v02) below were applied to the Agilent 8960 series 10 wireless communications test set which supports 3G / HSDPA release 5 / HSUPA release 6.

**Sub-test 1 Setup for Release 5 HSDPA**

Sub-test	$\beta_c$	$\beta_d$	$B_d$ (SF)	$\beta_c/\beta_d$	$\beta_{hs}^{(1)}$	SM (dB) <sup>(2)</sup>
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15 <sup>(3)</sup>	15/15 <sup>(3)</sup>	64	12/15 <sup>(3)</sup>	24/15	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

Note 1:  $\Delta_{ACK}, \Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15, B_{hs}/\beta_c = 24/15$

Note 3: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$

**Sub-test 5 Setup for Release 6 HSUPA**

Sub-test	$\beta_c$	$\beta_d$	$B_d$ (SF)	$\beta_c/\beta_d$	$\beta_{hs}^{(1)}$	$B_{oc}$	$B_{od}$	$B_{od}$ (SF)	$B_{od}$ (codes)	CM <sup>(2)</sup> (dB)	MPR (dB)	AG <sup>(4)</sup> Index	E-TFCI
1	11/15 <sup>(3)</sup>	15/15 <sup>(3)</sup>	64	11/15 <sup>(3)</sup>	22/15	209/225	1039/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	31/15	$B_{a11}$ : 47/15 $B_{a12}$ : 47/15	4	1	2.0	1.0	15	92
4	2/15	15/15	64	2/15	2/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 <sup>(4)</sup>	15/15 <sup>(4)</sup>	64	15/15 <sup>(4)</sup>	24/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1:  $\Delta_{ACK}, \Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Leftrightarrow \beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15, B_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH AND E-DPCCH for the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .

Note 4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ .

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Tavle 5.1g.

Note 6:  $B_{od}$  can not be set directly; it is set by Absolute Grant Value.

Call Setup Screen			
<b>Call Control</b>	<b>Active Cell Operating Mode</b>		<b>Serving Grant</b>
Operating Mode	UE Information		AG Mode
Active Cell	INSI: INEI(SU): (---) Power Class:		Single Shot
Originate Call	UE Expected Open Loop Transmit Power		Single Shot AG
	Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -11.55 dBm		21: (134/15)*2
Paging Parameters	Call Processing Status		Send Single Shot Absolute Grant
	Current Service Type: None MM Status: Abs Single Shot AG GMM State: Index 18: (95/15)*2 Current DPCCH: Index 19: (106/15)*2		RB Setup AG
Handovers	HSUPA Information		AG Pattern Parameters
	Rep EDCH Cat: Index 20: (119/15)*2 Last received: Index 21: (134/15)*2 Throughput: Index 22: (150/15)*2 Acks Transmitted: Index 23: (168/15)*2		33: 4(134/15)*2
Clear UE Info	DPCCH Cat: ---- Ratio: ---- % : ---- kbps nsmitted: ----		Return
	Active Cell		
	Idle		
	Sys Type: UTRA FDD		
1 of 5	IntRef		1 of 2

Call Setup Screen			
<b>Call Control</b>	<b>Active Cell Operating Mode</b>		<b>Call Parms</b>
Additional Screens	UE Information		Cell Power
Cell Parameters	INSI: INEI(SU): (---) Power Class:		-35.00
	UE Expected Open Loop Transmit Power		dBm/3.84 MHz
Generator Info	Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -22.58 dBm		Channel Type
	Uplink Parameters		12.2k + HSDPA
Uplink Parameters	Value		Paging Service
	PRACH Preambles: 64		RB Test Mode
UE Rep Params	PRACH Ramping Cycles(MAX): 2		HSPA Parameters
	Available Subchannels (Bit Mask): 000000000001		34.121 Preset Call Configs
Close Menu	Uplink DPCCH Scrambling Code: 0		
	Uplink DPCCH Bc/Bd Control: Manual		Channel (UARFCN) Parms
Manual Uplink DPCCH Bc: 2			
Manual Uplink DPCCH Bd: 15			
Maximum Uplink Transmit Power Level: 24 dBm			
	Cell Off		
	Sys Type: UTRA FDD		
2 of 5	IntRef		1 of 3

- For HSUPA the Serving Grant Parameter needs to be set. On the Call Setup Screen, under Call Parameters, press the button against HSPA Parameters. On the new screen that pops up, press HSUPA and Serving Grant. The Serving Grant is set according to the table for HSPA in the KDB (AG Index). The correct AG is chosen from the Single Shot AG. Consecutively, the RG Setup AG is set as per the ratio set on Single Shot AG.

Call Setup Screen																		
<b>Call Control</b>	<b>Active Cell Operating Mode</b>					<b>Serving Grant</b>												
<b>Operating Mode</b>	<b>UE Information</b> INSI: INEI(SU): (---) Power Class:					<b>AG Mode</b>												
<b>Active Cell</b>						<b>AG Mode</b>												
	<b>UE Expected Open Loop Transmit Power</b> Initial PRACH TX Power: -60.00 dBm Initial DPCCH TX Power: -11.55 dBm					<b>Single Shot AG</b>												
<b>Originate Call</b>	<b>Call Processing Status</b> Current Service Type: None MM Status: None GMM State: None Current DPCH Offset: 0 chips					<b>31: 6(168/15)^2</b>												
						<b>Send Single Shot Absolute Grant</b>												
<b>Paging Parameters</b>	<b>HSUPA Information</b> Rep EDCH Cat/Ext: Unrep/Unrep Last received E-TFCI: ---- Throughput: ---- kbps Acks Transmitted: ----					<b>RB Setup AG</b>												
						<b>37: 6(168/15)^2</b>												
<b>Handovers</b>	<b>HSDPA Information</b> Cur UE HS-DSCH Cat: ---- Block Error Ratio: ---- % Throughput: ---- kbps Blocks Transmitted: ----					<b>AG Pattern Parameters</b>												
						<b>Return</b>												
<b>Clear UE Info</b>	<table border="1"> <tr> <td></td> <td></td> <td><b>Active Cell</b></td> <td></td> <td></td> <td><b>Sys Type: UTRA FDD</b></td> </tr> <tr> <td></td> <td></td> <td><b>Idle</b></td> <td></td> <td></td> <td></td> </tr> </table>							<b>Active Cell</b>			<b>Sys Type: UTRA FDD</b>			<b>Idle</b>				
		<b>Active Cell</b>			<b>Sys Type: UTRA FDD</b>													
		<b>Idle</b>																
<b>1 of 5</b>			<b>IntRef</b>			<b>1 of 2</b>												

Figure 8: Serving Grant Example

**Appendix 9. CAT24 Test set-up**

**A.9.1. Establish a DC-HSDPA RB Test Mode Connection with DL 42Mbps**

RB (radio bearer) test mode is a special, defined-channel configuration designed to simplify the testing environment. Since W-CDMA is an incredibly flexible system, defined radio bearers, called RMCs (reference measurement channels) simplify which configurations need to be tested for RF performance.

RB test mode provides the ability to set up a standalone channel configuration originating from the 8960 via call-processing. The direction of the call setup is always from the 8960 to the UE. This is the typical RF test that is used throughout the lifecycle of a device's design process. Using RB test mode is attractive to device manufacturers because it does not require extra software to control the UE. In this type of call connection, the radio bearer (within the 8960) essentially controls the UE during test.

**A.9.1.1 Configure 8960**

1. Press **Operating Mode (F1)**, select **Cell Off** operating mode.

Call Setup Screen			
Call Control	Active Cell Operating Mode		Call Parm
Operating Mode	UE Information		Cell Power
Cell Off	INSI:	Power Class:	-75.00
	INEL(SU):	Detected PRACH Sig: ----	dBm/3.84 MHz
	Called Party Number:		Channel Type
	UE Expected Open Loop Transmit Power		12.2k RMC
	Init PRACH TX Pou: -22.70 dBm	Init DPCCCH TX Pou: -11.55 dBm	Paging Service
Originate Call	Current Service Type		RB Test Mode
	None		
Paging Parameters	Call Processing Status		HSPA Parameters
	RRC State:	Operating Mode	Power State: Off
	RN Status:	Active Cell	Mode State: Off
	GINI State:	FDD Test	Offset: 0 chips
Handovers	HSUPA In CU		34.121 Preset Call Configs
	UE Rep E-DCH	Cell Off	DSCH Cat: 14
	Last Happy Bit		Ratio: ---- %
	Throughput:		---- kbps
Clear UE Info	ACKs Transmitt		Channel (UARFCH) Parm
	Background	Cell Off	Sys Type: UTRA FDD
			Logging: No Conn
1 of 5		IntRef Offset	1 of 3

2. Set the **Channel type** to **12.2k + HSDPA**.
3. Set the downlink channel code. In order to achieve the 42 Mbps maximum downlink throughput, you have to set up 15 HS-PDSCHs which will possibly cause a code collision. To easily configure the downlink 15 HS-PDSCH for a maximum throughput, use the code preset to configure the code channels for both the serving cell and the secondary serving cell. Select **Call Control 2 of 6-> Generator Info (F3) -> Downlink Channel Configs (F4) -> DL Chan code Preset Configs (F5)**, choose **34.121 Tables E.6.2.3,4 (HSDPA 15 HS-PDSCHs)**. Set the **Conn S-CCPCH Cfg** to **Off** to avoid the code collision. To see the channel code allocation for the serving cell and the secondary serving cell, select **Additional Gen Info Screens (F1) -> DC-HSDPA DL Code Chan Info (F4)**.

Call Setup Screen										
Screen Ctrl	DC-HSDPA DL Code Channel Information								Call Parms	
DL Code Channel Info Screen	Serving Cell Primary Scrambling Code: 0								Cell Power	
	Secondary Serving Cell Primary Scrambling Code: 2								-75.00	
Generated Power Info Screen	Channel				Serving Cell DL Chan Info				Sec Cell DL Chan Info	
	Channel	Level (dB)		Chan	Level (dB)		Chan			
OCNS Info Screen		Current	Desired	OVSF	Code	Current	Desired	OVSF	Code	
	CPICH:	Off	-3.30	256	0	Off	Off	256	0	
DC-HSDPA DL Code Chan Info	P-CCPCH/SCH:	Off	-5.30	256	1	Off	Off	256	1	
	S-CCPCH:	Off	-10.30	64	2					
Return	FICH:	Off	-8.30	256	2	Off	Off	256	2	
	AICH:	Off	-9.90	256	3					
	(F-)DPCH:	Off	Off	128	7					
	E-AGCH:	Off	Off	256	42					
	E-HICH:	Off	Off	128	22					
	E-RGCH:	Off	Off	128	22					
	HS-SCCH 1:	Off	Off	128	2	Off	Off	128	2	
	HS-SCCH 2:	Off	Off	128	3	Off	Off	128	3	
	HS-SCCH 3:									
	HS-SCCH 4:									
	HS-PDSCHs:	Off	Off	16	1-15	Off	Off	16	1-15	
	Comp OCNS:	Off	Off	128	HCDMA	Off	Off	128	HSDPA	
				Cell Off				Sys Type: UTRA FDD		
								Logging: No Conn		
				DBUS-INT	IntRef	Offset				
1 of 3										

4. Configure DC-HSDPA parameters to achieve the Maximum Downlink Data Rate: First of all, you must know the maximum data rate of the device under test according to its category and the key factors to achieve the maximum data rate. In this lab, you use a category 24 device whose maximum data rate is 42 Mbps when DC-HSDPA is configured.

a) Set up the HSDPA RB Test Mode Parameters

Path: Call Parms 1 of 3 -> HSPA Parameters (F10) -> HSDPA Parameters (F10) -> HSDPA RB Test Mode Setup (F8) -> HSDPA RB Test Mode Settings (F8).

- RB Test HS-DSCH Configuration Type = User Defined
- RB Test User Defined HS-DSCH MAC entity = MAC-ehs (Note 1)
- RB Test User Defined HARQ Processes = 6 (Note 2)
- RB Test User Defined UE IR Buffer Allocation = Implicit
- RB Test User Defined DC-HSDPA State = On
- RB Test Mode DC-HSDPA DPCH Loopback State = On

**Note 1:** DC-HSDPA requires MAC-ehs. You must set the MAC entity to MAC-ehs before setting the DC-HSDPA state)

**Note 2:** To restrict the amount of soft memory that can be allocated to a single HARQ process (and thus limit the amount of data that has to be transferred across the UE's internal data buses) the specifications require that when setting up a DC-HSDPA call with the implicit HARQ memory partitioning the network must configure 6, 7, or 8 HARQ processes per cell. For the explicit HARQ memory partitioning case, the number of HARQ processes can be 1 through 8, but the memory size for each HARQ process cannot be greater than the number of soft channel bits for an implicit memory partitioning with 6 processes per HS-DSCH channel.

b) Set up the Serving Cell Parameters

Path: F10

- RB Test User Defined 64QAM State =On
- RB Test User Defined Active HS-PDSCHs =15
- RB Test User Def Transport Block Size Index =62
- RB Test User Defined Modulation Type =64QAM
- RB Test User Defined Inter-TTI Interval =1

c) Set up the Secondary Serving Cell Parameters

*Path: F11*

- **RB Test User Def Secondary Cell 64QAM State = On**
- **RBTM User Def Sec Cell Active HS-PDSCHs = 15**
- **RBTM User Def Sec Cell TB Size Index = 62**
- **RBTM User Def Sec Cell Modulation Type = 64QAM**
- **RBTM User Def Sec Cell Inter-TTI Interval = 1**

d) Set the **Secondary Serving Cell Power (dBm/3.84 MHz) to -25 dBm/3.84 MHz**

*Path: Return (F12) -> HSDPA Parms 2 of 2 -> Secondary Serv Cell Parms (F10)*

e) Set the **Cell power to -25 dBm/3.84 MHz**

*Path: CALL SETUP -> F7*

f) Set the HSDPA Conn DL Channel Levels

*Path: CALL SETUP -> Call Control 2 of 6 -> Generator Info (F3) -> Downlink Channel Levels (F3) -> Connected DL Channel Levels (F3) -> F3*

- **HSDPA Cell 1 Connected CPICH Level = -8**
- **HSDPA Cell 1 Connected P-CCPCH/SCH Level = -20**
- **HSDPA Cell 1 Connected PICH Level = off**
- **HSDPA Cell 1 Connected DPCH Level = -30**
- **HSDPA Cell 1 Connected HS-PDSCH Level (Sum) = -1 dBm**
- **HSDPA Cell 1 Connected HS-SCCH 1 to 4 Level = -20,-20,off,off**
- **Secondary Cell HSDPA Conn CPICH Level = -8**
- **Secondary Cell HSDPA Conn PCCPCH/SCH Level = -20**
- **Secondary Cell HSDPA Conn PICH Level = off**
- **Secondary Cell HSDPA Conn HS-PDSCHs Lvl (Sum) = -1 dBm**
- **Secondary Cell HSDPA Conn HS-SCCH 1 to 4 Level = -20,-20,off,off**

5. Set the **Operating Mode (F1) to Active Cell.**

#### **A.9.1.2. Power on the UE and Set up the Connection**

Power on the device, and then wait for it to camp on 8960. You should be able to see the following screen.



Call Setup Screen										
Screen Ctrl	DC-HSDPA DL Code Channel Information								Call Parms	
DL Code Channel Info Screen	Serving Cell Primary Scrambling Code: 0								Cell Power	
	Secondary Serving Cell Primary Scrambling Code: 2								-25.00	
Generated Power Info Screen	Channel				Serving Cell DL Chan Info				Sec Cell DL Chan Info	
	Channel	Level (dB)		Chan		Level (dB)		Chan		Channel Type
OCNS Info Screen	CPICH:	-8.00	-8.00	256	0	-8.00	-8.00	256	0	12.2k + HSDPA
	P-CCPCH/SCH:	-20.00	-20.00	256	1	-20.00	-20.00	256	1	Paging Service
DC-HSDPA DL Code Chan Info	S-CCPCH:	Off	Off	64	2					RB Test Mode
	PICH:	Off	Off	256	2	Off	Off	256	2	
Return	AICH:									
	(F-)DPCH:	-30.00	-30.00	128	7					HSPA Parameters
	E-AGCH:	Off	Off	256	42					
	E-HICH:	Off	Off	128	22					
	E-RGCH:	Off	Off	128	22					
	HS-SCCH 1:	-20.00	-20.00	128	2	-20.00	-20.00	128	2	34,121 Preset Call Configs
	HS-SCCH 2:	-20.00	-20.00	128	3	-20.00	-20.00	128	3	
	HS-SCCH 3:									
	HS-SCCH 4:									
	HS-PDSCHs:	-1.00	-1.00	16	1-15	-1.00	-1.00	16	1-15	Channel (UARFCN) Parms
	Comp OCNS:	-17.91	-17.91	128	HSDPA	-17.65	-17.65	128	HSDPA	
	Active Cell Connected				Sys Type: UTRA FDD				Logging: No Conn	
	DBUS-INT		IntRef	Offset						1 of 3

### A.9.2. Activate/ Deactivate the Secondary Serving Cell

Once a DC-HSDPA connection is established, 8960 can control the UE to start or stop monitoring the secondary serving cell using HS-SCCH orders. The HS-SCCH orders can be sent on either the serving or secondary serving cell.

#### A.9.2.1 Deactivate the Secondary Serving Cell

1. Setup the Deactivate Secondary Cell Parameter

Path: CALL SETUP->Call Control 6 of 6 -> HS-SCCH Order (F3) -> Deactivate Secondary Cell (F2)  
 In this lab you set it to deactivate the secondary serving cell from the serving cell.

- Deactivate Secondary Cell HS-SCCH Order From = Serving Cell

Press **Send Deactivate Secondary Cell (F5)**

Press Measurement Reset key and see the throughput has dropped to 21 Mbps or so, like the figure below:

Call Setup Screen										
Call Control	Active Cell Operating Mode							Call Parm		
Operating Mode	UE Information							Cell Power		
Active Cell	MNSI: 001012345678901			Power Class: 4				-25.00		
	IMEI(SU):352358040214948(--)			Detected PRACH Sig: 0				dBm/3.84 MHz		
	Called Party Number:							Channel Type		
	UE Expected Open Loop Transmit Power							12.2k + HSDPA		
	Init PRACH TX Pou: -60.00 dBm			Init DPCH TX Pou: -11.55 dBm				Paging Service		
End Call	Current Service Type							RB Test Mode		
	RB Test Mode - HSDPA									
Paging Parameters	Call Processing Status							HSPA Parameters		
	RRC State: CELL_DCH		Soft Handover State: Off							
	MM Status: None		Compressed Mode State: Off							
	GMM State: Attached		Cur DPCH Offset: 0 chips							
Handovers	HSDPA Information				HSDPA Information				34,121 Preset Call Configs	
	Rep EDCH Cat/Ext: 6/Unrep		Cur UE HS-DSCH Cat: 24							
	Last Happy Bit: None		Block Error Ratio: 0 %							
	Throughput: ---- kbps		Throughput: 21088 kbps							
Clear UE Info	ACKs Transmitted: ----		Blocks Transmitted: 35000					Channel (UARFCN) Parm		
	Active Cell			Sys Type: UTRA FDD						
	Connected			Logging: No Conn						
1 of 6	DBUS-INT	IntRef	Offset						1 of 3	

You can see more on the DC-HSDPA Information screen.

Path: CALL SETUP->Call Control 2 of 6 -> Additional Screens (F1) -> HSDPA Information (F4) -> DC-HSDPA Information (F4).

Call Setup Screen									
Screen Ctrl	DC-HSDPA Information							Call Parm	
Channel (UARFCN) Info	Secondary Serving Cell Status							Cell Power	
	Current Secondary Serving Cell Status: Configured-Inactive							-25.00	
								dBm/3.84 MHz	
HSPA Information	DC-HSDPA Information							Channel Type	
	Summary Serving Cell Secondary Serving Cell							12.2k + HSDPA	
E-TFCI Recording Information	Block Error Ratio: 0 %		0 %		---- %			Paging Service	
	Throughput (kbps): 21082		21082		0			RB Test Mode	
	Blocks Transmitted: 66000		66000		0				
	ACKs Received: 65958		65958		0				
HSDPA Information	NACKs Received: 42		42		0			HSPA Parameters	
	statDTXs Received: 0		0		0				
	Count of Rep CQI Lim: ----		----		----				
	Last Received CQI: 30		30		30				
Clear UE Info	Max Allowed CQI: ----		----		----			34,121 Preset Call Configs	
	Test Mode User Def TBS: 42192		42192		42192				
	PS Data User Def TBS: 7298		7298		7298				
Return	Last Sig Meas Pur Offs (dB): 6.0		6.0		6.0			Channel (UARFCN) Parm	
	Active Cell			Sys Type: UTRA FDD					
	Connected			Logging: No Conn					
1 of 2	DBUS-INT	IntRef	Offset						1 of 3

### A.9.2.2 Re-activate the Secondary Serving Cell

Now you can activate the secondary serving cell by pressing back to the HS-SCCH Order menu.

Path: CALL SETUP->Call Control 6 of 6 -> HS-SCCH Order (F3)

Press **Send Activate Secondary Cell (F1)**.

Press the Measurement Reset key and see the throughput has increased to 42 Mbps. When you look at the DC-HSDPA Information screen, you can see the secondary serving cell is set up again.

Call Setup Screen									
Screen Ctrl	DC-HSDPA Information						Call Parms		
Channel (UARFCN) Info	Secondary Serving Cell Status						Cell Power		
	Current Secondary Serving Cell Status: Configured-Active						-25.00		
HSPA Information	DC-HSDPA Information						dBm/3.84 MHz		
							Channel Type		
E-TFCI Recording Information							12.2k + HSDPA		
							Paging Service		
HSDPA Information							RB Test Mode		
							HSPA Parameters		
Clear UE Info							34,121 Preset Call Configs ▾		
							Channel (UARFCN) Parms		
Return									
1 of 2	Active Cell Connected				Sys Type: UTRA FDD				
					Logging: No Conn				
	DBUS-INT	IntRef	Offset				1 of 3		

When DC-HSDPA is active, the HBLER measurement can also be used to perform receiver testing. 3GPP TS 34.121-1 sections 6.3C and 6.3D are supported and can be set up and tested as described in an appendix in another document, DC-HSDPA User Guide.