

Company Internal

Prepared (also subject responsible if other)

Flora Kang (28848956)

Approved

Flora Kang (28848956)

Checked

No.

XXXX-XXXX

Date

2013-09-23

Rev

1

Reference

4

C6916, Mobile Phone Label Content Specification, Made in, Front

1 General information

Mobile Phone label part no	<ul style="list-style-type: none"> 1275-7241
Bar code	<ul style="list-style-type: none"> Standard: according to Ericsson corporate standard 102 01–109 Uen Print quality: C, according to ANSI X3.182-1990 as stated in Ericsson corporate standard 102 01–1003 Uen Quiet zone: No bar codes are allowed to be closer to a label edge than 2 mm!
Text	If applicable, or nothing else specified, Zebra printer Scaleable Smooth Font CG Triumvirate Bold Condensed is imposed. When needed, the text is adjusted to fit the label.
Coordinates	“(x/y)” under each line number specifies the bottom / left alignment for text, graphics and bar codes, x is measured vertically, and y horizontally from the upper left corner of the label (landscape format), both in mm. When needed, the alignment is adjusted to fit the label.

2 Printing information

	Content	Format
Line 1 (2,3/3,0)	SONY stylized name.	Graphics, height 1,8 mm, width 10mm According to 1263-9535.
Line 2 (4,0/1,0)	Model Name of the included device “Model: C6916”	Text, height 1,2 mm. <i>According to Chapter 1 in MLCL.</i>
Line 3a (5,7/1,0)	“TYPE: PM-0590-BV”	Text, height 1,2 mm. <i>According to Chapter 1 in MLCL.</i>
Line 3b (5,7/13,0)	HW & SW identification field, if applicable; “EFF”	Text, height 1,2 mm. <i>According to Type-testing report under Product Model Specifying Document</i>
Line 4a (7,4/1,0)	“FCC ID: PY7PM-0590”	Text, height 1,2 mm, <i>According to Chapter 1 in MLCL.</i>
Line 4b (7,4/13,0)	Location code of where the phone is flashed, if applicable, “XXX”	Text, height 1,2 mm.
Line 5 (9,7/2,0)	Line 6 in bar code (only actual number, without data identifier).	Bar code, height 2,0 mm. Code 128 symbology, code C subset. If uneven number of digits, code B subset shall be used for the last digit.
Line 6 (11,2/1,0)	Actual electronic serial number (IMEI) of the mobile phone, “00000000-000000-0”	Text, height 1,2 mm. In the format TAC-SNR-CD. TAC and SNR derived from pos 500 in BOM. CD = check digit according to the Luhn formula (ISO/IEC 7812), GSM 02.16.

3 Layout

The conceptual picture (for Zebra 90XiII printer, or equivalent) should not be considered as specifications, but as an additional help for setting up the label.

Company Internal

Prepared (also subject responsible if other)

Flora Kang (28848956)

Approved

Flora Kang (28848956)

Checked

No.

1280-1289

Date

2013-09-23

Rev

1

Reference

4

3.1 Conceptual picture



double underlined = major changes since last revision.