FCC PART 15C
TEST REPORT
No. 2013WLN0792

for

Sony Mobile Communications AB

GSM/WCDMA/LTE mobile phone

Type: PM-0640-BV

With

FCC ID: PY7PM-0640

Hardware Version: A

Software Version: 14.2.A.0.78

Issued Date: 2013-11-18

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China, 100191

Tel: +86(0)10-62304633-2561, Fax: +86(0)10-62304633-2504 Email:welcome@emcite.com. www.emcite.com

CONTENTS

1. TEST LATORATORY

1.1. Testing Location

Company Name:	TMC Beijing, Telecommunication Metrology Center of MIIT
Address:	No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China
Postal Code:	100191
Telephone:	+86-10-62304633-2561
Fax:	+86-10-62304633-2504

1.2. Project data

Testing Start Date:	2013-10-30
Testing End Date:	2013-11-6

1.3. Signature



Xu Zhongfei

(Prepared this test report)



Jiang Afang

(Reviewed this test report)

Xiao Li

Deputy Director of the laboratory

(Approved this test report)

2. CLIENT INFORMATION

2.1. Applicant Information

Company Name:	Sony Mobile Communications AB
Address /Post:	Sony Mobile R&D Center, No. 16, Guangshun South Street, Chaoyang District
City:	Beijing
Postal Code:	100102
Country:	China
Contact Person:	Ma, Gang
Telephone:	+86-10-58656312
Fax:	+86-10-58659049

2.2. Manufacturer Information

Company Name:	Sony Mobile Communications AB
Address /Post:	Sony Mobile R&D Center, No. 16, Guangshun South Street, Chaoyang District
City:	Beijing
Postal Code:	100102
Country:	China
Contact Person:	Ma, Gang
Telephone:	+86-10-58656312
Fax:	+86-10-58659049

3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT(AE)

3.1. About EUT

Description	GSM 850/900/1800/1900 quad bands, GPRS, EDGE, WCDMA FDD bands 1/2/4/5/8, HSDPA, HSUPA, LTE FDD bands 1/2/3/4/5/7/8/20, Bluetooth (EDR and 4.0), ANT+, WLAN (802.11 a/ac/b/g/n), NFC, FM, GPS mobile phone
Type	PM-0640-BV
FCC ID	PY7PM-0640
WLAN Frequency Range	ISM Band: 5725MHz~5850MHz
Type of modulation	OFDM
MAX Conducted Power	20.74dBm(OFDM)
MAX Radiated Power	22.69dBm(OFDM)
Extreme Temperature	-30/+55°C
Extreme vol. Limits	3.6VDC to 4.2VDC (nominal: 4.2VDC)

Note: Photographs of EUT are shown in ANNEX C of this test report. Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	S/N	IMEI	HW Version	SW Version
EUT1	CB5A1VG620	004402451604411	A	14.2.A.0.78
EUT2	CB5A1VG61J	004402451604122	A	14.2.A.0.78

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	Type	SN
AE1	USB Cable	AI-0401	123307DD003654E

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment Under Test (EUT) is a model of GSM/WCDMA/LTE mobile phone with integrated antenna and inbuilt battery.

The EUT supports GSM 850/900/1800/1900MHz bands, WCDMA FDD band 1/5/6/19 and LTE FDD bands 1/3/19/21. It supports GPRS service with multi-slots class 33 and EGPRS service with multi-slots class 33. The HSDPA and HSUPA features are also supported.

It has MP3, camera, USB memory, Mobile High-Definition Link (MHL), FM radio, GPS receiver, NFC, Bluetooth (EDR and Bluetooth 4.0), ANT+, WLAN (802.11 a/ac/b/g/n) and Wi-Fi hotspot functions. For WLAN 802.11n, it supports 20MHz bandwidth on 2.4GHz band and 20MHz/40MHz

bandwidths on 5GHz/5.8GHz band. For WLAN 802.11 ac, it supports 20MHz/40MHz/80MHz bandwidths.
It consists of normal options: battery and travel charger.
Manual and specifications of the EUT were provided to fulfil the test.
Samples undergoing test were selected by the client.

4. REFERENCE DOCUMENTS

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz.	Oct, 2012
ANSI C63.10	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2009
KDB558074	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247	2013
KDB644545	Guidance for IEEE 802.11ac and Pre-ac Device Emissions Testing	2013

5. LABORATORY ENVIRONMENT

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

6. SUMMARY OF TEST RESULTS

6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.247 (b)	/	**P**
Peak Power Spectral Density	15.247 (e)	/	**P**
Occupied 6dB Bandwidth	15.247 (a)	/	**P**
Band Edges Compliance	15.247 (b)	/	**P**
Transmitter Spurious Emission - Conducted	15.247	/	**P**
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	/	**P**
AC Powerline Conducted Emission	15.107, 15.207	/	**P**

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by TMC
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

6.2. Statements

TMC has evaluated the test cases requested by the client/manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.1.

This report only deals with the WLAN function among the features described in section 3.

6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26℃
Voltage	4.2V
Humidity	44%

7. TEST EQUIPMENTS UTILIZED

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	2013-07-08	2014-07-07
2	Test Receiver	ESS	847151/015	Rohde & Schwarz	2012-12-29	2013-10-30
3	LISN	ESH2-Z5	829991/012	Rohde & Schwarz	2013-4-15	2014-08-12
4	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Calibration Due date
1	Test Receiver	ESU26	100376	Rohde & Schwarz	2012-11-8	2013-11-7
2	BiLog Antenna	VULB9163	9163-514	Schwarzbeck	2011-11-11	2014-11-10
3	Dual-Ridge Waveguide Horn Antenna	3117	00119024	ETS-Lindgren	2011-2-2	2014-2-1
4	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2011-7-1	2014-06-30
5	Loop antenna	HFH2-Z2	829324/007	Rohde & Schwarz	2011-12-21	2014-12-20
6	Semi-anechoic chamber	/	CT000332-1074	Frankonia German	/	/

ANNEX A: MEASUREMENT RESULTS

A.1. Measurement Method

A.1.1. Conducted Measurements

1). Connect the EUT to the test system correctly.
2). Set the EUT to the required work mode.
3). Set the EUT to the required channel.
4). Set the spectrum analyzer to start measurement.
5). Record the values. Vector Signal Analyzer



A.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,
Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;
Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



The measurement is made according to ANSI C63.10 and KDB558074
The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

A.2. Maximum Peak Output Power

Measurement Limit and Method:

Standard	Limit (dBm)
FCC CRF Part 15.247(b)	< 30

The measurement is made according to ANSI C63.10 .

Measurement Uncertainty:

Measurement Uncertainty	0.75dB

A.2.1. Output Power Verification

This test is only for mode verification, and the selected mode will be used for the future measurement.

Measurement Results:

OFDM/a mode	Maximum Conducted Power (dBm)							
data rate (Mbps)	6	9	12	18	24	36	48	54
149 (5745 MHz)	20.54	20.49	20.31	20.29	14.96	14.92	15.02	15.03

OFDM/n-HT20 mode	Maximum Conducted Power (dBm)							
data rate (Mbps)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
149 (5745 MHz)	20.46	20.29	20.31	14.92	14.96	15.01	15.03	15.03

OFDM/n-HT40 mode	Maximum Conducted Power (dBm)							
data rate (Mbps)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
151 (5755 MHz)	19.29	18.64	19.11	17.08	17.10	17.19	17.17	17.16

OFDM/ac-HT80 mode	Maximum Conducted Power (dBm)							
data rate (Mbps)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
155 (5775 MHz)	17.28	16.73	16.79	15.01	14.91	14.84	15.02	14.66

Selected data rate for all measurement:

OFDM /a-mode: 6Mbps

OFDM /n-HT20 mode: MCS0

OFDM /n-HT40 mode: MCS0

OFDM /ac-HT80 mode: MCS0

A.2.2. Antenna Gain

The antenna gain of the complete system is calculated by the difference of radiated power and the conducted power of the EUT.

Test	Channel		
Tnom,Vnom	149	157	165
Conducted Power(dBm)	16.05	16.14	16.22
Radiated Power(dBm)	17.66	18.09	18.05
Gain(dBi)	1.61	1.95	1.83

Antenna Gain = Radiated value (with radiated sample) - Conducted values (with conducted samples)

A.2.3. Maximum Peak Output Power

Measurement Results:

802.11a

Mode	Test Result (dBm)					
	5745 MHz (Ch149)		5785 MHz (Ch157)		5825 MHz (Ch165)	
	Conducted	Radiated	Conducted	Radiated	Conducted	Radiated
802.11a	20.54	22.15	20.36	22.31	20.41	22.24

802.11n-HT20

Mode	Test Result (dBm)					
	5745 MHz (Ch149)		5785 MHz (Ch157)		5825 MHz (Ch165)	
	Conducted	Radiated	Conducted	Radiated	Conducted	Radiated
802.11n-HT20	20.46	22.07	20.74	22.69	20.41	22.24

802.11n-HT40

Mode	Test Result (dBm)			
	5755 MHz (Ch151)		5795 MHz (Ch159)	
	Conducted	Radiated	Conducted	Radiated
802.11n-HT40	19.29	20.90	17.41	19.36

802.11ac-HT80

Mode	Test Result (dBm)	
	5775 MHz (Ch155)	
	Conducted	Radiated
802.11ac-HT80	17.28	19.23

Conclusion: PASS

A.3. Peak Power Spectral Density

Measurement Limit:

Standard	Limit
FCC CRF Part 15.247(e)	< 8 dBm/3 kHz

The measurement is made according to ANSI C63.10 and KDB558074

Measurement Uncertainty:

Measurement Uncertainty	0.75dB

Measurement Results:

Mode	Channel	Power Spectral Density (dBm/3 kHz)	Conclusion
802.11a	149	-13.23	P
	157	-11.87	P
	165	-14.23	P
802.11n HT20	149	-13.66	P
	157	-12.85	P
	165	-14.13	P
802.11n HT40	151	-18.19	P
	159	-19.21	P
802.11ac-HT80	155	-22.41	P

Conclusion: PASS

A.4. Occupied 6dB Bandwidth

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500

The measurement is made according to ANSI C63.10 .

Measurement Uncertainty:

Measurement Uncertainty	60.80Hz

Measurement Result:

Mode	Channel	Occupied 6dB Bandwidth (kHz)		conclusion
802.11a	149	Fig.1	16506	P
	157	Fig.2	16506	P
	165	Fig.3	16506	P
802.11n HT20	149	Fig.4	17788	P
	157	Fig.5	17788	P
	165	Fig.6	17788	P
802.11n HT40	151	Fig.7	35737	P
	159	Fig.8	35737	P
802.11ac-HT80	155	Fig.9	75641	P

Conclusion: PASS

Test graphs as below:



Fig. 1 Occupied 6dB Bandwidth (802.11a, Ch 149)



Fig. 2 Occupied 6dB Bandwidth (802.11a, Ch 157)



Fig. 3 Occupied 6dB Bandwidth (802.11a, Ch 165)



Fig. 4 Occupied 6dB Bandwidth (802.11n-HT20, Ch 149)



Fig. 5 Occupied 6dB Bandwidth (802.11n-HT20, Ch 157)



Fig. 6 Occupied 6dB Bandwidth (802.11n-HT20, Ch 165)



Fig. 7 Occupied 6dB Bandwidth (802.11n-HT40, Ch 151)



Fig. 8 Occupied 6dB Bandwidth (802.11n-HT40, Ch 159)



Fig. 9 Occupied 6dB Bandwidth (802.11ac-HT80, Ch 155)

A.5. Transmitter Spurious Emission

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

The measurement is made according to ANSI C63.10 .

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Measurement Uncertainty:

Frequency Range	Uncertainty(dB)
30MHz ≤ f ≤ 2GHz	0.63
2GHz ≤ f ≤3.6GHz	0.82
3.6GHz ≤ f ≤8GHz	1.55
8GHz ≤ f ≤20GHz	1.86
20GHz ≤ f ≤22GHz	1.90
22GHz ≤ f ≤26GHz	2.20

A.5.1 Transmitter Spurious Emission - Conducted

Measurement Results:

802.11a mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11a	149	5.745 GHz	Fig.10	P
		30 MHz ~ 12 GHz	Fig.11	P
		12 GHz ~ 25 GHz	Fig.12	P
		25 GHz ~ 40 GHz	Fig.13	P
	157	5.785 GHz	Fig.14	P
		30 MHz ~ 12 GHz	Fig.15	P
		12 GHz ~ 25 GHz	Fig.16	P
		25 GHz ~ 40 GHz	Fig.17	P
	165	5.825 GHz	Fig.18	P
		30 MHz ~ 12 GHz	Fig.19	P
		12 GHz ~ 25 GHz	Fig.20	P
		25 GHz ~ 40 GHz	Fig.21	P

802.11n-HT20 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n HT20	149	5.745 GHz	Fig.22	P
		30 MHz ~ 12 GHz	Fig.23	P
		12 GHz ~ 25 GHz	Fig.24	P
		25 GHz ~ 40 GHz	Fig.25	P
	157	5.785 GHz	Fig.26	P
		30 MHz ~ 12 GHz	Fig.27	P
		12 GHz ~ 25 GHz	Fig.28	P
		25 GHz ~ 40 GHz	Fig.29	P
	165	5.825 GHz	Fig.30	P
		30 MHz ~ 12 GHz	Fig.31	P
		12 GHz ~ 25 GHz	Fig.32	P
		25 GHz ~ 40 GHz	Fig.33	P

802.11n-HT40 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11n HT40	151	5.755 GHz	Fig.34	P
		30 MHz ~ 12 GHz	Fig.35	P
		12 GHz ~ 25 GHz	Fig.36	P
		25 GHz ~ 40 GHz	Fig.37	P
	159	5.795 GHz	Fig.38	P
		30 MHz ~ 12 GHz	Fig.39	P
		12 GHz ~ 25 GHz	Fig.40	P
		25 GHz ~ 40 GHz	Fig.41	P

802.11ac-HT80 mode

MODE	Channel	Frequency Range	Test Results	Conclusion
802.11ac HT80	155	5.775 GHz	Fig.42	P
		30 MHz ~ 12 GHz	Fig.43	P
		12 GHz ~ 25 GHz	Fig.44	P
		25 GHz ~ 40 GHz	Fig.45	P

Conclusion: PASS

Test graphs as below:



Fig. 10 Conducted Spurious Emission (802.11a, Ch149, Center Frequency)



Fig. 11 Conducted Spurious Emission (802.11a, Ch149, 30 MHz-12 GHz)



Fig. 12 Conducted Spurious Emission (802.11a, Ch149, 12 GHz-25 GHz)



Fig. 13 Conducted Spurious Emission (802.11a, Ch149, 25 GHz-40 GHz)



Fig. 14 Conducted Spurious Emission (802.11a, Ch157, Center Frequency)



Fig. 15 Conducted Spurious Emission (802.11a, Ch157, 30 MHz-12 GHz)



Fig. 16 Conducted Spurious Emission (802.11a, Ch157, 12 GHz-25 GHz)



Fig. 17 Conducted Spurious Emission (802.11a, Ch157, 25 GHz-40 GHz)



Fig. 18 Conducted Spurious Emission (802.11a, Ch165, Center Frequency)



Fig. 19 Conducted Spurious Emission (802.11a, Ch165, 30 MHz-12 GHz)



Fig. 20 Conducted Spurious Emission (802.11a, Ch165, 12 GHz-25 GHz)



Fig. 21 Conducted Spurious Emission (802.11a, Ch165, 25 GHz-40 GHz)



Fig. 22 Conducted Spurious Emission (802.11n-HT20, Ch149, Center Frequency)



Fig. 23 Conducted Spurious Emission (802.11n-HT20, Ch149, 30 MHz-12 GHz)



Fig. 24 Conducted Spurious Emission (802.11n-HT20, Ch149, 12 GHz-25 GHz)



Fig. 25 Conducted Spurious Emission (802.11n-HT20, Ch149, 25 GHz-40 GHz)



Fig. 26 Conducted Spurious Emission (802.11n-HT20, Ch157, Center Frequency)



Fig. 27 Conducted Spurious Emission (802.11n-HT20, Ch157, 30 MHz-12 GHz)



Fig. 28 Conducted Spurious Emission (802.11n-HT20, Ch157, 12 GHz-25 GHz)



Fig. 29 Conducted Spurious Emission (802.11n-HT20, Ch157, 25 GHz-40 GHz)



Fig. 30 Conducted Spurious Emission (802.11n-HT20, Ch165, Center Frequency)



Fig. 31 Conducted Spurious Emission (802.11n-HT20, Ch165, 30 MHz-12 GHz)



Fig. 32 Conducted Spurious Emission (802.11n-HT20, Ch165, 12 GHz-25 GHz)



Fig. 33 Conducted Spurious Emission (802.11n-HT20, Ch165, 25 GHz-40 GHz)



Fig. 34 Conducted Spurious Emission (802.11n-HT40, Ch151, Center Frequency)



Fig. 35 Conducted Spurious Emission (802.11n-HT40, Ch151, 30 MHz-12 GHz)



Fig. 36 Conducted Spurious Emission (802.11n-HT40, Ch151, 12 GHz-25 GHz)



Fig. 37 Conducted Spurious Emission (802.11n-HT40, Ch151, 25 GHz-40 GHz)



Fig. 38 Conducted Spurious Emission (802.11n-HT40, Ch159, Center Frequency)



Fig. 39 Conducted Spurious Emission (802.11n-HT40, Ch159, 30 MHz-12 GHz)



Fig. 40 Conducted Spurious Emission (802.11n-HT40, Ch159, 12 GHz-25 GHz)



Fig. 41 Conducted Spurious Emission (802.11n-HT40, Ch159, 25 GHz-40 GHz)



Fig. 42 Conducted Spurious Emission (802.11ac-HT80, Ch155, Center Frequency)



Fig. 43 Conducted Spurious Emission (802.11ac-HT80, Ch155, 30 MHz-12 GHz)



Fig. 44 Conducted Spurious Emission (802.11ac-HT80, Ch155, 12 GHz-25 GHz)



Fig. 45 Conducted Spurious Emission (802.11ac-HT80, Ch155, 25 GHz-40 GHz)

A.5.2 Transmitter Spurious Emission - Radiated

Measurement Uncertainty:

Frequency Range	Uncertainty(dB)
f ≤ 1GHz	3.9
f>1GHz	4.3

Measurement Results:

802.11a mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11a	149	30 MHz ~1 GHz	Fig.46	P
		1 GHz ~ 6 GHz	Fig.47	P
		6 GHz ~ 18 GHz	Fig.48	P
	157	30 MHz ~1 GHz	Fig.49	P
		1 GHz ~ 6 GHz	Fig.50	P
		6 GHz ~ 18 GHz	Fig.51	P
	165	30 MHz ~1 GHz	Fig.52	P
		1 GHz ~ 6 GHz	Fig.53	P
		6 GHz ~ 18 GHz	Fig.54	P
/	All channels	18 GHz ~ 26.5 GHz	Fig.55	P
		26.5 GHz~ 40 GHz	Fig.56	P

802.11n-HT20 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT20)	149	30 MHz ~1 GHz	Fig.57	P
		1 GHz ~ 6 GHz	Fig.58	P
		6 GHz ~ 18 GHz	Fig.59	P
	157	30 MHz ~1 GHz	Fig.60	P
		1 GHz ~ 6 GHz	Fig.61	P
		6 GHz ~ 18 GHz	Fig.62	P
	165	30 MHz ~1 GHz	Fig.63	P
		1 GHz ~ 6 GHz	Fig.64	P
		6 GHz ~ 18 GHz	Fig.65	P
/	All channels	18 GHz ~ 26.5 GHz	Fig.66	P
		26.5 GHz~ 40 GHz	Fig.67	P

802.11n-HT40 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n (HT40)	151	30 MHz ~1 GHz	Fig.68	P
		1 GHz ~ 6 GHz	Fig.69	P
		6 GHz ~ 18 GHz	Fig.70	P
	159	30 MHz ~1 GHz	Fig.71	P
		1 GHz ~ 6 GHz	Fig.72	P
		6 GHz ~ 18 GHz	Fig.73	P
/	All channels	18 GHz ~ 26.5 GHz	Fig.74	P
		26.5 GHz~ 40 GHz	Fig.75	P

802.11ac-HT80 mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11ac (HT80)	155	30 MHz ~1 GHz	Fig.76	P
		1 GHz ~ 6 GHz	Fig.77	P
		6 GHz ~ 18 GHz	Fig.78	P
		18 GHz ~ 26.5 GHz	Fig.79	P
		26.5 GHz~ 40 GHz	Fig.80	P

Conclusion: PASS

Note:

A "reference path loss" is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

802.11a

Ch149

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17891.250	55.7	-18.5	45.6	28.600	HORIZONTAL
17918.250	54.0	-17.7	45.6	26.100	VERTICAL
17790.750	54.0	-18.5	45.6	26.900	VERTICAL
17770.500	54.0	-18.5	45.6	26.900	VERTICAL
17877.750	54.0	-18.5	45.6	26.900	VERTICAL
17685.000	53.7	-18.9	45.6	27.000	HORIZONTAL

Ch157

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17958.000	55.1	-17.7	45.6	27.200	HORIZONTAL
17745.000	54.3	-18.5	45.6	27.200	VERTICAL
17940.000	54.3	-17.7	45.6	26.400	HORIZONTAL
17811.750	54.2	-18.5	45.6	27.100	HORIZONTAL
18000.000	54.1	-17.7	47.7	24.100	VERTICAL
17903.250	54.0	-18.5	45.6	26.900	HORIZONTAL

Ch165

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17988.000	54.9	-17.7	45.6	27.000	HORIZONTAL
17917.500	54.6	-17.7	45.6	26.700	VERTICAL
17981.250	54.4	-17.7	45.6	26.500	HORIZONTAL
17959.500	54.4	-17.7	45.6	26.500	VERTICAL
17748.750	54.3	-18.5	45.6	27.200	VERTICAL
17938.500	54.0	-17.7	45.6	26.100	VERTICAL

802.11n-HT20

Ch149

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17970.750	54.3	-17.7	45.6	26.400	HORIZONTAL
17975.250	54.0	-17.7	45.6	26.100	VERTICAL
17974.500	53.9	-17.7	45.6	26.000	HORIZONTAL
17879.250	53.9	-18.5	45.6	26.800	HORIZONTAL
17968.500	53.8	-17.7	45.6	25.900	HORIZONTAL
17913.000	53.7	-18.5	45.6	26.600	VERTICAL

Ch157

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17793.000	54.2	-18.5	45.6	27.100	VERTICAL
17922.750	53.7	-17.7	45.6	25.800	VERTICAL
17666.250	53.6	-18.9	45.6	26.900	HORIZONTAL
17955.000	53.6	-17.7	45.6	25.700	VERTICAL
17961.000	53.5	-17.7	45.6	25.600	HORIZONTAL
17799.750	53.4	-18.5	45.6	26.300	VERTICAL

Ch165

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17973.750	54.3	-17.7	45.6	26.400	VERTICAL
17925.750	54.2	-17.7	45.6	26.300	VERTICAL
17925.000	54.1	-17.7	45.6	26.200	HORIZONTAL
17826.000	53.8	-18.5	45.6	26.700	VERTICAL
17737.500	53.7	-18.5	45.6	26.600	VERTICAL
17759.250	53.5	-18.5	45.6	26.400	VERTICAL

802.11n-HT40

Ch151

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17982.000	54.6	-17.7	45.6	26.700	VERTICAL
17496.750	54.2	-19.2	41.5	31.900	VERTICAL
17735.250	53.9	-18.9	45.6	27.200	HORIZONTAL
17763.750	53.8	-18.5	45.6	26.700	VERTICAL
17946.000	53.6	-17.7	45.6	25.700	VERTICAL
17712.750	53.5	-18.9	45.6	26.800	HORIZONTAL

Ch159

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17936.250	53.9	-17.7	45.6	26.000	VERTICAL
17813.250	53.7	-18.5	45.6	26.600	VERTICAL
17792.250	53.5	-18.5	45.6	26.400	VERTICAL
17968.500	53.3	-17.7	45.6	25.400	HORIZONTAL
17900.250	53.2	-18.5	45.6	26.100	VERTICAL
17909.250	53.2	-18.5	45.6	26.100	VERTICAL

802.11ac-HT80

Ch155

Frequency(MHz)	Result (dBuV/m)	Cable Loss(dB)	Antenna Factor	P_{Mea} (dBuV/m)	Polarization
17690.250	55.1	-18.9	45.6	28.400	VERTICAL
17698.500	54.9	-18.9	45.6	28.200	HORIZONTAL
17939.250	54.2	-17.7	45.6	26.300	VERTICAL
17794.500	54.0	-18.5	45.6	26.900	HORIZONTAL
17862.000	54.0	-18.5	45.6	26.900	VERTICAL
17916.000	53.8	-17.7	45.6	25.900	HORIZONTAL

Test graphs as below:



Fig. 46 Radiated Spurious Emission (802.11a, Ch149, 30 MHz-1 GHz)



Fig. 47 Radiated Spurious Emission (802.11a, Ch149, 1 GHz-6 GHz)



Fig. 48 Radiated Spurious Emission (802.11a, Ch149, 6 GHz-18 GHz)



Fig. 49 Radiated Spurious Emission (802.11a, Ch157, 30 MHz-1 GHz)



Fig. 50 Radiated Spurious Emission (802.11a, Ch157, 1 GHz-6 GHz)



Fig. 51 Radiated Spurious Emission (802.11a, Ch157, 6 GHz-18 GHz)



Fig. 52 Radiated Spurious Emission (802.11a, Ch165, 30 MHz-1 GHz)



Fig. 53 Radiated Spurious Emission (802.11a, Ch165, 1 GHz-6 GHz)



Fig. 54 Radiated Spurious Emission (802.11a, Ch165, 6 GHz-18 GHz)



Fig. 55 Radiated Spurious Emission (802.11a, Ch157, 18 GHz-26.5 GHz)



Fig. 56 Radiated emission: 802.11n, (802.11a, Ch157, 26.5 GHz - 40 GHz)



Fig. 57 Radiated Spurious Emission (802.11n-HT20, Ch149, 30 MHz-1 GHz)



Fig. 58 Radiated Spurious Emission (802.11n-HT20, Ch149, 1 GHz-6 GHz)



Fig. 59 Radiated Spurious Emission (802.11n-HT20, Ch149, 6 GHz-18 GHz)



Fig. 60 Radiated Spurious Emission (802.11n-HT20, Ch157, 30 MHz-1 GHz)



Fig. 61 Radiated Spurious Emission (802.11n-HT20, Ch157, 1 GHz-6 GHz)



Fig. 62 Radiated Spurious Emission (802.11n-HT20, Ch157, 6 GHz-18 GHz)



Fig. 63 Radiated Spurious Emission (802.11n-HT20, Ch165, 30 MHz-1 GHz)



Fig. 64 Radiated Spurious Emission (802.11n-HT20, Ch165, 1 GHz-6 GHz)



Fig. 65 Radiated Spurious Emission (802.11n-HT20, Ch165, 6 GHz-18 GHz)



Fig. 66 Radiated Spurious Emission (802.11n-HT20, Ch157, 18 GHz-26.5 GHz)



Fig. 67 Radiated emission: 802.11n, (802.11n-HT20, Ch157, 26.5 GHz - 40 GHz)



Fig. 68 Radiated Spurious Emission (802.11n-HT40, Ch151, 30 MHz-1 GHz)



Fig. 69 Radiated Spurious Emission (802.11n-HT40, Ch151, 1 GHz-6 GHz)



Fig. 70 Radiated Spurious Emission (802.11n-HT40, Ch151, 6 GHz-18 GHz)



Fig. 71 Radiated Spurious Emission (802.11n-HT40, Ch159, 30 MHz-1 GHz)



Fig. 72 Radiated Spurious Emission (802.11n-HT40, Ch159 1 GHz-6 GHz)



Fig. 73 Radiated Spurious Emission (802.11n-HT40, Ch159, 6 GHz-18 GHz)



Fig. 74 Radiated Spurious Emission (802.11n-HT40, Ch151, 18 GHz-26.5 GHz)



Fig. 75 Radiated emission: 802.11n, (802.11n-HT40, Ch151, 26.5 GHz - 40 GHz)



Fig. 76 Radiated Spurious Emission (802.11ac-HT80, Ch155, 30 MHz-1 GHz)



Fig. 77 Radiated Spurious Emission (802.11ac-HT80, Ch155, 1 GHz-6 GHz)



Fig. 78 Radiated Spurious Emission (802.11ac-HT80, Ch155, 6 GHz-18 GHz)



Fig. 79 Radiated Spurious Emission (802.11ac-HT80, Ch155, 18 GHz-26.5 GHz)



Fig. 80 Radiated emission: 802.11n, (802.11ac-HT80, Ch155, 26.5 GHz - 40 GHz)

A.6. AC Powerline Conducted Emission

Test Condition:

Voltage（V）	Frequency（Hz）
110	60

Measurement uncertainty:
Expanded measurement uncertainty for this test item is U =3.2dB, k=2.

Measurement Result and limit:
WLAN (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		802.11a	Idle	
0.15 to 0.5	66 to 56	Fig.81	Fig.82	P
0.5 to 5	56			
5 to 30	60			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

WLAN (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		802.11a	Idle	
0.15 to 0.5	56 to 46	Fig.81	Fig.82	P
0.5 to 5	46			
5 to 30	50			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

The measurement is made according to ANSI C63.10 .

Conclusion: PASS

Test graphs as below:



Fig. 81 AC Powerline Conducted Emission-802.11a

Measurement Result 1:

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.090500	45.4	GND	L1	9.7	10.6	56.0
1.338000	46.9	GND	L1	9.7	9.1	56.0
1.387500	46.5	GND	L1	9.7	9.5	56.0
1.473000	44.9	GND	L1	9.7	11.1	56.0
1.522500	44.6	GND	L1	9.7	11.4	56.0
1.581000	46.7	GND	L1	9.7	9.3	56.0

Measurement Result 2:

Frequency (MHz)	CAverage (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.892500	36.1	GND	L1	9.7	9.9	46.0
0.937500	38.2	GND	L1	9.7	7.8	46.0
1.140000	31.3	GND	L1	9.7	14.7	46.0
1.185000	33.6	GND	L1	9.7	12.4	46.0
1.387500	33.8	GND	L1	9.7	12.2	46.0
1.581000	32.7	GND	L1	9.7	13.3	46.0



Fig. 82 AC Powerline Conducted Emission-Idle

Measurement Result 1:

Frequency (MHz)	QuasiPeak (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
1.027500	45.3	GND	L1	9.7	10.7	56.0
1.338000	46.6	GND	L1	9.7	9.4	56.0
1.383000	46.9	GND	L1	9.7	9.1	56.0
1.423500	44.9	GND	L1	9.7	11.1	56.0
1.486500	44.2	GND	L1	9.7	11.8	56.0
1.531500	44.3	GND	L1	9.7	11.7	56.0

Measurement Result 2:

Frequency (MHz)	CAverage (dBµV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.442500	37.5	GND	L1	9.8	9.5	47.0
0.888000	36.5	GND	L1	9.7	9.5	46.0
1.027500	35.9	GND	L1	9.7	10.1	46.0
1.288500	34.9	GND	L1	9.7	11.1	46.0
1.383000	38.0	GND	L1	9.7	8.0	46.0
1.531500	30.6	GND	L1	9.7	15.4	46.0