


FCC SAR Test Report

APPLICANT : Sony Mobile Communications AB
EQUIPMENT : Smart phone
BRAND NAME : SONY
MODEL NAME : D2302
TYPE NAME : PM-0721-BV
FCC ID : PY7PM-0721
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2003

We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

Table of Contents

1. Statement of Compliance	4
2. Administration Data	8
2.1 Testing Laboratory	8
2.2 Applicant	8
2.3 Manufacturer	8
2.4 Application Details	8
3. General Information	9
3.1 Description of Equipment Under Test (EUT)	9
3.2 Device Serial Number	10
3.3 Maximum RF output power among production units	10
3.4 Applied Standard	12
3.5 Device Category and SAR Limits	12
3.6 Test Conditions	12
4. Specific Absorption Rate (SAR)	13
4.1 Introduction	13
4.2 SAR Definition	13
5. SAR Measurement System	14
5.1 E-Field Probe	15
5.2 Data Acquisition Electronics (DAE)	16
5.3 Robot	16
5.4 Measurement Server	16
5.5 Phantom	17
5.6 Device Holder	18
5.7 Data Storage and Evaluation	19
5.8 Test Equipment List	21
6. Tissue Simulating Liquids	22
7. System Verification Procedures	24
7.1 Purpose of System Performance check	24
7.2 System Setup	24
7.3 SAR System Verification Results	25
8. EUT Testing Position	26
8.1 Define two imaginary lines on the handset	26
8.2 Cheek Position	27
8.3 Tilted Position	27
8.4 Body Worn Position	28
9. Measurement Procedures	29
9.1 Spatial Peak SAR Evaluation	29
9.2 Power Reference Measurement	30
9.3 Area & Zoom Scan Procedures	30
9.4 Volume Scan Procedures	31
9.5 SAR Averaged Methods	31
9.6 Power Drift Monitoring	31
10. Bluetooth Exclusions Applied	31
11. Conducted RF Output Power (Unit: dBm)	32
12. Antenna Location	41
13. SAR Test Results	42
13.1 Head SAR	42
13.2 Hotspot SAR	44
13.3 Body Worn SAR	45
13.4 Repeated SAR Measurement	46
14. Simultaneous Transmission Analysis	47
14.1 Head Exposure Conditions	48
14.2 Hotspot Exposure Conditions	54
14.3 Body-Worn Exposure Conditions	60
15. Uncertainty Assessment	63
16. References	66
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA3N0205	Rev. 01	Initial issue of report	Jan. 20, 2014
FA3N0205	Rev. 02	1. Corrected 802.11g Tune-up limit on page38 2. Remove frequency 5600 MHz ~ 5650 MHz conducted power in the report.	Feb. 18, 2014
FA3N0205	Rev. 03	Add ANT+ feature on page9.	Mar. 14, 2014

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Sony Mobile Communications AB Smart phone, D2302** are as follows.

<Highest 1g-SAR Summary>

Exposure Position	Frequency Band	Equipment Class	Maximum RF output power (dBm)	Reported 1g-SAR (W/kg)	Highest Reported 1g-SAR (W/kg)
Head (Separation 0cm)	GSM850 Voice	PCE	33.50	0.28	0.62
	EDGE1900 (4Tx Slots)		25.90	0.26	
	WCDMA Band V		24.00	0.41	
	WCDMA Band II		24.00	0.58	
	WLAN 5.2GHz Band	NII	14.00	0.08	
	WLAN 5.3GHz Band		14.00	0.08	
	WLAN 5.5GHz Band		14.00	0.10	
	WLAN 5.8GHz Band	DTS	14.00	0.14	
	WLAN 2.4GHz Band		17.00	0.62	
Hotspot (Separation 1cm)	GPRS850(2Tx slot)	PCE	30.50	0.46	1.11
	GPRS1900(1Tx slot)		29.50	1.03	
	WCDMA Band V		24.00	0.61	
	WCDMA Band II		20.50	1.11	
	WLAN 5.8GHz Band	DTS	14.00	0.19	
	WLAN 2.4GHz Band		17.00	0.16	
Body-worn (Separation 1.5cm)	GSM850 Voice	PCE	30.50	0.33	1.11
	EDGE1900 (4Tx Slots)		25.90	0.80	
	WCDMA Band V		24.00	0.53	
	WCDMA Band II		24.00	1.11	
	WLAN 5.2GHz Band	NII	14.00	0.06	
	WLAN 5.3GHz Band		14.00	0.07	
	WLAN 5.5GHz Band		14.00	0.09	
	WLAN 5.8GHz Band	DTS	14.00	0.13	
	WLAN 2.4GHz Band		17.00	0.10	

<Highest Simultaneous transmission 1gSAR>

Exposure Position	Frequency Band	Equipment Class	Maximum RF output power (dBm)	Highest Reported Simultaneous Transmission 1g-SAR (W/kg)
Head (Separation 0cm)	WCDMA Band V	PCE	24.0	1.03
	WLAN 2.4GHz Band	DTS	17.0	
	WCDMA Band II	PCE	24.0	0.96
	Bluetooth	DSS	9.5	
Hotspot (Separation 1cm)	WCDMA Band II	PCE	20.5	1.21
	WLAN 5.8GHz Band	DTS	14.0	
	WCDMA Band II	PCE	20.5	1.23
	Bluetooth	DSS	9.5	
Body-worn (Separation 1.5cm)	WCDMA Band II	PCE	24.0	1.21
	WLAN 2.4GHz Band	DTS	17.0	
	WCDMA Band II	PCE	24.0	1.24
	Bluetooth	DSS	9.5	

Note: Simultaneous transmission was not evaluated as the sum of the individual SAR for WWAN and WLAN/Bluetooth was < 1.6 W/kg. This meets the requirements and simultaneous transmission exclusion specified in FCC KDB publication 648474 D04v01r02 - SAR Handset SAR.

<Highest 10g-SAR Summary>

Exposure Position	Frequency Band	Maximum RF output power (dBm)	Reported 10g-SAR (W/kg)	Highest Reported 10g-SAR (W/kg)
Head (Separation 0cm)	GSM850 Voice	33.50	0.21	0.36
	EDGE1900 (4Tx Slots)	25.90	0.14	
	WCDMA Band V	24.00	0.31	
	WCDMA Band II	24.00	0.36	
	WLAN 5.2GHz Band	14.00	0.02	
	WLAN 5.3GHz Band	14.00	0.01	
	WLAN 5.5GHz Band	14.00	0.04	
	WLAN 5.8GHz Band	14.00	0.04	
	WLAN 2.4GHz Band	17.00	0.29	
Hotspot (Separation 1cm)	GPRS850(2Tx slot)	30.50	0.36	0.57
	GPRS1900(1Tx slot)	29.50	0.53	
	WCDMA Band V	24.00	0.47	
	WCDMA Band II	20.50	0.57	
	WLAN 5.8GHz Band	14.00	0.05	
	WLAN 2.4GHz Band	17.00	0.09	
Body-worn (Separation 1.5cm)	GSM850 Voice	30.50	0.26	0.62
	EDGE1900 (4Tx Slots)	25.90	0.45	
	WCDMA Band V	24.00	0.41	
	WCDMA Band II	24.00	0.62	
	WLAN 5.2GHz Band	14.00	0.03	
	WLAN 5.3GHz Band	14.00	0.03	
	WLAN 5.5GHz Band	14.00	0.03	
	WLAN 5.8GHz Band	14.00	0.05	
	WLAN 2.4GHz Band	17.00	0.06	

**<Highest Simultaneous transmission 10gSAR>**

Exposure Position	Frequency Band	Maximum RF output power (dBm)	Highest Reported Simultaneous Transmission 10g-SAR (W/kg)
Head (Separation 0cm)	WCDMA Band V	24.0	0.61
	WLAN 2.4GHz Band	17.0	
	WCDMA Band II	24.0	0.51
	Bluetooth	9.5	
Hotspot (Separation 1cm)	WCDMA Band II	20.5	0.62
	WLAN 2.4GHz Band	17.0	
	WCDMA Band II	20.5	0.61
	Bluetooth	9.5	
Body-worn (Separation 1.5cm)	WCDMA Band II	24.0	0.68
	WLAN 2.4GHz Band	17.0	
	WCDMA Band II	24.0	0.67
	Bluetooth	9.5	

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2. Administration Data

2.1 Testing Laboratory

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978

2.2 Applicant

Company Name	Sony Mobile Communications AB
Address	Nya Vattentornet, 22188 Lund, Sweden

2.3 Manufacturer

Company Name	Compal Communications, INC
Address	No. 385, Yangguang Street, Neihu, Taipei 11491, Taiwan

2.4 Application Details

Date of Start during the Test	Nov. 20, 2013
Date of End during the Test	Jan. 07, 2014

3. General Information

3.1 Description of Equipment Under Test (EUT)

The equipment under test is a smart phone supporting, GSM850/900/1800/1900, UMTS I / II / V / VIII, 802.11 a/b/g/n, Bluetooth, FM Receiver and GPS features, and below is details of information. For FCC, only wireless modes in US frequency bands are tested.

Product Feature & Specification	
EUT	Smart phone
Brand Name	SONY
Model Name	D2302
Type Name	PM-0721-BV
FCC ID	PY7PM-0721
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
Mode	• GSM/GPRS/EGPRS • RMC/AMR 12.2Kbps Rel 99 • HSDPA Rel 7, Cat14 • HSUPA Rel 6, Cat6 • 802.11a/b/g/n HT20/HT40 • Bluetooth v3.0+EDR • Bluetooth v4.0+LE • ANT+ • NFC:ASK
Antenna Type	WWAN: PIFA Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna NFC: Single Loop Antenna
HW Version	A
SW Version	18.0.B.0.23
Dual Transfer Mode Category	Class A – EUT can support Packet Switched and Circuit Switched Network simultaneously.
EUT Stage	Production Unit
Remark: 1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description. 2. 802.11n-HT40 is not supported in 2.4GHz WLAN and 5GHz WLAN operated in 5600 MHz ~ 5650 MHz is notched 3. This device supports VoIP in GSM, WCDMA (e.g. 3rd part VoIP) and supports GRPS/EGPRS mode up to multi-slot class33 and supports DTM up to multi-slot class11. 4. When hotspot mode is enabled, power reduction will be activated to limit the maximum power of GSM1900 band and UMTS band 2. 5. This device 2.4GHz WLAN supports Hotspot operation, and 2.4GHz / 5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.2GHz / 5.3GHz / 5.5GHz supports WiFi Direct (GC only). 6. This device has 2 SIM slots and supports Dual SIM Dual Standby. The WWAN radio transmission will be enabled by either one SIM at a time (Single active).	

3.2 Device Serial Number

Sample	Serial Number	IMEI Code
WWAN SAR measurements	ZH8001K5F8	004402146970516
WLAN SAR measurements	ZH8001K0Z9	004402146970896
WWAN Conducted measurements	ZH8001K5F8	004402146970516
BT/WLAN Conducted measurements	ZH8001K0XF	004402146971357

Note: Several samples were used with identical hardware to support SAR testing. The manufacturer has confirmed that the device tested gave the same physical, mechanical and thermal characteristics and are within operational tolerances expected for production units.

3.3 Maximum RF output power among production units

Mode		Burst Average Power (dBm)		
		GSM 850	GSM 1900	
		Full Power Mode	Full Power Mode	Reduced Power Mode
GSM (GMSK, 1 Tx slot)		33.5	30.5	29.5
GPRS (GMSK, 1 Tx slot)		33.5	30.5	29.5
GPRS (GMSK, 2 Tx slots)		30.5	27.5	26.5
GPRS (GMSK, 3 Tx slots)		28.5	25.5	24.5
GPRS (GMSK, 4 Tx slots)		27.5	24.5	23.5
EDGE (8PSK, 1 Tx slot)		27.5	26.5	22.0
EDGE (8PSK, 2 Tx slots)		27.3	26.3	21.8
EDGE (8PSK, 3 Tx slots)		27.1	26.1	21.6
EDGE (8PSK, 4 Tx slots)		26.9	25.9	21.4
DTM 5	GSM (GMSK, 1 Tx slot)	30.5	27.5	26.5
	GPRS (GMSK, 1 Tx slot)	30.5	27.5	26.5
DTM 9	GSM (GMSK, 1 Tx slot)	30.5	27.5	26.5
	GPRS (GMSK, 1 Tx slot)	30.5	27.5	26.5
DTM11	GSM (GMSK, 1 Tx slot)	28.5	25.5	24.5
	GPRS (GMSK, 2 Tx slots)	28.5	25.5	24.5
DTM 5	GSM (GMSK, 1 Tx slot)	30.5	27.5	26.5
	EDGE (8PSK, 1 Tx slot)	27.3	26.3	21.8
DTM 9	GSM (GMSK, 1 Tx slot)	30.5	27.5	26.5
	EDGE (8PSK, 1 Tx slot)	27.3	26.3	21.8
DTM 11	GSM (GMSK, 1 Tx slot)	28.5	25.5	24.5
	EDGE (8PSK, 2 Tx slots)	27.1	26.1	21.6

Mode		Average Power (dBm)		
		WCDMA Band V	WCDMA Band II	
		Full Power Mode	Full Power Mode	Reduced Power Mode
AMR 12.2Kbps		24.0	24.0	20.5
RMC 12.2Kbps		24.0	24.0	20.5
HSDPA Subtest-1		24.0	24.0	20.5
HSUPA Subtest-5		24.0	24.0	20.5

Mode		Maximum Target Average Power (dBm)
2.4GHz	802.11b	17.0
	802.11g	15.0
	802.11n-HT20	14.0
5GHz	802.11a	14.0
	802.11n-HT20	14.0
	802.11n-HT40	14.0
Bluetooth v3.0+EDR		9.5
Bluetooth v4.0+LE		2.75

Target Power reduction applied for each wireless mode

Exposure Position / wireless mode		Hotspot ⁽¹⁾
GSM1900 (GMSK 1 Tx slot) - CS1		1.0 dB
GSM1900 GPRS (GMSK 1 Tx slot) - CS1		1.0 dB
GSM1900 GPRS (GMSK 2 Tx slots) - CS1		1.0 dB
GSM1900 GPRS (GMSK 3 Tx slots) - CS1		1.0 dB
GSM1900 GPRS (GMSK 4 Tx slots) - CS1		1.0 dB
GSM1900 EDGE (8PSK 1 Tx slot) - MCS5		4.5 dB
GSM1900 EDGE (8PSK 2 Tx slots) - MCS5		4.5 dB
GSM1900 EDGE (8PSK 3 Tx slots) - MCS5		4.5 dB
GSM1900 EDGE (8PSK 4 Tx slots) - MCS5		4.5 dB
DTM 5	GSM (GMSK, 1 Tx slot)	1.0 dB
	GPRS (GMSK, 1 Tx slot)	1.0 dB
DTM 9	GSM (GMSK, 1 Tx slot)	1.0 dB
	GPRS (GMSK, 1 Tx slot)	1.0 dB
DTM11	GSM (GMSK, 1 Tx slot)	1.0 dB
	GPRS (GMSK, 2 Tx slots)	1.0 dB
DTM 5	GSM (GMSK, 1 Tx slot)	1.0 dB
	EDGE (8PSK, 1 Tx slot)	4.5 dB
DTM 9	GSM (GMSK, 1 Tx slot)	1.0 dB
	EDGE (8PSK, 1 Tx slot)	4.5 dB
DTM 11	GSM (GMSK, 1 Tx slot)	1.0 dB
	EDGE (8PSK, 2 Tx slots)	4.5 dB
WCDMA Band 2		3.5 dB

Remark:

- ⁽¹⁾: Reduced maximum limit applied by activation of Hotspot operation
- When hotspot mode is enabled, power reduction will be activated to limit the maximum power of GSM1900 band and UMTS band 2.
- Power reduction is not applicable for GSM850 Band, UMTS Band 5, WLAN and Bluetooth.

3.4 Applied Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r02
- FCC KDB 865664 D02 SAR Reporting v01r01
- FCC KDB 447498 D01 General RF Exposure Guidance v05r01
- FCC KDB 648474 D04 Handset SAR v01r02
- FCC KDB 248227 D01 SAR meas for 802 11abg v01r02
- FCC KDB 941225 D01 SAR test for 3G devices v02
- FCC KDB 941225 D02 HSPA and 1x Advanced v02r02
- FCC KDB 941225 D03 SAR Test Reduction GSM GPRS EDGE v01
- FCC KDB 941225 D04 SAR for GSM E GPRS Dual Xfer Mode v01
- FCC KDB 941225 D06 Hotspot Mode SAR v01r01

3.5 Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

3.6 Test Conditions

3.5.1 Ambient Condition

Ambient Temperature	20 to 24 °C
Humidity	< 60 %

3.5.2 Test Configuration

For WWAN SAR testing, the device was controlled by using a base station emulator. Communication between the device and the emulator was established by air link. The distance between the EUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT.

During WLAN SAR testing EUT is configured with the WLAN continuous TX tool, and the transmission duty factor was monitored on the spectrum analyzer with zero-span setting

Duty factor observed as below:

802.11b, 1Mbps: 97.63%

802.11a, 6Mbps: 87.26%

For WLAN SAR testing, WLAN engineering testing software installed on the EUT can provide continuous transmitting RF signal.

4. Specific Absorption Rate (SAR)

4.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

4.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\text{SAR} = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

5. SAR Measurement System




Fig 5.1 SPEAG DASY System Configurations

The DASY system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- The electro-optical converter (EOC) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- A computer operating Windows XP
- DASY software
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom
- A device holder
- Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

Component details are described in in the following sub-sections.

5.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

5.1.1 E-Field Probe Specification

<ES3DV3 Probe >

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Frequency	10 MHz to 3 GHz; Linearity: ± 0.2 dB
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic Range	5 μ W/g to 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 337 mm (Tip: 10 mm) Tip diameter: 4 mm (Body: 10 mm) Distance from probe tip to dipole centers: 3 mm



Fig 5.2 Photo of ES3DV3

<EX3DV4 Probe>

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Frequency	10 MHz to 6 GHz; Linearity: ± 0.2 dB
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 μ W/g to 100 mW/g; Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 330 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm



Fig 5.3 Photo of EX3DV4/ES3DV4

5.1.2 E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

5.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.4 Photo of DAE

5.3 Robot

The SPEAG DASY system uses the high precision robots (DASY4: RX90BL; DASY5: TX90XL) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY4: CS7MB; DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



Fig 5.5 Photo of DASY4




Fig 5.6 Photo of DASY5

5.4 Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY4: 166 MHz, Intel Pentium; DASY5: 400 MHz, Intel Celeron), chipdisk (DASY4: 32 MB; DASY5: 128 MB), RAM (DASY4: 64 MB, DASY5: 128 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



Fig 5.7 Photo of Server for DASY4



Fig 5.8 Photo of Server for DASY5

5.5 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm
Filling Volume	Approx. 25 liters
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet
Measurement Areas	Left Hand, Right Hand, Flat Phantom



Fig 5.9 Photo of SAM Phantom

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI4 Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)
Filling Volume	Approx. 30 liters
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm



Fig 5.10 Photo of ELI4 Phantom

The ELI4 phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

5.6 Device Holder

<Device Holder for SAM Twin Phantom>

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Fig 5.11 Device Holder

<Laptop Extension Kit>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.




Fig 5.12 Laptop Extension Kit

5.7 Data Storage and Evaluation

5.7.1 Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [mW/g]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-lose media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

5.7.2 Data Evaluation

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software :

Probe parameters :	- Sensitivity	$Norm_i, a_{i0}, a_{i1}, a_{i2}$
	- Conversion factor	$ConvF_i$
	- Diode compression point	dcp_i
Device parameters :	- Frequency	f
	- Crest factor	cf
Media parameters :	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

The formula for each channel can be given as :

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with V_i = compensated signal of channel i, (i = x, y, z)
 U_i = input signal of channel i, (i = x, y, z)
 cf = crest factor of exciting field (DASY parameter)
 dcp_i = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated :

$$\text{E-field Probes : } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$\text{H-field Probes : } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with V_i = compensated signal of channel i, (i = x, y, z)
 Norm_i = sensor sensitivity of channel i, (i = x, y, z), $\mu\text{V}/(\text{V/m})^2$ for E-field Probes
 ConvF = sensitivity enhancement in solution
 a_{ij} = sensor sensitivity factors for H-field probes
 f = carrier frequency [GHz]
 E_i = electric field strength of channel i in V/m
 H_i = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude) :

$$E_{\text{tot}} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$\text{SAR} = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g
 E_{tot} = total field strength in V/m
 σ = conductivity in [mho/m] or [Siemens/m]
 ρ = equivalent tissue density in g/cm^3

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.

5.8 Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	499	Mar. 18, 2013	Mar. 17, 2014
SPEAG	1900MHz System Validation Kit	D1900V2	5d041	Mar. 20, 2013	Mar. 19, 2014
SPEAG	2450MHz System Validation Kit	D2450V2	924	Nov. 13, 2013	Nov. 12, 2014
SPEAG	5GHz System Validation Kit	D5GHzV2	1128	Jul. 24, 2013	Jul. 23, 2014
SPEAG	Data Acquisition Electronics	DAE3	577	May. 08, 2013	May. 07, 2014
SPEAG	Data Acquisition Electronics	DAE4	778	Aug. 21, 2013	Aug. 20, 2014
SPEAG	Data Acquisition Electronics	DAE3	495	May. 08, 2013	May. 07, 2014
SPEAG	Data Acquisition Electronics	DAE4	1279	Jan. 28, 2013	Jan. 27, 2014
SPEAG	Data Acquisition Electronics	DAE4	913	Jan. 17, 2013	Jan. 16, 2014
SPEAG	Dosimetric E-Field Probe	EX3DV4	3931	Sep. 10, 2013	Sep. 09, 2014
SPEAG	Dosimetric E-Field Probe	EX3DV4	3801	Jun. 20, 2013	Jun. 19, 2014
SPEAG	Dosimetric E-Field Probe	EX3DV4	3925	Jun. 12, 2013	Jun. 11, 2014
SPEAG	Dosimetric E-Field Probe	EX3DV4	3954	Nov. 04, 2013	Nov. 03, 2014
SPEAG	Dosimetric E-Field Probe	ES3DV3	3270	Sep. 24, 2013	Sep. 23, 2014
SPEAG	Dosimetric E-Field Probe	EX3DV4	3661	Jan. 15, 2013	Jan. 14, 2014
Wisewind	Thermometer	ETP-101	TM560	Oct. 22, 2013	Oct. 21, 2014
Wisewind	Thermometer	ETP-101	TM685	Oct. 22, 2013	Oct. 21, 2014
Wisewind	Thermometer	HTC-1	TM642	Oct. 22, 2013	Oct. 21, 2014
Wisewind	Thermometer	HTC-1	TM281	Oct. 22, 2013	Oct. 21, 2014
H.M.IRIS	Thermometer	TH-08	TM658	Oct. 22, 2013	Oct. 21, 2014
Agilent	Wireless Communication Test Set	E5515C	GB46311322	Mar. 25, 2013	Mar. 24, 2014
Agilent	Wireless Communication Test Set	E5515C	MY50264370	Apr. 29, 2013	Apr. 28, 2014
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 06, 2013	May. 05, 2014
SPEAG	Device Holder	N/A	N/A	NCR	NCR
R&S	Signal Generator	SMF 100A	101107	May. 27, 2013	May. 26, 2014
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Jul. 23, 2013	Jul. 22, 2014
Agilent	ENA Network Analyzer	E5071C	MY46316648	Feb. 07, 2013	Feb. 06, 2014
Anritsu	Power Meter	ML2495A	1132003	Aug. 28, 2013	Aug. 27, 2014
Anritsu	Power Sensor	MA2411B	1126017	Aug. 27, 2013	Aug. 26, 2014
Agilent	Dual Directional Coupler	778D	50422	Note 2	
Woken	Attenuator 1	WK0602-XX	N/A	Note 2	
PE	Attenuator 2	PE7005-10	N/A	Note 2	
PE	Attenuator 3	PE7005- 3	N/A	Note 2	
AR	Power Amplifier	5S1G4M2	328767	Note 3	
R&S	Spectrum Analyzer	FSP 7	101131	Jul. 09, 2013	Jul. 08, 2014

Table 5.1 Test Equipment List

Note:

1. The calibration certificate of DASY can be referred to appendix C of this report.
2. The Insertion Loss calibration of Dual Directional Coupler and Attenuator were characterized via the network analyzer and compensated during system check.
3. In system check we need to monitor the level on the power meter, and adjust the power amplifier level to have precise power level to the dipole; the measured SAR will be normalized to 1W input power according to the ratio of 1W to the input power to the dipole. For system check, the calibration of the power amplifier is deemed not critically required for correct measurement; the power meter is critical and we do have calibration for it
4. Attenuator 1 insertion loss is calibrated by the network Analyzer, which the calibration is valid, before system check.

6. Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.2.


Fig 6.1 Photo of Liquid Height for Head SAR

Fig 6.2 Photo of Liquid Height for Body SAR

The following table gives the recipes for tissue simulating liquid.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Table 6.1 Recipes of Tissue Simulating Liquid

Simulating Liquid for 5G, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an SPEAG DAK-3.5 Dielectric Probe Kit and an Agilent Network Analyzer.

The following table shows the measuring results for simulating liquid.

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ε _r)	Conductivity Target (σ)	Permittivity Target (ε _r)	Delta (σ) (%)	Delta (ε _r) (%)	Limit (%)	Date
835	Head	22.3	0.901	40.119	0.90	41.50	0.11	-3.33	±5	2013/12/26
835	Head	22.4	0.910	40.083	0.90	41.50	1.11	-3.41	±5	2013/11/21
835	Head	22.6	0.885	42.000	0.90	41.50	-1.67	1.20	±5	2014/1/3
1900	Head	22.4	1.386	39.814	1.40	40.00	-1.00	-0.47	±5	2013/12/26
1900	Head	22.6	1.432	38.828	1.40	40.00	2.29	-2.93	±5	2013/11/22
1900	Head	22.5	1.440	38.100	1.40	40.00	2.86	-4.75	±5	2014/1/3
2450	Head	22.6	1.798	38.374	1.80	39.20	-0.11	-2.11	±5	2013/12/20
5200	Head	22.5	4.795	35.457	4.66	36.00	2.90	-1.51	±5	2013/11/20
5300	Head	22.5	4.898	35.314	4.76	35.87	2.90	-1.55	±5	2013/11/20
5600	Head	22.5	5.206	34.730	5.06	35.53	2.89	-2.25	±5	2013/11/20
5800	Head	22.5	5.393	34.362	5.27	35.30	2.33	-2.66	±5	2013/11/20
835	Body	22.5	0.983	54.742	0.97	55.20	1.34	-0.83	±5	2013/11/21
835	Body	22.4	0.963	54.529	0.97	55.20	-0.72	-1.22	±5	2013/12/26
1900	Body	22.4	1.532	52.506	1.52	53.30	0.79	-1.49	±5	2013/11/29
1900	Body	22.1	1.568	51.571	1.52	53.30	3.16	-3.24	±5	2014/1/7
1900	Body	22.4	1.561	52.117	1.52	53.30	2.70	-2.22	±5	2013/12/27
2450	Body	22.6	1.965	53.842	1.97	53.84	-0.25	0.00	±5	2013/12/20
5200	Body	22.6	5.244	47.499	5.30	49.00	-1.06	-3.06	±5	2013/11/23
5300	Body	22.6	5.380	47.244	5.42	48.88	-0.74	-3.35	±5	2013/11/23
5600	Body	22.6	5.773	46.756	5.77	48.47	0.05	-3.54	±5	2013/11/23
5800	Body	22.6	6.113	47.156	6.00	48.20	1.88	-2.17	±5	2013/12/25
5800	Body	22.6	6.127	46.464	6.00	48.20	2.12	-3.60	±5	2013/11/23

Table 6.2 Measuring Results for Simulating Liquid

7. System Verification Procedures

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

7.1 Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

7.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:




Fig 7.1 System Setup for System Evaluation

1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. Calibrated Dipole



Fig 7.2 Photo of Dipole Setup

7.3 SAR System Verification Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Table 7.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured SAR (W/kg)	Targeted SAR (W/kg)	Normalized SAR (W/kg)	Deviation (%)
2013/12/26	835	Head	250	D835V2-SN:499	3270	778	2.39	9.57	9.56	-0.10
2013/11/21	835	Head	250	D835V2-SN:499	3931	778	2.35	9.57	9.40	-1.78
2014/1/3	835	Head	250	D835V2-SN:499	3931	1279	2.47	9.57	9.88	3.24
2013/12/26	1900	Head	250	D1900V2-SN:5d041	3270	778	9.50	40.60	38.00	-6.40
2013/11/22	1900	Head	250	D1900V2-SN:5d041	3931	778	10.80	40.60	43.20	6.40
2014/1/3	1900	Head	250	D1900V2-SN:5d041	3931	1279	10.50	40.60	42.00	3.45
2013/12/20	2450	Head	250	D2450V2-SN:924	3925	495	13.60	52.40	54.40	3.82
2013/11/20	5200	Head	100	D5GHzV2-SN:1128	3801	913	7.80	73.40	78.00	6.27
2013/11/20	5300	Head	100	D5GHzV2-SN:1128	3801	913	8.59	80.60	85.90	6.58
2013/11/20	5600	Head	100	D5GHzV2-SN:1128	3801	913	8.29	80.50	82.90	2.98
2013/11/20	5800	Head	100	D5GHzV2-SN:1128	3801	913	7.67	77.20	76.70	-0.65
2013/11/21	835	Body	250	D835V2-SN:499	3931	778	2.47	9.63	9.88	2.60
2013/12/26	835	Body	250	D835V2-SN:499	3954	1279	2.43	9.63	9.72	0.93
2013/11/29	1900	Body	250	D1900V2-SN:5d041	3931	577	10.30	40.80	41.20	0.98
2014/1/7	1900	Body	250	D1900V2-SN:5d041	3661	1279	10.80	40.80	43.20	5.88
2013/12/27	1900	Body	250	D1900V2-SN:5d041	3954	1279	10.70	40.80	42.80	4.90
2013/12/20	2450	Body	250	D2450V2-SN:924	3955	1279	12.10	50.20	48.40	-3.59
2013/11/23	5200	Body	100	D5GHzV2-SN:1128	3801	913	6.78	73.40	67.80	-7.63
2013/11/23	5300	Body	100	D5GHzV2-SN:1128	3801	913	7.62	74.30	76.20	2.56
2013/11/23	5600	Body	100	D5GHzV2-SN:1128	3801	913	7.79	77.80	77.90	0.13
2013/12/25	5800	Body	100	D5GHzV2-SN:1128	3925	495	7.46	72.20	74.60	3.32
2013/11/23	5800	Body	100	D5GHzV2-SN:1128	3801	913	7.20	72.20	72.00	-0.28

Table 7.1 Target and Measurement SAR after Normalized

8. EUT Testing Position

8.1 Define two imaginary lines on the handset

- The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
- The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig 8.1 Illustration for Handset Vertical and Horizontal Reference Lines

8.2 Cheek Position

- To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 8.2).




Fig 8.2 Illustration for Cheek Position

8.3 Tilted Position

- To position the device in the “cheek” position described above.
- While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 8.3).




Fig 8.3 Illustration for Tilted Position

8.4 Body Worn Position

- (a) To position the device parallel to the phantom surface with either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1.5 cm.




Fig 8.4 Illustration for Body Worn Position

8.5 Hotspot Position

- (a) To position the device parallel to the phantom surface with all sides and either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device and the flat phantom to 1.0cm.

<EUT Setup Photos>

Please refer to Appendix D for the test setup photos.

9. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

9.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r02 quoted below.

When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1" two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the area scan based 1-g SAR estimation procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.4 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

9.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

10. Bluetooth Exclusions Applied

Mode Band	Average power(dBm)	
	Bluetooth v3.0+EDR	Bluetooth v4.0+LE
2.4GHz Bluetooth	9.5	2.75

Note:

- Per KDB 447498 D01v05r01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
 - $f(\text{GHz})$ is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison

Bluetooth Max Power (dBm)	Test Distance (mm)	Frequency (GHz)	exclusion thresholds
9.5	5	2.48	2.83

- Per KDB 447498 D01v05r01 exclusion thresholds is $2.83 < 3$, RF exposure evaluation is not required.

11. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

Note:

- For DTM multi-slot class mode, the device was linked with base station simulator (Agilent E5515C) and transmit maximum power on maximum number of TX slots, i.e. one CS timeslot, and additional PS timeslots (1 for DTM class 5 and 9, 2 for DTM class 11) in one TDMA frame.
- Agilent E5515C was used to setup the device operated under DTM mode for power measurement and SAR testing. For conducted power, the power of the burst for voice and the power of the bursts for data was reported separately in the table above, and the frame-average power is derived below to determine SAR testing.

$$DTM \text{ frame average power (dBm)} = 10 \cdot \log [\sum (\text{power of each slot, in mW}) / 8]$$
- Per KDB 447498 D01v05r01, the maximum output power channel is used for SAR testing and for further SAR test reduction.
- For Head and Body-worn SAR testing, the EUT was set in GSM Voice for GSM850 and DTM Multi-slot class 11 for GSM1900 due to its highest frame-average power and considering the possibility of e.g. 3rd part VoIP operation was additional EGPRS SAR testing performed on GSM mode worse case.
- For hotspot mode SAR testing of GSM850 band, GPRS, EDGE and DTM were evaluated and EUT was set in GPRS 2 Tx slots due to its highest frame-average power.
- Power reduction which is triggered by hotspot mode is implemented in GSM1900 band, for hotspot mode SAR testing EUT was set in reduced power mode and GPRS 1 Tx slot due to its highest frame-average power.

<Full power mode>

Band GSM850		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		128	189	251		128	189	251	
Frequency (MHz)		824.2	836.4	848.8		824.2	836.4	848.8	
GSM (GMSK, 1 Tx slot)		33.49	33.46	33.43	33.50	24.49	24.46	24.43	24.50
		33.47	33.45	33.41	33.50	24.47	24.45	24.41	24.50
GPRS (GMSK, 1 Tx slot)		30.49	30.45	30.38	30.50	24.49	24.45	24.38	24.50
GPRS (GMSK, 2 Tx slots)		28.24	28.14	28.13	28.50	23.98	23.88	23.87	24.24
GPRS (GMSK, 3 Tx slots)		27.36	27.34	27.32	27.50	24.36	24.34	24.32	24.50
EDGE (8PSK, 1 Tx slot)		27.48	27.41	27.36	27.50	18.48	18.41	18.36	18.50
EDGE (8PSK, 2 Tx slots)		27.23	27.18	27.12	27.30	21.23	21.18	21.12	21.30
EDGE (8PSK, 3 Tx slots)		27.01	27.00	26.98	27.10	22.75	22.74	22.72	22.84
EDGE (8PSK, 4 Tx slots)		26.89	26.86	26.79	26.90	23.89	23.86	23.79	23.90
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	30.47	30.44	30.36	30.50	24.38	24.36	24.29	24.50
	GPRS (GMSK, 1 Tx slot)	30.34	30.32	30.26	30.50				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	30.46	30.43	30.33	30.50	24.38	24.34	24.27	24.50
	GPRS (GMSK, 1 Tx slot)	30.34	30.30	30.25	30.50				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	28.23	28.12	28.12	28.50	23.96	23.85	23.84	24.24
	GPRS (GMSK, 2 Tx slots)	28.22	28.10	28.09	28.50				
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	30.44	30.41	30.33	30.50	23.10	23.06	22.99	23.17
	EDGE (8PSK, 1 Tx slot)	27.21	27.16	27.11	27.30				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	30.42	30.40	30.31	30.50	23.08	23.05	22.97	23.17
	EDGE (8PSK, 1 Tx slot)	27.20	27.14	27.08	27.30				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	28.22	28.12	28.10	28.50	23.18	23.13	23.11	23.36
	EDGE (8PSK, 2 Tx slots)	26.99	26.97	26.96	27.10				

Remark: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB

<Hotspot inactive - full power mode>

Band GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM (GMSK, 1 Tx slot)		28.70	28.92	28.96	30.50	19.70	19.92	19.96	21.50
GPRS (GMSK, 1 Tx slot)		28.71	28.89	28.95	30.50	19.71	19.89	19.95	21.50
GPRS (GMSK, 2 Tx slots)		27.23	27.43	27.48	27.50	21.23	21.43	21.48	21.50
GPRS (GMSK, 3 Tx slots)		25.27	25.41	25.46	25.50	21.01	21.15	21.20	21.24
GPRS (GMSK, 4 Tx slots)		22.69	22.84	22.96	24.50	19.69	19.84	19.96	21.50
EDGE (8PSK, 1 Tx slot)		26.22	26.31	26.45	26.50	17.22	17.31	17.45	17.50
EDGE (8PSK, 2 Tx slots)		26.08	26.19	26.27	26.30	20.08	20.19	20.27	20.30
EDGE (8PSK, 3 Tx slots)		25.87	26.00	26.08	26.10	21.61	21.74	21.82	21.84
EDGE (8PSK, 4 Tx slots)		24.11	24.27	24.38	25.90	21.11	21.27	21.38	22.90
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	27.18	27.38	27.41	27.50	21.10	21.32	21.36	21.50
	GPRS (GMSK, 1 Tx slot)	27.06	27.31	27.36	27.50				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	27.16	27.37	27.42	27.50	21.11	21.30	21.34	21.50
	GPRS (GMSK, 1 Tx slot)	27.11	27.28	27.30	27.50				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	25.24	25.38	25.45	25.50	20.94	21.06	21.10	21.24
	GPRS (GMSK, 2 Tx slots)	25.18	25.29	25.31	25.50				
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	27.19	27.34	27.40	27.50	20.63	20.77	20.84	20.92
	EDGE (8PSK, 1 Tx slot)	26.04	26.17	26.24	26.30				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	27.20	27.40	27.43	27.50	20.64	20.79	20.84	20.92
	EDGE (8PSK, 1 Tx slot)	26.05	26.12	26.20	26.30				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	25.21	25.38	25.43	25.50	21.51	21.59	21.61	21.65
	EDGE (8PSK, 2 Tx slots)	26.02	26.06	26.08	26.10				

Remark: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB

<Hotspot active - reduced power mode>

Band GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM (GMSK, 1 Tx slot)		28.64	28.87	28.91	29.50	19.64	19.87	19.91	20.50
GPRS (GMSK, 1 Tx slot)		28.62	28.85	28.88	29.50	19.62	19.85	19.88	20.50
GPRS (GMSK, 2 Tx slots)		25.26	25.43	25.47	26.50	19.26	19.43	19.47	20.50
GPRS (GMSK, 3 Tx slots)		23.14	23.30	23.42	24.50	18.88	19.04	19.16	20.24
GPRS (GMSK, 4 Tx slots)		21.92	22.08	22.21	23.50	18.92	19.08	19.21	20.50
EDGE (8PSK, 1 Tx slot)		21.06	21.15	21.32	22.00	12.06	12.15	12.32	13.00
EDGE (8PSK, 2 Tx slots)		20.64	20.77	20.93	21.80	14.64	14.77	14.93	15.80
EDGE (8PSK, 3 Tx slots)		20.22	20.30	20.37	21.60	15.96	16.04	16.11	17.34
EDGE (8PSK, 4 Tx slots)		19.77	19.91	20.04	21.40	16.77	16.91	17.04	18.40
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	25.14	25.31	25.42	26.50	19.09	19.21	19.34	20.50
	GPRS (GMSK, 1 Tx slot)	25.09	25.14	25.30	26.50				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	25.16	25.27	25.38	26.50	19.09	19.19	19.28	20.50
	GPRS (GMSK, 1 Tx slot)	25.06	25.16	25.21	26.50				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	23.08	23.24	23.28	24.50	18.77	18.92	18.96	20.24
	GPRS (GMSK, 2 Tx slots)	23.01	23.15	23.19	24.50				
DTM 5 (2Tx slots)	GSM (GMSK, 1 Tx slot)	25.14	25.19	25.40	26.50	17.43	17.51	17.72	18.74
	EDGE (8PSK, 1 Tx slot)	20.65	20.81	21.01	21.80				
DTM 9 (2Tx slots)	GSM (GMSK, 1 Tx slot)	25.16	25.38	25.41	26.50	17.45	17.64	17.70	18.74
	EDGE (8PSK, 1 Tx slot)	20.66	20.76	20.92	21.80				
DTM 11 (3Tx slots)	GSM (GMSK, 1 Tx slot)	23.16	23.21	23.38	24.50	17.16	17.23	17.34	18.53
	EDGE (8PSK, 2 Tx slots)	20.19	20.28	20.34	21.60				

Remark: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3 dB

<WCDMA Conducted Power>

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 5) (Note 6)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2)	AG Index (Note 6)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/225	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15 (Note 4)	15/15 (Note 4)	64	15/15 (Note 4)	30/15	24/15	134/15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$.

Note 2: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: For subtest 5 the β_c/β_d ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14/15$ and $\beta_d = 15/15$.

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6: β_{ed} can not be set directly, it is set by Absolute Grant Value.

Setup Configuration

<WCDMA Conducted Power>
Note:

- Per KDB 941225 D02v02r02, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA/HSUPA output power is < 0.25dB higher than RMC, or reported SAR with RMC 12.2kbps setting is $\leq 1.2\text{W/kg}$, HSDPA/HSUPA SAR evaluation can be excluded..

<Hotspot inactive – full power mode>

Band			WCDMA V			WCDMA II		
TX Channel			4132	4182	4233	9262	9400	9538
Frequency (MHz)			826.4	836.4	846.6	1852.4	1880	1907.6
MPR (dB)	3GPP Rel 99	AMR 12.2Kbps	23.89	23.91	23.97	22.28	22.45	22.44
	3GPP Rel 99	RMC 12.2Kbps	23.91	23.92	23.99	23.74	23.88	23.79
0	3GPP Rel 6	HSDPA Subtest-1	23.01	23.04	23.08	22.65	22.81	22.74
0	3GPP Rel 6	HSDPA Subtest-2	23.00	23.01	23.02	22.68	22.85	22.78
0.5	3GPP Rel 6	HSDPA Subtest-3	22.47	22.54	22.70	22.25	22.43	22.37
0.5	3GPP Rel 6	HSDPA Subtest-4	22.46	22.53	22.57	22.28	22.45	22.40
0	3GPP Rel 6	HSUPA Subtest-1	22.31	22.46	22.47	22.09	22.28	22.20
2	3GPP Rel 6	HSUPA Subtest-2	21.56	21.75	21.81	21.58	21.69	21.62
1	3GPP Rel 6	HSUPA Subtest-3	21.93	21.96	21.98	21.85	21.98	21.95
2	3GPP Rel 6	HSUPA Subtest-4	22.33	22.38	22.55	21.70	21.95	21.85
0	3GPP Rel 6	HSUPA Subtest-5	22.49	22.50	22.64	22.67	22.81	22.71

<Hotspot active - reduced power mode>

Band			WCDMA II		
TX Channel			9262	9400	9538
Frequency (MHz)			1852.4	1880	1907.6
MPR (dB)	3GPP Rel 99	AMR 12.2Kbps	20.11	20.47	20.40
	3GPP Rel 99	RMC 12.2Kbps	20.13	20.48	20.39
0	3GPP Rel 6	HSDPA Subtest-1	19.19	19.35	19.48
0	3GPP Rel 6	HSDPA Subtest-2	19.22	19.39	19.49
0.5	3GPP Rel 6	HSDPA Subtest-3	18.85	19.00	19.07
0.5	3GPP Rel 6	HSDPA Subtest-4	18.89	19.03	19.12
0	3GPP Rel 6	HSUPA Subtest-1	19.08	19.15	18.95
2	3GPP Rel 6	HSUPA Subtest-2	18.15	18.22	18.05
1	3GPP Rel 6	HSUPA Subtest-3	18.42	18.52	18.38
2	3GPP Rel 6	HSUPA Subtest-4	18.81	18.95	18.79
0	3GPP Rel 6	HSUPA Subtest-5	19.22	19.50	19.44

<WLAN 2.4GHz Conducted Power>

WLAN 2.4GHz 802.11b Average Power (dBm)							Tune up Limit (dBm)
Power vs. Channel			Power vs. Data Rate				
Channel	Frequency (MHz)	Data Rate	Channel	2Mbps	5.5Mbps	11Mbps	
		1Mbps					
CH 1	2412	16.90	CH 6	16.82	16.81	16.72	17.0
CH 6	2437	17.00					
CH 11	2462	16.92					

WLAN 2.4GHz 802.11g Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. Data Rate								
Channel	Frequency (MHz)	Data Rate	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps	
		6Mbps									
CH 1	2412	14.86	CH 6	14.86	14.95	14.57	14.88	14.73	14.71	14.68	15.0
CH 6	2437	14.97									
CH 11	2462	14.78									

WLAN 2.4GHz 802.11n-HT20 Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. MCS Index								
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	
		MCS0									
CH 1	2412	13.76	CH 6	13.71	13.69	13.65	13.78	13.77	13.67	13.52	14.0
CH 6	2437	13.98									
CH 11	2462	13.75									

Note:

1. Per KDB 248227 D01 v01r02, choose the highest output power channel to test SAR and determine further SAR exclusion
2. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4dB higher than those measured at the lowest data rate
3. Apply the test exclusion rule in KDB 248227 D01 v01r02 11g, 11n-HT20 output power is less than 1/4dB higher than 11b mode, thus the SAR can be excluded.

<WLAN 5GHz Conducted Power>

WLAN 5GHz 802.11a Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. Data Rate								
Channel	Frequency (MHz)	Data Rate 6Mbps	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps	
CH 36	5180	13.83	CH 36	13.75	13.78	13.79	13.73	13.81	13.80	13.82	14.0
CH 40	5200	13.72									
CH 44	5220	13.63									
CH 48	5240	13.75									
CH 52	5260	13.82	CH 60	13.96	13.95	13.96	13.93	13.92	13.96	13.93	
CH 56	5280	13.74									
CH 60	5300	13.98									
CH 64	5320	13.87									
CH 100	5500	13.97	CH 116	13.97	13.98	13.95	13.97	13.93	13.97	13.94	
CH 104	5520	13.88									
CH 108	5540	13.82									
CH 112	5560	13.86									
CH 116	5580	13.99									
CH 132	5660	13.89									
CH 136	5680	13.84									
CH 140	5700	13.97									
CH 149	5745	13.99	CH 149	13.94	13.96	13.67	13.60	13.69	13.71	13.68	
CH 153	5765	13.89									
CH 157	5785	13.95									
CH 161	5805	13.72									
CH 165	5825	13.77									

WLAN 5GHz 802.11n-HT20 Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. MCS Index								
Channel	Frequency (MHz)	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	
CH 36	5180	13.72	CH 48	13.83	13.83	13.82	13.83	13.78	13.76	13.81	14.0
CH 40	5200	13.68									
CH 44	5220	13.66									
CH 48	5240	13.84									
CH 52	5260	13.82	CH 60	13.93	13.98	13.98	13.97	13.92	13.94	13.94	
CH 56	5280	13.92									
CH 60	5300	13.99									
CH 64	5320	13.88									
CH 100	5500	13.72	CH 116	13.89	13.95	13.96	13.96	13.93	13.95	13.95	
CH 104	5520	13.74									
CH 108	5540	13.82									
CH 112	5560	13.85									
CH 116	5580	13.97									
CH 132	5660	13.76									
CH 136	5680	13.75									
CH 140	5700	13.79									
CH 149	5745	13.99	CH 149	13.92	13.97	13.98	13.97	13.81	13.76	13.85	
CH 153	5765	13.83									
CH 157	5785	13.96									
CH 161	5805	13.71									
CH 165	5825	13.79									


WLAN 5GHz 802.11n-HT40 Average Power (dBm)											Tune up Limit (dBm)
Power vs. Channel			Power vs. MCS Index								
Channel	Frequency (MHz)	MCS Index MCS0	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	
CH 38	5190	13.98	CH 38	13.90	13.79	13.91	13.95	13.97	13.97	13.92	14.0
CH 46	5230	13.97									
CH 54	5270	13.88	CH 62	13.88	13.88	13.81	13.88	13.86	13.77	13.88	
CH 62	5310	13.90									
CH 102	5510	13.99	CH 102	13.98	13.88	13.95	13.95	13.95	13.96	13.97	
CH 110	5550	13.89									
CH 134	5670	13.97									
CH 151	5755	13.72	CH 151	13.60	13.68	13.70	13.68	13.70	13.67	13.71	
CH 159	5795	13.67									

Note:

1. Per KDB 248227 D01 v01r02, choose the highest output power channel to test SAR and determine further SAR exclusion
2. For each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of these configurations is less than 1/4dB higher than those measured at the lowest data rate.
3. Apply the test exclusion rule in KDB 248227 D01 v01r02 11n-HT20/HT40 output power is less than 1/4dB higher than 11a mode, thus the SAR can be excluded.

12. Antenna Location

<Smart Phone>



Back View

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	≤ 25mm	≤ 25mm	120.5mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	104.9mm	58.9mm	≤ 25mm
Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	No	Yes

Note: Per KDB 941225 D06 v01r01, when the overall device length and width are ≥ 9cm*5cm, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

13. SAR Test Results

Note:

1. Per KDB 447498 D01v05r01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v05r01, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the reported 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Considering the possibility of e.g. 3rd part VoIP operation in the head exposure positions and body-worn positions were additional EGPRS SAR testing performed on voice mode worse case.
4. For GSM1900 DTM of head exposure positions and body worn exposure positions, the tune-up scaling factor was used source-based time-average power and tune-up limit calculation.
5. Per KDB 941225 D02v02r02, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA /HSUPA output power is < 0.25 dB higher than RMC12.2Kbps, or reported SAR with RMC 12.2kbps setting is ≤ 1.2 W/kg, HSDPA /HSUPA SAR evaluation can be excluded.
6. Per KDB 648474 D04v01r02, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is < 1.2 W/kg, SAR testing with a headset connected to the handset is required.
7. When hotspot mode is enabled, power reduction will be activated to limit the maximum power of GSM1900 band and UMTS band 2.
8. This device 2.4GHz WLAN supports Hotspot operation, and 2.4GHz / 5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.2GHz / 5.3GHz / 5.5GHz supports WiFi Direct (GC only).

13.1 Head SAR

<GSM SAR>

Plot No.	Band	Mode	Modulation	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
01	GSM850	GSM Voice	GMSK	Right Cheek	128	824.2	33.49	33.50	1.002	0.02	0.275	0.276	0.212	0.212
	GSM850	GSM Voice	GMSK	Right Tilted	128	824.2	33.49	33.50	1.002	0.02	0.157	0.157	0.124	0.124
	GSM850	GSM Voice	GMSK	Left Cheek	128	824.2	33.49	33.50	1.002	0.05	0.230	0.231	0.179	0.179
	GSM850	GSM Voice	GMSK	Left Tilted	128	824.2	33.49	33.50	1.002	0.09	0.123	0.123	0.098	0.098
	GSM850	GPRS (2 Tx slots)	GMSK	Right Cheek	189	836.4	30.49	30.50	1.002	-0.064	0.267	0.268	0.180	0.180
	GSM1900	DTM Multi-slot class 11	GSM Voice with 8PSK 2Tx	Right Cheek	810	1909.8	21.61	21.65	1.008	0.19	0.133	0.134	0.086	0.087
	GSM1900	DTM Multi-slot class 11	GSM Voice with 8PSK 2Tx	Right Tilted	810	1909.8	21.61	21.65	1.008	0.19	0.064	0.065	0.038	0.038
	GSM1900	DTM Multi-slot class 11	GSM Voice with 8PSK 2Tx	Left Cheek	810	1909.8	21.61	21.65	1.008	0.04	0.197	0.199	0.119	0.120
	GSM1900	DTM Multi-slot class 11	GSM Voice with 8PSK 2Tx	Left Tilted	810	1909.8	21.61	21.65	1.008	0.1	0.071	0.072	0.044	0.044
	GSM1900	EGPRS (4 Tx slots)	8PSK	Left Cheek	810	1909.8	24.38	25.90	1.419	0.09	0.184	0.261	0.098	0.139

**<WCDMA SAR>**

Plot No.	Band	Mode	Modulation	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
03	WCDMA V	RMC 12.2Kbps	QPSK	Right Cheek	4233	846.6	23.99	24.00	1.002	-0.08	0.404	0.405	0.309	0.310
	WCDMA V	RMC 12.2Kbps	QPSK	Right Tilted	4233	846.6	23.99	24.00	1.002	0.12	0.212	0.212	0.159	0.159
	WCDMA V	RMC 12.2Kbps	QPSK	Left Cheek	4233	846.6	23.99	24.00	1.002	0.06	0.376	0.377	0.282	0.283
	WCDMA V	RMC 12.2Kbps	QPSK	Left Tilted	4233	846.6	23.99	24.00	1.002	0.14	0.199	0.199	0.152	0.152
	WCDMA II	RMC 12.2Kbps	QPSK	Right Cheek	9400	1880	23.88	24.00	1.028	0	0.279	0.287	0.186	0.191
	WCDMA II	RMC 12.2Kbps	QPSK	Right Tilted	9400	1880	23.88	24.00	1.028	0.05	0.174	0.179	0.108	0.111
04	WCDMA II	RMC 12.2Kbps	QPSK	Left Cheek	9400	1880	23.88	24.00	1.028	0.02	0.564	0.580	0.346	0.356
	WCDMA II	RMC 12.2Kbps	QPSK	Left Tilted	9400	1880	23.88	24.00	1.028	0.07	0.197	0.203	0.128	0.132

<WLAN SAR DTS>

Plot No.	Band	Mode	Modulation	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
05	WLAN2.4Ghz	802.11b 1Mbps	DBPSK	Right Cheek	6	2437	16.98	17.00	1.004	97.63	1.024	0.01	0.607	0.624	0.287	0.295
	WLAN2.4Ghz	802.11b 1Mbps	DBPSK	Right Tilted	6	2437	16.98	17.00	1.004	97.63	1.024	-0.03	0.377	0.387	0.171	0.176
	WLAN2.4Ghz	802.11b 1Mbps	DBPSK	Left Cheek	6	2437	16.98	17.00	1.004	97.63	1.024	-0.05	0.231	0.237	0.131	0.135
	WLAN2.4Ghz	802.11b 1Mbps	DBPSK	Left Tilted	6	2437	16.98	17.00	1.004	97.63	1.024	0.06	0.217	0.223	0.111	0.114
06	WLAN5GHz	802.11a 6Mbps	OFDM	Right Cheek	149	5745	13.99	14.00	1.002	87.26	1.146	0.11	0.122	0.140	0.033	0.038
	WLAN5GHz	802.11a 6Mbps	OFDM	Right Tilted	149	5745	13.99	14.00	1.002	87.26	1.146	0.18	0.083	0.095	0.020	0.023
	WLAN5GHz	802.11a 6Mbps	OFDM	Left Cheek	149	5745	13.99	14.00	1.002	87.26	1.146	0.15	0.094	0.108	0.024	0.028
	WLAN5GHz	802.11a 6Mbps	OFDM	Left Tilted	149	5745	13.99	14.00	1.002	87.26	1.146	0.13	0.092	0.106	0.023	0.026

<WLAN SAR NII>

Plot No.	Band	Mode	Modulation	Test Position	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN5GHz	802.11a 6Mbps	OFDM	Right Cheek	36	5180	13.83	14.00	1.039	87.26	1.146	0.11	0.064	0.076	0.014	0.017
07	WLAN5GHz	802.11a 6Mbps	OFDM	Right Tilted	36	5180	13.83	14.00	1.039	87.26	1.146	0.1	0.065	0.077	0.016	0.019
	WLAN5GHz	802.11a 6Mbps	OFDM	Left Cheek	36	5180	13.83	14.00	1.039	87.26	1.146	0.12	0.009	0.011	0.002	0.002
	WLAN5GHz	802.11a 6Mbps	OFDM	Left Tilted	36	5180	13.83	14.00	1.039	87.26	1.146	0.12	0.013	0.015	0.002	0.003
	WLAN5GHz	802.11a 6Mbps	OFDM	Right Cheek	60	5300	13.98	14.00	1.004	87.26	1.146	0.12	0.052	0.060	0.010	0.012
08	WLAN5GHz	802.11a 6Mbps	OFDM	Right Tilted	60	5300	13.98	14.00	1.004	87.26	1.146	0.19	0.065	0.075	0.011	0.013
	WLAN5GHz	802.11a 6Mbps	OFDM	Left Cheek	60	5300	13.98	14.00	1.004	87.26	1.146	0.12	0.017	0.020	0.002	0.003
	WLAN5GHz	802.11a 6Mbps	OFDM	Left Tilted	60	5300	13.98	14.00	1.004	87.26	1.146	-0.19	0.022	0.025	0.004	0.004
09	WLAN5GHz	802.11a 6Mbps	OFDM	Right Cheek	116	5580	13.99	14.00	1.002	87.26	1.146	-0.05	0.091	0.104	0.031	0.036
	WLAN5GHz	802.11a 6Mbps	OFDM	Right Tilted	116	5580	13.99	14.00	1.002	87.26	1.146	0.02	0.084	0.096	0.021	0.024
	WLAN5GHz	802.11a 6Mbps	OFDM	Left Cheek	116	5580	13.99	14.00	1.002	87.26	1.146	0.16	0.035	0.040	0.010	0.011
	WLAN5GHz	802.11a 6Mbps	OFDM	Left Tilted	116	5580	13.99	14.00	1.002	87.26	1.146	0.15	0.032	0.037	0.008	0.010

13.2 Hotspot SAR

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	≤ 25mm	≤ 25mm	120.5mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	104.9mm	58.9mm	≤ 25mm
Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	No	Yes

Note:

- Per KDB 941225 D06 v01r01, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

<GSM SAR>

Plot No.	Band	Mode	Modulation	Test Position	Gap (cm)	Ch.	Freq. (MHz)	(Hotspot) Power Back-off	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
10	GSM850	GPRS (2 Tx slots)	GMSK	Front	1cm	128	824.2	-	30.49	30.50	1.002	-0.06	0.463	0.464	0.362	0.363
	GSM850	GPRS (2 Tx slots)	GMSK	Back	1cm	128	824.2	-	30.49	30.50	1.002	-0.02	0.448	0.449	0.351	0.352
	GSM850	GPRS (2 Tx slots)	GMSK	Left Side	1cm	128	824.2	-	30.49	30.50	1.002	0.01	0.384	0.385	0.269	0.270
	GSM850	GPRS (2 Tx slots)	GMSK	Right Side	1cm	128	824.2	-	30.49	30.50	1.002	0.03	0.426	0.427	0.299	0.300
	GSM850	GPRS (2 Tx slots)	GMSK	Bottom Side	1cm	128	824.2	-	30.49	30.50	1.002	0.19	0.077	0.077	0.045	0.045
	GSM1900	GPRS (1 Tx slots)	GMSK	Front	1cm	810	1909.8	ON	28.88	29.50	1.153	0.17	0.818	0.944	0.424	0.489
	GSM1900	GPRS (1 Tx slots)	GMSK	Front	1cm	512	1850.2	ON	28.62	29.50	1.225	0.07	0.651	0.797	0.343	0.420
	GSM1900	GPRS (1 Tx slots)	GMSK	Front	1cm	661	1880	ON	28.85	29.50	1.161	0.11	0.707	0.821	0.371	0.431
	GSM1900	GPRS (1 Tx slots)	GMSK	Back	1cm	810	1909.8	ON	28.88	29.50	1.153	-0.03	0.756	0.872	0.402	0.464
	GSM1900	GPRS (1 Tx slots)	GMSK	Back	1cm	512	1850.2	ON	28.62	29.50	1.225	0.13	0.554	0.678	0.303	0.371
	GSM1900	GPRS (1 Tx slots)	GMSK	Back	1cm	661	1880	ON	28.85	29.50	1.161	-0.1	0.646	0.750	0.348	0.404
	GSM1900	GPRS (1 Tx slots)	GMSK	Left Side	1cm	810	1909.8	ON	28.88	29.50	1.153	0.14	0.085	0.098	0.053	0.061
	GSM1900	GPRS (1 Tx slots)	GMSK	Right Side	1cm	810	1909.8	ON	28.88	29.50	1.153	0.16	0.054	0.062	0.033	0.038
11	GSM1900	GPRS (1 Tx slots)	GMSK	Bottom Side	1cm	810	1909.8	ON	28.88	29.50	1.153	0.05	0.896	1.033	0.461	0.532
	GSM1900	GPRS (1 Tx slots)	GMSK	Bottom Side	1cm	512	1850.2	ON	28.62	29.50	1.225	0.01	0.667	0.817	0.350	0.429
	GSM1900	GPRS (1 Tx slots)	GMSK	Bottom Side	1cm	661	1880	ON	28.85	29.50	1.161	0.01	0.764	0.887	0.398	0.462

<WCDMA SAR>

Plot No.	Band	Mode	Modulation	Test Position	Gap (cm)	Ch.	Freq. (MHz)	(Hotspot) Power Back-off	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
12	WCDMA V	RMC 12.2Kbps	QPSK	Front	1cm	4233	846.6	-	23.99	24.00	1.002	0.07	0.608	0.609	0.472	0.473
	WCDMA V	RMC 12.2Kbps	QPSK	Back	1cm	4233	846.6	-	23.99	24.00	1.002	-0.05	0.584	0.585	0.449	0.450
	WCDMA V	RMC 12.2Kbps	QPSK	Left Side	1cm	4233	846.6	-	23.99	24.00	1.002	0	0.455	0.456	0.316	0.317
	WCDMA V	RMC 12.2Kbps	QPSK	Right Side	1cm	4233	846.6	-	23.99	24.00	1.002	-0.02	0.507	0.508	0.354	0.355
	WCDMA V	RMC 12.2Kbps	QPSK	Bottom Side	1cm	4233	846.6	-	23.99	24.00	1.002	0.11	0.130	0.130	0.074	0.074
	WCDMA II	RMC 12.2Kbps	QPSK	Front	1cm	9400	1880	ON	20.48	20.50	1.005	0.18	0.921	0.925	0.475	0.477
	WCDMA II	RMC 12.2Kbps	QPSK	Front	1cm	9262	1852.4	ON	20.13	20.50	1.089	0.1	0.761	0.829	0.393	0.428
	WCDMA II	RMC 12.2Kbps	QPSK	Front	1cm	9538	1907.6	ON	20.39	20.50	1.026	0.13	1.010	1.036	0.516	0.529
	WCDMA II	RMC 12.2Kbps	QPSK	Back	1cm	9400	1880	ON	20.48	20.50	1.005	-0.01	0.818	0.822	0.431	0.433
	WCDMA II	RMC 12.2Kbps	QPSK	Back	1cm	9262	1852.4	ON	20.13	20.50	1.089	-0.11	0.620	0.675	0.330	0.359
	WCDMA II	RMC 12.2Kbps	QPSK	Back	1cm	9538	1907.6	ON	20.39	20.50	1.026	-0.02	0.960	0.985	0.500	0.513
	WCDMA II	RMC 12.2Kbps	QPSK	Left Side	1cm	9400	1880	ON	20.48	20.50	1.005	0.06	0.108	0.108	0.063	0.063
	WCDMA II	RMC 12.2Kbps	QPSK	Right Side	1cm	9400	1880	ON	20.48	20.50	1.005	0.01	0.061	0.061	0.035	0.035
13	WCDMA II	RMC 12.2Kbps	QPSK	Bottom Side	1cm	9400	1880	ON	20.48	20.50	1.005	0.01	1.100	1.105	0.565	0.568
	WCDMA II	RMC 12.2Kbps	QPSK	Bottom Side	1cm	9262	1852.4	ON	20.13	20.50	1.089	0.01	0.887	0.966	0.456	0.497
	WCDMA II	RMC 12.2Kbps	QPSK	Bottom Side	1cm	9538	1907.6	ON	20.39	20.50	1.026	-0.03	0.921	0.945	0.474	0.486

<WLAN SAR DTS>

Plot No.	Band	Mode	Modulation	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	DBPSK	Front	1cm	6	2437	16.98	17.00	1.004	97.63	1.024	-0.07	0.146	0.150	0.087	0.089
14	WLAN2.4GHz	802.11b 1Mbps	DBPSK	Back	1cm	6	2437	16.98	17.00	1.004	97.63	1.024	0.05	0.152	0.156	0.091	0.094
	WLAN2.4GHz	802.11b 1Mbps	DBPSK	Left Side	1cm	6	2437	16.98	17.00	1.004	97.63	1.024	0.06	0.122	0.125	0.066	0.068
	WLAN2.4GHz	802.11b 1Mbps	DBPSK	Top Side	1cm	6	2437	16.98	17.00	1.004	97.63	1.024	-0.03	0.125	0.128	0.071	0.073
	WLAN5GHz	802.11a 6Mbps	OFDM	Front	1cm	149	5745	13.99	14.00	1.002	97.63	1.024	-0.16	0.017	0.017	0.004	0.004
15	WLAN5GHz	802.11a 6Mbps	OFDM	Back	1cm	149	5745	13.99	14.00	1.002	97.63	1.024	-0.07	0.183	0.188	0.053	0.054
	WLAN5GHz	802.11a 6Mbps	OFDM	Left Side	1cm	149	5745	13.99	14.00	1.002	97.63	1.024	-0.06	0.144	0.148	0.042	0.043
	WLAN5GHz	802.11a 6Mbps	OFDM	Top Side	1cm	149	5745	13.99	14.00	1.002	97.63	1.024	0.16	0.030	0.031	0.011	0.011

13.3 Body Worn SAR
<GSM SAR>

Plot No.	Band	Mode	Modulation	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
16	GSM850	GSM Voice	GMSK	Front	1.5cm	128	824.2	33.49	33.50	1.002	-0.01	0.327	0.328	0.255	0.256
	GSM850	GSM Voice	GMSK	Back	1.5cm	128	824.2	33.49	33.50	1.002	-0.05	0.326	0.327	0.252	0.253
	GSM1900	DTM Multi-slot class 11	GSM Voice with 8PSK 2Tx	Front	1.5cm	810	1909.8	21.61	21.65	1.008	0.03	0.615	0.620	0.345	0.348
	GSM1900	DTM Multi-slot class 11	GSM Voice with 8PSK 2Tx	Back	1.5cm	810	1909.8	21.61	21.65	1.008	-0.01	0.549	0.553	0.316	0.319
17	GSM1900	EGPRS (4 Tx slots)	8PSK	Front	1.5cm	810	1909.8	24.38	25.90	1.419	0.11	0.563	0.799	0.317	0.450

<WCDMA SAR>

Plot No.	Band	Mode	Modulation	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
18	WCDMA V	RMC 12.2Kbps	QPSK	Front	1.5cm	4233	846.6	23.99	24.00	1.002	-0.02	0.532	0.533	0.408	0.409
	WCDMA V	RMC 12.2Kbps	QPSK	Back	1.5cm	4233	846.6	23.99	24.00	1.002	0.03	0.524	0.525	0.401	0.402
	WCDMA II	RMC 12.2Kbps	QPSK	Front	1.5cm	9400	1880	23.88	24.00	1.028	-0.03	0.907	0.932	0.510	0.524
	WCDMA II	RMC 12.2Kbps	QPSK	Front	1.5cm	9262	1852.4	23.74	24.00	1.062	-0.04	0.734	0.779	0.416	0.442
19	WCDMA II	RMC 12.2Kbps	QPSK	Front	1.5cm	9538	1907.6	23.79	24.00	1.050	0.01	1.060	1.113	0.587	0.616
	WCDMA II	RMC 12.2Kbps	QPSK	Back	1.5cm	9400	1880	23.88	24.00	1.028	0.02	0.808	0.831	0.466	0.479
	WCDMA II	RMC 12.2Kbps	QPSK	Back	1.5cm	9262	1852.4	23.74	24.00	1.062	-0.03	0.637	0.676	0.372	0.395
	WCDMA II	RMC 12.2Kbps	QPSK	Back	1.5cm	9538	1907.6	23.79	24.00	1.050	0.03	0.977	1.025	0.557	0.585

<WLAN SAR DTS>

Plot No.	Band	Mode	Modulation	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
20	WLAN2.4GHz	802.11b 1Mbps	DBPSK	Front	1.5cm	6	2437	16.98	17.00	1.004	97.63	1.024	-0.06	0.095	0.098	0.058	0.060
	WLAN2.4GHz	802.11b 1Mbps	DBPSK	Back	1.5cm	6	2437	16.98	17.00	1.004	97.63	1.024	0.09	0.078	0.080	0.046	0.047
	WLAN5GHz	802.11a 6Mbps	OFDM	Front	1.5cm	149	5745	13.99	14.00	1.002	87.26	1.146	-0.18	0.019	0.022	0.009	0.010
21	WLAN5GHz	802.11a 6Mbps	OFDM	Back	1.5cm	149	5745	13.99	14.00	1.002	87.26	1.146	-0.06	0.113	0.130	0.044	0.051

<WLAN SAR NII>

Plot No.	Band	Mode	Modulation	Test Position	Gap (cm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN5GHz	802.11a 6Mbps	OFDM	Front	1.5cm	36	5180	13.83	14.00	1.039	87.26	1.146	-0.13	0.011	0.013	0.007	0.008
22	WLAN5GHz	802.11a 6Mbps	OFDM	Back	1.5cm	36	5180	13.83	14.00	1.039	87.26	1.146	-0.1	0.051	0.061	0.021	0.025
	WLAN5GHz	802.11a 6Mbps	OFDM	Front	1.5cm	60	5300	13.98	14.00	1.004	87.26	1.146	0.16	0.007	0.009	0.002	0.002
23	WLAN5GHz	802.11a 6Mbps	OFDM	Back	1.5cm	60	5300	13.98	14.00	1.004	87.26	1.146	-0.03	0.063	0.073	0.024	0.028
	WLAN5GHz	802.11a 6Mbps	OFDM	Front	1.5cm	116	5580	13.99	14.00	1.002	87.26	1.146	0.18	0.012	0.014	0.004	0.005
24	WLAN5GHz	802.11a 6Mbps	OFDM	Back	1.5cm	116	5580	13.99	14.00	1.002	87.26	1.146	-0.18	0.082	0.094	0.029	0.033

13.4 Repeated SAR Measurement

No.	Band	Mode	Modulation	Test Position	Gap (cm)	Ch.	Freq. (MHz)	(Hotspot) Power Back-off	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WCDMA II	RMC 12.2Kbps	QPSK	Bottom Side	1cm	9400	1880	ON	20.48	20.5	1.005	0.01	1.100	-	1.105
2nd	WCDMA II	RMC 12.2Kbps	QPSK	Bottom Side	1cm	9400	1800	ON	20.48	20.5	1.005	0.01	0.967	1.14	0.971

Note:

- Per KDB 865664 D01v01r02, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg
- Per KDB 865664 D01v01r02, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.
- The ratio is the largest SAR to the smallest SAR among original and repeated measurement.
- All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

14. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Smart Phone			Note
		Head	Body-worn	Hotspot	
1.	GSM(Voice) + WLAN2.4GHz(data)	Yes	Yes		
2.	WCDMA(Voice) + WLAN2.4GHz(data)	Yes	Yes		
3.	GSM(Voice) + Bluetooth(data)	Yes	Yes		
4.	WCDMA((Voice) + Bluetooth(data)	Yes	Yes		
5.	GSM(Voice) + WLAN5GHz(data)	Yes	Yes		
6.	WCDMA(Voice) + WLAN5GHz(data)	Yes	Yes		
7.	GPRS/EDGE(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
8.	WCDMA(Data) + WLAN2.4GHz(data)	Yes	Yes	Yes	2.4GHz Hotspot
9.	GPRS/EDGE(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
10.	WCDMA(Data) + Bluetooth(data)	Yes	Yes	Yes	Bluetooth Tethering
11.	GPRS/EDGE(data) + WLAN5GHz(data)	Yes	Yes	Yes	WiFi Direct
12.	WCDMA(data) + WLAN5GHz(data)	Yes	Yes	Yes	WiFi Direct

Note:

- This device supports VoIP in GSM, WCDMA (e.g. 3rd part VoIP).
- WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
- This device 2.4GHz WLAN supports Hotspot operation, and 2.4GHz / 5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.2GHz / 5.3GHz / 5.5GHz supports WiFi Direct (GC only).
- EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
- The Scaled SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v05r01, simultaneous transmission SAR is compliant if,
 - Scalar SAR summation < 1.6W/kg.
 - $SPLSR = (SAR_1 + SAR_2)^{1.5} / (min. \text{ separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan
If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary
 - Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg
- For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01v05r01 based on the formula below.
 - $(max. \text{ power of channel, including tune-up tolerance, mW}) / (min. \text{ test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$; where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - When the minimum test separation distance is < 5mm, the distance is used 5mm to determine SAR test exclusion.
 - 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is > 50 mm.

Max Power	Exposure Position	Head	Hotspot	Body-worn
	Test separation	5 mm	10 mm	15mm
9.5 dBm	Estimated 1g SAR (W/kg)	0.378 W/kg	0.189 W/kg	0.126 W/kg
	Estimated 10g SAR (W/kg)	0.151 W/kg	0.076 W/kg	0.050 W/kg

14.1 Head Exposure Conditions

<WWAN + WLAN 2.4GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Right Cheek	GSM850	0.276	0.624	0.90
	GSM1900	0.134	0.624	0.76
	WCDMA V	0.405	0.624	1.03
	WCDMA II	0.287	0.624	0.91
Right Tilted	GSM850	0.157	0.387	0.54
	GSM1900	0.065	0.387	0.45
	WCDMA V	0.212	0.387	0.60
	WCDMA II	0.179	0.387	0.57
Left Cheek	GSM850	0.231	0.237	0.47
	GSM1900	0.199	0.237	0.44
	WCDMA V	0.377	0.237	0.61
	WCDMA II	0.580	0.237	0.82
Left Tilted	GSM850	0.123	0.223	0.35
	GSM1900	0.072	0.223	0.30
	WCDMA V	0.199	0.223	0.42
	WCDMA II	0.203	0.223	0.43

Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Right Cheek	GSM850	0.212	0.295	0.51
	GSM1900	0.087	0.295	0.38
	WCDMA V	0.310	0.295	0.61
	WCDMA II	0.191	0.295	0.49
Right Tilted	GSM850	0.124	0.176	0.30
	GSM1900	0.038	0.176	0.21
	WCDMA V	0.159	0.176	0.34
	WCDMA II	0.111	0.176	0.29
Left Cheek	GSM850	0.179	0.135	0.31
	GSM1900	0.120	0.135	0.26
	WCDMA V	0.283	0.135	0.42
	WCDMA II	0.356	0.135	0.49
Left Tilted	GSM850	0.098	0.114	0.21
	GSM1900	0.044	0.114	0.16
	WCDMA V	0.152	0.114	0.27
	WCDMA II	0.132	0.114	0.25

<WWAN + WLAN 5.2GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Right Cheek	GSM850	0.276	0.076	0.35
	GSM1900	0.134	0.076	0.21
	WCDMA V	0.405	0.076	0.48
	WCDMA II	0.287	0.076	0.36
Right Tilted	GSM850	0.157	0.077	0.23
	GSM1900	0.065	0.077	0.14
	WCDMA V	0.212	0.077	0.29
	WCDMA II	0.179	0.077	0.26
Left Cheek	GSM850	0.231	0.011	0.24
	GSM1900	0.199	0.011	0.21
	WCDMA V	0.377	0.011	0.39
	WCDMA II	0.580	0.011	0.59
Left Tilted	GSM850	0.123	0.015	0.14
	GSM1900	0.072	0.015	0.09
	WCDMA V	0.199	0.015	0.21
	WCDMA II	0.203	0.015	0.22

Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Right Cheek	GSM850	0.212	0.017	0.23
	GSM1900	0.087	0.017	0.10
	WCDMA V	0.310	0.017	0.33
	WCDMA II	0.191	0.017	0.21
Right Tilted	GSM850	0.124	0.019	0.14
	GSM1900	0.038	0.019	0.06
	WCDMA V	0.159	0.019	0.18
	WCDMA II	0.111	0.019	0.13
Left Cheek	GSM850	0.179	0.002	0.18
	GSM1900	0.120	0.002	0.12
	WCDMA V	0.283	0.002	0.29
	WCDMA II	0.356	0.002	0.36
Left Tilted	GSM850	0.098	0.003	0.10
	GSM1900	0.044	0.003	0.05
	WCDMA V	0.152	0.003	0.16
	WCDMA II	0.132	0.003	0.14

<WWAN + WLAN 5.3GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Right Cheek	GSM850	0.276	0.06	0.34
	GSM1900	0.134	0.06	0.19
	WCDMA V	0.405	0.06	0.47
	WCDMA II	0.287	0.06	0.35
Right Tilted	GSM850	0.157	0.075	0.23
	GSM1900	0.065	0.075	0.14
	WCDMA V	0.212	0.075	0.29
	WCDMA II	0.179	0.075	0.25
Left Cheek	GSM850	0.231	0.02	0.25
	GSM1900	0.199	0.02	0.22
	WCDMA V	0.377	0.02	0.40
	WCDMA II	0.580	0.02	0.60
Left Tilted	GSM850	0.123	0.025	0.15
	GSM1900	0.072	0.025	0.10
	WCDMA V	0.199	0.025	0.22
	WCDMA II	0.203	0.025	0.23

Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Right Cheek	GSM850	0.212	0.012	0.22
	GSM1900	0.087	0.012	0.10
	WCDMA V	0.310	0.012	0.32
	WCDMA II	0.191	0.012	0.20
Right Tilted	GSM850	0.124	0.013	0.14
	GSM1900	0.038	0.013	0.05
	WCDMA V	0.159	0.013	0.17
	WCDMA II	0.111	0.013	0.12
Left Cheek	GSM850	0.179	0.003	0.18
	GSM1900	0.120	0.003	0.12
	WCDMA V	0.283	0.003	0.29
	WCDMA II	0.356	0.003	0.36
Left Tilted	GSM850	0.098	0.004	0.10
	GSM1900	0.044	0.004	0.05
	WCDMA V	0.152	0.004	0.16
	WCDMA II	0.132	0.004	0.14

<WWAN + WLAN 5.5GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Right Cheek	GSM850	0.276	0.104	0.38
	GSM1900	0.134	0.104	0.24
	WCDMA V	0.405	0.104	0.51
	WCDMA II	0.287	0.104	0.39
Right Tilted	GSM850	0.157	0.096	0.25
	GSM1900	0.065	0.096	0.16
	WCDMA V	0.212	0.096	0.31
	WCDMA II	0.179	0.096	0.28
Left Cheek	GSM850	0.231	0.04	0.27
	GSM1900	0.199	0.04	0.24
	WCDMA V	0.377	0.04	0.42
	WCDMA II	0.580	0.04	0.62
Left Tilted	GSM850	0.123	0.037	0.16
	GSM1900	0.072	0.037	0.11
	WCDMA V	0.199	0.037	0.24
	WCDMA II	0.203	0.037	0.24

Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Right Cheek	GSM850	0.212	0.036	0.25
	GSM1900	0.087	0.036	0.12
	WCDMA V	0.310	0.036	0.35
	WCDMA II	0.191	0.036	0.23
Right Tilted	GSM850	0.124	0.024	0.15
	GSM1900	0.038	0.024	0.06
	WCDMA V	0.159	0.024	0.18
	WCDMA II	0.111	0.024	0.14
Left Cheek	GSM850	0.179	0.011	0.19
	GSM1900	0.120	0.011	0.13
	WCDMA V	0.283	0.011	0.29
	WCDMA II	0.356	0.011	0.37
Left Tilted	GSM850	0.098	0.010	0.11
	GSM1900	0.044	0.010	0.05
	WCDMA V	0.152	0.010	0.16
	WCDMA II	0.132	0.010	0.14

<WWAN + WLAN 5.8GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Right Cheek	GSM850	0.276	0.14	0.42
	GSM1900	0.134	0.14	0.27
	WCDMA V	0.405	0.14	0.55
	WCDMA II	0.287	0.14	0.43
Right Tilted	GSM850	0.157	0.095	0.25
	GSM1900	0.065	0.095	0.16
	WCDMA V	0.212	0.095	0.31
	WCDMA II	0.179	0.095	0.27
Left Cheek	GSM850	0.231	0.108	0.34
	GSM1900	0.199	0.108	0.31
	WCDMA V	0.377	0.108	0.49
	WCDMA II	0.580	0.108	0.69
Left Tilted	GSM850	0.123	0.106	0.23
	GSM1900	0.072	0.106	0.18
	WCDMA V	0.199	0.106	0.31
	WCDMA II	0.203	0.106	0.31

Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Right Cheek	GSM850	0.212	0.038	0.25
	GSM1900	0.087	0.038	0.13
	WCDMA V	0.310	0.038	0.35
	WCDMA II	0.191	0.038	0.23
Right Tilted	GSM850	0.124	0.023	0.15
	GSM1900	0.038	0.023	0.06
	WCDMA V	0.159	0.023	0.18
	WCDMA II	0.111	0.023	0.13
Left Cheek	GSM850	0.179	0.028	0.21
	GSM1900	0.120	0.028	0.15
	WCDMA V	0.283	0.028	0.31
	WCDMA II	0.356	0.028	0.38
Left Tilted	GSM850	0.098	0.026	0.12
	GSM1900	0.044	0.026	0.07
	WCDMA V	0.152	0.026	0.18
	WCDMA II	0.132	0.026	0.16

<WWAN + Bluetooth>

Position	WWAN		Bluetooth	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	Estimated 1g SAR (W/kg)	
Right Cheek	GSM850	0.276	0.378	0.65
	GSM1900	0.134	0.378	0.51
	WCDMA V	0.405	0.378	0.78
	WCDMA II	0.287	0.378	0.67
Right Tilted	GSM850	0.157	0.378	0.54
	GSM1900	0.065	0.378	0.44
	WCDMA V	0.212	0.378	0.59
	WCDMA II	0.179	0.378	0.56
Left Cheek	GSM850	0.231	0.378	0.61
	GSM1900	0.199	0.378	0.58
	WCDMA V	0.377	0.378	0.76
	WCDMA II	0.580	0.378	0.96
Left Tilted	GSM850	0.123	0.378	0.50
	GSM1900	0.072	0.378	0.45
	WCDMA V	0.199	0.378	0.58
	WCDMA II	0.203	0.378	0.58

Position	WWAN		Bluetooth	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	Estimated 10g SAR (W/kg)	
Right Cheek	GSM850	0.212	0.151	0.36
	GSM1900	0.087	0.151	0.24
	WCDMA V	0.310	0.151	0.46
	WCDMA II	0.191	0.151	0.34
Right Tilted	GSM850	0.124	0.151	0.28
	GSM1900	0.038	0.151	0.19
	WCDMA V	0.159	0.151	0.31
	WCDMA II	0.111	0.151	0.26
Left Cheek	GSM850	0.179	0.151	0.33
	GSM1900	0.120	0.151	0.27
	WCDMA V	0.283	0.151	0.43
	WCDMA II	0.356	0.151	0.51
Left Tilted	GSM850	0.098	0.151	0.25
	GSM1900	0.044	0.151	0.20
	WCDMA V	0.152	0.151	0.30
	WCDMA II	0.132	0.151	0.28

14.2 Hotspot Exposure Conditions

<WWAN + WLAN 2.4GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Front	GSM850	0.464	0.15	0.61
	GSM1900	0.944	0.15	1.09
	WCDMA V	0.609	0.15	0.76
	WCDMA II	1.036	0.15	1.19
Back	GSM850	0.449	0.156	0.61
	GSM1900	0.872	0.156	1.03
	WCDMA V	0.585	0.156	0.74
	WCDMA II	0.985	0.156	1.14
Left Side	GSM850	0.385	0.125	0.51
	GSM1900	0.098	0.125	0.22
	WCDMA V	0.456	0.125	0.58
	WCDMA II	0.108	0.125	0.23
Right Side	GSM850	0.427		0.43
	GSM1900	0.062		0.06
	WCDMA V	0.508		0.51
	WCDMA II	0.061		0.06
Top Side	GSM850		0.128	0.13
	GSM1900		0.128	0.13
	WCDMA V		0.128	0.13
	WCDMA II		0.128	0.13
Bottom Side	GSM850	0.077		0.08
	GSM1900	1.033		1.03
	WCDMA V	0.130		0.13
	WCDMA II	1.105		1.11



Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Front	GSM850	0.363	0.089	0.45
	GSM1900	0.489	0.089	0.58
	WCDMA V	0.473	0.089	0.56
	WCDMA II	0.529	0.089	0.62
Back	GSM850	0.352	0.094	0.45
	GSM1900	0.464	0.094	0.56
	WCDMA V	0.450	0.094	0.54
	WCDMA II	0.513	0.094	0.61
Left Side	GSM850	0.270	0.068	0.34
	GSM1900	0.061	0.068	0.13
	WCDMA V	0.317	0.068	0.39
	WCDMA II	0.063	0.068	0.13
Right Side	GSM850	0.300		0.30
	GSM1900	0.038		0.04
	WCDMA V	0.355		0.36
	WCDMA II	0.035		0.04
Top Side	GSM850		0.073	0.07
	GSM1900		0.073	0.07
	WCDMA V		0.073	0.07
	WCDMA II		0.073	0.07
Bottom Side	GSM850	0.045		0.05
	GSM1900	0.532		0.53
	WCDMA V	0.074		0.07
	WCDMA II	0.568		0.57

<WWAN + WLAN 5.8GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Front	GSM850	0.464	0.017	0.48
	GSM1900	0.944	0.017	0.96
	WCDMA V	0.609	0.017	0.63
	WCDMA II	1.036	0.017	1.05
Back	GSM850	0.449	0.225	0.67
	GSM1900	0.872	0.225	1.10
	WCDMA V	0.585	0.225	0.81
	WCDMA II	0.985	0.225	1.21
Left Side	GSM850	0.385	0.148	0.53
	GSM1900	0.098	0.148	0.25
	WCDMA V	0.456	0.148	0.60
	WCDMA II	0.108	0.148	0.26
Right Side	GSM850	0.427		0.43
	GSM1900	0.062		0.06
	WCDMA V	0.508		0.51
	WCDMA II	0.061		0.06
Top Side	GSM850		0.031	0.03
	GSM1900		0.031	0.03
	WCDMA V		0.031	0.03
	WCDMA II		0.031	0.03
Bottom Side	GSM850	0.077		0.08
	GSM1900	1.033		1.03
	WCDMA V	0.130		0.13
	WCDMA II	1.105		1.11



Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Front	GSM850	0.363	0.004	0.37
	GSM1900	0.489	0.004	0.49
	WCDMA V	0.473	0.004	0.48
	WCDMA II	0.529	0.004	0.53
Back	GSM850	0.352	0.064	0.42
	GSM1900	0.464	0.064	0.53
	WCDMA V	0.450	0.064	0.51
	WCDMA II	0.513	0.064	0.58
Left Side	GSM850	0.270	0.043	0.31
	GSM1900	0.061	0.043	0.10
	WCDMA V	0.317	0.043	0.36
	WCDMA II	0.063	0.043	0.11
Right Side	GSM850	0.300		0.30
	GSM1900	0.038		0.04
	WCDMA V	0.355		0.36
	WCDMA II	0.035		0.04
Top Side	GSM850		0.011	0.01
	GSM1900		0.011	0.01
	WCDMA V		0.011	0.01
	WCDMA II		0.011	0.01
Bottom Side	GSM850	0.045		0.05
	GSM1900	0.532		0.53
	WCDMA V	0.074		0.07
	WCDMA II	0.568		0.57

<WWAN + Bluetooth>

Position	WWAN		Bluetooth	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	Estimated 1g SAR (W/kg)	
Front	GSM850	0.464	0.189	0.65
	GSM1900	0.944	0.189	1.13
	WCDMA V	0.609	0.189	0.80
	WCDMA II	1.036	0.189	1.23
Back	GSM850	0.449	0.189	0.64
	GSM1900	0.872	0.189	1.06
	WCDMA V	0.585	0.189	0.77
	WCDMA II	0.985	0.189	1.17
Left Side	GSM850	0.385	0.189	0.57
	GSM1900	0.098	0.189	0.29
	WCDMA V	0.456	0.189	0.65
	WCDMA II	0.108	0.189	0.30
Right Side	GSM850	0.427		0.43
	GSM1900	0.062		0.06
	WCDMA V	0.508		0.51
	WCDMA II	0.061		0.06
Top Side	GSM850		0.189	0.19
	GSM1900		0.189	0.19
	WCDMA V		0.189	0.19
	WCDMA II		0.189	0.19
Bottom Side	GSM850	0.077		0.08
	GSM1900	1.033		1.03
	WCDMA V	0.130		0.13
	WCDMA II	1.105		1.11



Position	WWAN		Bluetooth	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	Estimated 10g SAR (W/kg)	
Front	GSM850	0.363	0.076	0.44
	GSM1900	0.489	0.076	0.57
	WCDMA V	0.473	0.076	0.55
	WCDMA II	0.529	0.076	0.61
Back	GSM850	0.352	0.076	0.43
	GSM1900	0.464	0.076	0.54
	WCDMA V	0.450	0.076	0.53
	WCDMA II	0.513	0.076	0.59
Left Side	GSM850	0.270	0.076	0.35
	GSM1900	0.061	0.076	0.14
	WCDMA V	0.317	0.076	0.39
	WCDMA II	0.063	0.076	0.14
Right Side	GSM850	0.300		0.30
	GSM1900	0.038		0.04
	WCDMA V	0.355		0.36
	WCDMA II	0.035		0.04
Top Side	GSM850		0.076	0.08
	GSM1900		0.076	0.08
	WCDMA V		0.076	0.08
	WCDMA II		0.076	0.08
Bottom Side	GSM850	0.045		0.05
	GSM1900	0.532		0.53
	WCDMA V	0.074		0.07
	WCDMA II	0.568		0.57

14.3 Body-Worn Exposure Conditions

<WWAN + WLAN 2.4GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Front	GSM850	0.328	0.098	0.43
	GSM1900	0.799	0.098	0.90
	WCDMA V	0.533	0.098	0.63
	WCDMA II	1.113	0.098	1.21
Back	GSM850	0.327	0.080	0.41
	GSM1900	0.553	0.080	0.63
	WCDMA V	0.525	0.080	0.61
	WCDMA II	1.025	0.080	1.11

Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Front	GSM850	0.256	0.060	0.32
	GSM1900	0.450	0.060	0.51
	WCDMA V	0.409	0.060	0.47
	WCDMA II	0.616	0.060	0.68
Back	GSM850	0.253	0.047	0.30
	GSM1900	0.319	0.047	0.37
	WCDMA V	0.402	0.047	0.45
	WCDMA II	0.585	0.047	0.63

<WWAN + WLAN 5.2GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Front	GSM850	0.328	0.013	0.34
	GSM1900	0.799	0.013	0.81
	WCDMA V	0.533	0.013	0.55
	WCDMA II	1.113	0.013	1.13
Back	GSM850	0.327	0.061	0.39
	GSM1900	0.553	0.061	0.61
	WCDMA V	0.525	0.061	0.59
	WCDMA II	1.025	0.061	1.09

Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Front	GSM850	0.256	0.008	0.26
	GSM1900	0.450	0.008	0.46
	WCDMA V	0.409	0.008	0.42
	WCDMA II	0.616	0.008	0.62
Back	GSM850	0.253	0.033	0.29
	GSM1900	0.319	0.033	0.35
	WCDMA V	0.402	0.033	0.44
	WCDMA II	0.585	0.033	0.62

<WWAN + WLAN 5.3GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Front	GSM850	0.328	0.009	0.34
	GSM1900	0.799	0.009	0.81
	WCDMA V	0.533	0.009	0.54
	WCDMA II	1.113	0.009	1.12
Back	GSM850	0.327	0.073	0.40
	GSM1900	0.553	0.073	0.63
	WCDMA V	0.525	0.073	0.60
	WCDMA II	1.025	0.073	1.10

Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Front	GSM850	0.256	0.002	0.26
	GSM1900	0.450	0.002	0.45
	WCDMA V	0.409	0.002	0.41
	WCDMA II	0.616	0.002	0.62
Back	GSM850	0.253	0.028	0.28
	GSM1900	0.319	0.028	0.35
	WCDMA V	0.402	0.028	0.43
	WCDMA II	0.585	0.028	0.61

<WWAN + WLAN 5.5GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Front	GSM850	0.328	0.014	0.34
	GSM1900	0.799	0.014	0.81
	WCDMA V	0.533	0.014	0.55
	WCDMA II	1.113	0.014	1.13
Back	GSM850	0.327	0.094	0.42
	GSM1900	0.553	0.094	0.65
	WCDMA V	0.525	0.094	0.62
	WCDMA II	1.025	0.094	1.12

Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Front	GSM850	0.256	0.005	0.26
	GSM1900	0.450	0.005	0.46
	WCDMA V	0.409	0.005	0.41
	WCDMA II	0.616	0.005	0.62
Back	GSM850	0.253	0.052	0.31
	GSM1900	0.319	0.052	0.37
	WCDMA V	0.402	0.052	0.45
	WCDMA II	0.585	0.052	0.64

<WWAN + WLAN 5.8GHz Band>

Position	WWAN		WLAN	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	1g SAR (W/kg)	
Front	GSM850	0.328	0.022	0.35
	GSM1900	0.799	0.022	0.82
	WCDMA V	0.533	0.022	0.56
	WCDMA II	1.113	0.022	1.14
Back	GSM850	0.327	0.132	0.46
	GSM1900	0.553	0.132	0.69
	WCDMA V	0.525	0.132	0.66
	WCDMA II	1.025	0.132	1.16

Position	WWAN		WLAN	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	10g SAR (W/kg)	
Front	GSM850	0.256	0.010	0.27
	GSM1900	0.450	0.010	0.46
	WCDMA V	0.409	0.010	0.42
	WCDMA II	0.616	0.010	0.63
Back	GSM850	0.253	0.051	0.30
	GSM1900	0.319	0.051	0.37
	WCDMA V	0.402	0.051	0.45
	WCDMA II	0.585	0.051	0.64

<WWAN + Bluetooth>

Position	WWAN		Bluetooth	Summed 1g SAR (W/kg)
	WWAN Band	1g SAR (W/kg)	Estimated 1g SAR (W/kg)	
Front	GSM850	0.328	0.126	0.45
	GSM1900	0.799	0.126	0.93
	WCDMA V	0.533	0.126	0.66
	WCDMA II	1.113	0.126	1.24
Back	GSM850	0.327	0.126	0.45
	GSM1900	0.553	0.126	0.68
	WCDMA V	0.525	0.126	0.65
	WCDMA II	1.025	0.126	1.15

Position	WWAN		Bluetooth	Summed 10g SAR (W/kg)
	WWAN Band	10g SAR (W/kg)	Estimated 10g SAR (W/kg)	
Front	GSM850	0.256	0.050	0.31
	GSM1900	0.450	0.050	0.50
	WCDMA V	0.409	0.050	0.46
	WCDMA II	0.616	0.050	0.67
Back	GSM850	0.253	0.050	0.30
	GSM1900	0.319	0.050	0.37
	WCDMA V	0.402	0.050	0.45
	WCDMA II	0.585	0.050	0.64

Test Engineer : Mood Huang, Aaron Chen, Jack Wu, Tom Jiang, Angelo Chang, Frank Wu, Nick Yu, and Galen Zhang

15. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 14.1

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	1/k ^(b)	1/√3	1/√6	1/√2

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) k is the coverage factor

Table 15.1. Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
Measurement System							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 11.0 %	± 10.8 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						± 22.0 %	± 21.5 %

Table 15.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
Measurement System							
Probe Calibration	6.55	Normal	1	1	1	± 6.55 %	± 6.55 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Probe Positioning	9.9	Rectangular	√3	1	1	± 5.7 %	± 5.7 %
Max. SAR Eval.	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 12.8 %	± 12.6 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						± 25.6 %	± 25.2 %

Table 15.3. Uncertainty Budget for frequency range 3 GHz to 6 GHz

16. References

- [1] FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”
- [2] ANSI/IEEE Std. C95.1-1992, “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz”, September 1992
- [3] IEEE Std. 1528-2003, “Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”, December 2003
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v01r02, “SAR Measurement Procedures for 802.11 a/b/g Transmitters”, May 2007
- [6] FCC KDB 447498 D01 v05r01, “Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies”, May 2013
- [7] FCC KDB 648474 D04 v01r01r02, “SAR Evaluation Considerations for Wireless Handsets”, Dec 2013
- [8] FCC KDB 941225 D03 v01, “Recommended SAR Test Reduction Procedures for GSM / GPRS / EDGE”, December 2008
- [9] FCC KDB 941225 D04 v01, “Evaluating SAR for GSM/(E)GPRS Dual Transfer Mode”, January 2010
- [10] FCC KDB 941225 D01 v02, “SAR Measurement Procedures for 3G Devices – CDMA 2000 / Ev-Do / WCDMA / HSDPA / HSPA”, October 2007
- [11] FCC KDB 941225 D02 v02r02, “SAR Guidance for HSPA, HSPA+, DC-HSDPA and 1x-Advanced”, May 2013.
- [12] FCC KDB 941225 D06 v01r01, “SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities”, May 2013
- [13] FCC KDB 865664 D01 v01r02, “SAR Measurement Requirements for 100 MHz to 6 GHz”, Dec 2013.