



TEST REPORT

No. 2013TAR895

for

Sony Mobile Communications AB

GSM/WCDMA/LTE Mobile Phone

Type: PM-0763-BV

FCC ID: PY7PM-0763

IC No.: 4170B-PM0763

with

Hardware Version: AP1

Software Version: 19.0.A.0.261

Issued Date: Jan. 28th, 2014

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

DAkks accreditation (DIN EN ISO/IEC 17025): No. D-PL-12123-01-01

FCC 2.948 Listed: No.733176

IC O.A.T.S listed: No.6629A-1

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0) 10-62304633-2561, Fax: +86(0)10-62304633-2504 Email:welcome@emcite.com. www.emcite.com

CONTENTS

1. TEST LABORATORY.....	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA.....	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	5
3.4. GENERAL DESCRIPTION	6
3.5. EUT SET-UPS	6
4. REFERENCE DOCUMENTS	7
4.1. REFERENCE DOCUMENTS FOR TESTING.....	7
5. LABORATORY ENVIRONMENT	8
6. SUMMARY OF TEST RESULTS.....	9
6.1. SUMMARY OF TEST RESULTS	9
6.2. STATEMENTS	10
7. TEST EQUIPMENTS UTILIZED.....	11
ANNEX A: MEASUREMENT RESULTS	12
A.1 OUTPUT POWER.....	12
A.2 EMISSION LIMIT	18
A.3 CONDUCTED EMISSION.....	22
A.4 FREQUENCY STABILITY	25
A.5 OCCUPIED BANDWIDTH	28
A.6 EMISSION BANDWIDTH.....	52
A.7 BAND EDGE COMPLIANCE	64
A.8 CONDUCTED SPURIOUS EMISSION	71
A.9 RECEIVER RADIATION EMISSION	94
ANNEX B: TEST LAYOUT	96
ANNEX C: EUT PHOTOGRAPH.....	97

1. Test Laboratory

1.1. Testing Location

Location A

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: No 52, Huayuan Bei Road, Haidian District, Beijing, P.R. China
Postal Code: 100191

Location B

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT
Address: Building Shouxian, No.51, Xueyuan Road, Haidian District, Beijing, China
Postal Code: 100191

1.2. Testing Environment

Normal Temperature: 15-35℃
Relative Humidity: 20-75%
Air pressure 980 - 1040 hPa

The climatic requirements above are general exclude the special requirements for dedicated test environments listed in section 5 and some specific test cases in other parts of this report.


1.3. Project data

Receipt of Sample Jan. 06th, 2014
Testing Start Date: Jan. 08th, 2014
Testing End Date: Jan. 27th, 2014


1.4. Signature



Qu Pengfei
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Song Chongwen
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: Sony Mobile Communications (China) Co. Ltd
Address /Post: Sony Mobile R&D Center, No. 16, Guangshun South Street,
Chaoyang District
City: Beijing
Postal Code: 100102
Country: China
Contact Person: Ma, Gang
Telephone: +86-10-58656312
Fax: +86-10-58659049

2.2. Manufacturer Information

Company Name: Sony Mobile Communications AB
Address /Post: Mobilvägen, 22188 Lund, Sweden
City: Lund
Postal Code: 22188
Country: Sweden
Contact Person: Nilsson, Mikael
Telephone: +46 703 227503
Fax: +46 706 127385

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM 850/900/1800/1900 quad bands, GPRS, EDGE, WCDMA FDD bands 1/2/4/5/8, HSDPA, HSUPA, LTE FDD bands 2/4/7/17, Bluetooth (EDR and 4.0), ANT+, WLAN (802.11 a/b/g/n), NFC, FM, GPS mobile phone
Type	PM-0763-BV
FCC ID	PY7PM-0763
IC No.	4170B-PM0763
GSM Frequency Band	GSM 850/900/1800/1900
UMTS Frequency Band	FDD Band 1 / FDD Band 2 / FDD Band 4/ FDD Band 5/ FDD Band 8
LTE Frequency Band	FDD Band 2 / FDD Band 4 / FDD Band 7 / FDD Band 17
Output power	32.13 dBm maximum ERP measured for GSM 850MHz band 32.72 dBm maximum EIRP measured for GSM 1900MHz band
Antenna	Internal
Power supply	Battery (charged by travel adapter or vehicle charger)
Extreme vol. Limits	3.5VDC to 4.1VDC (nominal: 3.7VDC)
Extreme temp. Tolerance	-20°C to +55°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN	IMEI	HW Version	SW Version
EUT2	CB51268CHN	004402451853752	AP1	19.0.A.0.261
EUT3	CB51268CUC	004402451853299	AP1	19.0.A.0.261

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN	Revision
AE1	Travel Charger	4413W 18 511285	1
AE3	USB Cable	131307D20BE8904	1
AE4	Embedded Battery	/	1C

AE1

Commercial name	EP880
Type	AC-0400-EU
Manufacturer	SALCOMP
Length of cable	98.5 cm (length of USB cable)

AE3

Commercial name	EC801
Type	AI-0401
Manufacturer	Sony Mobile
Length of cable	98.5 cm

AE4

Model name	1277-4767
Manufacturer	Sony Mobile
Minimum Capacitance	3000 mAh
Nominal Voltage	3.8V

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment Under Test (EUT) is a model of GSM/WCDMA/LTE Mobile Phone with integrated antenna and embedded battery.

The EUT supports GSM 850/900/1800/1900MHz bands, WCDMA FDD bands 1/2/4/5/8 and LTE FDD bands 2/4/7/17. It supports GPRS service with multi-slots class 33 and EGPRS service with multi-slots class 33. The HSDPA and HSUPA (Cat 6) features are also supported.

It has MP3, camera, USB memory, FM radio, GPS receiver, NFC, Bluetooth (EDR and Bluetooth 4.0), ANT+, WLAN (802.11 a/b/g/n) and Wi-Fi hotspot functions. For WLAN 802.11n, it supports 20MHz and 40MHz bandwidths on both 2.4GHz band and 5GHz/5.8GHz bands.

It consists of normal options: USB cable and travel charger.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

3.5. EUT set-ups

EUT Set-up No.	Combination of EUT and AE	Remarks
Set.3	EUT2 + AE1 + AE3 + AE4	Tests with travel charger
Set.4	EUT2 + AE4	ERP/EIRP/RSE tests
Set.5	EUT3 + AE4	Conducted RF tests

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 15	Radio frequency devices	10-1-12 Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-13 Edition
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-13 Edition
RSS-Gen	General Requirements and Information for the Certification of Radiocommunication Equipment	Issue 3
RSS-132	Cellular Telephones Employing New Technologies Operating in the Bands 824-849 MHz and 869-894 MHz	Issue 3
RSS-133	2 GHz Personal Communications Services	Issue 6
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2009

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber SAC-1 (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4Ω
Normalised site attenuation (NSA)	< ± 4 dB, 3m/10m distance, from 30 to 1000 MHz
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

Fully-anechoic chamber FAC-3 (9 meters×6.5 meters×4 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

Shielded room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω

6. SUMMARY OF TEST RESULTS

6.1. Summary of test results

Abbreviations used in this clause:		
Verdict Column	P	Pass
	F	Fail
	NA	Not applicable
	NM	Not measured
Location Column	A/B/C/D	The test is performed in test location A, B, C or D which are described in section 1.1 of this report

GSM 850

Items	Test Name	Clause in FCC rules	Clause in IC rules	Section in this report	Verdict	Test Location
1	Output Power	22.913(a)	5.4	A.1	P	B
2	Emission Limit	22.917, 2.1051	5.5	A.2	P	B
3	Conducted Emission	15.107/207	7.2.2	A.3	P	A
4	Frequency Stability	22.355, 2.1055	5.3	A.4	P	B
5	Occupied Bandwidth	2.1049(h)(i)	5.5	A.5	P	B
6	Emission Bandwidth	22.917(b)	5.5	A.6	P	B
7	Band Edge Compliance	22.917(b)	5.5	A.7	P	B
8	Conducted Spurious Emission	22.917, 2.1057	5.5	A.8	P	B
9	Receiver Spurious Emissions	15.109, 2.1053	5.6	A.9	P	A

PCS 1900

Items	Test Name	Clause in FCC rules	Clause in IC rules	Section in this report	Verdict	Test Location
1	Output Power	24.232(c)	6.4	A.1	P	B
2	Emission Limit	24.238, 2.1051	6.5	A.2	P	B
3	Conducted Emission	15.107/207	7.2.2	A.3	P	A
4	Frequency Stability	24.235, 2.1055	6.3	A.4	P	B
5	Occupied Bandwidth	2.1049(h)(i)	6.5	A.5	P	B
6	Emission Bandwidth	24.238(b)	6.5	A.6	P	B
7	Band Edge Compliance	24.238(b)	6.5	A.7	P	B
8	Conducted Spurious Emission	24.238, 2.1057	6.5	A.8	P	B
9	Receiver Spurious Emissions	15.109, 2.1053	6.6	A.9	P	A

6.2. Statements

The test cases listed in section 6.1 of this report for the EUT specified in section 3 were performed by TMC according to the standards or reference documents in section 4.1.

The EUT met all applicable requirements of the standards or reference documents in section 4.1. This report only deals with the GSM/GPRS/EGPRS functions among the features described in section 3.

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE
1.	Test Receiver	ESCI	100344	R&S	2014-03-28
2.	Test Receiver	ESCI 7	100948	R&S	2014-07-18
3.	Spectrum Analyzer	FSV40	101047	R&S	2014-06-30
4.	Spectrum Analyzer	E4440A	MY48250642	Agilent	2014-03-04
5.	LISN	ESH2-Z5	829991/012	R&S	2014-04-14
6.	EMI Antenna	VULB 9163	9163-482	Schwarzbeck	2014-02-17
7.	EMI Antenna	VULB 9163	9163-483	Schwarzbeck	2014-02-17
8.	EMI Antenna	3117	00119024	ETS-Lindgren	2014-02-02
9.	EMI Antenna	3117	00058889	ETS-Lindgren	2014-02-02
10.	EMI Antenna	3115	6914	ETS-Lindgren	2014-12-16
11.	EMI Antenna	VUBA 9117	167	Schwarzbeck	2014-04-01
12.	Signal Generator	N5183A	MY49060052	Agilent	2014-03-19
13.	Power Amplifier	5S1G4	0341863	AR	2016-03-01
14.	Climatic chamber	SH-241	92003546	ESPEC	2014-05-11
15.	Universal Radio Communication Tester	CMU200	109914	R&S	2014-04-18
16.	Universal Radio Communication Tester	CMU200	116455	R&S	2014-05-19
17.	Universal Radio Communication Tester	E5515C	MY48363198	Agilent	2014-07-08

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

Reference

FCC: CFR Part 22.913(a), 24.232(c).

IC: RSS-132 Issue 3, Section 5.4. RSS-133 Issue 6, Section 6.4.

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU200) to ensure max power transmission and proper modulation.

This result contains peak output power, ERP/EIRP measurements and peak-to-average power ratio (PAPR) for the EUT.

In all cases, output power is within the specified limits.

A.1.2 Conducted Power

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with spectrum analyzer's peak detector.

These measurements were done at 3 frequencies (bottom, middle and top of operational frequency range) for each band: 1850.2 MHz, 1880.0MHz and 1909.8MHz for PCS1900 band; 824.2MHz, 836.6MHz and 848.8MHz for GSM850 band.

GSM850

Limit

	Power step	Nominal Peak output power (dBm)	Tolerance (dB)	Target (dBm)
GSM	5	33dBm(2W)	± 2	33±1
GPRS	3	33dBm(2W)	± 2	33±1
EGPRS	6	33dBm(2W)	± 2	33±1

Measurement result

GSM (GMSK)

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	5	32.63
836.6	5	32.57
848.8	5	32.72

GPRS (GMSK, Time Slot 1)

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	3	32.61
836.6	3	32.55
848.8	3	32.72

EGPRS (8PSK, Time Slot 1)

Frequency(MHz)	Power Step	Peak output power(dBm)
824.2	6	27.01
836.6	6	26.91
848.8	6	26.80

Note: Expanded measurement uncertainty for GSM850 is $U = 0.52$ dB, $k = 2$.

PCS1900
Limit

	Power step	Nominal Peak output power (dBm)	Tolerance (dB)	Target (dBm)
GSM	0	30dBm(1W)	± 2	30 ± 1
GPRS	3	30dBm(1W)	± 2	30 ± 1
EGPRS	5	30dBm(1W)	± 2	30 ± 1

Measurement result
GSM (GMSK)

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	0	30.03
1880.0	0	30.07
1909.8	0	30.12

GPRS (GMSK, Time Slot 1)

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	3	30.07
1880.0	3	30.02
1909.8	3	30.08

EGPRS (8PSK, Time Slot 1)

Frequency(MHz)	Power Step	Peak output power(dBm)
1850.2	5	26.45
1880.0	5	26.58
1909.8	5	26.61

Note: Expanded measurement uncertainty for PCS1900 is $U = 0.83$ dB, $k = 2$.

A.1.3 Radiated Power

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.


Rule Part 24.232(c) specifies "Mobile and portable stations are limited to 2 watts EIRP" and 24.232(e) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603C-2004 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the amplifier and the substitution antenna.
The cable loss (P_{cl}), the substitution antenna Gain (G_a) and the amplifier Gain (P_{Ag}) should be recorded after test.
The measurement results are obtained as described below:
Power (EIRP) = $P_{Mea} - P_{Ag} - P_{cl} - G_a$
5. This value is EIRP since the measurement is calibrated using an antenna of known gain (Unit: dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15.

For test layout photo, please refer to Pic.1 in Annex B.

GSM 850- ERP 22.913(a)

Limits

	Power Step	Burst Peak ERP (dBm)
GSM	5	≤38.45dBm (7W)
GPRS	3	≤38.45dBm (7W)
EGPRS	6	≤38.45dBm (7W)

Measurement result

GSM (GMSK)

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	P_{Ag} (dB)	G_a (dBi)	Correction (dB)	Peak ERP(dBm)	Polarization
824.2	-15.84	2.07	-53	0.84	2.15	32.10	Vertical
836.6	-16.23	2.08	-53	0.9	2.15	31.64	Vertical
848.8	-16.26	2.09	-53	0.95	2.15	31.55	Vertical

GPRS (GMSK)

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	P_{Ag} (dB)	G_a (dBi)	Correction (dB)	Peak ERP(dBm)	Polarization
824.2	-15.81	2.07	-53.00	0.84	2.15	32.13	Vertical
836.6	-16.19	2.08	-53.00	0.90	2.15	31.68	Vertical
848.8	-16.21	2.09	-53.00	0.95	2.15	31.60	Vertical

EGPRS (8PSK)

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	P_{Ag} (dB)	G_a (dBi)	Correction (dB)	Peak ERP(dBm)	Polarization
824.2	-19.77	2.07	-53.00	0.84	2.15	28.17	Vertical
836.6	-20.49	2.08	-53.00	0.90	2.15	27.38	Vertical
848.8	-20.69	2.09	-53.00	0.95	2.15	27.12	Vertical

Sample calculation: GPRS, 824.20 MHz

$$\begin{aligned} \text{Peak ERP(dBm)} &= P_{\text{Mea}}(-15.81 \text{ dBm}) - G_a(0.84 \text{ dBi}) - P_{\text{Ag}}(-53.00 \text{ dB}) - P_{\text{cl}}(2.07 \text{ dB}) - 2.15 \text{ dB} \\ &= 32.13 \text{ dBm} \end{aligned}$$

ANALYZER SETTINGS: RBW = VBW = 3MHz

Note: Expanded measurement uncertainty for GSM850 is $U = 0.96\text{dB}$, $k = 2$.

PCS1900- EIRP 24.232(c)

Limits

	Power Step	Burst Peak EIRP (dBm)
GSM	0	$\leq 33\text{dBm}$ (2W)
GPRS	3	$\leq 33\text{dBm}$ (2W)
EGPRS	5	$\leq 33\text{dBm}$ (2W)

Measurement result

GSM (GMSK)

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	P_{Ag} (dB)	G_a (dBi)	Peak EIRP(dBm)	Polarization
1850.2	-19.38	3.19	-50.00	-4.56	31.99	Horizontal
1880.0	-18.88	3.11	-50.00	-4.43	32.44	Horizontal
1909.8	-18.40	3.18	-50.00	-4.30	32.72	Horizontal

GPRS (GMSK)

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	P_{Ag} (dB)	G_a (dBi)	Peak EIRP(dBm)	Polarization
1850.2	-19.41	3.19	-50.00	-4.56	31.96	Horizontal
1880.0	-18.84	3.11	-50.00	-4.43	32.48	Horizontal
1909.8	-18.68	3.18	-50.00	-4.30	32.44	Horizontal

EGPRS (8PSK)

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	P_{Ag} (dB)	G_a (dBi)	Peak EIRP(dBm)	Polarization
1850.2	-22.09	3.19	-50.00	-4.56	29.28	Horizontal
1880.0	-21.41	3.11	-50.00	-4.43	29.91	Horizontal
1909.8	-20.85	3.18	-50.00	-4.30	30.27	Horizontal

Sample calculation: GSM, 1909.8 MHz

$$\begin{aligned} \text{Peak EIRP(dBm)} &= P_{\text{Mea}}(-18.40 \text{ dBm}) - G_a(-4.30 \text{ dBi}) - P_{\text{Ag}}(-50.00 \text{ dB}) - P_{\text{cl}}(3.18 \text{ dB}) = 32.72 \\ &\text{dBm} \end{aligned}$$

ANALYZER SETTINGS: RBW = VBW = 3MHz

Note: Expanded measurement uncertainty for PCS1900 is $U = 1.07 \text{ dB}$, $k = 2$.

A.1.4 Peak-to-Average Power Ratio (PAPR)**A1.4.1 Description**

According to RSS 132 and 133, the transmitter's peak-to-average power ratio (PAPR) shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

The parameter of spectrum analyzer: RBW = 10MHz, detector = sample

A.1.4.2 Measurement results**GSM 850MHz**

Frequency (MHz)	PAPR Measurement Result (dB)		
	GSM 850MHz	GPRS 850MHz	EGPRS 850MHz
836.6	7.69	7.72	10.71

GSM 1900MHz

Frequency (MHz)	PAPR Measurement Result (dB)		
	GSM 1900MHz	GPRS 1900MHz	EGPRS 1900MHz
1880.0	7.72	7.72	10.19

Note: Expanded measurement uncertainty for PCS1900 is $U = 0.83$ dB, $k = 2$.

A.2 EMISSION LIMIT

Reference

FCC: CFR 2.1051, Part 22.917(a), 24.238(a).

IC: RSS-132 Issue 3, Section 5.5. RSS-133 Issue 6, Section 6.5.


A.2.1 Measurement Method

The measurements procedures in TIA-603C-2004 are used. This measurement is carried out in fully-anechoic chamber FAC-3.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the PCS1900 band, GSM850 band.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

An amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{Mea} + P_{pl} + G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit: dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dB}$.

A.2.2 Measurement Limit

Part 24.238 specifies that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS band (1850.2 MHz, 1880 MHz and 1909.8 MHz), GSM850 band (824.2MHz, 836.6MHz and 848.8MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the GSM850 or PCS1900 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

GSM Mode Channel 128/824.2MHz

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
2472.84	-39.75	3.56	-5.32	2.15	-40.14	-13.00	Vertical
4121.16	-53.76	4.68	-8.57	2.15	-52.02	-13.00	Vertical
5532.63	-66.39	5.47	-10.01	2.15	-64.00	-13.00	Horizontal
6266.45	-68.95	5.83	-10.41	2.15	-66.52	-13.00	Vertical
7239.33	-66.58	6.39	-11.24	2.15	-63.88	-13.00	Horizontal
7786.03	-66.49	6.63	-11.69	2.15	-63.58	-13.00	Horizontal

GSM Mode Channel 190/836.6MHz

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
2509.62	-41.08	3.59	-5.43	2.15	-41.39	-13.00	Vertical
4182.56	-52.55	4.68	-8.61	2.15	-50.77	-13.00	Vertical
4412.97	-67.88	4.85	-8.75	2.15	-66.13	-13.00	Horizontal
6276.35	-65.70	5.85	-10.42	2.15	-63.28	-13.00	Vertical
6885.28	-67.34	6.08	-10.99	2.15	-64.58	-13.00	Vertical
7813.48	-69.09	6.91	-11.71	2.15	-66.44	-13.00	Vertical

GSM Mode Channel 251/848.8MHz

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Polarization
2546.45	-41.63	3.63	-5.52	2.15	-41.89	-13.00	Vertical
4244.19	-53.44	4.76	-8.65	2.15	-51.70	-13.00	Vertical
5331.82	-66.39	5.41	-9.90	2.15	-64.05	-13.00	Horizontal
5978.40	-68.71	5.56	-10.19	2.15	-66.23	-13.00	Vertical
7000.94	-68.10	6.26	-11.10	2.15	-65.41	-13.00	Vertical
8092.28	-66.49	6.96	-11.96	2.15	-63.64	-13.00	Vertical

GSM Mode Channel 512/1850.2MHz

Frequency (MHz)	P _{Mea} (dBm)	P _{pl} (dB)	G _a (dBi)	Peak EIRP (dBm)	Limit (dBm)	Polarity
3831.00	-67.97	4.52	-8.30	-64.19	-13.00	Horizontal
5199.42	-70.06	5.23	-9.82	-65.47	-13.00	Horizontal
6472.13	-66.48	5.92	-10.58	-61.82	-13.00	Vertical
8853.11	-64.99	7.30	-12.48	-59.81	-13.00	Vertical
11353.62	-62.66	8.62	-12.40	-58.88	-13.00	Vertical
12952.07	-55.94	8.86	-13.24	-51.56	-13.00	Vertical

GSM Mode Channel 661/1880.0MHz

Frequency (MHz)	P _{Mea} (dBm)	P _{pl} (dB)	G _a (dBi)	Peak EIRP (dBm)	Limit (dBm)	Polarity
3518.08	-66.41	4.33	-7.92	-62.82	-13.00	Vertical
5013.42	-69.11	5.17	-9.71	-64.57	-13.00	Horizontal
7636.89	-68.26	6.76	-11.54	-63.48	-13.00	Vertical
10225.23	-66.30	7.53	-12.45	-61.38	-13.00	Vertical
13160.47	-53.88	9.15	-13.46	-49.57	-13.00	Vertical
15039.71	-57.08	9.65	-13.49	-53.24	-13.00	Vertical

GSM Mode Channel 810/1909.8MHz

Frequency (MHz)	P _{Mea} (dBm)	P _{pl} (dB)	G _a (dBi)	Peak EIRP (dBm)	Limit (dBm)	Polarity
3836.57	-67.99	4.54	-8.30	-64.23	-13.00	Horizontal
5013.85	-69.45	5.17	-9.71	-64.91	-13.00	Vertical
6843.98	-66.80	6.17	-10.94	-62.03	-13.00	Horizontal
8449.44	-69.77	6.91	-12.17	-64.51	-13.00	Vertical
9549.16	-60.34	7.79	-12.58	-55.55	-13.00	Vertical
13822.22	-60.82	9.20	-13.93	-56.09	-13.00	Horizontal

Note: Expanded measurement uncertainty for this test item is $U = 4.2$ dB, $k = 2$.

A.3 CONDUCTED EMISSION

Reference

FCC: CFR Part 15.107/207.

IC: RSS-Gen Issue 3, Section 7.2.2.

The measurement procedure in ANSI C63.4-2009 is used. Conducted Emission is measured with travel charger. The EUT is working under GSM 850/1900MHz traffic mode which is the worst case of conducted emission measurement.

For test layout photo, please refer to Pic.2 in Annex B.


A.3.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

A.3.2 Measurement result

GSM 850MHz



IF bandwidth 9 kHz

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.


Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.933000	34.9	GND	N	9.7	21.1	56.0
1.072500	40.4	GND	N	9.7	15.6	56.0
1.302000	38.9	GND	N	9.7	17.1	56.0
1.365000	38.6	GND	N	9.7	17.4	56.0
1.446000	40.1	GND	L1	9.7	15.9	56.0
1.468500	40.7	GND	N	9.7	15.3	56.0

Final Result 2

Frequency (MHz)	Average (dBμV)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.559500	25.4	GND	L1	9.8	20.6	46.0
0.928500	27.0	GND	L1	9.7	19.0	46.0
1.068000	29.1	GND	L1	9.7	16.9	46.0
1.441500	29.1	GND	L1	9.7	16.9	46.0
1.540500	30.1	GND	L1	9.7	15.9	46.0
1.909500	26.7	GND	L1	9.7	19.3	46.0

PCS 1900MHz



IF bandwidth 9 kHz

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.933000	40.0	GND	L1	9.7	16.0	56.0
1.302000	44.6	GND	L1	9.7	11.4	56.0
1.405500	40.6	GND	N	9.7	15.4	56.0
1.518000	42.6	GND	L1	9.7	13.4	56.0
1.576500	39.3	GND	N	9.7	16.7	56.0
1.653000	40.3	GND	L1	9.7	15.7	56.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
1.009500	32.2	GND	L1	9.7	13.8	46.0
1.302000	32.7	GND	L1	9.7	13.3	46.0
1.365000	32.5	GND	L1	9.7	13.5	46.0
1.468500	33.1	GND	L1	9.7	12.9	46.0
1.576500	31.8	GND	L1	9.7	14.2	46.0
1.590000	30.2	GND	L1	9.7	15.8	46.0

Note: The maximum value of expanded measurement uncertainty for this test item is $U = 2.9$ dB, $k=2$.

A.4 FREQUENCY STABILITY

Reference

FCC: CFR Part 2.1055, 22.355, 24.235.

IC: RSS-132 Issue 3, Section 5.3. RSS-133 Issue 6, Section 6.3.

A.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900, channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from +50°C to -30°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

A.4.2 Measurement Limit

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d) (2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.1VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance from -5.4% to 10.8%. For the purposes of measuring frequency stability these voltage limits are to be used.

A.4.3 Measurement results

GSM 850

Room Temperature: 24 °C

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.7	37	0.044
4.1	11	0.013
3.5	9	0.011

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
50°	15	0.018
40°	12	0.014
30°	19	0.023
20°	18	0.022
10°	17	0.021
0°	10	0.012
- 10°	10	0.012
- 20°	17	0.020
- 30°	9	0.011

Expanded measurement uncertainty for this test item is 10 Hz, $k=2$

PCS 1900
Room Temperature: 24 °C

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.7	52	0.028
4.1	52	0.028
3.5	53	0.028

Frequency Error vs Temperature

temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
50°	57	0.030
40°	66	0.035
30°	56	0.030
20°	60	0.032
10°	58	0.031
0°	51	0.027
- 10°	56	0.030
- 20°	58	0.031
- 30°	53	0.028

Expanded measurement uncertainty for this test item is 10 Hz, $k = 2$.

A.5 OCCUPIED BANDWIDTH

Reference

FCC: CFR Part 2.1049(h)(i).

IC: RSS-132 Issue 3, Section 5.3. RSS-133 Issue 6, Section 6.3.

A.5.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

Measurement Parameters:

RBW = 5 kHz, VBW = 20 kHz


GSM 850(99% BW) per FCC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	245.192
836.6	245.192
848.8	245.994

Expanded measurement uncertainty for this test item is 1.1 kHz, $k=2$.


GSM 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 16.JAN.2014 08:27:39

Channel 190-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 08:28:11

Channel 251-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 08:28:43


GSM 850(99% BW) per IC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	245.192
836.6	245.192
848.8	242.788

Expanded measurement uncertainty for this test item is 1.1 kHz, $k=2$.


GSM 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 16.JAN.2014 08:31:23

Channel 190-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 08:31:55

Channel 251-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 08:32:27


GPRS 850(99% BW) per FCC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	242.788
836.6	243.590
848.8	246.795

Expanded measurement uncertainty for this test item is 1.1 kHz, k=2


GPRS 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 16.JAN.2014 14:58:30

Channel 190-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 14:59:03

Channel 251-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 14:59:35


GPRS 850(99% BW) per IC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	245.192
836.6	244.391
848.8	241.987

Expanded measurement uncertainty for this test item is 1.1 kHz, k=2


GPRS 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 16.JAN.2014 15:02:14

Channel 190-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 15:02:46

Channel 251-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 15:03:18


EGPRS 850(99% BW) per FCC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	244.391
836.6	243.590
848.8	237.981

Expanded measurement uncertainty for this test item is 1.1 kHz, $k=2$


EGPRS 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 16.JAN.2014 15:05:47

Channel 190-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 15:06:20

Channel 251-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 15:06:52


EGPRS 850(99% BW) per IC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
824.2	243.590
836.6	242.788
848.8	242.788

Expanded measurement uncertainty for this test item is 1.1 kHz, $k=2$


EGPRS 850

Channel 128-Occupied Bandwidth (99% BW)




Date: 16.JAN.2014 15:09:31

Channel 190-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 15:10:03

Channel 251-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 15:10:36


PCS 1900(99% BW) per FCC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	246.795
1880.0	243.590
1909.8	245.994

Expanded measurement uncertainty for this test item is 1.1 kHz, $k=2$


PCS 1900

Channel 512-Occupied Bandwidth (99% BW)




Date: 16.JAN.2014 13:36:12

Channel 661-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 13:36:44

Channel 810-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 13:37:16


PCS 1900(99% BW) per IC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	244.391
1880.0	245.192
1909.8	245.192

Expanded measurement uncertainty for this test item is 1.1 kHz, $k=2$


PCS 1900

Channel 512-Occupied Bandwidth (99% BW)




Date: 16.JAN.2014 13:39:56

Channel 661-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 13:40:28

Channel 810-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 13:41:00


GPRS 1900(99% BW) per FCC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	243.590
1880.0	241.186
1909.8	245.192

Expanded measurement uncertainty for this test item is 1.1 kHz, $k=2$


GPRS 1900

Channel 512-Occupied Bandwidth 99% BW)




Date: 16.JAN.2014 15:13:42

Channel 661-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 15:14:14

Channel 810-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 15:14:46


GPRS 1900(99% BW) per IC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	245.192
1880.0	245.192
1909.8	243.590

Expanded measurement uncertainty for this test item is 1.1 kHz, $k=2$


GPRS 1900

Channel 512-Occupied Bandwidth 99% BW)




Date: 16.JAN.2014 15:17:26

Channel 661-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 15:17:58

Channel 810-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 15:18:30


EGPRS 1900(99% BW) per FCC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	249.199
1880.0	247.596
1909.8	245.192

Expanded measurement uncertainty for this test item is 1.1 kHz, $k=2$


EGPRS 1900

Channel 512-Occupied Bandwidth (99% BW)




Date: 16.JAN.2014 15:59:53

Channel 661-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 16:00:25

Channel 810-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 16:00:57


EGPRS 1900(99% BW) per IC rules

Frequency(MHz)	Occupied Bandwidth (99% BW)(kHz)
1850.2	244.391
1880.0	245.192
1909.8	245.994

Expanded measurement uncertainty for this test item is 1.1 kHz, $k=2$


EGPRS 1900

Channel 512-Occupied Bandwidth (99% BW)




Date: 16.JAN.2014 16:03:36

Channel 661-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 16:04:09

Channel 810-Occupied Bandwidth (99% BW)



Date: 16.JAN.2014 16:04:41

A.6 EMISSION BANDWIDTH

Reference

FCC: CFR Part 22.917(b), 24.238(b).

IC: RSS-132 Issue 3, Section 5.5. RSS-133 Issue 6, Section 6.5.

A.6.1 Emission Bandwidth Results

Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the PCS1900 band and GSM850 band. Table below lists the measured 100% BW. Spectrum analyzer plots are included on the following pages.

Measurement Parameters:

RBW = 5 kHz, VBW = 20 kHz


GSM 850(100% BW)

Frequency(MHz)	Occupied Bandwidth (100% BW)(kHz)
824.2	305.288
836.6	307.692
848.8	306.090

Expanded measurement uncertainty for this test item is 1.1 kHz, k=2


GSM 850

Channel 128-Occupied Bandwidth (100% BW)




Date: 16. JAN. 2014 08:29:17

Channel 190-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 08:29:49

Channel 251-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 08:30:21


GPRS 850(100% BW)

Frequency(MHz)	Occupied Bandwidth (100% BW)(kHz)
824.2	305.288
836.6	307.692
848.8	306.090

Expanded measurement uncertainty for this test item is 1.1 kHz, k=2


GPRS 850

Channel 128-Occupied Bandwidth (100% BW)




Date: 16.JAN.2014 15:00:08

Channel 190-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 15:00:41

Channel 251-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 15:01:13


EGPRS 850(100%)

Frequency(MHz)	Occupied Bandwidth (100% BW)(kHz)
824.2	298.878
836.6	297.276
848.8	299.679

Expanded measurement uncertainty for this test item is 1.1 kHz, k=2


EGPRS 850

Channel 128-Occupied Bandwidth (100% BW)




Date: 16.JAN.2014 15:07:25

Channel 190-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 15:07:57

Channel 251-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 15:08:30


PCS 1900(100% BW)

Frequency(MHz)	Occupied Bandwidth (100% BW)(kHz)
1850.2	307.692
1880.0	306.090
1909.8	306.891

Expanded measurement uncertainty for this test item is 1.1 kHz, k=2


PCS 1900

Channel 512-Occupied Bandwidth (100% BW)




Date: 16.JAN.2014 13:37:50

Channel 661-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 13:38:22

Channel 810-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 13:38:54


GPRS 1900(100%)

Frequency(MHz)	Occupied Bandwidth (100% BW)(kHz)
1850.2	307.692
1880.0	304.487
1909.8	306.891

Expanded measurement uncertainty for this test item is 1.1 kHz, $k=2$


GPRS 1900

Channel 512-Occupied Bandwidth (100% BW)




Date: 16.JAN.2014 15:15:20

Channel 661-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 15:15:52

Channel 810-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 15:16:24


EGPRS 1900(100% BW)

Frequency(MHz)	Occupied Bandwidth (100% BW)(kHz)
1850.2	304.487
1880.0	301.282
1909.8	301.282

Expanded measurement uncertainty for this test item is 1.1 kHz, k=2


EGPRS 1900

Channel 512-Occupied Bandwidth (100% BW)




Date: 16.JAN.2014 16:01:31

Channel 661-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 16:02:03

Channel 810-Occupied Bandwidth (100% BW)



Date: 16.JAN.2014 16:02:35

A.7 BAND EDGE COMPLIANCE

Reference

FCC: CFR Part 22.917(b), 24.238(b).

IC: RSS-132 Issue 3, Section 5.5. RSS-133 Issue 6, Section 6.5.


A.7.1 Measurement limit

On any frequency outside frequency band of the US Cellular/PCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43 + 10\log(P)$ dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

A.7.2 Measurement result


GSM 850

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128



Date: 16.JAN.2014 08:30:35


HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251



Date: 16.JAN.2014 08:30:49


GPRS 850

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128



Date: 16.JAN.2014 15:01:27


HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251



Date: 16. JAN. 2014 15:01:41


EGPRS 850-8PSK

LOW BAND EDGE BLOCK-A (GSM850)-Channel 128



Date: 16. JAN. 2014 15:08:44


HIGH BAND EDGE BLOCK-C (GSM850) –Channel 251



Date: 16.JAN.2014 15:08:58

PCS 1900

LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 16.JAN.2014 13:39:08

Ref 25 dBm Att 20 dB

- RBW 5 kHz
- VBW 10 kHz
- SWT 300 ms

Marker 1 [T1] -18.45 dBm
1.910022436 GHz

1 AV VIEW


22.4

1

Center 1.91 GHz 100 kHz/ Span 1 MHz


Date: 16.JAN.2014 13:39:22

LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 16.JAN.2014 15:16:38


HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810



Date: 16. JAN. 2014 15:16:52


EGPRS 1900-8PSK

LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 16. JAN. 2014 16:02:49

HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810



Date: 16.JAN.2014 16:03:03

A.8 CONDUCTED SPURIOUS EMISSION

Reference

FCC: CFR Part 2.1057, 22.917, 24.238.

IC: RSS-132 Issue 3, Section 5.5. RSS-133 Issue 6, Section 6.5.

A.8.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data are taken from 30 MHz to 20 GHz. For GSM850, data are taken from 30 MHz to 10 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

GSM850 Transmitter

Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

PCS1900 Transmitter

Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

A. 8.2 Measurement Limit

Part 24.238 and Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Measurement Uncertainty: 0.3dB


[illegible]

GSM850

A.8.3.1 Channel 128: 30MHz – 1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 16. JAN. 2014 08:33:11

A.8.3.2 Channel 128: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 08:33:39

A.8.3.3 Channel 128: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 16.JAN.2014 08:34:08

A.8.3.4 Channel 128: 7.5GHz –10GHz

Spurious emission limit –13dBm.




Date: 16.JAN.2014 08:34:36

A.8.3.5 Channel 190: 30MHz – 1GHz

Spurious emission limit –13dBm


NOTE: peak above the limit line is the carrier frequency.



Date: 16.JAN.2014 08:35:05

A.8.3.6 Channel 190: 1GHz –2.5GHz


Spurious emission limit –13dBm



Date: 16.JAN.2014 08:35:33

A.8.3.7 Channel 190: 2.5GHz –7.5GHz


Spurious emission limit –13dBm



Date: 16.JAN.2014 08:36:02

A.8.3.8 Channel 190: 7.5GHz –10GHz

Spurious emission limit –13dBm




Date: 16.JAN.2014 08:36:30

A.8.3.9 Channel 251: 30MHz – 1GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 16.JAN.2014 08:36:59

A.8.3.10 Channel 251: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 16.JAN.2014 08:37:27

A.8.3.11 Channel 251: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 16.JAN.2014 08:37:56

A.8.3.12 Channel 251: 7.5GHz – 10GHz


Spurious emission limit –13dBm.



Date: 16.JAN.2014 08:38:24

A.8.3.13 Idle mode: 30MHz – 1GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 08:38:53

A.8.3.14 Idle mode: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 08:39:21

A.8.3.15 Idle mode: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 16.JAN.2014 08:39:49

A.8.3.16 Idle mode: 7.5GHz – 10GHz

Spurious emission limit –13dBm.




Date: 16.JAN.2014 08:40:18

[illegible]

PCS1900

A.8.3.17 Channel 512: 30MHz – 1GHz

Spurious emission limit –13dBm.




Date: 16.JAN.2014 13:41:36

A.8.3.18 Channel 512: 1GHz – 2.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 16.JAN.2014 13:42:04

A.8.3.19 Channel 512: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 13:42:32

A.8.3.20 Channel 512: 7.5GHz –10GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 13:43:00

A.8.3.21 Channel 512: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 13:43:28

A.8.3.22 Channel 512: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 13:43:56

A.8.3.23 Channel 661: 30MHz – 1GHz

Spurious emission limit –13dBm




Date: 16.JAN.2014 13:44:25

A.8.3.24 Channel 661: 1GHz –2.5GHz

Spurious emission limit –13dBm


NOTE: peak above the limit line is the carrier frequency.



Date: 16.JAN.2014 13:44:53

A.8.3.25 Channel 661: 2.5GHz –7.5GHz


Spurious emission limit –13dBm



Date: 16.JAN.2014 13:45:21

A.8.3.26 Channel 661: 7.5GHz –10GHz


Spurious emission limit –13dBm



Date: 16.JAN.2014 13:45:50

A.8.3.27 Channel 661: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 13:46:18

A.8.3.28 Channel 661: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 13:46:46

A.8.3.29 Channel 810: 30MHz – 1GHz

Spurious emission limit –13dBm.




Date: 16.JAN.2014 13:47:15

A.8.3.30 Channel 810: 1GHz – 2.5GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 16.JAN.2014 13:47:43

A.8.3.31 Channel 810:2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 16.JAN.2014 13:48:11

A.8.3.32 Channel 810: 7.5GHz – 10GHz


Spurious emission limit –13dBm.



Date: 16.JAN.2014 13:48:39

A.8.3.33 Channel 810: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 13:49:07

A.8.3.34 Channel 810: 15GHz –20GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 13:49:35

A.8.3.35 Idle mode: 30MHz – 1GHz


Spurious emission limit –13dBm.



Date: 16.JAN.2014 13:50:04

A.8.3.36 Idle mode: 1GHz – 2.5GHz


Spurious emission limit –13dBm.



Date: 16.JAN.2014 13:50:32

A.8.3.37 Idle mode: 2.5GHz – 7.5GHz


Spurious emission limit –13dBm.



Date: 16.JAN.2014 13:51:00

A.8.3.38 Idle mode: 7.5GHz – 10GHz


Spurious emission limit –13dBm.



Date: 16.JAN.2014 13:51:28

A.8.3.39 Idle mode: 10GHz –15GHz


Spurious emission limit –13dBm.



Date: 16. JAN. 2014 13:51:56

A.8.3.40 IDLE mode: 15GHz –20GHz

Spurious emission limit –13dBm.



Date: 16. JAN. 2014 13:52:25

A.9 RECEIVER RADIATION EMISSION

Reference

FCC: CFR Part 2.1053, 15.109

IC: RSS-132 Issue 3, Section 5.6. RSS-133 Issue 6, Section 6.6

A.9.1 Method of Measurement

The measurement procedure in ANSI C63.4-2009 is used. The EUT is placed on an 80cm height non-conductive table locating on the center of turntable. From 30MHz-1GHz, the measurement distance is 10 m. For frequency range above 1GHz, the measurement distance is 3 m.


The EUT is measured with travel charger and the operating mode is idle without CMU200's signaling.

A.9.2 Measurement Limit

Limit from RSS-Gen

Frequency range (MHz)	Field strength limit ($\mu\text{V}/\text{m}$)		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000


A. 9.3 Measurement results



IF bandwidth: 120 kHz

Idle Mode: 30MHz-1GHz


Normal RE_1G-6GHz



RBW 1MHz, VBW 3MHz

Idle Mode: 1GHz-6GHz

Normal RE_6G-18GHz



RBW 1MHz, VBW 3MHz

Idle Mode: 4GHz-18GHz

ANNEX B: TEST LAYOUT

No Display.

Pic.1 Radiated spurious emission

No Display.

Pic.2 Conducted emission

ANNEX C: EUT photograph

No Display.

Mobile Phone

No Display.

Mobile Phone

No Display.

Mobile Phone

No Display.

Mobile Phone

No Display.

Mobile Phone

No Display.

Mobile Phone

No Display.

Mobile Phone Disassembly and Inbuilt Battery

No Display.

Mobile Phone Disassembly and Inbuilt Battery

No Display.

Mobile Phone Disassembly and Inbuilt Battery

No Display.

Mobile Phone Disassembly

No Display.

Mobile Phone Disassembly

No Display.

Mobile Phone Disassembly

No Display.

Travel Charger

No Display.

Label of Travel Charger

No Display.

USB Cable

*****END OF REPORT*****