



TEST REPORT

Test Report No. : UL-RPT-RP10295093JD01B V2.0

Manufacturer : Sony Mobile Communications Inc.

FCC ID : PY7PM-0802

Test Standard(s) : FCC Parts 15.107 & 15.109

1. This test report shall not be reproduced in full or partial, without the written approval of UL VS LTD.
2. The results in this report apply only to the sample(s) tested.
3. The sample tested is in compliance with the above standard(s).
4. The test results in this report are traceable to the national or international standards.
5. Version 2.0 supersedes all previous versions.

Date of Issue: 04 August 2014

Checked by:

Steven White
Project Lead, Radio Laboratory

Issued by :

pp

John Newell
Group Quality Manager
Basingstoke,
UL VS LTD



This laboratory is accredited by UKAS.
The tests reported herein have been
performed in accordance with its' terms
of accreditation.

UL VS LTD

Pavilion A, Ashwood Park, Ashwood Way, Basingstoke, Hampshire, RG23 8BG, UK
Telephone: +44 (0)1256 312000
Facsimile: +44 (0)1256 312001

This page has been left intentionally blank.

Table of Contents

1. Customer Information.....	4
2. Summary of Testing.....	5
2.1. General Information	5
2.2. Summary of Test Results	5
2.3. Methods and Procedures	5
2.4. Deviations from the Test Specification	5
3. Equipment Under Test (EUT)	6
3.1. Identification of Equipment Under Test (EUT)	6
3.2. Description of EUT	7
3.3. Modifications Incorporated in the EUT	7
3.4. Additional Information Related to Testing	7
3.5. Support Equipment	7
4. Operation and Monitoring of the EUT during Testing	8
4.1. Operating Modes	8
4.2. Configuration and Peripherals	8
5. Measurements, Examinations and Derived Results.....	9
5.1. General Comments	9
5.2. Test Results	10
5.2.1. Receiver/Idle Mode AC Conducted Spurious Emissions	10
5.2.2. Receiver/Idle Mode Radiated Spurious Emissions	13
6. Measurement Uncertainty	19
7. Report Revision History	20

1. Customer Information





Company Name:	Sony Mobile Communications Inc.
Address:	Nya Vattentornet Mobilvägen 10 Lund 22188 Sweden

2. Summary of Testing

2.1. General Information

Specification Reference:	47CFR15.107 and 47CFR15.109
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart B (Unintentional Radiators) – Sections 15.107 and 15.109
Site Registration:	209735
Location of Testing:	UL VS LTD, Unit 3 Horizon, Wade Road, Kingsland Business Park, Basingstoke, Hampshire, RG24 8AH, United Kingdom
Test Dates:	16 June 2014 to 18 June 2014

2.2. Summary of Test Results

FCC (47CFR)	Measurement	Result
Part 15.107(a)	Receiver/Idle Mode AC Conducted Spurious Emissions	
Part 15.109	Receiver/Idle Mode Radiated Spurious Emissions	
Key to Results		
 = Complied  = Did not comply		

2.3. Methods and Procedures

Reference:	ANSI C63.4 (2009)
Title:	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.

2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

3. Equipment Under Test (EUT)

3.1. Identification of Equipment Under Test (EUT)

Brand Name:	Sony
IMEI:	004402541516385 (<i>Radiated sample #1</i>)
Test Sample Serial Number:	CB5A1Z4RMX
Hardware Version Number:	A
Software Version Number:	23.0.B.0.108
FCC ID:	PY7PM-0802

Brand Name:	Sony
IMEI:	004402541516179 (<i>Radiated sample #2</i>)
Test Sample Serial Number:	CB5A1Z4RSA
Hardware Version Number:	A
Software Version Number:	23.0.B.0.108
FCC ID:	PY7PM-0802

Brand Name:	Sony
Description:	AC Charger
Model Name or Number:	EP880

Brand Name:	Monoprice
Description:	MHL Cable
Model Name or Number:	Not marked

Brand Name:	Sony
Description:	MHL Adaptor
Model Name or Number:	IM750

Brand Name:	Sony
Description:	USB Cable
Model Name or Number:	EC803

Brand Name:	Sony
Description:	Deskstand
Model Name or Number:	DK43

Identification of Equipment Under Test (EUT) (continued)

Brand Name:	Sony	
Description:	PHF	
Model Name or Number:	MH410c	

3.2. Description of EUT

The equipment under test (EUT) was a GSM/WCDMA/LTE Phone + Bluetooth, DTS/UNII a/b/g/n/ac + NFC & ANT+.

3.3. Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

3.4. Additional Information Related to Testing

Type of Radio Device:	Transceiver	
Power Supply Requirement(s):	Nominal	3.8 V

3.5. Support Equipment

The following support equipment was used to exercise the EUT during testing:

Description:	2 GB Micro SD Card	
Brand Name:	SanDisk	
Model Name or Number:	Not marked	

Description:	Logik	
Brand Name:	22" High Definition Television	
Model Name or Number:	L22FE12A	
Serial Number:	1309020661	

4. Operation and Monitoring of the EUT during Testing

4.1. Operating Modes

The EUT was tested in the following operating mode(s):

- Receiver/Idle mode.

4.2. Configuration and Peripherals

The EUT was tested in the following configuration(s):

- Idle radiated spurious emission tests were performed with the following configurations, employing all available accessories:
 - Configuration 1 – Handset with the AC charger, USB Cable, MHL cable (terminated in to a television), MHL adaptor and PHF
 - Configuration 2 – Handset with the AC charger, Deskstand and PHF

Pre-scans below 1 GHz were performed in both configurations 1 and 2, with final measurements limited to the configuration which provided worst case results. Pre-scans above 1 GHz were performed in the configuration that employed the most accessories (Configuration 1)

- The sample with IMEI 004402541516385 was used for AC conducted measurements.
- The radiated sample with IMEI 004402541516179 was used for all other measurements.

5. Measurements, Examinations and Derived Results

5.1. General Comments

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to *Section 6. Measurement Uncertainty* for details.

In accordance with UKAS requirements all the measurement equipment is on a calibration schedule. All equipment was within the calibration period on the date of testing.

5.2. Test Results**5.2.1. Receiver/Idle Mode AC Conducted Spurious Emissions****Test Summary:**

Test Engineer:	Georgios Vrezas	Test Date:	17 June 2014
Test Sample IMEI:	004402541516385		

FCC Reference:	Part 15.107
Test Method Used:	ANSI C63.4-2009

Environmental Conditions:

Temperature (°C):	21
Relative Humidity (%):	50

Results: Live / Quasi Peak

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.159	Live	48.4	65.5	17.1	Complied
0.186	Live	45.6	64.2	18.6	Complied
0.195	Live	44.1	63.8	19.7	Complied
0.321	Live	34.8	59.7	24.9	Complied
1.208	Live	31.6	56.0	24.4	Complied
15.608	Live	44.4	60.0	15.6	Complied

Results: Live / Average

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.155	Live	24.8	55.8	31.0	Complied
0.213	Live	27.2	53.1	25.9	Complied
0.492	Live	26.5	46.1	19.6	Complied
0.839	Live	21.7	46.0	24.3	Complied
3.098	Live	20.3	46.0	25.7	Complied
16.053	Live	30.7	50.0	19.3	Complied


Receiver/Idle Mode AC Conducted Spurious Emissions (continued)**Results: Neutral / Quasi Peak**

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.155	Neutral	48.2	65.8	17.6	Complied
0.204	Neutral	43.9	63.4	19.5	Complied
0.335	Neutral	34.3	59.3	25.0	Complied
0.470	Neutral	31.5	56.5	25.0	Complied
1.221	Neutral	36.0	56.0	20.0	Complied
15.243	Neutral	43.8	60.0	16.2	Complied


Results: Neutral / Average

Frequency (MHz)	Line	Level (dB μ V)	Limit (dB μ V)	Margin (dB)	Result
0.236	Neutral	28.9	52.3	23.4	Complied
0.416	Neutral	24.2	47.5	23.3	Complied
0.492	Neutral	27.8	46.1	18.3	Complied
0.839	Neutral	27.7	46.0	18.3	Complied
1.604	Neutral	24.1	46.0	21.9	Complied
15.977	Neutral	32.3	50.0	17.7	Complied

Receiver/Idle Mode AC Conducted Spurious Emissions (continued)



Live



Neutral

Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1625	Thermohygrometer	JM Handelpunkt	30.5015.06	None stated	31 Dec 2014	12
A004	Single phase LISN	Rohde & Schwarz	ESH3-Z5	890604/027	18 Nov 2014	12
A1830	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100668	27 Feb 2015	12
M1263	EMI Test Receiver	Rohde & Schwarz	ESIB 7	100265	14 Oct 2014	12

5.2.2. Receiver/Idle Mode Radiated Spurious Emissions**Test Summary:**

Test Engineer:	Georgios Vrezas	Test Date:	16 June 2014
Test Sample IMEI:	004402541516179		

FCC Reference:	Part 15.109
Test Method Used:	ANSI C63.4-2009
Frequency Range:	30 MHz to 1000 MHz

Environmental Conditions:

Temperature (°C):	24
Relative Humidity (%):	31


Note(s):

1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
2. All other emissions shown on the pre-scan plot were investigated and found to be ambient or >20 dB below the applicable limit or below the measurement system noise floor.
3. Measurements below 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.

Results: Quasi Peak

Frequency (MHz)	Antenna Polarity	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Result
31.345	Vertical	16.1	40.0	23.9	Complied
35.535	Vertical	17.0	40.0	23.0	Complied
76.259	Vertical	13.4	40.0	26.6	Complied
101.171	Vertical	12.5	43.5	31.0	Complied
144.669	Vertical	16.8	43.5	26.7	Complied
960.960	Horizontal	26.2	54.0	27.8	Complied

Receiver/Idle Mode Radiated Spurious Emissions (continued)



Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1622	Thermohygrometer	JM Handelpunkt	30.5015.06	None stated	31 Dec 2014	12
K0001	5m RSE Chamber	Rainford EMC	N/A	N/A	26 Nov 2014	12
A1834	Attenuator	Hewlett Packard	8491B	10444	15 Nov 2014	12
G0543	Amplifier	Sonoma	310N	230801	19 Aug 2014	3
M1273	Test Receiver	Rohde & Schwarz	ESIB 26	100275	15 Feb 2015	12
A490	Antenna	Chase	CBL6111A	1590	29 Apr 2015	12

Receiver/Idle Mode Radiated Spurious Emissions (continued)**Test Summary:**

Test Engineer:	Andrew Edwards	Test Date:	18 June 2014
Test Sample IMEI:	004402541516179		

FCC Reference:	Part 15.109
Test Method Used:	As detailed in ANSI C63.4 Section 8
Frequency Range:	1 GHz to 29.5 GHz

Environmental Conditions:

Temperature (°C):	24
Relative Humidity (%):	45


Note(s):

1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
2. No spurious emissions were detected above the noise floor of the measuring receiver therefore the highest peak noise floor reading of the measuring receiver was recorded as shown in the table below. The peak level was compared to the average limit as opposed to being compared to the peak limit because this is the more onerous limit.
3. Measurements were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.
4. Pre-scans above 1 GHz were performed in a fully anechoic chamber (Asset Number K0002) at a distance of 3 metres. The EUT was placed at a height of 1.5 metres above the test chamber floor in the centre of the chamber turntable. All measurement antennas were placed at a fixed height of 1.5 metres above the test chamber floor, in line with the EUT. Final measurements above 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.


Results:

Frequency (MHz)	Antenna Polarity	Peak Level (dB μ V/m)	Average Limit (dB μ V/m)	Margin (dB)	Result
25968.750	Vertical	51.2	54.0	2.6	Complied


Receiver/Idle Mode Radiated Spurious Emissions (continued)




10295093
Date: 18.JUN.2014 22:52:47



10295093
Date: 18.JUN.2014 22:59:51




10295093
Date: 18.JUN.2014 23:08:13




10295093
Date: 18.JUN.2014 22:43:13


Receiver/Idle Mode Radiated Spurious Emissions (continued)



10295093
Date: 18.JUN.2014 22:25:15



10295093
Date: 18.JUN.2014 21:21:42



10295093
Date: 18.JUN.2014 20:34:41

Receiver/Idle Mode Radiated Spurious Emissions (continued)**Test Equipment Used:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1656	Thermohygrometer	JM Handelspunkt	30.5015.13	None stated	14 Mar 2015	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	14 Nov 2014	12
M1874	Test Receiver	Rohde & Schwarz	ESU26	100553	13 May 2015	12
A1534	Pre Amplifier	Hewlett Packard	8449B	3008A0040 5	18 May 2015	12
A1818	Antenna	EMCO	3115	00075692	14 Nov 2014	12
A253	Antenna	Flann Microwave	12240-20	128	14 Nov 2014	12
A254	Antenna	Flann Microwave	14240-20	139	14 Nov 2014	12
A255	Antenna	Flann Microwave	16240-20	519	14 Nov 2014	12
A256	Antenna	Flann Microwave	18240-20	400	14 Nov 2014	12
A436	Antenna	Flann Microwave	20240-20	330	14 Nov 2014	12
A203	Antenna	Flann Microwave	22240-20	343	19 May 2016	36
A1785	Pre Amplifier	Farran Technology	FLNA-28-30	FTL 6483	13 Jan 2015	12
M1630	Test Receiver	Rohde & Schwarz	ESU40	100233	13 Mar 2015	12
M1229	Multimeter	Fluke	179	87640015	24 Apr 2015	12
S0558	DC Power Supply	TTi	EL303R	395825	Calibrated before use	-

6. Measurement Uncertainty

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	±4.69 dB
Radiated Spurious Emissions	30 MHz to 1 GHz	95%	±5.65 dB
Radiated Spurious Emissions	1 GHz to 29.5 GHz	95%	±2.94 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

7. Report Revision History

Version Number	Revision Details		
	Page No(s)	Clause	Details
1.0	-	-	Initial Version
2.0	-	-	EUT Description update

--- END OF REPORT ---