

## Appendix 5. Simulated Tissues

The body mixture consists of water, Polysorbate (Tween 20) and salt. Visual inspection is made to ensure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue.

| Ingredient<br>(% by weight) | Frequency 750/835/850/900 MHz |       |
|-----------------------------|-------------------------------|-------|
|                             | Head                          | Body  |
| De-Ionized Water            | 52.87                         | 71.30 |
| Polysorbate 20              | 46.10                         | 28.00 |
| Salt                        | 1.03                          | 0.70  |

| Ingredient<br>(% by weight) | Frequency 1800/1900 MHz |       |
|-----------------------------|-------------------------|-------|
|                             | Head                    | Body  |
| De-Ionized Water            | 55.40                   | 71.50 |
| Polysorbate 20              | 44.22                   | 28.00 |
| Salt                        | 0.38                    | 0.50  |

| Ingredient<br>(% by weight) | Frequency 2450/2600 MHz |       |
|-----------------------------|-------------------------|-------|
|                             | Head                    | Body  |
| De-Ionized Water            | 55.75 <sup>(1)</sup>    | 71.70 |
| Polysorbate 20              | 45.25 <sup>(1)</sup>    | 28.00 |
| Salt                        | 0.00                    | 0.30  |

Stimulating Liquid for 3700 MHz to 5800 MHz are supplied and manufactured by SPEAG

| Ingredient<br>(% by weight) | Frequency                      |
|-----------------------------|--------------------------------|
|                             | 3700 - 5800 MHz<br>Head / Body |
| De-Ionized Water            | ~78.00                         |
| Mineral Oil                 | ~11.00                         |
| Emulsifiers                 | ~9.00                          |
| Additives and Salt          | ~2.00                          |

**Note(s):**

- As per the recipe provided by National Physical Laboratory, the 2450 MHz Head Fluid recipe is mixed to the total percentage of weight is by 101.0 %.

### Appendix 6. System Check and Dielectric Parameters

**Dielectric Property Measurements:** The temperature of the tissue-equivalent medium used during measurement must also be within 18°C to 25°C and within ± 2°C of the temperature when the tissue parameters are characterized.

The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements. The parameters should be re-measured after each 3 – 4 days of use; or earlier if the dielectric parameters can become out of tolerance; for example, when the parameters are marginal at the beginning of the measurement series.

Tissue dielectric parameters were measured at the low, middle and high frequency of each operating frequency range of the test device.

**System Performance Check:** Prior to the assessment, the system was verified in the flat region of the phantom, 900 MHz, 1900 MHz, 2450 MHz, 2600 MHz and 5.0 GHz dipoles were used. A forward power of 250 mW was applied to the 900 MHz, 1900 MHz, 2450 MHz, 2600 MHz dipoles and 100 mW was applied to 5.0 GHz dipole and the system was verified to a tolerance of ±5% for the 900MHz, 1900MHz, 2450 MHz, 2600 MHz and 5.0 GHz dipoles.

The applicable verification normalised to 1 Watt.

| System Check 900 Head                                |                 |           |             |              |              |                |               |           |
|--|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Date: 09/06/2014                                     |                 |           |             |              |              |                |               |           |
| Validation Dipole and Serial Number: D900V2; SN: 035 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Head   | 900             | 24.0 °C   | 24.0 °C     | $\epsilon_r$ | 41.50        | 41.40          | -0.24         | 5.00      |
|  |                 |           |             | $\sigma$     | 0.97         | 0.97           | -0.05         | 5.00      |
|  |                 |           |             | 1g SAR       | 10.50        | 10.60          | 0.95          | 5.00      |
|  |                 |           |             | 10g SAR      | 6.69         | 6.84           | 2.24          | 5.00      |
| Date: 11/06/2014                                     |                 |           |             |              |              |                |               |           |
| Validation Dipole and Serial Number: D900V3; SN: 035 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Head   | 900             | 24.0 °C   | 24.0 °C     | $\epsilon_r$ | 41.50        | 40.56          | -2.27         | 5.00      |
|  |                 |           |             | $\sigma$     | 0.97         | 0.95           | -1.60         | 5.00      |
|  |                 |           |             | 1g SAR       | 10.50        | 10.56          | 0.57          | 5.00      |
|  |                 |           |             | 10g SAR      | 6.69         | 6.80           | 1.64          | 5.00      |
| Date: 16/06/2014                                     |                 |           |             |              |              |                |               |           |
| Validation Dipole and Serial Number: D900V2; SN: 035 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Head   | 900             | 24.0 °C   | 22.0 °C     | $\epsilon_r$ | 41.50        | 39.84          | -4.00         | 5.00      |
|  |                 |           |             | $\sigma$     | 0.97         | 0.97           | 0.05          | 5.00      |
|  |                 |           |             | 1g SAR       | 10.50        | 10.24          | -2.48         | 5.00      |
|  |                 |           |             | 10g SAR      | 6.69         | 6.60           | -1.35         | 5.00      |

| System Check 900 Body                                |                 |           |             |              |              |                |               |           |
|--|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Date: 09/06/2014                                     |                 |           |             |              |              |                |               |           |
| Validation Dipole and Serial Number: D900V3; SN: 035 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Body   | 900             | 22.7 °C   | 22.0 °C     | $\epsilon_r$ | 55.00        | 53.45          | -2.82         | 5.00      |
|  |                 |           |             | $\sigma$     | 1.05         | 1.08           | 2.43          | 5.00      |
|  |                 |           |             | 1g SAR       | 10.40        | 10.12          | -2.69         | 5.00      |
|  |                 |           |             | 10g SAR      | 6.73         | 6.56           | -2.53         | 5.00      |
| Date: 11/06/2014                                     |                 |           |             |              |              |                |               |           |
| Validation Dipole and Serial Number: D900V3; SN: 035 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Body   | 900             | 22.7 °C   | 22.0 °C     | $\epsilon_r$ | 55.00        | 53.30          | -3.09         | 5.00      |
|  |                 |           |             | $\sigma$     | 1.05         | 1.05           | -0.10         | 5.00      |
|  |                 |           |             | 1g SAR       | 10.40        | 10.12          | -2.69         | 5.00      |
|  |                 |           |             | 10g SAR      | 6.73         | 6.60           | -1.93         | 5.00      |
| Date: 16/06/2014                                     |                 |           |             |              |              |                |               |           |
| Validation Dipole and Serial Number: D900V3; SN: 035 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Body   | 900             | 23 °C     | 22.0 °C     | $\epsilon_r$ | 55.00        | 54.13          | -1.58         | 5.00      |
|  |                 |           |             | $\sigma$     | 1.05         | 1.09           | 3.48          | 5.00      |
|  |                 |           |             | 1g SAR       | 10.40        | 10.24          | -1.54         | 5.00      |
|  |                 |           |             | 10g SAR      | 6.73         | 6.56           | -2.53         | 5.00      |

**System Check 1900 Head**

Date: 09/06/2014

Validation Dipole and Serial Number: D1900V2: SN:537

| Simulant | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
|----------|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Head     | 1900            | 24.0 °C   | 24.0 °C     | $\epsilon_r$ | 40.00        | 41.75          | 4.38          | 5.00      |
|          |                 |           |             | $\sigma$     | 1.40         | 1.38           | -1.31         | 5.00      |
|          |                 |           |             | 1g SAR       | 39.80        | 39.16          | -1.61         | 5.00      |
|          |                 |           |             | 10g SAR      | 20.70        | 20.12          | -2.80         | 5.00      |

**System Check 1900 Body**

Date: 09/06/2014

Validation Dipole and Serial Number: D1900V2: SN: 537

| Simulant | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
|----------|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Body     | 1900            | 23.0 °C   | 22.8 °C     | $\epsilon_r$ | 53.30        | 50.86          | -4.58         | 5.00      |
|          |                 |           |             | $\sigma$     | 1.52         | 1.50           | -1.25         | 5.00      |
|          |                 |           |             | 1g SAR       | 40.20        | 40.40          | 0.50          | 5.00      |
|          |                 |           |             | 10g SAR      | 21.10        | 21.04          | -0.28         | 5.00      |

**System Check 2450 Head**

Date: 11/06/2014

Validation Dipole and Serial Number: D2450V2; SN: 725

| Simulant | Frequency (MHz) | Room Temp | Liquid Temp | Parameters     | Target Value | Measured Value | Deviation (%) | Limit (%) |
|----------|-----------------|-----------|-------------|----------------|--------------|----------------|---------------|-----------|
| Head     | 2450            | 24.0 °C   | 22.7 °C     | $\epsilon_r$   | 39.20        | 38.26          | -2.40         | 5.00      |
|          |                 |           |             | $\sigma$       | 1.80         | 1.82           | 0.95          | 5.00      |
|          |                 |           |             | <b>1g SAR</b>  | 52.60        | 53.60          | 1.90          | 5.00      |
|          |                 |           |             | <b>10g SAR</b> | 24.4         | 24.76          | 1.48          | 5.00      |

**System Check 2450 Body**

Date: 13/06/2014

Validation Dipole and Serial Number: D2440V2; SN: 701

| Simulant | Frequency (MHz) | Room Temp | Liquid Temp | Parameters     | Target Value | Measured Value | Deviation (%) | Limit (%) |
|----------|-----------------|-----------|-------------|----------------|--------------|----------------|---------------|-----------|
| Body     | 2450            | 24.0 °C   | 24.0 °C     | $\epsilon_r$   | 52.70        | 50.83          | -3.55         | 5.00      |
|          |                 |           |             | $\sigma$       | 1.95         | 2.03           | 3.86          | 5.00      |
|          |                 |           |             | <b>1g SAR</b>  | 51.40        | 52.40          | 1.95          | 5.00      |
|          |                 |           |             | <b>10g SAR</b> | 23.90        | 24.16          | 1.09          | 5.00      |

| System Check 2600 Head                                 |                 |           |             |              |              |                |               |           |
|--|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Date: 09/06/2014                                       |                 |           |             |              |              |                |               |           |
| Validation Dipole and Serial Number: D2600V2; SN: 1046 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Head   | 2600            | 24.0 °C   | 22.6 °C     | $\epsilon_r$ | 39.00        | 38.69          | -0.79         | 5.00      |
|  |                 |           |             | $\sigma$     | 1.96         | 1.92           | -1.98         | 5.00      |
|  |                 |           |             | 1g SAR       | 57.60        | 57.60          | 0.00          | 5.00      |
|  |                 |           |             | 10g SAR      | 25.8         | 25.44          | -1.40         | 5.00      |

| Date: 12/06/2014                                       |                 |           |             |              |              |                |               |           |
|--|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Validation Dipole and Serial Number: D2600V2; SN: 1046 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Head   | 2600            | 24.0 °C   | 22.6 °C     | $\epsilon_r$ | 39.00        | 37.56          | -3.69         | 5.00      |
|  |                 |           |             | $\sigma$     | 1.96         | 1.94           | -0.80         | 5.00      |
|  |                 |           |             | 1g SAR       | 57.60        | 60.00          | 4.17          | 5.00      |
|  |                 |           |             | 10g SAR      | 25.8         | 26.68          | 3.41          | 5.00      |

| System Check 2600 Body                                 |                 |           |             |              |              |                |               |           |
|--|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Date: 09/06/2014                                       |                 |           |             |              |              |                |               |           |
| Validation Dipole and Serial Number: D2600V2; SN: 1046 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Body   | 2600            | 23.4 °C   | 22.5°C      | $\epsilon_r$ | 52.50        | 53.67          | 2.23          | 5.00      |
|  |                 |           |             | $\sigma$     | 2.16         | 2.20           | 1.98          | 5.00      |
|  |                 |           |             | 1g SAR       | 56.80        | 55.60          | -2.11         | 5.00      |
|  |                 |           |             | 10g SAR      | 25.20        | 24.12          | -4.29         | 5.00      |

| Date: 12/06/2014                                       |                 |           |             |              |              |                |               |           |
|--|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Validation Dipole and Serial Number: D2600V2; SN: 1046 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Body   | 2600            | 23.4 °C   | 22.5°C      | $\epsilon_r$ | 52.50        | 50.62          | 3.50          | 5.00      |
|  |                 |           |             | $\sigma$     | 2.16         | 2.18           | 0.90          | 5.00      |
|  |                 |           |             | 1g SAR       | 56.80        | 57.60          | 1.41          | 5.00      |
|  |                 |           |             | 10g SAR      | 25.20        | 24.84          | -1.43         | 5.00      |

| System Check 5200 Head                                |                 |           |             |              |              |                |               |           |
|---|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Date 12/06/2014                                       |                 |           |             |              |              |                |               |           |
| Validation dipole and Serial Number: D5GHzV2 SN: 1016 |                 |           |             |              |              |                |               |           |
| Simulant  | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Head  | 5200            | 24.0°C    | 22.8°C      | $\epsilon_r$ | 36.00        | 35.40          | -1.64         | 5.00      |
|   |                 |           |             | $\sigma$     | 4.66         | 4.51           | -3.17         | 5.00      |
|   |                 |           |             | 1g SAR       | 77.40        | 79.90          | 3.23          | 5.00      |
|   |                 |           |             | 10g SAR      | 22.30        | 22.90          | 2.69          | 5.00      |

| System Check 5500 Head                                |                 |           |             |              |              |                |               |           |
|---|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Date 12/06/2014                                       |                 |           |             |              |              |                |               |           |
| Validation dipole and Serial Number: D5GHzV2 SN: 1016 |                 |           |             |              |              |                |               |           |
| Simulant  | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Head  | 5200            | 24.0°C    | 22.8°C      | $\epsilon_r$ | 35.60        | 35.02          | -1.63         | 5.00      |
|   |                 |           |             | $\sigma$     | 4.96         | 4.78           | -3.71         | 5.00      |
|   |                 |           |             | 1g SAR       | 84.80        | 84.20          | -0.71         | 5.00      |
|   |                 |           |             | 10g SAR      | 24.1         | 23.60          | -2.07         | 5.00      |

| System Check 5800 Head                                |                 |           |             |              |              |                |               |           |
|---|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Date 12/06/2014                                       |                 |           |             |              |              |                |               |           |
| Validation dipole and Serial Number: D5GHzV2 SN: 1016 |                 |           |             |              |              |                |               |           |
| Simulant  | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Head  | 5200            | 24.0°C    | 22.8°C      | $\epsilon_r$ | 35.30        | 34.54          | -2.15         | 5.00      |
|   |                 |           |             | $\sigma$     | 5.27         | 5.02           | -4.80         | 5.00      |
|   |                 |           |             | 1g SAR       | 80.10        | 76.90          | 4.16          | 5.00      |
|   |                 |           |             | 10g SAR      | 22.0         | 22.70          | 3.18          | 5.00      |

| System Check 5200 Body                               |                 |           |             |              |              |                |               |           |
|--|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Date: 09/06/2014                                     |                 |           |             |              |              |                |               |           |
| Validation Dipole and Serial Number: D5GHzV2 SN:1016 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Body   | 5200            | 23.0°C    | 23.0°C      | $\epsilon_r$ | 49.00        | 48.11          | -1.84         | 5.00      |
|  |                 |           |             | $\sigma$     | 5.30         | 5.14           | -2.98         | 5.00      |
|  |                 |           |             | 1g SAR       | 73.10        | 72.20          | -1.23         | 5.00      |
|  |                 |           |             | 10g SAR      | 20.40        | 20.30          | -0.49         | 5.00      |

| System Check 5500 Body                               |                 |           |             |              |              |                |               |           |
|--|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Date: 09/06/2014                                     |                 |           |             |              |              |                |               |           |
| Validation Dipole and Serial Number: D5GHzV2 SN:1016 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Body   | 5200            | 24.0°C    | 24.0°C      | $\epsilon_r$ | 48.60        | 47.09          | -3.11         | 5.00      |
|  |                 |           |             | $\sigma$     | 5.65         | 5.59           | -1.14         | 5.00      |
|  |                 |           |             | 1g SAR       | 79.00        | 81.00          | 2.53          | 5.00      |
|  |                 |           |             | 10g SAR      | 21.9         | 22.80          | 4.11          | 5.00      |

| System Check 5800 Body                               |                 |           |             |              |              |                |               |           |
|--|-----------------|-----------|-------------|--------------|--------------|----------------|---------------|-----------|
| Date: 09/06/2014                                     |                 |           |             |              |              |                |               |           |
| Validation Dipole and Serial Number: D5GHzV2 SN:1016 |                 |           |             |              |              |                |               |           |
| Simulant   | Frequency (MHz) | Room Temp | Liquid Temp | Parameters   | Target Value | Measured Value | Deviation (%) | Limit (%) |
| Body   | 5200            | 24.0°C    | 24.2°C      | $\epsilon_r$ | 48.20        | 46.36          | -3.82         | 5.00      |
|  |                 |           |             | $\sigma$     | 6.00         | 6.02           | 0.26          | 5.00      |
|  |                 |           |             | 1g SAR       | 73.20        | 71.60          | -2.19         | 5.00      |
|  |                 |           |             | 10g SAR      | 20.20        | 19.70          | -2.48         | 5.00      |

**Appendix 7. measurement Uncertainty Table**

Measurement uncertainty tables for technologies tested.

**A.7.1. Uncertainty -GSM 850 / UMTS FDD 5 / LTE Band 5 Head Configuration 1g**

| Type | Source of uncertainty                                  | + Value | - Value | Probability Distribution | Divisor | C <sub>i</sub> (1g) | Standard Uncertainty |         | U <sub>i</sub> or U <sub>eff</sub> |
|------|--|---------|---------|--------------------------|---------|---------------------|----------------------|---------|------------------------------------|
|      |  |         |         |                          |         |                     | + u (%)              | - u (%) |                                    |
| B    | Probe calibration                                      | 6.000   | 6.000   | normal (k=1)             | 1.0000  | 1.0000              | 6.000                | 6.000   | ∞                                  |
| B    | Axial Isotropy   | 0.250   | 0.250   | normal (k=1)             | 1.0000  | 1.0000              | 0.250                | 0.250   | ∞                                  |
| B    | Hemispherical Isotropy                                 | 1.300   | 1.300   | normal (k=1)             | 1.0000  | 1.0000              | 1.300                | 1.300   | ∞                                  |
| B    | Spatial Resolution                                     | 0.500   | 0.500   | Rectangular              | 1.7321  | 1.0000              | 0.289                | 0.289   | ∞                                  |
| B    | Boundary Effect  | 0.769   | 0.769   | Rectangular              | 1.7321  | 1.0000              | 0.444                | 0.444   | ∞                                  |
| B    | Linearity  | 0.600   | 0.600   | Rectangular              | 1.7321  | 1.0000              | 0.346                | 0.346   | ∞                                  |
| B    | Detection Limits                                       | 0.200   | 0.200   | Rectangular              | 1.7321  | 1.0000              | 0.115                | 0.115   | ∞                                  |
| B    | Readout Electronics                                    | 0.160   | 0.160   | normal (k=1)             | 1.0000  | 1.0000              | 0.160                | 0.160   | ∞                                  |
| B    | Response Time  | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | Integration Time                                       | 1.730   | 1.730   | Rectangular              | 1.7321  | 1.0000              | 0.999                | 0.999   | ∞                                  |
| B    | RF Ambient conditions                                  | 3.000   | 3.000   | Rectangular              | 1.7321  | 1.0000              | 1.732                | 1.732   | ∞                                  |
| B    | Probe Positioner Mechanical Restrictions               | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Probe Positioning with regard to Phantom Shell         | 2.850   | 2.850   | Rectangular              | 1.7321  | 1.0000              | 1.645                | 1.645   | ∞                                  |
| B    | Extrapolation and integration / Maximum SAR evaluation | 5.080   | 5.080   | Rectangular              | 1.7321  | 1.0000              | 2.933                | 2.933   | ∞                                  |
| A    | Test Sample Positioning                                | 2.510   | 2.510   | normal (k=1)             | 1.0000  | 1.0000              | 2.510                | 2.510   | 10                                 |
| A    | Device Holder uncertainty                              | 0.154   | 0.154   | normal (k=1)             | 1.0000  | 1.0000              | 0.154                | 0.154   | 10                                 |
| B    | Phantom Uncertainty                                    | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Drift of output power                                  | 5.000   | 5.000   | Rectangular              | 1.7321  | 1.0000              | 2.887                | 2.887   | ∞                                  |
| B    | Liquid Conductivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6400              | 1.848                | 1.848   | ∞                                  |
| A    | Liquid Conductivity (measured value)                   | 2.950   | 2.950   | normal (k=1)             | 1.0000  | 0.6400              | 1.888                | 1.888   | 5                                  |
| B    | Liquid Permittivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6000              | 1.732                | 1.732   | ∞                                  |
| A    | Liquid Permittivity (measured value)                   | 2.840   | 2.840   | normal (k=1)             | 1.0000  | 0.6000              | 1.704                | 1.704   | 5                                  |
|      | Combined standard uncertainty                          |         |         | t-distribution           |         |                     | 9.58                 | 9.58    | >500                               |
|      | Expanded uncertainty                                   |         |         | k = 1.96                 |         |                     | 18.77                | 18.77   | >500                               |

**A.7.2. Uncertainty Rate-GSM / GPRS / EDGE 850 / UMTS FDD 5 / LTE Band 5 Configuration 1g**

| Type | Source of uncertainty                                 | + Value | - Value | Probability Distribution | Divisor | C <sub>i</sub> (1g) | Standard Uncertainty |         | U <sub>i</sub> or U <sub>eff</sub> |
|------|---|---------|---------|--------------------------|---------|---------------------|----------------------|---------|------------------------------------|
|      |   |         |         |                          |         |                     | + u (%)              | - u (%) |                                    |
| B    | Probe calibration                                     | 6.000   | 6.000   | normal (k=1)             | 1.0000  | 1.0000              | 6.000                | 6.000   | ∞                                  |
| B    | Axial Isotropy  | 0.250   | 0.250   | normal (k=1)             | 1.0000  | 1.0000              | 0.250                | 0.250   | ∞                                  |
| B    | Hemispherical Isotropy                                | 1.300   | 1.300   | normal (k=1)             | 1.0000  | 1.0000              | 1.300                | 1.300   | ∞                                  |
| B    | Spatial Resolution                                    | 0.500   | 0.500   | Rectangular              | 1.7321  | 1.0000              | 0.289                | 0.289   | ∞                                  |
| B    | Boundary Effect                                       | 0.769   | 0.769   | Rectangular              | 1.7321  | 1.0000              | 0.444                | 0.444   | ∞                                  |
| B    | Linearity   | 0.600   | 0.600   | Rectangular              | 1.7321  | 1.0000              | 0.346                | 0.346   | ∞                                  |
| B    | Detection Limits                                      | 0.200   | 0.200   | Rectangular              | 1.7321  | 1.0000              | 0.115                | 0.115   | ∞                                  |
| B    | Readout Electronics                                   | 0.160   | 0.160   | normal (k=1)             | 1.0000  | 1.0000              | 0.160                | 0.160   | ∞                                  |
| B    | Response Time   | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | Integration Time                                      | 1.730   | 1.730   | Rectangular              | 1.7321  | 1.0000              | 0.999                | 0.999   | ∞                                  |
| B    | RF Ambient conditions                                 | 3.000   | 3.000   | Rectangular              | 1.7321  | 1.0000              | 1.732                | 1.732   | ∞                                  |
| B    | Probe Positioner Mechanical Restrictions              | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Probe Positioning with regard to Phantom Shell        | 2.850   | 2.850   | Rectangular              | 1.7321  | 1.0000              | 1.645                | 1.645   | ∞                                  |
| B    | Extrapolation and integration /Maximum SAR evaluation | 5.080   | 5.080   | Rectangular              | 1.7321  | 1.0000              | 2.933                | 2.933   | ∞                                  |
| A    | Test Sample Positioning                               | 2.510   | 2.510   | normal (k=1)             | 1.0000  | 1.0000              | 2.510                | 2.510   | 10                                 |
| A    | Device Holder uncertainty                             | 0.154   | 0.154   | normal (k=1)             | 1.0000  | 1.0000              | 0.154                | 0.154   | 10                                 |
| B    | Phantom Uncertainty                                   | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Drift of output power                                 | 5.000   | 5.000   | Rectangular              | 1.7321  | 1.0000              | 2.887                | 2.887   | ∞                                  |
| B    | Liquid Conductivity (target value)                    | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6400              | 1.848                | 1.848   | ∞                                  |
| A    | Liquid Conductivity (measured value)                  | 2.000   | 2.000   | normal (k=1)             | 1.0000  | 0.6400              | 1.280                | 1.280   | 5                                  |
| B    | Liquid Permittivity (target value)                    | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6000              | 1.732                | 1.732   | ∞                                  |
| A    | Liquid Permittivity (measured value)                  | 1.560   | 1.560   | normal (k=1)             | 1.0000  | 0.6000              | 0.936                | 0.936   | 5                                  |
|      | Combined standard uncertainty                         |         |         | t-distribution           |         |                     | 9.37                 | 9.37    | >500                               |
|      | Expanded uncertainty                                  |         |         | k = 1.96                 |         |                     | 18.36                | 18.36   | >500                               |

**A.7.3. Uncertainty -PCS 1900 / UMTS FDD 2 Head Configuration 1g**

| Type | Source of uncertainty                                  | + Value | - Value | Probability Distribution | Divisor | C <sub>i</sub> (1g) | Standard Uncertainty |         | U <sub>i</sub> or U <sub>eff</sub> |
|------|--|---------|---------|--------------------------|---------|---------------------|----------------------|---------|------------------------------------|
|      |  |         |         |                          |         |                     | + u (%)              | - u (%) |                                    |
| B    | Probe calibration                                      | 6.000   | 6.000   | normal (k=1)             | 1.0000  | 1.0000              | 6.000                | 6.000   | ∞                                  |
| B    | Axial Isotropy   | 0.250   | 0.250   | normal (k=1)             | 1.0000  | 1.0000              | 0.250                | 0.250   | ∞                                  |
| B    | Hemispherical Isotropy                                 | 1.300   | 1.300   | normal (k=1)             | 1.0000  | 1.0000              | 1.300                | 1.300   | ∞                                  |
| B    | Spatial Resolution                                     | 0.500   | 0.500   | Rectangular              | 1.7321  | 1.0000              | 0.289                | 0.289   | ∞                                  |
| B    | Boundary Effect  | 0.769   | 0.769   | Rectangular              | 1.7321  | 1.0000              | 0.444                | 0.444   | ∞                                  |
| B    | Linearity  | 0.600   | 0.600   | Rectangular              | 1.7321  | 1.0000              | 0.346                | 0.346   | ∞                                  |
| B    | Detection Limits                                       | 0.200   | 0.200   | Rectangular              | 1.7321  | 1.0000              | 0.115                | 0.115   | ∞                                  |
| B    | Readout Electronics                                    | 0.160   | 0.160   | normal (k=1)             | 1.0000  | 1.0000              | 0.160                | 0.160   | ∞                                  |
| B    | Response Time  | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | Integration Time                                       | 1.730   | 1.730   | Rectangular              | 1.7321  | 1.0000              | 0.999                | 0.999   | ∞                                  |
| B    | RF Ambient conditions                                  | 3.000   | 3.000   | Rectangular              | 1.7321  | 1.0000              | 1.732                | 1.732   | ∞                                  |
| B    | Probe Positioner Mechanical Restrictions               | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Probe Positioning with Regard to Phantom Shell         | 2.850   | 2.850   | Rectangular              | 1.7321  | 1.0000              | 1.645                | 1.645   | ∞                                  |
| B    | Extrapolation and integration / Maximum SAR evaluation | 5.080   | 5.080   | Rectangular              | 1.7321  | 1.0000              | 2.933                | 2.933   | ∞                                  |
| A    | Test Sample Positioning                                | 2.490   | 2.490   | normal (k=1)             | 1.0000  | 1.0000              | 2.490                | 2.490   | 10                                 |
| A    | Device Holder uncertainty                              | 0.154   | 0.154   | normal (k=1)             | 1.0000  | 1.0000              | 0.154                | 0.154   | 10                                 |
| B    | Phantom Uncertainty                                    | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Drift of output power                                  | 5.000   | 5.000   | Rectangular              | 1.7321  | 1.0000              | 2.887                | 2.887   | ∞                                  |
| B    | Liquid Conductivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6400              | 1.848                | 1.848   | ∞                                  |
| A    | Liquid Conductivity (measured value)                   | 3.560   | 3.560   | normal (k=1)             | 1.0000  | 0.6400              | 2.278                | 2.278   | 5                                  |
| B    | Liquid Permittivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6000              | 1.732                | 1.732   | ∞                                  |
| A    | Liquid Permittivity (measured value)                   | 2.620   | 2.620   | normal (k=1)             | 1.0000  | 0.6000              | 1.572                | 1.572   | 5                                  |
|      | Combined standard uncertainty                          |         |         | t-distribution           |         |                     | 9.63                 | 9.63    | >500                               |
|      | Expanded uncertainty                                   |         |         | k = 1.96                 |         |                     | 18.88                | 18.88   | >500                               |

**A.7.4. Uncertainty -PCS / GPRS / EDGE 1900 / UMTS FDD 2 Body Configuration 1g**

| Type | Source of uncertainty                                  | + Value | - Value | Probability Distribution | Divisor | C <sub>i</sub> (1g) | Standard Uncertainty |         | U <sub>i</sub> or U <sub>eff</sub> |
|------|--|---------|---------|--------------------------|---------|---------------------|----------------------|---------|------------------------------------|
|      |  |         |         |                          |         |                     | + u (%)              | - u (%) |                                    |
| B    | Probe calibration                                      | 6.000   | 6.000   | normal (k=1)             | 1.0000  | 1.0000              | 6.000                | 6.000   | ∞                                  |
| B    | Axial Isotropy   | 0.250   | 0.250   | normal (k=1)             | 1.0000  | 1.0000              | 0.250                | 0.250   | ∞                                  |
| B    | Hemispherical Isotropy                                 | 1.300   | 1.300   | normal (k=1)             | 1.0000  | 1.0000              | 1.300                | 1.300   | ∞                                  |
| B    | Spatial Resolution                                     | 0.500   | 0.500   | Rectangular              | 1.7321  | 1.0000              | 0.289                | 0.289   | ∞                                  |
| B    | Boundary Effect  | 0.769   | 0.769   | Rectangular              | 1.7321  | 1.0000              | 0.444                | 0.444   | ∞                                  |
| B    | Linearity  | 0.600   | 0.600   | Rectangular              | 1.7321  | 1.0000              | 0.346                | 0.346   | ∞                                  |
| B    | Detection Limits                                       | 0.200   | 0.200   | Rectangular              | 1.7321  | 1.0000              | 0.115                | 0.115   | ∞                                  |
| B    | Readout Electronics                                    | 0.160   | 0.160   | normal (k=1)             | 1.0000  | 1.0000              | 0.160                | 0.160   | ∞                                  |
| B    | Response Time  | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | Integration Time                                       | 1.730   | 1.730   | Rectangular              | 1.7321  | 1.0000              | 0.999                | 0.999   | ∞                                  |
| B    | RF Ambient conditions                                  | 3.000   | 3.000   | Rectangular              | 1.7321  | 1.0000              | 1.732                | 1.732   | ∞                                  |
| B    | Probe Positioner Mechanical Restrictions               | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Probe Positioning with regard to Phantom Shell         | 2.850   | 2.850   | Rectangular              | 1.7321  | 1.0000              | 1.645                | 1.645   | ∞                                  |
| B    | Extrapolation and integration / Maximum SAR evaluation | 5.080   | 5.080   | Rectangular              | 1.7321  | 1.0000              | 2.933                | 2.933   | ∞                                  |
| A    | Test Sample Positioning                                | 1.860   | 1.860   | normal (k=1)             | 1.0000  | 1.0000              | 1.860                | 1.860   | 10                                 |
| A    | Device Holder uncertainty                              | 0.154   | 0.154   | normal (k=1)             | 1.0000  | 1.0000              | 0.154                | 0.154   | 10                                 |
| B    | Phantom Uncertainty                                    | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Drift of output power                                  | 5.000   | 5.000   | Rectangular              | 1.7321  | 1.0000              | 2.887                | 2.887   | ∞                                  |
| B    | Liquid Conductivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6400              | 1.848                | 1.848   | ∞                                  |
| A    | Liquid Conductivity (measured value)                   | 2.610   | 2.610   | normal (k=1)             | 1.0000  | 0.6400              | 1.670                | 1.670   | 5                                  |
| B    | Liquid Permittivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6000              | 1.732                | 1.732   | ∞                                  |
| A    | Liquid Permittivity (measured value)                   | 2.140   | 2.140   | normal (k=1)             | 1.0000  | 0.6000              | 1.284                | 1.284   | 5                                  |
|      | Combined standard uncertainty                          |         |         | t-distribution           |         |                     | 9.32                 | 9.32    | >500                               |
|      | Expanded uncertainty                                   |         |         | k = 1.96                 |         |                     | 18.26                | 18.26   | >500                               |

**A.7.5. Uncertainty –LTE Band 7 / Wi-Fi 2450 MHz Head Configuration 1g**

| Type | Source of uncertainty                                  | + Value | - Value | Probability Distribution | Divisor | C <sub>i</sub> (1g) | Standard Uncertainty |         | U <sub>i</sub> or U <sub>eff</sub> |
|------|--|---------|---------|--------------------------|---------|---------------------|----------------------|---------|------------------------------------|
|      |  |         |         |                          |         |                     | + u (%)              | - u (%) |                                    |
| B    | Probe calibration                                      | 6.000   | 6.000   | normal (k=1)             | 1.0000  | 1.0000              | 6.000                | 6.000   | ∞                                  |
| B    | Axial Isotropy   | 0.250   | 0.250   | normal (k=1)             | 1.0000  | 1.0000              | 0.250                | 0.250   | ∞                                  |
| B    | Hemispherical Isotropy                                 | 1.300   | 1.300   | normal (k=1)             | 1.0000  | 1.0000              | 1.300                | 1.300   | ∞                                  |
| B    | Spatial Resolution                                     | 0.500   | 0.500   | Rectangular              | 1.7321  | 1.0000              | 0.289                | 0.289   | ∞                                  |
| B    | Boundary Effect  | 0.769   | 0.769   | Rectangular              | 1.7321  | 1.0000              | 0.444                | 0.444   | ∞                                  |
| B    | Linearity  | 0.600   | 0.600   | Rectangular              | 1.7321  | 1.0000              | 0.346                | 0.346   | ∞                                  |
| B    | Detection Limits                                       | 0.200   | 0.200   | Rectangular              | 1.7321  | 1.0000              | 0.115                | 0.115   | ∞                                  |
| B    | Readout Electronics                                    | 0.160   | 0.160   | normal (k=1)             | 1.0000  | 1.0000              | 0.160                | 0.160   | ∞                                  |
| B    | Response Time  | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | Integration Time                                       | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | RF Ambient conditions                                  | 3.000   | 3.000   | Rectangular              | 1.7321  | 1.0000              | 1.732                | 1.732   | ∞                                  |
| B    | Probe Positioner Mechanical Restrictions               | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Probe Positioning with regard to Phantom Shell         | 2.850   | 2.850   | Rectangular              | 1.7321  | 1.0000              | 1.645                | 1.645   | ∞                                  |
| B    | Extrapolation and integration / Maximum SAR evaluation | 5.080   | 5.080   | Rectangular              | 1.7321  | 1.0000              | 2.933                | 2.933   | ∞                                  |
| A    | Test Sample Positioning                                | 2.180   | 2.180   | normal (k=1)             | 1.0000  | 1.0000              | 2.180                | 2.180   | 10                                 |
| A    | Device Holder uncertainty                              | 0.154   | 0.154   | normal (k=1)             | 1.0000  | 1.0000              | 0.154                | 0.154   | 10                                 |
| B    | Phantom Uncertainty                                    | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Drift of output power                                  | 5.000   | 5.000   | Rectangular              | 1.7321  | 1.0000              | 2.887                | 2.887   | ∞                                  |
| B    | Liquid Conductivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6400              | 1.848                | 1.848   | ∞                                  |
| A    | Liquid Conductivity (measured value)                   | 1.840   | 1.840   | normal (k=1)             | 1.0000  | 0.6400              | 1.178                | 1.178   | 5                                  |
| B    | Liquid Permittivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6000              | 1.732                | 1.732   | ∞                                  |
| A    | Liquid Permittivity (measured value)                   | 2.030   | 2.030   | normal (k=1)             | 1.0000  | 0.6000              | 1.218                | 1.218   | 5                                  |
|      | Combined standard uncertainty                          |         |         | t-distribution           |         |                     | 9.25                 | 9.25    | >500                               |
|      | Expanded uncertainty                                   |         |         | k = 1.96                 |         |                     | 18.13                | 18.13   | >500                               |

**A.7.6. Uncertainty –LTE Band 7 / Wi-Fi 2450 MHz Body Configuration 1g**

| Type | Source of uncertainty                                  | + Value | - Value | Probability Distribution | Divisor | C <sub>i</sub> (1g) | Standard Uncertainty |         | U <sub>i</sub> or U <sub>eff</sub> |
|------|--|---------|---------|--------------------------|---------|---------------------|----------------------|---------|------------------------------------|
|      |  |         |         |                          |         |                     | + u (%)              | - u (%) |                                    |
| B    | Probe calibration                                      | 6.000   | 6.000   | normal (k=1)             | 1.0000  | 1.0000              | 6.000                | 6.000   | ∞                                  |
| B    | Axial Isotropy   | 0.250   | 0.250   | normal (k=1)             | 1.0000  | 1.0000              | 0.250                | 0.250   | ∞                                  |
| B    | Hemispherical Isotropy                                 | 1.300   | 1.300   | normal (k=1)             | 1.0000  | 1.0000              | 1.300                | 1.300   | ∞                                  |
| B    | Spatial Resolution                                     | 0.500   | 0.500   | Rectangular              | 1.7321  | 1.0000              | 0.289                | 0.289   | ∞                                  |
| B    | Boundary Effect  | 0.769   | 0.769   | Rectangular              | 1.7321  | 1.0000              | 0.444                | 0.444   | ∞                                  |
| B    | Linearity  | 0.600   | 0.600   | Rectangular              | 1.7321  | 1.0000              | 0.346                | 0.346   | ∞                                  |
| B    | Detection Limits                                       | 0.200   | 0.200   | Rectangular              | 1.7321  | 1.0000              | 0.115                | 0.115   | ∞                                  |
| B    | Readout Electronics                                    | 0.160   | 0.160   | normal (k=1)             | 1.0000  | 1.0000              | 0.160                | 0.160   | ∞                                  |
| B    | Response Time  | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | Integration Time                                       | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | RF Ambient conditions                                  | 3.000   | 3.000   | Rectangular              | 1.7321  | 1.0000              | 1.732                | 1.732   | ∞                                  |
| B    | Probe Positioner Mechanical Restrictions               | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Probe Positioning with regard to Phantom Shell         | 2.850   | 2.850   | Rectangular              | 1.7321  | 1.0000              | 1.645                | 1.645   | ∞                                  |
| B    | Extrapolation and integration / Maximum SAR evaluation | 5.080   | 5.080   | Rectangular              | 1.7321  | 1.0000              | 2.933                | 2.933   | ∞                                  |
| A    | Test Sample Positioning                                | 2.440   | 2.440   | normal (k=1)             | 1.0000  | 1.0000              | 2.440                | 2.440   | 10                                 |
| A    | Device Holder uncertainty                              | 0.154   | 0.154   | normal (k=1)             | 1.0000  | 1.0000              | 0.154                | 0.154   | 10                                 |
| B    | Phantom Uncertainty                                    | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Drift of output power                                  | 5.000   | 5.000   | Rectangular              | 1.7321  | 1.0000              | 2.887                | 2.887   | ∞                                  |
| B    | Liquid Conductivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6400              | 1.848                | 1.848   | ∞                                  |
| A    | Liquid Conductivity (measured value)                   | 2.260   | 2.260   | normal (k=1)             | 1.0000  | 0.6400              | 1.446                | 1.446   | 5                                  |
| B    | Liquid Permittivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6000              | 1.732                | 1.732   | ∞                                  |
| A    | Liquid Permittivity (measured value)                   | 2.150   | 2.150   | normal (k=1)             | 1.0000  | 0.6000              | 1.290                | 1.290   | 5                                  |
|      | Combined standard uncertainty                          |         |         | t-distribution           |         |                     | 9.36                 | 9.36    | >500                               |
|      | Expanded uncertainty                                   |         |         | k = 1.96                 |         |                     | 18.35                | 18.35   | >500                               |

**A.7.7. Uncertainty -Wi-Fi 5GHz Head Configuration 1g**

| Type | Source of uncertainty                                  | + Value | - Value | Probability Distribution | Divisor | C <sub>i</sub> (1g) | Standard Uncertainty |         | U <sub>i</sub> or U <sub>eff</sub> |
|------|--|---------|---------|--------------------------|---------|---------------------|----------------------|---------|------------------------------------|
|      |  |         |         |                          |         |                     | + u (%)              | - u (%) |                                    |
| B    | Probe calibration                                      | 6.550   | 6.550   | normal (k=1)             | 1.0000  | 1.0000              | 6.550                | 6.550   | ∞                                  |
| B    | Axial Isotropy   | 0.250   | 0.250   | normal (k=1)             | 1.0000  | 1.0000              | 0.250                | 0.250   | ∞                                  |
| B    | Hemispherical Isotropy                                 | 1.300   | 1.300   | normal (k=1)             | 1.0000  | 1.0000              | 1.300                | 1.300   | ∞                                  |
| B    | Spatial Resolution                                     | 0.500   | 0.500   | Rectangular              | 1.7321  | 1.0000              | 0.289                | 0.289   | ∞                                  |
| B    | Boundary Effect  | 0.769   | 0.769   | Rectangular              | 1.7321  | 1.0000              | 0.444                | 0.444   | ∞                                  |
| B    | Linearity  | 0.600   | 0.600   | Rectangular              | 1.7321  | 1.0000              | 0.346                | 0.346   | ∞                                  |
| B    | Detection Limits                                       | 0.200   | 0.200   | Rectangular              | 1.7321  | 1.0000              | 0.115                | 0.115   | ∞                                  |
| B    | Readout Electronics                                    | 0.160   | 0.160   | normal (k=1)             | 1.0000  | 1.0000              | 0.160                | 0.160   | ∞                                  |
| B    | Response Time  | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | Integration Time                                       | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | RF Ambient conditions                                  | 3.000   | 3.000   | Rectangular              | 1.7321  | 1.0000              | 1.732                | 1.732   | ∞                                  |
| B    | Probe Positioner Mechanical Restrictions               | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Probe Positioning with regard to Phantom Shell         | 2.850   | 2.850   | Rectangular              | 1.7321  | 1.0000              | 1.645                | 1.645   | ∞                                  |
| B    | Extrapolation and integration / Maximum SAR evaluation | 5.080   | 5.080   | Rectangular              | 1.7321  | 1.0000              | 2.933                | 2.933   | ∞                                  |
| A    | Test Sample Positioning                                | 2.380   | 2.380   | normal (k=1)             | 1.0000  | 1.0000              | 2.380                | 2.380   | 10                                 |
| A    | Device Holder uncertainty                              | 0.154   | 0.154   | normal (k=1)             | 1.0000  | 1.0000              | 0.154                | 0.154   | 10                                 |
| B    | Phantom Uncertainty                                    | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Drift of output power                                  | 5.000   | 5.000   | Rectangular              | 1.7321  | 1.0000              | 2.887                | 2.887   | ∞                                  |
| B    | Liquid Conductivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6400              | 1.848                | 1.848   | ∞                                  |
| A    | Liquid Conductivity (measured value)                   | 6.220   | 6.220   | normal (k=1)             | 1.0000  | 0.6400              | 3.981                | 3.981   | 5                                  |
| B    | Liquid Permittivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6000              | 1.732                | 1.732   | ∞                                  |
| A    | Liquid Permittivity (measured value)                   | 5.580   | 5.580   | normal (k=1)             | 1.0000  | 0.6000              | 3.348                | 3.348   | 5                                  |
|      | Combined standard uncertainty                          |         |         | t-distribution           |         |                     | 10.84                | 10.84   | >150                               |
|      | Expanded uncertainty                                   |         |         | k = 1.96                 |         |                     | 21.25                | 21.25   | >150                               |

**A.7.8. Uncertainty -Wi-Fi 5GHz Body Configuration 1g**

| Type | Source of uncertainty                                  | + Value | - Value | Probability Distribution | Divisor | C <sub>i</sub> (1g) | Standard Uncertainty |         | u <sub>i</sub> or u <sub>eff</sub> |
|------|--|---------|---------|--------------------------|---------|---------------------|----------------------|---------|------------------------------------|
|      |  |         |         |                          |         |                     | + u (%)              | - u (%) |                                    |
| B    | Probe calibration                                      | 6.550   | 6.550   | normal (k=1)             | 1.0000  | 1.0000              | 6.550                | 6.550   | ∞                                  |
| B    | Axial Isotropy   | 0.250   | 0.250   | normal (k=1)             | 1.0000  | 1.0000              | 0.250                | 0.250   | ∞                                  |
| B    | Hemispherical Isotropy                                 | 1.300   | 1.300   | normal (k=1)             | 1.0000  | 1.0000              | 1.300                | 1.300   | ∞                                  |
| B    | Spatial Resolution                                     | 0.500   | 0.500   | Rectangular              | 1.7321  | 1.0000              | 0.289                | 0.289   | ∞                                  |
| B    | Boundary Effect  | 0.769   | 0.769   | Rectangular              | 1.7321  | 1.0000              | 0.444                | 0.444   | ∞                                  |
| B    | Linearity  | 0.600   | 0.600   | Rectangular              | 1.7321  | 1.0000              | 0.346                | 0.346   | ∞                                  |
| B    | Detection Limits                                       | 0.200   | 0.200   | Rectangular              | 1.7321  | 1.0000              | 0.115                | 0.115   | ∞                                  |
| B    | Readout Electronics                                    | 0.160   | 0.160   | normal (k=1)             | 1.0000  | 1.0000              | 0.160                | 0.160   | ∞                                  |
| B    | Response Time  | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | Integration Time                                       | 0.000   | 0.000   | Rectangular              | 1.7321  | 1.0000              | 0.000                | 0.000   | ∞                                  |
| B    | RF Ambient conditions                                  | 3.000   | 3.000   | Rectangular              | 1.7321  | 1.0000              | 1.732                | 1.732   | ∞                                  |
| B    | Probe Positioner Mechanical Restrictions               | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Probe Positioning with regard to Phantom Shell         | 2.850   | 2.850   | Rectangular              | 1.7321  | 1.0000              | 1.645                | 1.645   | ∞                                  |
| B    | Extrapolation and integration / Maximum SAR evaluation | 5.080   | 5.080   | Rectangular              | 1.7321  | 1.0000              | 2.933                | 2.933   | ∞                                  |
| A    | Test Sample Positioning                                | 1.960   | 1.960   | normal (k=1)             | 1.0000  | 1.0000              | 1.960                | 1.960   | 10                                 |
| A    | Device Holder uncertainty                              | 0.154   | 0.154   | normal (k=1)             | 1.0000  | 1.0000              | 0.154                | 0.154   | 10                                 |
| B    | Phantom Uncertainty                                    | 4.000   | 4.000   | Rectangular              | 1.7321  | 1.0000              | 2.309                | 2.309   | ∞                                  |
| B    | Drift of output power                                  | 5.000   | 5.000   | Rectangular              | 1.7321  | 1.0000              | 2.887                | 2.887   | ∞                                  |
| B    | Liquid Conductivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6400              | 1.848                | 1.848   | ∞                                  |
| A    | Liquid Conductivity (measured value)                   | 4.370   | 4.370   | normal (k=1)             | 1.0000  | 0.6400              | 2.797                | 2.797   | 5                                  |
| B    | Liquid Permittivity (target value)                     | 5.000   | 5.000   | Rectangular              | 1.7321  | 0.6000              | 1.732                | 1.732   | ∞                                  |
| A    | Liquid Permittivity (measured value)                   | 4.270   | 4.270   | normal (k=1)             | 1.0000  | 0.6000              | 2.562                | 2.562   | 5                                  |
|      | Combined standard uncertainty                          |         |         | t-distribution           |         |                     | 10.15                | 10.15   | >450                               |
|      | Expanded uncertainty                                   |         |         | k = 1.96                 |         |                     | 19.90                | 19.90   | >450                               |

### Appendix 8. 3G Test set-up 3G (12.K RMC / HSDPA / HSUPA) setup

To switch from 2G to 3G, on the system config screen choose Format Switch and select WCDMA. The Call Setup Screen as shown in figure 1 pops up.

| Call Setup Screen   |   |  |                            |
|---------------------|---|--|----------------------------|
| <b>Call Control</b> | <b>Active Cell Operating Mode</b>   |  | <b>Call Parm</b>           |
| Operating Mode      | UE Information  |  | Cell Power                 |
| Active Cell         | INSI:<br>INEI(SU): (--)<br>Power Class:   |  | -35.00                     |
|                     | UE Expected Open Loop Transmit Power  |  | dBm/3.84 MHz               |
|                     | Initial PRACH TX Power: -60.00 dBm<br>Initial DPCCCH TX Power: -11.55 dBm   |  | Channel Type               |
| Originate Call      | Call Processing Status  |  | 12.2k RMC                  |
|                     | Current Service Type: None<br>MM Status: None<br>GMM State: None<br>Current DPCH Offset: 0 chips                                    |  | Paging Service             |
| Paging Parameters   | HSUPA Information<br>Rep EDCH Cat/Ext: Unrep/Unrep<br>Last received E-TFCI: ----<br>Throughput: ---- kbps<br>Acks Transmitted: ---- |  | RB Test Mode               |
|                     | HSDPA Information<br>Cur UE HS-DSCH Cat: ----<br>Block Error Ratio: ---- %<br>Throughput: ---- kbps<br>Blocks Transmitted: ----     |  | HSPA Parameters            |
| Handovers           | Active Cell   |  | 34.121 Preset Call Configs |
|                     | Idle  |  |                            |
| Clear UE Info       | Sys Type: UTRA FDD  |  | Channel (UARFCN) Parm      |
| 1 of 5              | IntRef  |  | 1 of 3                     |

Figure 1: 3G Call Setup Screen

For a 12.2k RMC call follow the steps below.

#### 8.1. Steps for 12.2k RMC

1. Ensure that the Operating Mode of the cell is off before setting up the instrument.
2. On the Call Setup Screen, under Call Parameters, press the button against Cell Power. The Cell Power value is set to about -35dBm to account for all the losses and ensure sufficient signal strength to the EUT.
3. The Channel Type is selected to 12.2k RMC. Press button against Channel (UARFCN) Parm select the correct Downlink Channel for the required UMTS FDD Band.
4. On the Call Setup Screen, under Call Parameters, press the button against HSPA Parameters. Under HSDPA Parameters on page 1, press HSDPA Uplink parameters and set the Delta ACK, Delta NACK, Delta CQI values to 8. Under HSDPA Parm itself, press HSDPA RB Test Mode Setup button and then the HSDPA RB Test Mode Settings and change HS-DSCH Data Pattern to All Ones.

| Call Setup Screen          |  |            |                  |  |      |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
|----------------------------|--|------------|------------------|--|------|--------------------|---------------------------|--------------------------------------|--|-------------------------|------------|-------------------------|------------|--------------------------|--|--------------------------|--|
| Call Control               | Active Cell Operating Mode   |            |                  |  |      |                    |                           | HSDPA Parms                          |  |                         |            |                         |            |                          |  |                          |  |
| Close Menu                 | <table border="1"> <thead> <tr> <th colspan="2">UE Information</th> </tr> </thead> <tbody> <tr> <td>INSI:</td> <td></td> </tr> <tr> <td>INEI(SU):</td> <td>(--)</td> </tr> <tr> <td>Power Class:</td> <td></td> </tr> </tbody> </table>                            |            |                  |  |      |                    |                           | UE Information                       |  | INSI:                   |            | INEI(SU):               | (--)       | Power Class:             |  | HSDPA RB Test Mode Setup |  |
|                            | UE Information   |            |                  |  |      |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
|                            | INSI:  |            |                  |  |      |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
|                            | INEI(SU):  | (--)       |                  |  |      |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
|                            | Power Class:   |            |                  |  |      |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
|                            | <table border="1"> <thead> <tr> <th colspan="2">UE Expected Open Loop Transmit Power</th> </tr> </thead> <tbody> <tr> <td>Initial PRACH TX Power:</td> <td>-60.00 dBm</td> </tr> <tr> <td>Initial DPCCH TX Power:</td> <td>-11.55 dBm</td> </tr> </tbody> </table> |            |                  |  |      |                    |                           | UE Expected Open Loop Transmit Power |  | Initial PRACH TX Power: | -60.00 dBm | Initial DPCCH TX Power: | -11.55 dBm | UE Category Parameters ▾ |  |                          |  |
|                            | UE Expected Open Loop Transmit Power   |            |                  |  |      |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
|                            | Initial PRACH TX Power:  | -60.00 dBm |                  |  |      |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
|                            | Initial DPCCH TX Power:  | -11.55 dBm |                  |  |      |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
|                            | HSDPA Uplink Parameters  |            |                  |  |      | Value              |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
| DeltaACK                   |  |            |                  |  | 8    |                    | MAC-(e)hs Parameters ▾    |                                      |  |                         |            |                         |            |                          |  |                          |  |
| DeltaNACK                  |  |            |                  |  | 8    |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
| DeltaCQI                   |  |            |                  |  | 8    |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
| Ack-Nack Repetition Factor |  |            |                  |  | 1    |                    | HSDPA Uplink Parameters ▾ |                                      |  |                         |            |                         |            |                          |  |                          |  |
| CQI Feedback Cycle (k)     |  |            |                  |  | 2 ms |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
| CQI Repetition Factor      |  |            |                  |  | 1    |                    |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
|                            |  |            |                  |  |      |                    | Return                    |                                      |  |                         |            |                         |            |                          |  |                          |  |
|                            |  |            | Active Cell Idle |  |      | Sys Type: UTRA FDD |                           |                                      |  |                         |            |                         |            |                          |  |                          |  |
|                            |  |            | IntRef           |  |      |                    |                           | 1 of 2                               |  |                         |            |                         |            |                          |  |                          |  |

Figure 2: HSDPA Parameters

- On the Call Setup Screen, under Call Parameters, on page 2, check if the DL DTCH Data is set to All Ones. On page 3, ensure that the Receiver is set to Manual. On page 3 itself, under UL CL Power Ctrl Parameters, UL CL Power Ctrl Mode is set to All Up Bits.

| Call Setup Screen                    |  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
|--------------------------------------|--|--------------------|--------|--|--|--|--|--------------------------------------|-------------------|-------------------------------|--------------------------|----------------------------|---------------------------|-----------------------|-----------------------|------------------------|--------------------------|----------------------|--|
| Call Control                         | Active Cell Operating Mode   |                    |        |  |  |  |  | Call Parms                           |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Operating Mode                       | <table border="1"> <thead> <tr> <th colspan="2">UE Information</th> </tr> </thead> <tbody> <tr> <td>INSI:</td> <td></td> </tr> <tr> <td>INEI(SU):</td> <td>(--)</td> </tr> <tr> <td>Power Class:</td> <td></td> </tr> </tbody> </table>  |                    |        |  |  |  |  | UE Information                       |                   | INSI:                         |                          | INEI(SU):                  | (--)                      | Power Class:          |                       | DL DTCH Data           |                          |                      |  |
| UE Information                       |  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| INSI:                                |  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| INEI(SU):                            | (--)   |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Power Class:                         |  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Active Cell                          | <table border="1"> <thead> <tr> <th colspan="2">UE Expected Open Loop Transmit Power</th> </tr> </thead> <tbody> <tr> <td>Initial PRACH TX Power:</td> <td>-60.00 dBm</td> </tr> <tr> <td>Initial DPCCH TX Power:</td> <td>-11.55 dBm</td> </tr> </tbody> </table>   |                    |        |  |  |  |  | UE Expected Open Loop Transmit Power |                   | Initial PRACH TX Power:       | -60.00 dBm               | Initial DPCCH TX Power:    | -11.55 dBm                | All Ones              |                       |                        |                          |                      |  |
| UE Expected Open Loop Transmit Power |  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Initial PRACH TX Power:              | -60.00 dBm   |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Initial DPCCH TX Power:              | -11.55 dBm   |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Originate Call                       | <table border="1"> <thead> <tr> <th colspan="2">Call Processing Status</th> </tr> </thead> <tbody> <tr> <td>Current Service Type:</td> <td>None</td> </tr> <tr> <td>RN Status:</td> <td>None</td> </tr> <tr> <td>GMN State:</td> <td>None</td> </tr> <tr> <td>Current DPCH Offset:</td> <td>0 chips</td> </tr> </tbody> </table>   |                    |        |  |  |  |  | Call Processing Status               |                   | Current Service Type:         | None                     | RN Status:                 | None                      | GMN State:            | None                  | Current DPCH Offset:   | 0 chips                  | RLC Reestablish Auto |  |
| Call Processing Status               |  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Current Service Type:                | None   |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| RN Status:                           | None   |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| GMN State:                           | None   |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Current DPCH Offset:                 | 0 chips  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Paging Parameters ▾                  | <table border="1"> <thead> <tr> <th>HSUPA Information</th> <th>HSDPA Information</th> </tr> </thead> <tbody> <tr> <td>Rep EDCH Cat/Ext: Unrep/Unrep</td> <td>Cur UE HS-DSCH Cat: ----</td> </tr> <tr> <td>Last received E-TFCI: ----</td> <td>Block Error Ratio: ---- %</td> </tr> <tr> <td>Throughput: ---- kbps</td> <td>Throughput: ---- kbps</td> </tr> <tr> <td>Acks Transmitted: ----</td> <td>Blocks Transmitted: ----</td> </tr> </tbody> </table> |                    |        |  |  |  |  | HSUPA Information                    | HSDPA Information | Rep EDCH Cat/Ext: Unrep/Unrep | Cur UE HS-DSCH Cat: ---- | Last received E-TFCI: ---- | Block Error Ratio: ---- % | Throughput: ---- kbps | Throughput: ---- kbps | Acks Transmitted: ---- | Blocks Transmitted: ---- | Call Limit State Off |  |
| HSUPA Information                    | HSDPA Information  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Rep EDCH Cat/Ext: Unrep/Unrep        | Cur UE HS-DSCH Cat: ----   |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Last received E-TFCI: ----           | Block Error Ratio: ---- %  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Throughput: ---- kbps                | Throughput: ---- kbps  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Acks Transmitted: ----               | Blocks Transmitted: ----   |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Handovers                            | <table border="1"> <thead> <tr> <th colspan="2">Active Cell</th> <th colspan="2">Sys Type: UTRA FDD</th> </tr> </thead> <tbody> <tr> <td colspan="2">Idle</td> <td colspan="2"></td> </tr> </tbody> </table>   |                    |        |  |  |  |  | Active Cell                          |                   | Sys Type: UTRA FDD            |                          | Idle                       |                           |                       |                       | Call Drop Timer On     |                          |                      |  |
| Active Cell                          |  | Sys Type: UTRA FDD |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Idle                                 |  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Clear UE Info                        | <table border="1"> <thead> <tr> <th colspan="2">Active Cell</th> <th colspan="2">Sys Type: UTRA FDD</th> </tr> </thead> <tbody> <tr> <td colspan="2">Idle</td> <td colspan="2"></td> </tr> </tbody> </table>   |                    |        |  |  |  |  | Active Cell                          |                   | Sys Type: UTRA FDD            |                          | Idle                       |                           |                       |                       | SRB Parameters ▾       |                          |                      |  |
| Active Cell                          |  | Sys Type: UTRA FDD |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
| Idle                                 |  |                    |        |  |  |  |  |                                      |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
|                                      |  |                    | IntRef |  |  |  |  | 2 of 3                               |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |
|                                      |  |                    |        |  |  |  |  | 1 of 5                               |                   |                               |                          |                            |                           |                       |                       |                        |                          |                      |  |

Figure 3: DL DTCH Data Parms



| Call Setup Screen  |  |  |        |              |                            |  |
|--------------------|--|--|--------|--------------|----------------------------|--|
| Call Control       | Active Cell Operating Mode   |  |        |              | Call Parm                  |  |
| Additional Screens | UE Information   |  |        |              | Cell Power                 |  |
|                    | IMSI:<br>IMEI(SV): (---)<br>Power Class:                                 |  |        |              | -35.00                     |  |
| Cell Parameters    | UE Expected Open Loop Transmit Power                                     |  |        |              | dBm/3.84 MHz               |  |
|                    | Initial PRACH TX Power: -60.00 dBm<br>Initial DPCCH TX Power: -11.55 dBm |  |        |              | Channel Type               |  |
| Generator Info     | Uplink Parameters  |  |        |              | Paging Service             |  |
|                    | Value  |  |        |              | RB Test Mode               |  |
| Uplink Parameters  | PRACH Preambles  |  |        | 64           | HSPA Parameters            |  |
|                    | PRACH Ramping Cycles(MMAX)   |  |        | 2            | 34,121 Preset Call Configs |  |
| UE Rep Neas        | Available Subchannels (Bit Mask)   |  |        | 000000000001 | Channel (UARFCN) Parm      |  |
|                    | Uplink DPCCH Scrambling Code   |  |        | 0            | 1 of 3                     |  |
| Close Menu         | Uplink DPCCH Bc/Bd Control   |  |        | Auto         |                            |  |
|                    | Manual Uplink DPCCH Bc   |  |        | 8            |                            |  |
|                    | Manual Uplink DPCCH Bd   |  |        | 15           |                            |  |
|                    | Maximum Uplink Transmit Power Level                                      |  |        | 24 dBm       |                            |  |
|                    | Active Cell  |  |        | Idle         | Sys Type: UTRA FDD         |  |
| 2 of 5             |  |  | IntRef |              |                            |  |

Figure 6: Uplink Parameters

- On page 3 under Call Control, for the RB Test Mode setup, Asymmetric RMC CN Domain is ensured to be in CS Domain for RMC call.

| Call Setup Screen |  |  |        |            |                            |  |
|-------------------|--|--|--------|------------|----------------------------|--|
| Call Control      | Active Cell Operating Mode   |  |        |            | Call Parm                  |  |
|                   | UE Information   |  |        |            | Cell Power                 |  |
|                   | IMSI:<br>IMEI(SV): (---)<br>Power Class:                                 |  |        |            | -35.00                     |  |
|                   | UE Expected Open Loop Transmit Power                                     |  |        |            | dBm/3.84 MHz               |  |
|                   | Initial PRACH TX Power: -60.00 dBm<br>Initial DPCCH TX Power: -11.55 dBm |  |        |            | Channel Type               |  |
| Voice Call        | RB Test Mode Settings  |  |        |            | Paging Service             |  |
|                   | Value  |  |        |            | RB Test Mode               |  |
|                   | Uplink DTCH RMC CRC Presence   |  |        | Present    | HSPA Parameters            |  |
|                   | Uplink Dummy DCCH Data   |  |        | Off        | 34,121 Preset Call Configs |  |
| Close Menu        | UE Loopback Type   |  |        | Type 1     | Channel (UARFCN) Parm      |  |
|                   | Asymmetric RMC Loopback Messaging  |  |        | Close/Open | 1 of 3                     |  |
|                   | Asymmetric RMC CN Domain   |  |        | CS Domain  |                            |  |
|                   | Active Cell  |  |        | Idle       | Sys Type: UTRA FDD         |  |
| 3 of 5            |  |  | IntRef |            |                            |  |

Figure 7: RB Test Mode Settings

- After the test set has been set up, change the cell Operating Mode to Active Cell and originate a call.

**8.2. Steps for 12.2k RMC + HSDPA/HSUPA**

1. Most of the steps to be followed are as in the case of 12.2k RMC however, some of the settings need to be changed. The Channel Type is changed to 12.2k RMC+HSDPA or 12.2k RMC+HSUPA as required.
2. For HSDPA and HSUPA, the settings remain same as the case for RMC but the PS Domain is made Present for Cell Parameters (Figure 5) and RB Test Mode Setup (Figure 7).
3. The following tables taken from FCC 3G SAR procedures (KDB 941225 D01 SAR test for 3G devices v02) below were applied to the Agilent 8960 series 10 wireless communications test set which supports 3G / HSDPA release 5 / HSUPA release 6.

**Sub-test 1 Setup for Release 5 HSDPA**

| Sub-test | $\beta_c$            | $\beta_d$            | $B_d$ (SF) | $\beta_c/\beta_d$    | $\beta_{hs}^{(1)}$ | SM (dB) <sup>(2)</sup> |
|----------|----------------------|----------------------|------------|----------------------|--------------------|------------------------|
| 1        | 2/15                 | 15/15                | 64         | 2/15                 | 4/15               | 0.0                    |
| 2        | 12/15 <sup>(3)</sup> | 15/15 <sup>(3)</sup> | 64         | 12/15 <sup>(3)</sup> | 24/15              | 1.0                    |
| 3        | 15/15                | 8/15                 | 64         | 15/8                 | 30/15              | 1.5                    |
| 4        | 15/15                | 4/15                 | 64         | 15/4                 | 30/15              | 1.5                    |

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Rightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Rightarrow \beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $B_{hs}/\beta_c = 24/15$

Note 3: For subtest 2 the  $\beta_c/\beta_d$  ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 11/15$  and  $\beta_d = 15/15$

**Sub-test 5 Setup for Release 6 HSUPA**

| Sub-test | $\beta_c$            | $\beta_d$            | $B_d$ (SF) | $\beta_c/\beta_d$    | $\beta_{hs}^{(1)}$ | $B_{oc}$ | $B_{od}$                             | $B_{od}$ (SF) | $B_{od}$ (codes) | CM <sup>(2)</sup> (dB) | MPR (dB) | AG <sup>(4)</sup> Index | E-TFCl |
|----------|----------------------|----------------------|------------|----------------------|--------------------|----------|--------------------------------------|---------------|------------------|------------------------|----------|-------------------------|--------|
| 1        | 11/15 <sup>(3)</sup> | 15/15 <sup>(3)</sup> | 64         | 11/15 <sup>(3)</sup> | 22/15              | 209/225  | 1039/225                             | 4             | 1                | 1.0                    | 0.0      | 20                      | 75     |
| 2        | 6/15                 | 15/15                | 64         | 6/15                 | 12/15              | 12/15    | 94/75                                | 4             | 1                | 3.0                    | 2.0      | 12                      | 67     |
| 3        | 15/15                | 9/15                 | 64         | 15/9                 | 30/15              | 31/15    | $B_{d11}: 47/15$<br>$B_{d12}: 47/15$ | 4             | 1                | 2.0                    | 1.0      | 15                      | 92     |
| 4        | 2/15                 | 15/15                | 64         | 2/15                 | 2/15               | 2/15     | 56/75                                | 4             | 1                | 3.0                    | 2.0      | 17                      | 71     |
| 5        | 15/15 <sup>(4)</sup> | 15/15 <sup>(4)</sup> | 64         | 15/15 <sup>(4)</sup> | 24/15              | 24/15    | 134/15                               | 4             | 1                | 1.0                    | 0.0      | 21                      | 81     |

Note 1:  $\Delta_{ACK}$ ,  $\Delta_{NACK}$  and  $\Delta_{CQI} = 8 \Rightarrow A_{hs} = \beta_{hs}/\beta_c = 30/15 \Rightarrow \beta_{hs} = 30/15 * \beta_c$

Note 2: CM = 1 for  $\beta_c/\beta_d = 12/15$ ,  $B_{hs}/\beta_c = 24/15$ . For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH AND E-DPCCH for the MPR is based on the relative CM difference.

Note 3: For subtest 1 the  $\beta_c/\beta_d$  ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 10/15$  and  $\beta_d = 15/15$ .

Note 4: For subtest 5 the  $\beta_c/\beta_d$  ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to  $\beta_c = 14/15$  and  $\beta_d = 15/15$ .

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Tavle 5.1g.

Note 6:  $B_{od}$  can not be set directly; it is set by Absolute Grant Value.

| Call Setup Screen |  |  |  |  |                                 |  |
|-------------------|--|--|--|--|---------------------------------|--|
| Call Control      | Active Cell Operating Mode   |  |  |  | Serving Grant                   |  |
| Operating Mode    | UE Information   |  |  |  | AG Mode                         |  |
| Active Cell       | INSI:<br>INEI(SU): (---)<br>Power Class:   |  |  |  | Single Shot                     |  |
|                   | UE Expected Open Loop Transmit Power   |  |  |  | Single Shot AG                  |  |
| Originate Call    | Initial PRACH TX Power: -60.00 dBm<br>Initial DPCCH TX Power: -11.55 dBm   |  |  |  | 21: (134/15)^2                  |  |
|                   | Call Processing Status   |  |  |  | Send Single Shot Absolute Grant |  |
| Paging Parameters | Current Service Type: None<br>MM Status: Abs Single Shot AG<br>GMM State: Index 18: (95/15)^2<br>Current DPCH: Index 19: (106/15)^2                                    |  |  |  | RB Setup AG                     |  |
| Handovers         | HSUPA In: Index 20: (119/15)^2<br>Rep EDCH Cat/B: Index 21: (134/15)^2<br>Last received: Index 22: (150/15)^2<br>Throughput: Index 23: (168/15)^2<br>Acks Transmitted: |  |  |  | 33: 4(134/15)^2                 |  |
| Clear UE Info     | DPCCH Cat: ----<br>Ratio: ---- %<br>: ---- kbps<br>nsmitted: ----  |  |  |  | AG Pattern Parameters           |  |
|                   | Active Cell<br>Idle  |  |  |  | Return                          |  |
|                   | Sys Type: UTRA FDD   |  |  |  |                                 |  |
| 1 of 5            | IntRef   |  |  |  | 1 of 2                          |  |

| Call Setup Screen  |  |  |  |  |                            |  |
|--------------------|--|--|--|--|----------------------------|--|
| Call Control       | Active Cell Operating Mode   |  |  |  | Call Parm                  |  |
| Additional Screens | UE Information   |  |  |  | Cell Power                 |  |
| Cell Parameters    | INSI:<br>INEI(SU): (---)<br>Power Class:                                 |  |  |  | -35.00                     |  |
| Generator Info     | UE Expected Open Loop Transmit Power                                     |  |  |  | dBm/3.84 MHz               |  |
|                    | Initial PRACH TX Power: -60.00 dBm<br>Initial DPCCH TX Power: -22.58 dBm |  |  |  | Channel Type               |  |
|                    | Uplink Parameters  |  |  |  | 12.2k + HSDPA              |  |
| Uplink Parameters  | Value  |  |  |  | Paging Service             |  |
|                    | PRACH Preambles: 64  |  |  |  | RB Test Mode               |  |
|                    | PRACH Ramping Cycles(MAX): 2   |  |  |  | HSPA Parameters            |  |
|                    | Available Subchannels (Bit Mask): 000000000001                           |  |  |  | 34.121 Preset Call Configs |  |
| UE Rep Params      | Uplink DPCH Scrambling Code: 0   |  |  |  | Channel (UARFCN) Params    |  |
|                    | Uplink DPCH Bc/Bd Control: Manual  |  |  |  |                            |  |
|                    | Manual Uplink DPCH Bc: 2   |  |  |  |                            |  |
| Close Menu         | Manual Uplink DPCH Bd: 15  |  |  |  |                            |  |
|                    | Maximum Uplink Transmit Power Level: 24 dBm                              |  |  |  |                            |  |
|                    | Cell Off   |  |  |  | Sys Type: UTRA FDD         |  |
| 2 of 5             | IntRef   |  |  |  | 1 of 3                     |  |

- For HSUPA the Serving Grant Parameter needs to be set. On the Call Setup Screen, under Call Parameters, press the button against HSPA Parameters. On the new screen that pops up, press HSUPA and Serving Grant. The Serving Grant is set according to the table for HSPA in the KDB (AG Index). The correct AG is chosen from the Single Shot AG. Consecutively, the RG Setup AG is set as per the ratio set on Single Shot AG.

| Call Setup Screen |  |   |  |  |   |                    |  |                                 |  |
|-------------------|--|---|--|--|---|--------------------|--|---------------------------------|--|
| Call Control      |  | Active Cell Operating Mode  |  |  |   |                    |  | Serving Grant                   |  |
| Operating Mode    |  | UE Information  |  |  |   |                    |  | AG Node                         |  |
| Active Cell       |  | INSI:<br>INEI(SU): (---)<br>Power Class:  |  |  |   |                    |  | Single Shot                     |  |
|                   |  | UE Expected Open Loop Transmit Power<br>Initial PRACH TX Power: -60.00 dBm<br>Initial DPCH TX Power: -11.55 dBm                     |  |  |   |                    |  | Single Shot AG                  |  |
| Originate Call    |  | Call Processing Status<br>Current Service Type: None<br>RIM Status: None<br>GMM State: None<br>Current DPCH Offset: 0 chips         |  |  |   |                    |  | 31: 6(168/15)^2                 |  |
| Paging Parameters |  | HSUPA Information<br>Rep EDCH Cat/Ext: Unrep/Unrep<br>Last received E-TFCI: ----<br>Throughput: ---- kbps<br>Acks Transmitted: ---- |  |  | HSDPA Information<br>Cur UE HS-DSCH Cat: ----<br>Block Error Ratio: ---- %<br>Throughput: ---- kbps<br>Blocks Transmitted: ---- |                    |  | Send Single Shot Absolute Grant |  |
| Handovers         |  |   |  |  |   |                    |  | RB Setup AG                     |  |
| Clear UE Info     |  |   |  |  |   |                    |  | 37: 6(168/15)^2                 |  |
|                   |  |   |  |  |   |                    |  | AG Pattern Parameters           |  |
|                   |  |   |  |  |   |                    |  | Return                          |  |
|                   |  | Active Cell   |  |  |   | Sys Type: UTRA FDD |  |                                 |  |
|                   |  | Idle  |  |  |   |                    |  |                                 |  |
| 1 of 5            |  | IntRef  |  |  |   |                    |  | 1 of 2                          |  |

Figure 8: Serving Grant Example

## Appendix 9. CAT24 Test set-up

### A.9.1. Establish a DC-HSDPA RB Test Mode Connection with DL 42Mbps

RB (radio bearer) test mode is a special, defined-channel configuration designed to simplify the testing environment. Since W-CDMA is an incredibly flexible system, defined radio bearers, called RMCs (reference measurement channels) simplify which configurations need to be tested for RF performance.

RB test mode provides the ability to set up a standalone channel configuration originating from the 8960 via call processing. The direction of the call setup is always from the 8960 to the UE. This is the typical RF test that is used throughout the lifecycle of a device's design process. Using RB test mode is attractive to device manufacturers because it does not require extra software to control the UE. In this type of call connection, the radio bearer (within the 8960) essentially controls the UE during test.

#### A.9.1.1 Configure 8960

1. Press **Operating Mode (F1)**, select **Cell Off** operating mode.

| Call Setup Screen        |  |                            |
|--------------------------|--|----------------------------|
| <b>Call Control</b>      | <b>Active Cell Operating Mode</b>  | <b>Call Parms</b>          |
| <b>Operating Mode</b>    | <b>UE Information</b>  | <b>Cell Power</b>          |
| <b>Cell Off</b>          | IMSI: _____ Power Class: _____<br>INEI(SV): (--) Detected PRACH Sig: ----<br>Called Party Number: _____<br>UE Expected Open Loop Transmit Power<br>Init PRACH TX Pou: -22.70 dBm Init DPCCH TX Pou: -11.55 dBm | -75.00<br>dBm/3.84 MHz     |
| <b>Originate Call</b>    | <b>Current Service Type</b>  | <b>Channel Type</b>        |
|                          | None   | 12.2k RNC                  |
| <b>Paging Parameters</b> | <b>Call Processing Status</b>  | <b>Paging Service</b>      |
|                          | <b>Operating Mode</b>  | RB Test Mode               |
|                          | RRC State: _____<br>MMI Status: Active Cell<br>GMM State: FDD Test   | HSPA Parameters            |
| <b>Handovers</b>         | <b>HSUPA In CH</b>   | 34.121 Preset Call Configs |
|                          | UE Rep E-DCH Cell Off<br>Last Happy Bit _____<br>Throughput: _____<br>ACKs Transmitted: _____  | Channel (UARFCN) Parms     |
| <b>Clear UE Info</b>     | <b>Background</b>  |                            |
|                          | Cell Off   |                            |
|                          | IntRef Offset  |                            |
|                          | Sys Type: UTRA FDD<br>Logging: No Conn   |                            |
| 1 of 5                   |  | 1 of 3                     |

2. Set the **Channel type** to **12.2k + HSDPA**.

3. Set the downlink channel code. In order to achieve the 42 Mbps maximum downlink throughput, you have to set up 15 HS-PDSCHs which will possibly cause a code collision.

To easily configure the downlink 15 HS-PDSCH for a maximum throughput, use the code preset to configure the code channels for both the serving cell and the secondary serving cell.

Select **Call Control 2 of 6-> Generator Info (F3) -> Downlink Channel Configs (F4) -> DL Chan code Preset Configs (F5)**, choose **34.121 Tables E.6.2.3,4 (HSDPA 15 HS-PDSCHs)**.

Set the **Conn S-CCPCH Cfg** to **Off** to avoid the code collision.

To see the channel code allocation for the serving cell and the secondary serving cell, select **Additional Gen Info Screens (F1) -> DC-HSDPA DL Code Chan Info (F4)**.

| Call Setup Screen           |   |                           |           |         |                       |      |                    |              |         |         |                            |
|-----------------------------|---|---------------------------|-----------|---------|-----------------------|------|--------------------|--------------|---------|---------|----------------------------|
| Screen Ctrl                 | DC-HSDPA DL Code Channel Information              |                           |           |         |                       |      |                    | Call Parms   |         |         |                            |
| DL Code Channel Info Screen | Serving Cell Primary Scrambling Code: 0           |                           |           |         |                       |      |                    | Cell Power   |         |         |                            |
|                             | Secondary Serving Cell Primary Scrambling Code: 2 |                           |           |         |                       |      |                    | -75.00       |         |         |                            |
| Generated Power Info Screen | Channel   | Serving Cell DL Chan Info |           |         | Sec Cell DL Chan Info |      |                    | dBm/3.84 MHz |         |         |                            |
|                             | Channel   | Level (dB)                | Chan Code | Current | Desired               | OVSF | Level (dB)         | Chan Code    | Current | Desired | OVSF                       |
| OCNS Info Screen            | CPICH:  | Off                       | -3.30     | 256     | 0                     |      | Off                | Off          | 256     | 0       | Channel Type               |
|                             | P-CCPCH/SCH:                                      | Off                       | -5.30     | 256     | 1                     |      | Off                | Off          | 256     | 1       | 12.2k + HSDPA              |
| DC-HSDPA DL Code Chan Info  | S-CCPCH:  | Off                       | -10.30    | 64      | 2                     |      | Off                | Off          | 256     | 2       | Paging Service             |
|                             | FICH:   | Off                       | -8.30     | 256     | 2                     |      | Off                | Off          | 256     | 2       | RB Test Mode               |
| Return                      | AICH:   | Off                       | -9.90     | 256     | 3                     |      |                    |              |         |         |                            |
|                             | (F-)DPCH:   | Off                       | Off       | 128     | 7                     |      |                    |              |         |         | HSPA Parameters            |
|                             | E-AGCH:   | Off                       | Off       | 256     | 42                    |      |                    |              |         |         |                            |
|                             | E-HICH:   | Off                       | Off       | 128     | 22                    |      |                    |              |         |         |                            |
|                             | E-RGCH:   | Off                       | Off       | 128     | 22                    |      |                    |              |         |         |                            |
|                             | HS-SCCH 1:  | Off                       | Off       | 128     | 2                     |      | Off                | Off          | 128     | 2       | 34.121 Preset Call Configs |
|                             | HS-SCCH 2:  | Off                       | Off       | 128     | 3                     |      | Off                | Off          | 128     | 3       |                            |
|                             | HS-SCCH 3:  |                           |           |         |                       |      |                    |              |         |         |                            |
|                             | HS-SCCH 4:  |                           |           |         |                       |      |                    |              |         |         |                            |
|                             | HS-PDSCHs:  | Off                       | Off       | 16      | 1-15                  |      | Off                | Off          | 16      | 1-15    | Channel (UARFCN) Parms     |
|                             | Comp OCNS:  | Off                       | Off       | 128     | WCDMA                 |      | Off                | Off          | 128     | HSDPA   |                            |
|                             |   | Cell Off                  |           |         |                       |      | Sys Type: UTRA FDD |              |         |         |                            |
|                             |   |                           |           |         |                       |      | Logging: No Conn   |              |         |         |                            |
|                             |   | DBUS-INT                  |           | IntRef  | Offset                |      |                    |              |         |         | 1 of 3                     |

4. Configure DC-HSDPA parameters to achieve the Maximum Downlink Data Rate:

First of all, you must know the maximum data rate of the device under test according to its category and the key factors to achieve the maximum data rate. In this lab, you use a category 24 device whose maximum data rate is 42 Mbps when DC-HSDPA is configured.

a) Set up the HSDPA RB Test Mode Parameters

Path: Call Parms 1 of 3 -> HSPA Parameters (F10) -> HSDPA Parameters (F10) -> HSDPA RB Test Mode Setup (F8) -> HSDPA RB Test Mode Settings (F8).

- RB Test HS-DSCH Configuration Type = User Defined
- RB Test User Defined HS-DSCH MAC entity = MAC-ehs (Note 1)
- RB Test User Defined HARQ Processes = 6 (Note 2)
- RB Test User Defined UE IR Buffer Allocation = Implicit
- RB Test User Defined DC-HSDPA State = On
- RB Test Mode DC-HSDPA DPCH Loopback State = On

**Note 1:** DC-HSDPA requires MAC-ehs. You must set the MAC entity to MAC-ehs before setting the DC-HSDPA state)

**Note 2:** To restrict the amount of soft memory that can be allocated to a single HARQ process (and thus limit the amount of data that has to be transferred across the UE's internal data buses) the specifications require that when setting up a DC-HSDPA call with the implicit HARQ memory partitioning the network must configure 6, 7, or 8 HARQ processes per cell. For the explicit HARQ memory partitioning case, the number of HARQ processes can be 1 through 8, but the memory size for each HARQ process cannot be greater than the number of soft channel bits for an implicit memory partitioning with 6 processes per HS-DSCH channel.

b) Set up the Serving Cell Parameters

Path: F10

- RB Test User Defined 64QAM State =On
- RB Test User Defined Active HS-PDSCHs =15
- RB Test User Def Transport Block Size Index =62
- RB Test User Defined Modulation Type =64QAM
- RB Test User Defined Inter-TTI Interval =1

c) Set up the Secondary Serving Cell Parameters

*Path: F11*

- **RB Test User Def Secondary Cell 64QAM State =On**
- **RBTM User Def Sec Cell Active HS-PDSCHs = 15**
- **RBTM User Def Sec Cell TB Size Index = 62**
- **RBTM User Def Sec Cell Modulation Type =64QAM**
- **RBTM User Def Sec Cell Inter-TTI Interval = 1**

d) Set the **Secondary Serving Cell Power (dBm/3.84 MHz) to -25 dBm/3.84 MHz**

*Path: Return (F12) -> HSDPA Parms 2 of 2 -> Secondary Serv Cell Parms (F10)*

e) Set the **Cell power to -25 dBm/3.84 MHz**

*Path: CALL SETUP -> F7*

f) Set the HSDPA Conn DL Channel Levels

*Path: CALL SETUP -> Call Control 2 of 6 -> Generator Info (F3) ->Downlink Channel Levels (F3) -> Connected DL Channel Levels (F3) -> F3*

- **HSDPA Cell 1 Connected CPICH Level = -8**
- **HSDPA Cell 1 Connected P-CCPCH/SCH Level = -20**
- **HSDPA Cell 1 Connected PICH Level = off**
- **HSDPA Cell 1 Connected DPCH Level = -30**
- **HSDPA Cell 1 Connected HS-PDSCH Level (Sum) = -1 dBm**
- **HSDPA Cell 1 Connected HS-SCCH 1 to 4 Level = -20,-20,off,off**
- **Secondary Cell HSDPA Conn CPICH Level = -8**
- **Secondary Cell HSDPA Conn PCCPCH/SCH Level = -20**
- **Secondary Cell HSDPA Conn PICH Level = off**
- **Secondary Cell HSDPA Conn HS-PDSCHs Lvl (Sum) = -1 dBm**
- **Secondary Cell HSDPA Conn HS-SCCH 1 to 4 Level = -20,-20,off,off**

5. Set the **Operating Mode (F1) to Active Cell.**

#### **A.9.1.2. Power on the UE and Set up the Connection**

Power on the device, and then wait for it to camp on 8960. You should be able to see the following screen.

| Call Setup Screen |                                      |                            |                                |  |                            |        |
|-------------------|--------------------------------------|----------------------------|--------------------------------|--|----------------------------|--------|
| Call Control      | Active Cell Operating Mode           |                            |                                |  | Call Params                |        |
| Operating Mode    | UE Information                       |                            |                                |  | Cell Power                 |        |
| Active Cell       | INSI: 001012345678901                |                            | Power Class: 4                 |  | -25.00                     |        |
|                   | IMEI(SV):352358040214948(--)         |                            | Detected PRACH Sig: 0          |  | dBm/3.84 MHz               |        |
|                   | Called Party Number:                 |                            |                                |  | Channel Type               |        |
|                   | UE Expected Open Loop Transmit Power |                            |                                |  | 12.2k + HSDPA              |        |
|                   | Init PRACH TX Pou: -60.00 dBm        |                            | Init DPCCCH TX Pou: -11.55 dBm |  | Paging Service             |        |
| Originate Call    | Current Service Type                 |                            |                                |  | RB Test Mode               |        |
|                   | None                                 |                            |                                |  |                            |        |
| Paging Parameters | Call Processing Status               |                            |                                |  | HSPA Parameters            |        |
|                   | RRC State: Idle                      | Soft Handover State: Off   |                                |  |                            |        |
|                   | MM Status: None                      | Compressed Mode State: Off |                                |  |                            |        |
|                   | GMM State: Attached                  | Cur DPCH Offset: 0 chips   |                                |  |                            |        |
| Handovers         | HSUPA Information                    |                            | HSDPA Information              |  | 34.121 Preset Call Configs |        |
|                   | Rep EDCH Cat/Ext: 6/Unrep            | Cur UE HS-DSCH Cat: 24     |                                |  |                            |        |
|                   | Last Happy Bit: None                 | Block Error Ratio: ---- %  |                                |  |                            |        |
|                   | Throughput: ---- kbps                | Throughput: ---- kbps      |                                |  |                            |        |
| Clear UE Info     | ACKs Transmitted: ----               |                            | Blocks Transmitted: ----       |  | Channel (UARFCN) Params    |        |
|                   | Active Cell                          |                            | Sys Type: UTRA FDD             |  |                            |        |
|                   | Idle                                 |                            | Logging: No Conn               |  |                            |        |
| 1 of 6            | DBUS-INT                             | IntRef                     | Offset                         |  |                            | 1 of 3 |

The UE reports HSDPA categories to 8960, which represents its maximum data rate capability. DC-HSDPA requires UE categories 21 to 24.

The GMM state must be **Attached**, otherwise you cannot establish a HSDPA connection.

2. Originate the Connection

a) Now, Originate an RB Test call with DC-HSDPA by pressing „F3“ from the main Call Setup screen.

b) After a connection is set up, you will be able to see the throughput from the HSDPA Information window. Press the **Measurement Reset** key to reset the calculation.

| Call Setup Screen |                                      |                            |                                |  |                            |        |
|-------------------|--------------------------------------|----------------------------|--------------------------------|--|----------------------------|--------|
| Call Control      | Active Cell Operating Mode           |                            |                                |  | Call Params                |        |
| Operating Mode    | UE Information                       |                            |                                |  | Cell Power                 |        |
| Active Cell       | INSI: 001012345678901                |                            | Power Class: 4                 |  | -25.00                     |        |
|                   | IMEI(SV):352358040214948(--)         |                            | Detected PRACH Sig: 0          |  | dBm/3.84 MHz               |        |
|                   | Called Party Number:                 |                            |                                |  | Channel Type               |        |
|                   | UE Expected Open Loop Transmit Power |                            |                                |  | 12.2k + HSDPA              |        |
|                   | Init PRACH TX Pou: -60.00 dBm        |                            | Init DPCCCH TX Pou: -11.55 dBm |  | Paging Service             |        |
| End Call          | Current Service Type                 |                            |                                |  | RB Test Mode               |        |
|                   | RB Test Mode - HSDPA                 |                            |                                |  |                            |        |
| Paging Parameters | Call Processing Status               |                            |                                |  | HSPA Parameters            |        |
|                   | RRC State: CELL_DCH                  | Soft Handover State: Off   |                                |  |                            |        |
|                   | MM Status: None                      | Compressed Mode State: Off |                                |  |                            |        |
|                   | GMM State: Attached                  | Cur DPCH Offset: 0 chips   |                                |  |                            |        |
| Handovers         | HSUPA Information                    |                            | HSDPA Information              |  | 34.121 Preset Call Configs |        |
|                   | Rep EDCH Cat/Ext: 6/Unrep            | Cur UE HS-DSCH Cat: 24     |                                |  |                            |        |
|                   | Last Happy Bit: None                 | Block Error Ratio: 0 %     |                                |  |                            |        |
|                   | Throughput: ---- kbps                | Throughput: 42101 kbps     |                                |  |                            |        |
| Clear UE Info     | ACKs Transmitted: ----               |                            | Blocks Transmitted: 115500     |  | Channel (UARFCN) Params    |        |
|                   | Active Cell                          |                            | Sys Type: UTRA FDD             |  |                            |        |
|                   | Connected                            |                            | Logging: No Conn               |  |                            |        |
| 1 of 6            | DBUS-INT                             | IntRef                     | Offset                         |  |                            | 1 of 3 |

Now you can also check the connected DC-HSDPA downlink channel levels.

Path: CALL SETUP->Call Control 2 of 6 -> Generator Info (F3) -> Additional Gen Info Screens (F1) ->DC-HSDPA DL Code Chan Info (F4).

| Call Setup Screen           |   |                           |         |        |                       |                    |         |              |              |
|-----------------------------|---|---------------------------|---------|--------|-----------------------|--------------------|---------|--------------|--------------|
| Screen Ctrl                 | DC-HSDPA DL Code Channel Information              |                           |         |        |                       |                    |         |              | Call Parms   |
|                             | Serving Cell Primary Scrambling Code: 0           |                           |         |        |                       |                    |         |              | Cell Power   |
|                             | Secondary Serving Cell Primary Scrambling Code: 2 |                           |         |        |                       |                    |         |              | -25.00       |
| DL Code Channel Info Screen | Channel   | Serving Cell DL Chan Info |         |        | Sec Cell DL Chan Info |                    |         |              | dBm/3.84 MHz |
|                             |   | Level (dB)                | Chan    |        | Level (dB)            | Chan               |         | Channel Type |              |
| Generated Power Info Screen | Channel   | Current                   | Desired | OVSF   | Code                  | Current            | Desired | OVSF         | Code         |
|                             | CPICH:  | -8.00                     | -8.00   | 256    | 0                     | -8.00              | -8.00   | 256          | 0            |
|                             | P-CCPCH/SCH:                                      | -20.00                    | -20.00  | 256    | 1                     | -20.00             | -20.00  | 256          | 1            |
| OCNS Info Screen            | S-CCPCH:  | Off                       | Off     | 64     | 2                     |                    |         |              |              |
|                             | PICH:   | Off                       | Off     | 256    | 2                     | Off                | Off     | 256          | 2            |
|                             | AICH:   |                           |         |        |                       |                    |         |              |              |
|                             | (F-)DPCH:   | -30.00                    | -30.00  | 128    | 7                     |                    |         |              |              |
| DC-HSDPA DL Code Chan Info  | E-AGCH:   | Off                       | Off     | 256    | 42                    |                    |         |              |              |
|                             | E-HICH:   | Off                       | Off     | 128    | 22                    |                    |         |              |              |
|                             | E-RGCH:   | Off                       | Off     | 128    | 22                    |                    |         |              |              |
|                             | HS-SCCH 1:  | -20.00                    | -20.00  | 128    | 2                     | -20.00             | -20.00  | 128          | 2            |
|                             | HS-SCCH 2:  | -20.00                    | -20.00  | 128    | 3                     | -20.00             | -20.00  | 128          | 3            |
|                             | HS-SCCH 3:  |                           |         |        |                       |                    |         |              |              |
|                             | HS-SCCH 4:  |                           |         |        |                       |                    |         |              |              |
|                             | HS-PDSCHs:  | -1.00                     | -1.00   | 16     | 1-15                  | -1.00              | -1.00   | 16           | 1-15         |
| Return                      | Comp OCNS:  | -17.31                    | -17.31  | 128    | HSDPA                 | -17.65             | -17.65  | 128          | HSDPA        |
|                             |   | Active Cell Connected     |         |        |                       | Sys Type: UTRA FDD |         |              |              |
|                             |   |                           |         |        |                       | Logging: No Conn   |         |              |              |
|                             |   | DBUS-INT                  |         | IntRef | Offset                |                    |         |              |              |
|                             |   |                           |         |        |                       |                    |         |              | 1 of 3       |

### A.9.2. Activate/ Deactivate the Secondary Serving Cell

Once a DC-HSDPA connection is established, 8960 can control the UE to start or stop monitoring the secondary serving cell using HS-SCCH orders. The HS-SCCH orders can be sent on either the serving or secondary serving cell.

#### A.9.2.1 Deactivate the Secondary Serving Cell

1. Setup the Deactivate Secondary Cell Parameter

Path: CALL SETUP->Call Control 6 of 6 -> HS-SCCH Order (F3) -> Deactivate Secondary Cell (F2)

In this lab you set it to deactivate the secondary serving cell from the serving cell.

- Deactivate Secondary Cell HS-SCCH Order From = Serving Cell

Press **Send Deactivate Secondary Cell (F5)**

Press Measurement Reset key and see the throughput has dropped to 21 Mbps or so, like the figure below:

| Call Setup Screen |                                      |                            |                               |  |                            |        |
|-------------------|--------------------------------------|----------------------------|-------------------------------|--|----------------------------|--------|
| Call Control      | Active Cell Operating Mode           |                            |                               |  | Call Parm                  |        |
| Operating Mode    | UE Information                       |                            |                               |  | Cell Power                 |        |
| Active Cell       | INSI: 001012345678901                |                            | Power Class: 4                |  | -25.00                     |        |
|                   | INEI(SU):352358040214948(--)         |                            | Detected PRACH Sig: 0         |  | dBm/3.84 MHz               |        |
|                   | Called Party Number:                 |                            |                               |  | Channel Type               |        |
|                   | UE Expected Open Loop Transmit Power |                            |                               |  | 12.2k + HSDPA              |        |
|                   | Init PRACH TX Pou: -60.00 dBm        |                            | Init DPCCH TX Pou: -11.55 dBm |  | Paging Service             |        |
| End Call          | Current Service Type                 |                            |                               |  | RB Test Mode               |        |
|                   | RB Test Mode - HSDPA                 |                            |                               |  |                            |        |
|                   | Call Processing Status               |                            |                               |  | HSPA Parameters            |        |
| Paging Parameters | RRC State: CELL_DCH                  | Soft Handover State: Off   |                               |  |                            |        |
|                   | MN Status: None                      | Compressed Mode State: Off |                               |  |                            |        |
|                   | GN State: Attached                   | Cur DPCCH Offset: 0 chips  |                               |  |                            |        |
| Handovers         | HSUPA Information                    |                            | HSDPA Information             |  | 34.121 Preset Call Configs |        |
|                   | Rep EDCH Cat/Ext: 6/Unrep            | Cur UE HS-DSCH Cat: 24     |                               |  |                            |        |
|                   | Last Happy Bit: None                 | Block Error Ratio: 0 %     |                               |  |                            |        |
|                   | Throughput: ---- kbps                | Throughput: 21088 kbps     |                               |  |                            |        |
| Clear UE Info     | ACKs Transmitted: ----               | Blocks Transmitted: 35000  |                               |  | Channel (UARFCH) Parm      |        |
|                   | Active Cell                          |                            | Sys Type: UTRA FDD            |  |                            |        |
|                   | Connected                            |                            | Logging: No Conn              |  |                            |        |
| 1 of 6            | DBUS-INT                             | IntRef                     | Offset                        |  |                            | 1 of 3 |

You can see more on the DC-HSDPA Information screen.

Path: CALL SETUP->Call Control 2 of 6 -> Additional Screens (F1) -> HSDPA Information (F4) -> DC-HSDPA Information (F4).

| Call Setup Screen            |  |        |                    |              |                        |                            |
|------------------------------|--|--------|--------------------|--------------|------------------------|----------------------------|
| Screen Ctrl                  | DC-HSDPA Information                                       |        |                    |              | Call Parm              |                            |
| Channel (UARFCH) Info        | Secondary Serving Cell Status                              |        |                    |              | Cell Power             |                            |
|                              | Current Secondary Serving Cell Status: Configured-Inactive |        |                    |              | -25.00                 |                            |
|                              |  |        |                    |              | dBm/3.84 MHz           |                            |
| HSPA Information             | DC-HSDPA Information                                       |        |                    |              | Channel Type           |                            |
|                              |  |        | Summary            | Serving Cell | Secondary Serving Cell | 12.2k + HSDPA              |
|                              | Block Error Ratio:   | 0 %    | 0 %                | ----         | %                      | Paging Service             |
| E-TFCI Recording Information | Throughput (kbps):   | 21082  | 21082              | 0            |                        | RB Test Mode               |
|                              | Blocks Transmitted:  | 66000  | 66000              | 0            |                        |                            |
|                              | ACKs Received:   | 65958  | 65958              | 0            |                        |                            |
|                              | NACKs Received:  | 42     | 42                 | 0            |                        |                            |
| HSDPA Information            | statDTXs Received:   | 0      | 0                  | 0            |                        | HSPA Parameters            |
|                              | Count of Rep CQI Lim:                                      | ----   | ----               | ----         |                        |                            |
|                              | Last Received CQI:   |        | 30                 | 30           |                        |                            |
|                              | Max Allowed CQI:   |        | ----               | ----         |                        |                            |
| Clear UE Info                | Test Mode User Def TBS:                                    |        | 42192              | 42192        |                        | 34.121 Preset Call Configs |
|                              | PS Data User Def TBS:                                      |        | 7298               | 7298         |                        |                            |
|                              | Last Sig Meas Pur Offs (dB):                               |        | 6.0                | 6.0          |                        |                            |
| Return                       |  |        |                    |              | Channel (UARFCH) Parm  |                            |
|                              | Active Cell  |        | Sys Type: UTRA FDD |              |                        |                            |
|                              | Connected  |        | Logging: No Conn   |              |                        |                            |
| 1 of 2                       | DBUS-INT   | IntRef | Offset             |              |                        | 1 of 3                     |

### A.9.2.2 Re-activate the Secondary Serving Cell

Now you can activate the secondary serving cell by pressing back to the HS-SCCH Order menu.

Path: CALL SETUP->Call Control 6 of 6 -> HS-SCCH Order (F3)

Press **Send Activate Secondary Cell (F1)**.

Press the Measurement Reset key and see the throughput has increased to 42 Mbps. When you look at the DC-HSDPA Information screen, you can see the secondary serving cell is set up again.

| Call Setup Screen            |  |              |                        |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
|------------------------------|--|--------------|------------------------|--|--------------------|--|------------------------------|---------|--------------|------------------------|--------------------|-----|-----|-----|--------------------|-------|-------|-------|---------------------|-------|------|------|----------------|-------|------|------|-----------------|----|---|----|--------------------|---|---|---|-----------------------|------|------|------|--------------------|--|----|----|------------------|--|------|------|-------------------------|--|-------|-------|-----------------------|--|------|------|------------------------------|--|-----|-----|---------------|--|
| Screen Ctrl                  | DC-HSDPA Information   |              |                        |  |                    |  | Call Params                  |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| Channel (UARFCN) Info        | Secondary Serving Cell Status  |              |                        |  |                    |  | Cell Power                   |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
|                              | Current Secondary Serving Cell Status: Configured-Active   |              |                        |  |                    |  | -25.00 dBm/3.84 MHz          |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| HSPA Information             | DC-HSDPA Information   |              |                        |  |                    |  | Channel Type                 |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
|                              | <table border="1"> <thead> <tr> <th></th> <th>Summary</th> <th>Serving Cell</th> <th>Secondary Serving Cell</th> </tr> </thead> <tbody> <tr> <td>Block Error Ratio:</td> <td>0 %</td> <td>0 %</td> <td>0 %</td> </tr> <tr> <td>Throughput (kbps):</td> <td>41996</td> <td>21064</td> <td>20941</td> </tr> <tr> <td>Blocks Transmitted:</td> <td>11000</td> <td>6000</td> <td>6000</td> </tr> <tr> <td>ACKs Received:</td> <td>10949</td> <td>5991</td> <td>5956</td> </tr> <tr> <td>NACKs Received:</td> <td>51</td> <td>9</td> <td>44</td> </tr> <tr> <td>statDTXs Received:</td> <td>0</td> <td>0</td> <td>0</td> </tr> <tr> <td>Count of Rep CQI Lim:</td> <td>----</td> <td>----</td> <td>----</td> </tr> <tr> <td>Last Received CQI:</td> <td></td> <td>30</td> <td>30</td> </tr> <tr> <td>Max Allowed CQI:</td> <td></td> <td>----</td> <td>----</td> </tr> <tr> <td>Test Node User Def TBS:</td> <td></td> <td>42192</td> <td>42192</td> </tr> <tr> <td>PS Data User Def TBS:</td> <td></td> <td>7298</td> <td>7298</td> </tr> <tr> <td>Last Sig Meas Pur Offs (dB):</td> <td></td> <td>6.0</td> <td>6.0</td> </tr> </tbody> </table> |              |                        |  |                    |  |                              | Summary | Serving Cell | Secondary Serving Cell | Block Error Ratio: | 0 % | 0 % | 0 % | Throughput (kbps): | 41996 | 21064 | 20941 | Blocks Transmitted: | 11000 | 6000 | 6000 | ACKs Received: | 10949 | 5991 | 5956 | NACKs Received: | 51 | 9 | 44 | statDTXs Received: | 0 | 0 | 0 | Count of Rep CQI Lim: | ---- | ---- | ---- | Last Received CQI: |  | 30 | 30 | Max Allowed CQI: |  | ---- | ---- | Test Node User Def TBS: |  | 42192 | 42192 | PS Data User Def TBS: |  | 7298 | 7298 | Last Sig Meas Pur Offs (dB): |  | 6.0 | 6.0 | 12.2k + HSDPA |  |
|                              | Summary  | Serving Cell | Secondary Serving Cell |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| Block Error Ratio:           | 0 %  | 0 %          | 0 %                    |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| Throughput (kbps):           | 41996  | 21064        | 20941                  |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| Blocks Transmitted:          | 11000  | 6000         | 6000                   |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| ACKs Received:               | 10949  | 5991         | 5956                   |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| NACKs Received:              | 51   | 9            | 44                     |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| statDTXs Received:           | 0  | 0            | 0                      |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| Count of Rep CQI Lim:        | ----   | ----         | ----                   |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| Last Received CQI:           |  | 30           | 30                     |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| Max Allowed CQI:             |  | ----         | ----                   |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| Test Node User Def TBS:      |  | 42192        | 42192                  |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| PS Data User Def TBS:        |  | 7298         | 7298                   |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| Last Sig Meas Pur Offs (dB): |  | 6.0          | 6.0                    |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| E-TFCI Recording Information |  |              |                        |  |                    |  | Paging Service               |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| HSDPA Information            |  |              |                        |  |                    |  | RB Test Mode                 |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
|                              |  |              |                        |  |                    |  | HSPA Parameters              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| Clear UE Info                |  |              |                        |  |                    |  | 34.121 Preset Call Configs ▾ |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| Return                       |  |              |                        |  |                    |  | Channel (UARFCN) Params      |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
|                              |  |              |                        |  |                    |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
|                              | Active Cell Connected  |              |                        |  | Sys Type: UTRA FDD |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
|                              |  |              |                        |  | Logging: No Conn   |  |                              |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |
| 1 of 2                       | DBUS-INT   | IntRef       | Offset                 |  |                    |  | 1 of 3                       |         |              |                        |                    |     |     |     |                    |       |       |       |                     |       |      |      |                |       |      |      |                 |    |   |    |                    |   |   |   |                       |      |      |      |                    |  |    |    |                  |  |      |      |                         |  |       |       |                       |  |      |      |                              |  |     |     |               |  |

When DC-HSDPA is active, the HBLER measurement can also be used to perform receiver testing. 3GPP TS 34.121-1 sections 6.3C and 6.3D are supported and can be set up and tested as described in an appendix in another document, DC-HSDPA User Guide.