



TEST REPORT

Test Report No. : UL-RPT-RP10295117JD02B V2.0

Manufacturer : Sony Mobile Communications Inc.

FCC ID : PY7PM-0807

Technology : UMTS850 Band V

Test Standard(s) : FCC Part 22

1. This test report shall not be reproduced in full or partial, without the written approval of UL VS LTD.
2. The results in this report apply only to the sample(s) tested.
3. The sample tested is in compliance with the above standard(s).
4. The test results in this report are traceable to the national or international standards.
5. Version 2.0 supersedes all previous versions.

Date of Issue: 02 August 2014


Checked by:

Sarah Williams
Engineer, Radio Laboratory

Issued by :

pp

John Newell
Group Quality Manager
Basingstoke,
UL VS LTD



This laboratory is accredited by UKAS.
The tests reported herein have been
performed in accordance with its' terms
of accreditation.

UL VS LTD

Pavilion A, Ashwood Park, Ashwood Way, Basingstoke, Hampshire, RG23 8BG, UK
Telephone: +44 (0)1256 312000
Facsimile: +44 (0)1256 312001

This page has been left intentionally blank.

Table of Contents

1. Customer Information	4
2. Summary of Testing	5
2.1. General Information	5
2.2. Summary of Test Results	5
2.3. Methods and Procedures	5
2.4. Deviations from the Test Specification	5
3. Equipment Under Test (EUT).....	6
3.1. Identification of Equipment Under Test (EUT)	6
3.2. Description of EUT	7
3.3. Modifications Incorporated in the EUT	7
3.4. Additional Information Related to Testing	8
3.5. Support Equipment	8
4. Operation and Monitoring of the EUT during Testing.....	9
4.1. Operating Modes	9
4.2. Configuration and Peripherals	9
5. Measurements, Examinations and Derived Results	10
5.1. General Comments	10
5.2. Test Results	11
5.2.1. Transmitter Effective Radiated Power (ERP)	11
5.2.2. Transmitter Occupied Bandwidth	14
5.2.3. Transmitter Out of Band Radiated Emissions	25
5.2.4. Transmitter Band Edge Radiated Emissions	28
5.2.5. Transmitter Frequency Stability (Temperature Variation)	38
5.2.6. Transmitter Frequency Stability (Voltage Variation)	40
6. Measurement Uncertainty	41
7. Report Revision History	42

1.Customer Information








Company Name:	Sony Mobile Communications Inc.
Address:	Nya Vattentornet Mobilvägen 10 Lund 22188 Sweden

2. Summary of Testing

2.1. General Information

Specification Reference:	47CFR22
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 22 Subpart H (Public Mobile Services)
Site Registration:	209735
Location of Testing:	UL VS LTD, Unit 3 Horizon, Wade Road, Kingsland Business Park, Basingstoke, Hampshire, RG24 8AH, United Kingdom
Test Dates:	07 July 2014 to 08 July 2014

2.2. Summary of Test Results

FCC Reference (47CFR)	Measurement	Result
Part 22.913(a)(2)	Transmitter Effective Radiated Power (ERP)	
Part 2.1055/22.355	Transmitter Frequency Stability (Temperature and Voltage Variation)	
Part 2.1049	Transmitter Occupied Bandwidth	
Part 2.1053/22.917	Transmitter Out of Band Radiated Emissions	
Part 2.1053/22.917	Transmitter Band Edge Radiated Emissions	
Key to Results		
 = Complied  = Did not comply		

2.3. Methods and Procedures

Reference:	ANSI/TIA-603-C-2004
Title:	Land Mobile Communications Equipment, Measurements and performance Standards
Reference:	FCC KDB 971168 D01 v02r01, 7 June 2013
Title:	Measurement Guidance for Certification of Licensed Digital Transmitters

2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

3. Equipment Under Test (EUT)

3.1. Identification of Equipment Under Test (EUT)

Brand Name:	Sony
IMEI:	004402452692654 (<i>Radiated sample #1</i>)
Test Sample Serial Number:	CB5A1ZG8UF
Hardware Version Number:	A
Software Version Number:	23.0.H.0.61
FCC ID:	PY7PM-0807

Brand Name:	Sony
IMEI:	004402452693934 (<i>Radiated sample #2</i>)
Test Sample Serial Number:	CB5A1ZG8UW
Hardware Version Number:	A
Software Version Number:	23.0.H.0.61
FCC ID:	PY7PM-0807

Brand Name:	Sony
IMEI:	004402452695228 (<i>Conducted sample with RF port</i>)
Test Sample Serial Number:	CB5A1ZG8TB
Hardware Version Number:	A
Software Version Number:	23.0.H.0.61
FCC ID:	PY7PM-0807

Brand Name:	Sony
Description:	AC Charger
Model Name or Number:	EP880

Brand Name:	Generic
Description:	MHL Cable
Model Name or Number:	Not marked

Brand Name:	Sony
Description:	MHL Adaptor
Model Name or Number:	IM750

Identification of Equipment Under Test (EUT) (continued)

Brand Name:	Sony
Description:	USB Cable
Model Name or Number:	EC803

Brand Name:	Sony
Description:	Deskstand
Model Name or Number:	DK43

Brand Name:	Sony
Description:	PHF
Model Name or Number:	MH410c

3.2. Description of EUT

The equipment under test (EUT) was a GSM/WCDMA/LTE Phone + Bluetooth, DTS/UNII a/b/g/n/ac + NFC & ANT+

3.3. Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

3.4. Additional Information Related to Testing

Technology Tested:	UMTS850		
Type of Radio Device:	Transceiver		
Mode:	UMTS FDD V		
Modulation Type:	QPSK / 8PSK		
Channel Spacing:	5 MHz		
Power Supply Requirement(s):	Nominal	3.8 V	
	Minimum	3.42 V	
	Maximum	4.18 V	
Maximum Output Power (ERP):	Voice (12.2 kbps)	22.6 dBm	
	HSDPA Sub-Test 3	23.8 dBm	
	HSUPA Sub-Test 5	23.6 dBm	
Transmit Frequency Range:	824 to 849 MHz		
Transmit Channels Tested:	Channel ID	Channel Number	Channel Frequency (MHz)
	Bottom	4132	826.4
	Middle	4183	836.6
	Top	4233	846.6

3.5. Support Equipment

The following support equipment was used to exercise the EUT during testing:

Description:	2 GB Micro SD Card
Brand Name:	SanDisk
Model Name or Number:	Not marked

Description:	22" High Definition Television
Brand Name:	Logik
Model Name or Number:	L22FE12A
Serial Number:	1309020661

Description:	Voltage variation jig
Brand Name:	Not marked
Model Name or Number:	Not marked
Serial Number:	Not marked

4. Operation and Monitoring of the EUT during Testing

4.1. Operating Modes

The EUT was tested in the following operating mode(s):

- Constantly transmitting at full power on bottom, middle and top channels as required.
- Occupied bandwidth, ERP and band edge tests were performed with the EUT in Voice (12.2 kbps), HSDPA (Sub-tests 1 to 4) or HSUPA (Sub-tests 1 to 5) modes.
- Transmitter radiated spurious emissions were checked in all modes during pre-scans. Voice / 12.2 kbps was found to be the worst case and all final measurements were performed with the EUT in this mode.

4.2. Configuration and Peripherals

The EUT was tested in the following configuration(s):

- Connected to a Rohde & Schwarz CMW 500 Universal Radio Communications Tester, operating in UMTS Band V mode.
- Transmitter radiated spurious emission tests were performed with the following configurations, employing all available accessories:
 - Configuration 1 – Handset with the AC charger, USB Cable, MHL cable (terminated in to a television), MHL adaptor and PHF.
 - Configuration 2 – Handset with the AC charger, USB Cable, Deskstand and PHF.

Pre-scans below 1 GHz were performed in both configurations 1 and 2, with final measurements limited to the configuration which provided worst case results. Pre-scans above 1 GHz were performed in the configuration that employed the most accessories (Configuration 1), with any final measurements being performed in both configurations.

- Testing at temperature and voltage extremes was performed using a voltage variation jig and adaptor supplied by the customer. The adaptor plugs onto the handset in place of the battery connector.
- The voltage variation jig and adaptor were used for conducted measurements set at the nominal voltage.
- The conducted sample with IMEI 004402452695228 was used for conducted power, occupied bandwidth and frequency stability measurements.
- The radiated sample with IMEI 004402452693934 was used for transmitter radiated emissions below 1 GHz measurements.
- The radiated sample with IMEI 004402452692654 was used for all other radiated measurements.

5. Measurements, Examinations and Derived Results

5.1. General Comments

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to *Section 6. Measurement Uncertainty* for details.

In accordance with UKAS requirements all the measurement equipment is on a calibration schedule. All equipment was within the calibration period on the date of testing.

5.2. Test Results**5.2.1. Transmitter Effective Radiated Power (ERP)****Test Summary:**

Test Engineer:	David Doyle	Test Date:	08 July 2014
Test Sample IMEI:	004402452695228		

FCC Reference:	Part 22.913(a)(2)
Test Method Used:	As detailed in KDB 971168 Section 5.1.1 and 5.2.1

Environmental Conditions:

Temperature (C):	22
Relative Humidity (%):	48

Note(s):

- All modes were compared on each channel and the highest power recorded was subtracted from the limit to show the margin.
- The signal analyser was connected to the RF port on the EUT using suitable attenuation and RF cable. An RF level offset was entered on the signal analyser to compensate for the loss of the attenuator and RF cable.
- The customer stated a maximum antenna gain of -2.1 dBi. As the limit is an ERP limit, the gain in dBi has been converted to dBd. The dBd was calculated as:

$$-2.1 \text{ dBi} - 2.15 \text{ dB} = -4.25 \text{ dBd}.$$
- The antenna gain was added to the conducted output power to obtain the ERP.

Results: Peak ERP / HSDPA and Voice

Modes		HSDPA				Voice			
Sub-test		1	2	3	4	12.2 kbps			
Band	Channel	Power (dBm)	Power (dBm)	Power (dBm)	Power (dBm)	Power (dBm)	Limit (dBm)	Margin (dB)	Result
850	4132	22.0	23.8	23.8	23.8	22.3	38.5	14.7	Complied
	4183	22.1	23.4	23.3	23.3	22.5	38.5	15.1	Complied
	4233	22.4	23.4	23.5	23.5	22.6	38.5	15.0	Complied
βc		2	11	15	15				
βd		15	15	8	4				
ΔACK, ΔNACK, ΔCQI		8	8	8	8				

Transmitter Effective Radiated Power (ERP) (continued)**Results: RMS ERP / HSDPA and Voice**

Modes		HSDPA				Voice			
Sub-test		1	2	3	4	12.2 kbps			
Band	Channel	Power (dBm)	Power (dBm)	Power (dBm)	Power (dBm)	Power (dBm)	Limit (dBm)	Margin (dB)	Result
850	4132	16.5	16.5	16.6	16.5	17.0	38.5	21.5	Complied
	4183	16.6	16.8	16.7	16.8	17.0	38.5	21.5	Complied
	4233	16.7	16.9	16.7	16.9	17.2	38.5	21.3	Complied
β_c		2	11	15	15				
β_d		15	15	8	4				
$\Delta ACK, \Delta NACK, \Delta CQI$		8	8	8	8				

Results: Peak ERP / HSUPA

Modes		HSUPA							
Sub-test		1	2	3	4	5			
Band	Channel	Power (dBm)	Power (dBm)	Power (dBm)	Power (dBm)	Power (dBm)	Limit (dBm)	Margin (dB)	Result
850	4132	23.5	22.9	23.6	22.1	23.6	38.5	14.9	Complied
	4183	23.3	23.0	23.4	22.0	23.4	38.5	15.1	Complied
	4233	23.5	23.0	23.5	22.4	23.5	38.5	15.0	Complied
β_c		10	6	15	2	15			
β_d		15	15	9	15	1			
$\Delta ACK, \Delta NACK, \Delta CQI$		8	8	8	8	8			

Results: RMS ERP / HSUPA

Modes		HSUPA							
Sub-test		1	2	3	4	5			
Band	Channel	Power (dBm)	Power (dBm)	Power (dBm)	Power (dBm)	Power (dBm)	Limit (dBm)	Margin (dB)	Result
850	4132	16.5	16.5	16.5	16.6	16.7	38.5	21.8	Complied
	4183	16.6	16.7	16.8	16.6	16.6	38.5	21.7	Complied
	4233	16.7	16.8	16.8	16.7	16.7	38.5	21.7	Complied
β_c		10	6	15	2	15			
β_d		15	15	9	15	1			
$\Delta ACK, \Delta NACK, \Delta CQI$		8	8	8	8	8			

Transmitter Effective Radiated Power (ERP) (continued)**Test Equipment Used:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1658	Thermohygrometer	JMHandelspunkt	30.5015.13	None stated	14 Mar 2015	12
A2533	Directional Coupler	Atlan TecRF	CDC-003060-20	14041701717	Calibrated before use	-
A2525	Attenuator	Atlan TecRF	AN18W5-10	832827#3	Calibrated before use	-
L1138	Signal Analyser	Rohde & Schwarz	FSV13.6	101389	17 Apr 2015	12
M1229	Multimeter	Fluke	179	87640015	24 Apr 2015	12
S0558	DC Power Supply	TTI	EL303R	395825	Calibrated before use	-

5.2.2. Transmitter Occupied Bandwidth**Test Summary:**

Test Engineer:	David Doyle	Test Date:	08 July 2014
Test Sample IMEI:	004402452695228		

FCC Reference:	Part 2.1049
Test Method Used:	As detailed in KBD 971168 Section 4.2

Environmental Conditions:

Temperature (C):	22
Relative Humidity (%):	48


Note(s):

1. Occupied bandwidth (99% bandwidth) was measured using a signal analyser occupied bandwidth function.
2. The signal analyser was connected to the RF port on the EUT using suitable attenuation and RF cable.

Transmitter Occupied Bandwidth (continued)

Results: Voice / 12.2 kbps

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	836.6	4177.424



Middle Channel

Transmitter Occupied Bandwidth (continued)

Results: HSDPA Sub-Test 1

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	836.6	4162.663




Middle Channel

Transmitter Occupied Bandwidth (continued)

Results: HSDPA Sub-Test 2

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	836.6	4162.663




Middle Channel

Transmitter Occupied Bandwidth (continued)

Results: HSDPA Sub-Test 3

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	836.6	4162.663




Middle Channel

Transmitter Occupied Bandwidth (continued)

Results: HSDPA Sub-Test 4

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	836.6	4162.663




Middle Channel

Transmitter Occupied Bandwidth (continued)

Results: HSUPA Sub-Test 1

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	836.6	4162.663




Middle Channel

Transmitter Occupied Bandwidth (continued)

Results: HSUPA Sub-Test 2

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	836.6	4162.663




Middle Channel

Transmitter Occupied Bandwidth (continued)

Results: HSUPA Sub-Test 3

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	836.6	4162.663




Middle Channel

Transmitter Occupied Bandwidth (continued)

Results: HSUPA Sub-Test 4

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	836.6	4162.663




Middle Channel

Transmitter Occupied Bandwidth (continued)

Results: HSUPA Sub-Test 5

Channel	Frequency (MHz)	Occupied Bandwidth (kHz)
Middle	836.6	4177.424



Middle Channel

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1658	Thermohygrometer	JM Handelpunkt	30.5015.13	None stated	14 Mar 2015	12
A2533	Directional Coupler	Atlan TecRF	CDC-003060-20	14041701717	Calibrated before use	-
A2525	Attenuator	Atlan TecRF	AN18W5-10	832827#3	Calibrated before use	-
L1138	Signal Analyser	Rohde & Schwarz	FSV13.6	101389	17 Apr 2015	12
M1229	Multimeter	Fluke	179	87640015	24 Apr 2015	12
S0558	DC Power Supply	TTI	EL303R	395825	Calibrated before use	-

5.2.3. Transmitter Out of Band Radiated Emissions**Test Summary:**

Test Engineers:	Georgios Vrezas & David Doyle	Test Date:	07 July 2014
Test Sample IMEIs:	004402452693934 & 004402452692654		

FCC Reference:	Parts 2.1053 & 22.917
Test Method Used:	As detailed in KDB 971168 Section 6.1 referencing FCC Part 2.1053
Frequency Range:	30 MHz to 9 GHz
Configuration:	Voice / 12.2 kbps

Environmental Conditions:

Temperature (C):	23 to 25
Relative Humidity (%):	31 to 38





Note(s):


1. The uplink traffic channel is shown on the 30 MHz to 1 GHz plot.
2. No spurious emissions were detected above the noise floor of the measuring receiver; the highest peak noise floor reading of the measuring receiver was recorded.
3. Measurements below 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.
4. Pre-scans above 1 GHz were performed in a fully anechoic chamber (Asset Number K0002) at a distance of 3 metres. The EUT was placed at a height of 1.5 metres above the test chamber floor in the centre of the chamber turntable. All measurement antennas were placed at a fixed height of 1.5 metres above the test chamber floor, in line with the EUT. Final measurements above 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.

Results: Voice / 12.2 kbps - Top Channel

Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Margin (dB)	Result
3783.567	-35.9	-13.0	22.9	Complied

Transmitter Out of Band Radiated Emissions (continued)



Transmitter Out of Band Radiated Emissions (continued)**Test Equipment Used:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1622	Thermohygrometer	JMHandelspunkt	30.5015.06	None stated	31 Dec 2014	12
K0001	5m RSE Chamber	Rainford EMC	N/A	N/A	26 Nov 2014	12
M1273	Test Receiver	Rohde & Schwarz	ESIB 26	100275	15 Feb 2015	12
G0543	Amplifier	Sonoma	310N	230801	19 Aug 2014	3
A490	Antenna	Chase	CBL6111A	1590	29 Apr 2015	12
A1834	Attenuator	Hewlett Packard	8491B	10444	15 Nov 2014	12
A1393	Attenuator	Huber & Suhner	6820.17.B	757456	02 May 2015	12
M1656	Thermohygrometer	JMHandelspunkt	30.5015.13	None stated	14 Mar 2015	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	14 Nov 2014	12
M1124	Test Receiver	Rohde & Schwarz	ESIB 26	100046K	01 Oct 2014	12
A1534	Pre Amplifier	Hewlett Packard	8449B	3008A00405	18 May 2015	12
A1396	Attenuator	Huber & Suhner	6810.17.B	757987	02 May 2015	12
A148	High Pass Filter	AtlanTechRF	5H036	32218	17 May 2015	12
A1818	Antenna	EMCO	3115	00075692	14 Nov 2014	12
A253	Antenna	Flann Microwave	12240-20	128	14 Nov 2014	12
A254	Antenna	Flann Microwave	14240-20	139	14 Nov 2014	12
A255	Antenna	Flann Microwave	16240-20	519	14 Nov 2014	12

5.2.4. Transmitter Band Edge Radiated Emissions

Test Summary:

Test Engineer:	David Doyle	Test Date:	07 July 2014
Test Sample IMEI:	004402452692654		



FCC Reference:	Parts 2.1053 & 22.917
Test Method Used:	As detailed in KDB 971168 Section 6.1 referencing FCC Part 22.917

Environmental Conditions:

Temperature (C):	23
Relative Humidity (%):	38

Results: Voice / 12.2 kbps



Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	-33.8	-13.0	20.8	Complied
849	-26.3	-13.0	13.3	Complied



Transmitter Band Edge Radiated Emissions (continued)

Results: HSDPA Sub-Test 1



Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	-35.7	-13.0	22.7	Complied
849	-26.3	-13.0	13.3	Complied



Transmitter Band Edge Radiated Emissions (continued)

Results: HSDPA Sub-Test 2



Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	-35.7	-13.0	22.7	Complied
849	-26.3	-13.0	13.3	Complied



Transmitter Band Edge Radiated Emissions (continued)

Results: HSDPA Sub-Test 3



Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	-35.7	-13.0	22.7	Complied
849	-27.1	-13.0	14.1	Complied
849.152	-26.3	-13.0	13.3	Complied



Transmitter Band Edge Radiated Emissions (continued)

Results: HSDPA Sub-Test 4



Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	-35.7	-13.0	22.7	Complied
849	-27.1	-13.0	14.1	Complied



Transmitter Band Edge Radiated Emissions (continued)

Results: HSUPA Sub-Test 1



Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	-35.7	-13.0	22.7	Complied
849	-26.3	-13.0	13.3	Complied



Transmitter Band Edge Radiated Emissions (continued)

Results: HSUPA Sub-Test 2



Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	-35.7	-13.0	22.7	Complied
849	-26.3	-13.0	13.3	Complied



Transmitter Band Edge Radiated Emissions (continued)

Results: HSUPA Sub-Test 3



Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	-35.7	-13.0	22.7	Complied
849	-27.1	-13.0	14.1	Complied
849.192	-26.3	-13.0	13.3	Complied



Transmitter Band Edge Radiated Emissions (continued)

Results: HSUPA Sub-Test 4



Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	-35.7	-13.0	22.7	Complied
849	-26.3	-13.0	13.3	Complied



Transmitter Band Edge Radiated Emissions (continued)

Results: HSUPA Sub-Test 5

Frequency (MHz)	Peak Level (dBm)	Limit (dBm)	Margin (dB)	Result
824	-35.7	-13.0	22.7	Complied
849	-27.1	-13.0	14.1	Complied



Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1656	Thermohygrometer	JMHandelspunkt	30.5015.13	None stated	14 Mar 2015	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	14 Nov 2014	12
M1124	Test Receiver	Rohde & Schwarz	ESIB 26	100046K	01 Oct 2014	12
A1393	Attenuator	Huber & Suhner	6820.17.B	757456	02 May 2015	12
A288	Antenna	Chase	CBL6111A	1589	20 Aug 2014	12

5.2.5. Transmitter Frequency Stability (Temperature Variation)**Test Summary:**

Test Engineer:	Keith Tucker	Test Date:	07 July 2014
Test Sample IMEI:	004402452695228		

FCC Reference:	Parts 2.1055 & 22.355
Test Method Used:	As detailed in KDB 971168 Section 9.0 referencing ANSI TIA-603-C-2004 Section 2.2.2 and FCC Part 2.1055

Environmental Conditions:

Ambient Temperature (C):	26
Ambient Relative Humidity (%):	38

Note(s):

1. A voltage variation jig was connected to the EUT which was powered via a bench power supply at the nominal voltage of 3.8V.
2. Frequency error was measured using a calibrated Rohde & Schwarz CMW 500 Universal Radio Communications Tester in accordance with current Rohde & Schwarz application notes. The EUT was connected by suitable RF cables to the CMW 500. A bi-directional communications link was established between the EUT and CMW 500. The frequency meter value was recorded.
3. Temperature was monitored throughout the test with a calibrated digital thermometer.

Results: Middle Channel (836.6 MHz)

Temperature (°C)	Measured Frequency (MHz)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	Margin (ppm)	Result
-30	836.599997	3	0.0036	2.5	2.4964	Complied
-20	836.599996	4	0.0048	2.5	2.4952	Complied
-10	836.599996	4	0.0048	2.5	2.4952	Complied
0	836.599997	3	0.0036	2.5	2.4964	Complied
10	836.599997	3	0.0036	2.5	2.4964	Complied
20	836.599996	4	0.0048	2.5	2.4952	Complied
30	836.599997	3	0.0036	2.5	2.4964	Complied
40	836.599997	3	0.0036	2.5	2.4964	Complied
50	836.599996	4	0.0048	2.5	2.4952	Complied

Transmitter Frequency Stability (Temperature Variation) (continued)**Test Equipment Used:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1659	Thermohygrometer	JM Handelpunkt	30.5015.13	None stated	14 Mar 2015	12
M1870	Wideband Radio Comms Tester	Rohde & Schwarz	CMW500	145919	05 May 2015	12
S021	Dual DC power supply	TTi	CPX200	061034	Calibrated before use	-
M1251	Multimeter	Fluke	175	89170179	19 May 2015	12
M1249	Thermometer	Fluke	52II	88800049	02 May 2015	12
E0513	Environmental Chamber	TAS	LT600 Series 3	23900506	Calibration before use	-

5.2.6. Transmitter Frequency Stability (Voltage Variation)**Test Summary:**

Test Engineer:	Keith Tucker	Test Date:	07 July 2014
Test Sample IMEI:	004402452695228		

FCC Reference:	Parts 2.1055 & 22.355
Test Method Used:	As detailed in KDB 971168 Section 9.0 referencing ANSI TIA-603-C-2004 Section 2.2.2 and FCC Part 2.1055

Environmental Conditions:

Temperature (C):	26
Relative Humidity (%):	38

Note(s):

1. A voltage variation jig was connected to the EUT which was powered via a bench power supply.
2. Frequency error was measured using a calibrated Rohde & Schwarz CMW 500 Universal Radio Communications Tester in accordance with current Rohde & Schwarz application notes. The EUT was connected by suitable RF cables to the CMW 500. A bi-directional communications link was established between the EUT and CMW 500. The frequency meter value was recorded.
3. Voltage was monitored throughout the test with a calibrated digital voltmeter.

Results: Middle Channel (836.6 MHz)

Supply Voltage (V)	Measured Frequency (MHz)	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	Margin (ppm)	Result
3.42	836.599997	3	0.0036	2.5	2.4964	Complied
4.18	836.599997	3	0.0036	2.5	2.4964	Complied

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1659	Thermohygrometer	JMHandelspunkt	30.5015.13	None stated	14 Mar 2015	12
M1870	Wideband Radio Comms Tester	Rohde & Schwarz	CMW500	145919	05 May 2015	12
S021	Dual DC power supply	TTi	CPX200	061034	Calibrated before use	-
M1251	Multimeter	Fluke	175	89170179	19 May 2015	12

6.Measurement Uncertainty

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value of the measurand (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
Conducted Output Power	824 to 849 MHz	95%	±1.13 dB
Frequency Stability	824 to 849 MHz	95%	±23 Hz
Occupied Bandwidth	824 to 849 MHz	95%	±3.92 %
Radiated Spurious Emissions	30 MHz to 1 GHz	95%	±5.65 dB
Radiated Spurious Emissions	1 GHz to 9 GHz	95%	±2.94 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

7. Report Revision History

Version Number	Revision Details		
	Page No(s)	Clause	Details
1.0	-	-	Initial Version
2.0	-	-	EUT Description update

--- END OF REPORT ---