



**FCC PART 15  
TEST REPORT  
No. I14Z47255-SRD08**

**for**

**Sony Mobile Communications Inc.**

**GSM/WCDMA/LTE mobile phone**

**With**

**FCC ID: PY7PM-0808**

**Hardware Version: A**

**Software Version: 23.0.F.0.56**

**Issued Date: 2014-08-21**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

**Test Laboratory:**

TMC Beijing, Telecommunication Metrology Center of Ministry of Industry and Information Technology

No. 52, Huayuan Bei Road, Haidian District, Beijing, P.R.China 100191

Tel: +86(0)10-62304633-2561, Fax: +86(0)10-62304633-2504 Email:welcome@emcite.com. [www.emcite.com](http://www.emcite.com)

## **CONTENTS**

<b>CONTENTS .....</b>	<b>2</b>
<b>1. TEST LATORATORY .....</b>	<b>8</b>
1.1. TESTING LOCATION .....	8
1.2. PROJECT DATA .....	8
1.3. SIGNATURE .....	8
<b>2. CLIENT INFORMATION.....</b>	<b>9</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>9</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>9</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT(AE) .....</b>	<b>10</b>
3.1. ABOUT EUT .....	10
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	10
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....	10
3.4. GENERAL DESCRIPTION.....	10
<b>4. REFERENCE DOCUMENTS.....</b>	<b>11</b>
4.1. DOCUMENTS SUPPLIED BY APPLICANT .....	11
4.2. REFERENCE DOCUMENTS FOR TESTING.....	11
<b>5. LABORATORY ENVIRONMENT.....</b>	<b>11</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>12</b>
6.1. SUMMARY OF TEST RESULTS.....	12
6.2. STATEMENTS.....	12
6.3. TEST CONDITIONS .....	12
<b>7. TEST EQUIPMENTS UTILIZED .....</b>	<b>13</b>
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>14</b>
A.1. MEASUREMENT METHOD .....	14
A.2. MAXIMUM OUTPUT POWER .....	15
A.2.1. OUTPUT POWER VERIFICATION .....	15
A.2.2. ANTENNA GAIN.....	16
A.2.3. MAXIMUM OUTPUT POWER.....	16
A.3. PEAK POWER SPECTRAL DENSITY (CONDUCTED).....	18
A.4. OCCUPIED 26dB BANDWIDTH(CONDUCTED).....	19
FIG. 1 OCCUPIED 26dB BANDWIDTH (802.11A, 5180MHZ) .....	20
FIG. 2 OCCUPIED 26dB BANDWIDTH (802.11A, 5200MHZ) .....	20
FIG. 3 OCCUPIED 26dB BANDWIDTH (802.11A, 5240MHZ) .....	21
FIG. 4 OCCUPIED 26dB BANDWIDTH (802.11A, 5260MHZ) .....	21
FIG. 5 OCCUPIED 26dB BANDWIDTH (802.11A, 5280MHZ) .....	22
FIG. 6 OCCUPIED 26dB BANDWIDTH (802.11A, 5320MHZ) .....	22

FIG. 7	OCCUPIED 26dB BANDWIDTH (802.11A, 5500MHZ) .....	23
FIG. 8	OCCUPIED 26dB BANDWIDTH (802.11A, 5580MHZ) .....	23
FIG. 9	OCCUPIED 26dB BANDWIDTH (802.11A, 5700MHZ) .....	24
FIG. 10	OCCUPIED 26dB BANDWIDTH (802.11N-HT20, 5180MHZ).....	24
FIG. 11	OCCUPIED 26dB BANDWIDTH (802.11N-HT20, 5200MHZ).....	25
FIG. 12	OCCUPIED 26dB BANDWIDTH (802.11N-HT20, 5240MHZ).....	25
FIG. 13	OCCUPIED 26dB BANDWIDTH (802.11N-HT20, 5260MHZ).....	26
FIG. 14	OCCUPIED 26dB BANDWIDTH (802.11N-HT20, 5280MHZ).....	26
FIG. 15	OCCUPIED 26dB BANDWIDTH (802.11N-HT20, 5320MHZ).....	27
FIG. 16	OCCUPIED 26dB BANDWIDTH (802.11N-HT20, 5500MHZ).....	27
FIG. 17	OCCUPIED 26dB BANDWIDTH (802.11N-HT20, 5580MHZ).....	28
FIG. 18	OCCUPIED 26dB BANDWIDTH (802.11N-HT20, 5700MHZ).....	28
FIG. 19	OCCUPIED 26dB BANDWIDTH (802.11N-HT40, 5190MHZ).....	29
FIG. 20	OCCUPIED 26dB BANDWIDTH (802.11N-HT40, 5230MHZ).....	29
FIG. 21	OCCUPIED 26dB BANDWIDTH (802.11N-HT40, 5270MHZ).....	30
FIG. 22	OCCUPIED 26dB BANDWIDTH (802.11N-HT40, 5310MHZ).....	30
FIG. 23	OCCUPIED 26dB BANDWIDTH (802.11N-HT40, 5510MHZ).....	31
FIG. 24	OCCUPIED 26dB BANDWIDTH (802.11N-HT40, 5550MHZ).....	31
FIG. 25	OCCUPIED 26dB BANDWIDTH (802.11N-HT40, 5670MHZ).....	32
FIG. 26	OCCUPIED 26dB BANDWIDTH (802.11AC-HT80, 5210MHZ).....	32
FIG. 27	OCCUPIED 26dB BANDWIDTH (802.11AC-HT80, 5290MHZ).....	33
FIG. 28	OCCUPIED 26dB BANDWIDTH (802.11AC-HT80, 5530MHZ).....	33
A.5. BAND EDGES COMPLIANCE .....		34
A5.1 BAND EDGES - CONDUCTED.....		34
FIG. 29	BAND EDGES (802.11A, 5180MHZ) .....	35
FIG. 30	BAND EDGES (802.11A, 5320MHZ) .....	35
FIG. 31	BAND EDGES (802.11A, 5500MHZ) .....	36
FIG. 32	BAND EDGES (802.11N-HT20, 5180MHZ).....	36
FIG. 33	BAND EDGES (802.11N-HT20, 5320MHZ).....	37
FIG. 34	BAND EDGES (802.11N-HT20, 5500MHZ).....	37
FIG. 35	BAND EDGES (802.11N-HT40, 5190MHZ).....	38
FIG. 36	BAND EDGES (802.11N-HT40, 5310MHZ).....	38
FIG. 37	BAND EDGES (802.11N-HT40, 5510MHZ).....	39
FIG. 38	BAND EDGES (802.11AC-HT80, 5210MHZ).....	39
FIG. 39	BAND EDGES (802.11AC-HT80, 5290MHZ).....	40
FIG. 40	BAND EDGES (802.11AC-HT80, 5530MHZ).....	40
A5.2 BAND EDGES - RADIATED.....		41
FIG. 41	BAND EDGES (802.11A, 5180MHZ) .....	42
FIG. 42	BAND EDGES (802.11A, 5320MHZ) .....	42
FIG. 43	BAND EDGES (802.11A, 5550MHZ) .....	43
FIG. 44	BAND EDGES (802.11N-HT20, 5180MHZ).....	43
FIG. 45	BAND EDGES (802.11N-HT20, 5320MHZ).....	44
FIG. 46	BAND EDGES (802.11N-HT20, 5500MHZ).....	44
FIG. 47	BAND EDGES (802.11N-HT40, 5190MHZ).....	45

FIG. 48	BAND EDGES (802.11N-HT40, 5310MHZ).....	45
FIG. 49	BAND EDGES (802.11N-HT40, 5510MHZ).....	46
FIG. 50	BAND EDGES (802.11AC-HT80, 5210MHZ).....	46
FIG. 51	BAND EDGES (802.11AC-HT80, 5290MHZ).....	47
FIG. 52	BAND EDGES (802.11AC-HT80, 5530MHZ).....	47
A.6. TRANSMITTER SPURIOUS EMISSION .....		48
FIG. 53	RADIATED SPURIOUS EMISSION (802.11A, CH36, 1 GHZ-6 GHZ).....	53
FIG. 54	RADIATED SPURIOUS EMISSION (802.11A, CH36, 6 GHZ-18 GHZ).....	53
FIG. 55	RADIATED SPURIOUS EMISSION (802.11A, CH40, 30 MHZ-1 GHZ).....	54
FIG. 56	RADIATED SPURIOUS EMISSION (802.11A, CH40, 1 GHZ-6 GHZ).....	54
FIG. 57	RADIATED SPURIOUS EMISSION (802.11A, CH40, 6 GHZ-18 GHZ).....	55
FIG. 58	RADIATED SPURIOUS EMISSION (802.11A, CH40, 18 GHZ-26.5 GHZ).....	55
FIG. 59	RADIATED SPURIOUS EMISSION (802.11A, CH40, 26.5 GHZ-40 GHZ).....	56
FIG. 60	RADIATED SPURIOUS EMISSION (802.11A, CH48, 1 GHZ-6 GHZ).....	56
FIG. 61	RADIATED SPURIOUS EMISSION (802.11A, CH48, 6 GHZ-18 GHZ).....	57
FIG. 62	RADIATED SPURIOUS EMISSION (802.11A, CH52, 1 GHZ-6 GHZ).....	57
FIG. 63	RADIATED SPURIOUS EMISSION (802.11A, CH52, 6 GHZ-18 GHZ).....	58
FIG. 64	RADIATED SPURIOUS EMISSION (802.11A, CH56, 30 MHZ-1 GHZ).....	58
FIG. 65	RADIATED SPURIOUS EMISSION (802.11A, CH56, 1 GHZ-6 GHZ).....	59
FIG. 66	RADIATED SPURIOUS EMISSION (802.11A, CH56, 6 GHZ-18 GHZ).....	59
FIG. 67	RADIATED SPURIOUS EMISSION (802.11A, CH56, 18 GHZ-26.5 GHZ).....	60
FIG. 68	RADIATED SPURIOUS EMISSION (802.11A, CH56, 26.5 GHZ-40 GHZ).....	60
FIG. 69	RADIATED SPURIOUS EMISSION (802.11A, CH64, 1 GHZ-6 GHZ).....	61
FIG. 70	RADIATED SPURIOUS EMISSION (802.11A, CH64, 6 GHZ-18 GHZ).....	61
FIG. 71	RADIATED SPURIOUS EMISSION (802.11A, CH100, 1 GHZ-6 GHZ).....	62
FIG. 72	RADIATED SPURIOUS EMISSION (802.11A, CH100, 6 GHZ-18 GHZ).....	62
FIG. 73	RADIATED SPURIOUS EMISSION (802.11A, CH120, 30 MHZ-1 GHZ).....	63
FIG. 74	RADIATED SPURIOUS EMISSION (802.11A, CH120, 1 GHZ-6 GHZ).....	63
FIG. 75	RADIATED SPURIOUS EMISSION (802.11A, CH120, 6 GHZ-18 GHZ).....	64
FIG. 76	RADIATED SPURIOUS EMISSION (802.11A, CH120, 18 GHZ-26.5 GHZ).....	64
FIG. 77	RADIATED SPURIOUS EMISSION (802.11A, CH120, 26.5 GHZ-40 GHZ).....	65
FIG. 78	RADIATED SPURIOUS EMISSION (802.11A, CH140, 1 GHZ-6 GHZ).....	65
FIG. 79	RADIATED SPURIOUS EMISSION (802.11A, CH140, 6 GHZ-18 GHZ).....	66
FIG. 80	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH36, 1 GHZ-6 GHZ).....	66
FIG. 81	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH36, 6 GHZ-18 GHZ).....	67
FIG. 82	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH40, 30 MHZ-1 GHZ).....	67
FIG. 83	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH40, 1 GHZ-6 GHZ).....	68
FIG. 84	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH40, 6 GHZ-18 GHZ).....	68
FIG. 85	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH40, 18 GHZ-26.5 GHZ).....	69
FIG. 86	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH40, 26.5 GHZ-40 GHZ).....	69
FIG. 87	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH48, 1 GHZ-6 GHZ).....	70
FIG. 88	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH48, 6 GHZ-18 GHZ).....	70
FIG. 89	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH52, 1 GHZ-6 GHZ).....	71
FIG. 90	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH52, 6 GHZ-18 GHZ).....	71

FIG. 91	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH56, 30 MHz-1 GHz) .....	72
FIG. 92	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH56, 1 GHz-6 GHz) .....	72
FIG. 93	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH56, 6 GHz-18 GHz) .....	73
FIG. 94	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH56, 18 GHz-26.5 GHz) .....	73
FIG. 95	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH56, 26.5 GHz-40 GHz) .....	74
FIG. 96	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH64, 1 GHz-6 GHz) .....	74
FIG. 97	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH64, 6 GHz-18 GHz) .....	75
FIG. 98	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH100, 1 GHz-6 GHz) .....	75
FIG. 99	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH100, 6 GHz-18 GHz) .....	76
FIG. 100	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH120, 30 MHz-1 GHz) .....	76
FIG. 101	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH120, 1 GHz-6 GHz) .....	77
FIG. 102	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH120, 6 GHz-18 GHz) .....	77
FIG. 103	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH120, 18 GHz-26.5 GHz) .....	78
FIG. 104	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH120, 26.5 GHz-40 GHz) .....	78
FIG. 105	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH140, 1 GHz-6 GHz) .....	79
FIG. 106	RADIATED SPURIOUS EMISSION (802.11N-HT20, CH140, 6 GHz-18 GHz) .....	79
FIG. 107	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH38, 30 MHz-1 GHz) .....	80
FIG. 108	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH38, 1 GHz-6 GHz) .....	80
FIG. 109	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH38, 6 GHz-18 GHz) .....	81
FIG. 110	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH38, 18 GHz-26.5 GHz) .....	81
FIG. 111	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH38, 26.5 GHz-40 GHz) .....	82
FIG. 112	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH46, 1 GHz-6 GHz) .....	82
FIG. 113	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH46, 6 GHz-18 GHz) .....	83
FIG. 114	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH54, 1 GHz-6 GHz) .....	83
FIG. 115	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH54, 6 GHz-18 GHz) .....	84
FIG. 116	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH54, 18 GHz-26.5 GHz) .....	84
FIG. 117	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH62, 30 MHz-1 GHz) .....	85
FIG. 118	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH62, 1 GHz-6 GHz) .....	85
FIG. 119	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH62, 6 GHz-18 GHz) .....	86
FIG. 120	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH102, 1 GHz-6 GHz) .....	86
FIG. 121	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH102, 6 GHz-18 GHz) .....	87
FIG. 122	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH118, 30 MHz-1 GHz) .....	87
FIG. 123	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH118, 1 GHz-6 GHz) .....	88
FIG. 124	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH118, 6 GHz-18 GHz) .....	88
FIG. 125	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH118, 18 GHz-26.5 GHz) .....	89
FIG. 126	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH134, 1 GHz-6 GHz) .....	89
FIG. 127	RADIATED SPURIOUS EMISSION (802.11N-HT40, CH134, 6 GHz-18 GHz) .....	90
FIG. 128	RADIATED SPURIOUS EMISSION (802.11AC-HT80, CH42, 1 GHz-6 GHz) .....	90
FIG. 129	RADIATED SPURIOUS EMISSION (802.11AC-HT80, CH42, 6 GHz-18 GHz) .....	91
FIG. 130	RADIATED SPURIOUS EMISSION (802.11AC-HT80, CH58, 30 MHz-1 GHz) .....	91
FIG. 131	RADIATED SPURIOUS EMISSION (802.11AC-HT80, CH58, 1 GHz-6 GHz) .....	92
FIG. 132	RADIATED SPURIOUS EMISSION (802.11AC-HT80, CH58, 6 GHz-18 GHz) .....	92
FIG. 133	RADIATED SPURIOUS EMISSION (802.11AC-HT80, CH58, 18 GHz-26.5 GHz) .....	93
FIG. 134	RADIATED SPURIOUS EMISSION (802.11AC-HT80, CH58, 26.5 GHz-40 GHz) .....	93

FIG. 135	RADIATED SPURIOUS EMISSION (802.11AC-HT80, CH106, 1 GHz-6 GHz).....	94
FIG. 136	RADIATED SPURIOUS EMISSION (802.11AC-HT80, CH106, 6 GHz-18 GHz).....	94
A.7.	SPURIOUS EMISSIONS RADIATED < 30MHZ.....	95
FIG. 137	RADIATED SPURIOUS EMISSION (802.11A, CH40, 9 kHz ~30 MHz).....	95
A.8.	CONDUCTED EMISSION (150kHz- 30MHZ).....	96
FIG. 138	CONDUCTED EMISSION(802.11A, CH40, TX).....	97
FIG. 139	CONDUCTED EMISSION(802.11A, IDLE).....	98
A.9.	PEAK EXCURSION.....	99
FIG. 140	PEAK EXCURSIONS (802.11A, CH36, PEAK).....	101
FIG. 141	PEAK EXCURSIONS (802.11A, CH40, PEAK).....	101
FIG. 142	PEAK EXCURSIONS (802.11A, CH48, PEAK).....	102
FIG. 143	PEAK EXCURSIONS (802.11A, CH36, AVERAGE).....	102
FIG. 144	PEAK EXCURSIONS (802.11A, CH40, AVERAGE).....	103
FIG. 145	PEAK EXCURSIONS (802.11A, CH48, AVERAGE).....	103
FIG. 146	PEAK EXCURSIONS (802.11A, CH52, PEAK).....	104
FIG. 147	PEAK EXCURSIONS (802.11A, CH56, PEAK).....	104
FIG. 148	PEAK EXCURSIONS (802.11A, CH64, PEAK).....	105
FIG. 149	PEAK EXCURSIONS (802.11A, CH52, AVERAGE).....	105
FIG. 150	PEAK EXCURSIONS (802.11A, CH56, AVERAGE).....	106
FIG. 151	PEAK EXCURSIONS (802.11A, CH64, AVERAGE).....	106
FIG. 152	PEAK EXCURSIONS (802.11A, CH100, PEAK).....	107
FIG. 153	PEAK EXCURSIONS (802.11A, CH116, PEAK).....	107
FIG. 154	PEAK EXCURSIONS (802.11A, CH140, PEAK).....	108
FIG. 155	PEAK EXCURSIONS (802.11A, CH100, AVERAGE).....	108
FIG. 156	PEAK EXCURSIONS (802.11A, CH116, AVERAGE).....	109
FIG. 157	PEAK EXCURSIONS (802.11A, CH140, AVERAGE).....	109
FIG. 158	PEAK EXCURSIONS (802.11N-HT20, CH36, PEAK).....	110
FIG. 159	PEAK EXCURSIONS (802.11N-HT20, CH40, PEAK).....	110
FIG. 160	PEAK EXCURSIONS (802.11N-HT20, CH48, PEAK).....	111
FIG. 161	PEAK EXCURSIONS (802.11N-HT20, CH36, AVERAGE).....	111
FIG. 162	PEAK EXCURSIONS (802.11N-HT20, CH40, AVERAGE).....	112
FIG. 163	PEAK EXCURSIONS (802.11N-HT20, CH48, AVERAGE).....	112
FIG. 164	PEAK EXCURSIONS (802.11N-HT20, CH52, PEAK).....	113
FIG. 165	PEAK EXCURSIONS (802.11N-HT20, CH56, PEAK).....	113
FIG. 166	PEAK EXCURSIONS (802.11N-HT20, CH64, PEAK).....	114
FIG. 167	PEAK EXCURSIONS (802.11N-HT20, CH52, AVERAGE).....	114
FIG. 168	PEAK EXCURSIONS (802.11N-HT20, CH56, AVERAGE).....	115
FIG. 169	PEAK EXCURSIONS (802.11N-HT20, CH64, AVERAGE).....	115
FIG. 170	PEAK EXCURSIONS (802.11N-HT20, CH100, PEAK).....	116
FIG. 171	PEAK EXCURSIONS (802.11N-HT20, CH116, PEAK).....	116
FIG. 172	PEAK EXCURSIONS (802.11N-HT20, CH140, PEAK).....	117
FIG. 173	PEAK EXCURSIONS (802.11N-HT20, CH100, AVERAGE).....	117
FIG. 174	PEAK EXCURSIONS (802.11N-HT20, CH116, AVERAGE).....	118
FIG. 175	PEAK EXCURSIONS (802.11N-HT20, CH140, AVERAGE).....	118

FIG. 176	PEAK EXCURSIONS (802.11N-HT40, CH38, PEAK) .....	119
FIG. 177	PEAK EXCURSIONS (802.11N-HT40, CH46, PEAK) .....	119
FIG. 178	PEAK EXCURSIONS (802.11N-HT40, CH54, PEAK) .....	120
FIG. 179	PEAK EXCURSIONS (802.11N-HT40, CH62, PEAK) .....	120
FIG. 180	PEAK EXCURSIONS (802.11N-HT40, CH38, AVERAGE) .....	121
FIG. 181	PEAK EXCURSIONS (802.11N-HT40, CH46, AVERAGE) .....	121
FIG. 182	PEAK EXCURSIONS (802.11N-HT40, CH54, AVERAGE) .....	122
FIG. 183	PEAK EXCURSIONS (802.11N-HT40, CH62, AVERAGE) .....	122
FIG. 184	PEAK EXCURSIONS (802.11N-HT40, CH102, PEAK).....	123
FIG. 185	PEAK EXCURSIONS (802.11N-HT40, CH110, PEAK).....	123
FIG. 186	PEAK EXCURSIONS (802.11N-HT40, CH134, PEAK).....	124
FIG. 187	PEAK EXCURSIONS (802.11N-HT40, CH102, AVERAGE) .....	124
FIG. 188	PEAK EXCURSIONS (802.11N-HT40, CH110, AVERAGE) .....	125
FIG. 189	PEAK EXCURSIONS (802.11N-HT40, CH134, AVERAGE) .....	125
FIG. 190	PEAK EXCURSIONS (802.11AC-HT80, CH42, PEAK) .....	126
FIG. 191	PEAK EXCURSIONS (802.11AC-HT80, CH58, PEAK) .....	126
FIG. 192	PEAK EXCURSIONS (802.11AC-HT80, CH106, PEAK) .....	127
FIG. 193	PEAK EXCURSIONS (802.11AC-HT80, CH42, AVERAGE) .....	127
FIG. 194	PEAK EXCURSIONS (802.11AC-HT80, CH58, AVERAGE) .....	128
FIG. 195	PEAK EXCURSIONS (802.11AC-HT80, CH106, AVERAGE) .....	128
A.10.	FREQUENCY STABILITY .....	129
A.11.	POWER CONTROL .....	129

## 1. TEST LATORATORY

### 1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MIIT  
Address: No 52 Hua Yuanbei Road, Haidian District, Beijing, P.R.China  
Postal Code: 100191  
Telephone: 008610623046332561  
Fax: 008610623046332504

### 1.2. Project data

Testing Start Date: 2014-07-23  
Testing End Date: 2014-08-18

### 1.3. Signature



---

Xu Zhongfei

(Prepared this test report)



---

Jiang Afang

(Reviewed this test report)



---

Xiao Li

Deputy Director of the laboratory

(Approved this test report)



## **2. CLIENT INFORMATION**

### **2.1. Applicant Information**

Company Name: Sony Mobile Communications (China) Co. Ltd  
Address /Post: Sony Mobile R&D Center, No. 16, Guangshun South Street,  
Chaoyang District  
City: Beijing  
Postal Code: 100102  
Country: China  
Contact Person: Ma, Gang  
Telephone: +86-10-58656312  
Fax: +86-10-58659049

### **2.2. Manufacturer Information**

Company Name: Sony Mobile Communications Inc.  
Address /Post: 1-8-15 Konan, Minato-ku, Tokyo, 108-0075, Japan  
City: Tokyo  
Postal Code: 108-0075  
Country: Japan

### 3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY

#### EQUIPMENT(AE)

##### 3.1. About EUT

Description	GSM, GPRS, EDGE,WCDMA FDD, HSDPA, HSUPA,LTE mobile phone
FCC ID	PY7PM-0808
WLAN Frequency Range	ISM Bands: -5150MHz~5250MHz -5250MHz~5350MHz -5470MHz~5725MHz
Type of modulation	OFDM
Antenna	Integral Antenna
Extreme vol. Limits	3.6VDC to 4.2VDC (nominal: 3.8VDC)

Note: Photographs of EUT are shown in ANNEX C of this test report. Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MIIT of People's Republic of China.

##### 3.2. Internal Identification of EUT used during the test

EUT ID*	S/N	IMEI	HW Version	SW Version
EUT1	CB5A1ZTFRY	004402452521432	A	23.0.F.0.56
EUT2	CB5A1ZTFTL	004402452521085	A	23.0.F.0.56

\*EUT ID: is used to identify the test sample in the lab internally.

##### 3.3. Internal Identification of AE used during the test

AE ID*	Description	Type	SN
AE1	Travel Charger	/	/
AE3	USB Cable	134912A21208328	AP1.0

\*AE ID: is used to identify the test sample in the lab internally.

##### 3.4. General Description

The Equipment Under Test (EUT) is a model of GSM/WCDMA/LTE Mobile Phone with integrated antenna and embedded battery.

It consists of normal options: USB cable and travel charger.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

#### **4. REFERENCE DOCUMENTS**

##### **4.1. Documents supplied by applicant**

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

##### **4.2. Reference Documents for testing**

The following documents listed in this section are referred for testing.

FCC Part15	Title 47 of the Code of Federal Regulations; Chapter I Part 15 - Radio frequency devices	2014
UNII: KDB 789033	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Subpart E	2014-06

#### **5. LABORATORY ENVIRONMENT**

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

## 6. SUMMARY OF TEST RESULTS

### 6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15E	Sub-clause of IC	Verdict
Maximum Output Power	15.407	/	<b>P</b>
Power Spectral Density	15.407	/	<b>P</b>
Occupied 26dB Bandwidth	15.403	/	<b>P</b>
Occupied 6dB Bandwidth	15.407	/	<b>P</b>
Band edge compliance	15.407	/	<b>P</b>
Transmitter spurious emissions radiated	15.407	/	<b>P</b>
Spurious emissions radiated < 30 MHz	15.407	/	<b>P</b>
Spurious emissions conducted < 30 MHz	15.407	/	<b>P</b>
Peak Excursion	15.407	/	<b>P</b>
Frequency Stability	15.407	/	<b>NA</b>
Transmit Power Control	15.407	/	<b>NA</b>

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by TMC
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

### 6.2. Statements

TMC has evaluated the test cases requested by the client/manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.1.

This report only deals with the WLAN function among the features described in section 3.

### 6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26°C
Voltage	3.8V
Humidity	44%

## 7. TEST EQUIPMENTS UTILIZED

### Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	2014-07-08	2015-07-07
2	Test Receiver	ESS	847151/015	Rohde & Schwarz	2013-11-29	2014-11-28
3	LISN	ESH2-Z5	829991/012	Rohde & Schwarz	2014-4-15	2015-4-14
4	Shielding Room	S81	/	ETS-Lindgren	/	/

### Radiated emission test system


No.	Equipment	Model	Serial Number	Manufacturer	Calibration date	Calibration Due date
1	Test Receiver	ESU26	100376	Rohde & Schwarz	2013-11-6	2014-11-5
2	BiLog Antenna	VULB9163	9163-514	Schwarzbeck	2011-11-11	2014-11-10
3	Dual-Ridge Waveguide Horn Antenna	3117	00119024	ETS-Lindgren	2014-4-20	2017-4-19
4	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2014-7-1	2017-06-30
5	Loop antenna	HFH2-Z2	829324/007	Rohde & Schwarz	2011-12-21	2014-12-20
6	Semi-anechoic chamber	/	CT000332-1074	Frankonia German	/	/

## ANNEX A: MEASUREMENT RESULTS

### A.1. Measurement Method

#### A.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer




#### A.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



The measurement is made according to KDB 789033

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

## A.2. Maximum output Power

### Measurement Limit and Method:

Standard	Frequency (MHz)	Limit (dBm)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	24dBm
	5250MHz~5350MHz	24dBm or 11+10logB
	5470MHz~5725MHz	24dBm or 11+10logB

Limit use the less value, and B is the 26dB bandwidth.

The measurement method SA-1 is made according to KDB 789033

### Measurement Uncertainty:

Measurement Uncertainty	0.75dB
-------------------------	--------

### A.2.1. Output Power Verification

This test is only for mode verification, and the selected mode will be used for the future measurement.

### Measurement Results:

OFDM/a mode	Maximum Conducted Power (dBm)							
data rate (Mbps)	6	9	12	18	24	36	48	54
36 (5180 MHz)	14.28	14.21	14.02	13.98	13.20	12.79	12.69	12.57

OFDM/n-HT20 mode	Maximum Conducted Power (dBm)							
data rate (Mbps)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
36 (5180 MHz)	13.18	13.03	12.86	12.83	12.81	12.68	12.61	12.52

OFDM/n-HT40 mode	Maximum Conducted Power (dBm)							
data rate (Index)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
38 (5190 MHz)	11.69	11.59	11.31	11.24	10.94	10.66	10.51	10.49

OFDM/ac-HT80 mode	Maximum Conducted Power (dBm)							
data rate (Index)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
42 (5210 MHz)	10.94	10.59	10.34	10.48	10.17	9.91	9.80	9.75

Selected data rate for all measurement:

OFDM /a-mode: 6Mbps

OFDM /n-HT20 mode: MCS0

OFDM /n-HT40 mode: MCS0

OFDM /ac-HT80 mode: MCS0

### A.2.2. Antenna Gain

The antenna gain of the complete system is calculated by the difference of radiated power and the conducted power of the EUT.

Band 5150MHz to 5350MHz,

Test	Channel			
	Low(5180MHz)	High(5240MHz)	Low(5260MHz)	High(5320MHz)
Tnom,Vnom				
<b>Conducted Power(dBm)</b>	19.68	19.74	19.52	19.37
<b>Radiated Power(dBm)</b>	10.61	11.29	12.36	14.01
<b>Gain(dBi)</b>	-9.07	-8.45	-7.16	-5.36

Band 5470MHz to 5725MHz,

Test	Channel		
	Low(5500MHz)	Middle(5600MHz)	High(5700MHz)
Tnom,Vnom			
<b>Conducted Power(dBm)</b>	18.55	19.38	19.31
<b>Radiated Power(dBm)</b>	13.81	12.71	12.49
<b>Gain(dBi)</b>	-4.74	-6.67	-6.82

Antenna Gain = Radiated value (with radiated sample) - Conducted values (with conducted samples)

### A.2.3. Maximum Output Power

#### Measurement Results:

#### 802.11a mode

Type	Test Result					
	5180MHz (Ch36)	5200MHz (Ch40)	5240MHz (Ch48)	5260MHz (Ch52)	5280MHz (Ch56)	5320 MHz (Ch64)
Conducted(dBm)	14.28	14.03	14.52	14.24	14.63	14.62
radiated(dBm)	5.21	4.96	6.07	7.08	7.47	9.26

Type	Test Result		
	5500MHz (Ch100)	5600MHz (Ch120)	5700MHz (Ch140)
conducted(dBm)	13.74	14.35	14.59
radiated(dBm)	9.00	7.29	7.77



**802.11n-HT20 mode**

Type	Test Result					
	5180MHz (Ch36)	5200MHz (Ch40)	5240MHz (Ch48)	5260MHz (Ch52)	5280MHz (Ch56)	5320 MHz (Ch64)
conducted(dBm)	13.18	13.06	13.57	13.18	13.68	13.58
radiated(dBm)	4.11	3.99	5.12	4.73	6.52	9.26

Type	Test Result		
	5500MHz (Ch100)	5600MHz (Ch120)	5700MHz (Ch140)
conducted(dBm)	12.79	13.21	13.72
radiated(dBm)	8.05	6.54	6.9

**802.11n-HT40 mode**

Type	Test Result			
	5190MHz (Ch38)	5230MHz (Ch46)	5270MHz (Ch54)	5310 MHz (Ch62)
conducted(dBm)	11.69	12.24	12.82	12.86
radiated(dBm)	2.62	3.79	5.66	7.5

Type	Test Result		
	5510MHz (Ch102)	5590MHz (Ch118)	5670MHz (Ch134)
conducted(dBm)	11.80	12.15	12.71
radiated(dBm)	7.06	5.48	5.89

**802.11ac-HT80 mode**

Type	Test Result		
	5210MHz (Ch42)	5290MHz (Ch58)	5530MHz (Ch106)
conducted(dBm)	10.94	11.21	10.95
radiated(dBm)	1.87	5.85	6.21

**Conclusion: PASS**

### A.3. Peak Power Spectral Density (conducted)

**Measurement Limit:**

Standard	Frequency (MHz)	Limit (dBm/MHz)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	11
	5250MHz~5350MHz	11
	5470MHz~5725MHz	11

The output power measurement method SA-1 is made according to KDB 789033

**Measurement Uncertainty:**

Measurement Uncertainty	0.75dB
-------------------------	--------

**Measurement Results:**

Mode	Channel	Power Spectral Density (dBm/MHz)	Conclusion
802.11a	5180 MHz	3.65	P
	5200 MHz	3.23	P
	5240 MHz	3.69	P
	5260 MHz	3.82	P
	5280 MHz	3.30	P
	5320 MHz	3.49	P
	5500 MHz	2.27	P
	5580 MHz	2.92	P
	5700 MHz	2.91	P
802.11n HT20	5180 MHz	3.25	P
	5200 MHz	3.10	P
	5240 MHz	3.33	P
	5260 MHz	3.27	P
	5280 MHz	3.05	P
	5320 MHz	2.99	P
	5500 MHz	1.50	P
	5600 MHz	1.50	P
	5700 MHz	1.73	P
802.11n HT40	5190 MHz	1.08	P
	5230 MHz	1.50	P
	5270 MHz	1.32	P
	5310 MHz	1.49	P
	5510 MHz	0.79	P
	5550 MHz	0.72	P
	5670 MHz	1.10	P
802.11ac HT80	5210 MHz	-1.97	P
	5290 MHz	-2.22	P
	5530 MHz	-2.47	P

**Conclusion: PASS**

#### A.4. Occupied 26dB Bandwidth(conducted)

##### Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.403 (i)	/

The measurement is made according to KDB 789033

##### Measurement Uncertainty:

Measurement Uncertainty	60.80Hz
-------------------------	---------

##### Measurement Result:

Mode	Channel	Occupied 26dB Bandwidth ( kHz)		conclusion
		Fig.	Value	
802.11a	5180 MHz	Fig.1	23397	P
	5200 MHz	Fig.2	23397	P
	5240 MHz	Fig.3	23558	P
	5260 MHz	Fig.4	23478	P
	5280 MHz	Fig.5	23237	P
	5320 MHz	Fig.6	23157	P
	5500 MHz	Fig.7	23478	P
	5580 MHz	Fig.8	23878	P
802.11n HT20	5180 MHz	Fig.10	23910	P
	5200 MHz	Fig.11	23958	P
	5240 MHz	Fig.12	23765	P
	5260 MHz	Fig.13	23866	P
	5280 MHz	Fig.14	23558	P
	5320 MHz	Fig.15	23397	P
	5500 MHz	Fig.16	23397	P
	5580 MHz	Fig.17	23558	P
802.11n HT40	5190 MHz	Fig.19	41680	P
	5230 MHz	Fig.20	41680	P
	5270 MHz	Fig.21	41840	P
	5310 MHz	Fig.22	41760	P
	5510 MHz	Fig.23	41360	P
	5590 MHz	Fig.24	41600	P
	5670 MHz	Fig.25	41280	P
802.11ac HT80	5210 MHz	Fig.26	81920	P
	5290 MHz	Fig.27	82240	P
	5530 MHz	Fig.28	82240	P

**Conclusion: PASS**

Test graphs as below:




Fig. 1 Occupied 26dB Bandwidth (802.11a, 5180MHz)






Fig. 2 Occupied 26dB Bandwidth (802.11a, 5200MHz)



**Fig. 3 Occupied 26dB Bandwidth (802.11a, 5240MHz)**



**Fig. 4 Occupied 26dB Bandwidth (802.11a, 5260MHz)**




Fig. 5 Occupied 26dB Bandwidth (802.11a, 5280MHz)




Fig. 6 Occupied 26dB Bandwidth (802.11a, 5320MHz)




Fig. 7 Occupied 26dB Bandwidth (802.11a, 5500MHz)




Fig. 8 Occupied 26dB Bandwidth (802.11a, 5580MHz)




Fig. 9 Occupied 26dB Bandwidth (802.11a, 5700MHz)




Fig. 10 Occupied 26dB Bandwidth (802.11n-HT20, 5180MHz)






Fig. 11 Occupied 26dB Bandwidth (802.11n-HT20, 5200MHz)




Fig. 12 Occupied 26dB Bandwidth (802.11n-HT20, 5240MHz)




Fig. 13 Occupied 26dB Bandwidth (802.11n-HT20, 5260MHz)




Fig. 14 Occupied 26dB Bandwidth (802.11n-HT20, 5280MHz)




Fig. 15 Occupied 26dB Bandwidth (802.11n-HT20, 5320MHz)




Fig. 16 Occupied 26dB Bandwidth (802.11n-HT20, 5500MHz)




Fig. 17 Occupied 26dB Bandwidth (802. 11n-HT20, 5580MHz)




Fig. 18 Occupied 26dB Bandwidth (802. 11n-HT20, 5700MHz)




Fig. 19 Occupied 26dB Bandwidth (802.11n-HT40, 5190MHz)




Fig. 20 Occupied 26dB Bandwidth (802.11n-HT40, 5230MHz)




Fig. 21 Occupied 26dB Bandwidth (802.11n-HT40, 5270MHz)




Fig. 22 Occupied 26dB Bandwidth (802.11n-HT40, 5310MHz)




Fig. 23 Occupied 26dB Bandwidth (802. 11n-HT40, 5510MHz)




Fig. 24 Occupied 26dB Bandwidth (802. 11n-HT40, 5550MHz)




Fig. 25 Occupied 26dB Bandwidth (802. 11n-HT40, 5670MHz)




Fig. 26 Occupied 26dB Bandwidth (802. 11ac-HT80, 5210MHz)






Fig. 27 Occupied 26dB Bandwidth (802.11ac-HT80, 5290MHz)




Fig. 28 Occupied 26dB Bandwidth (802.11ac-HT80, 5530MHz)

## A.5. Band Edges Compliance

### A5.1 Band Edges - conducted

#### Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.209	> 20

The measurement is made according to KDB 789033

#### Measurement Uncertainty:


Measurement Uncertainty	0.75dB
-------------------------	--------

#### Measurement Result:

Mode	Channel	Test Results	Conclusion
802.11a	5180 MHz	Fig.29	P
	5320 MHz	Fig.30	P
	5500 MHz	Fig.31	P
802.11n HT20	5180 MHz	Fig.32	P
	5320 MHz	Fig.33	P
	5500 MHz	Fig.34	P
802.11n HT40	5190 MHz	Fig.35	P
	5310 MHz	Fig.36	P
	5510 MHz	Fig.37	P
802.11ac HT80	5210 MHz	Fig.38	P
	5290 MHz	Fig.39	P
	5530 MHz	Fig.40	P


**Conclusion: PASS**

Test graphs as below:




Date: 18.AUG.2014 10:53:50

**Fig. 29 Band Edges (802.11a, 5180MHz)**




Date: 18.AUG.2014 11:08:38

**Fig. 30 Band Edges (802.11a, 5320MHz)**




Date: 18.AUG.2014 11:14:12

**Fig. 31 Band Edges (802.11a, 5500MHz)**




Date: 18.AUG.2014 10:55:04

**Fig. 32 Band Edges (802.11n-HT20, 5180MHz)**




Date: 18.AUG.2014 11:07:55

**Fig. 33 Band Edges (802.11n-HT20, 5320MHz)**




Date: 18.AUG.2014 11:15:03

**Fig. 34 Band Edges (802.11n-HT20, 5500MHz)**




Date: 18.AUG.2014 11:00:33

**Fig. 35 Band Edges (802.11n-HT40, 5190MHz)**




Date: 18.AUG.2014 11:06:27

**Fig. 36 Band Edges (802.11n-HT40, 5310MHz)**




Date: 18.AUG.2014 11:16:15

**Fig. 37 Band Edges (802.11n-HT40, 5510MHz)**




Date: 18.AUG.2014 11:03:01

**Fig. 38 Band Edges (802.11ac-HT80, 5210MHz)**



Date: 18.AUG.2014 11:05:27

**Fig. 39 Band Edges (802.11ac-HT80, 5290MHz)**



Date: 18.AUG.2014 11:16:15

**Fig. 40 Band Edges (802.11ac-HT80, 5530MHz)**



**A5.2 Band Edges - Radiated**

**Measurement Limit:**

Standard	Limit (dBc)
FCC 47 CFR Part 15.209	> 20

The measurement is made according to KDB 789033

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

**Measurement Uncertainty:**


Measurement Uncertainty	0.75dB
-------------------------	--------

**Measurement Result:**


Mode	Channel	Test Results	Conclusion
802.11a	5180 MHz	Fig.41	P
	5320 MHz	Fig.42	P
	5500 MHz	Fig.43	P
802.11n HT20	5180 MHz	Fig.44	P
	5320 MHz	Fig.45	P
	5500 MHz	Fig.46	P
802.11n HT40	5190 MHz	Fig.47	P
	5310 MHz	Fig.48	P
	5510 MHz	Fig.49	P
802.11ac HT80	5210 MHz	Fig.50	P
	5290 MHz	Fig.51	P
	5530 MHz	Fig.52	P

**Conclusion: PASS**

**Test graphs as below:**




**Fig. 41 Band Edges (802.11a, 5180MHz)**




**Fig. 42 Band Edges (802.11a, 5320MHz)**

RE-Power\_5.45G-5.5GHz




**Fig. 43 Band Edges (802.11a, 5550MHz)**


RE-Power\_5.125G-5.175GHz




**Fig. 44 Band Edges (802.11n-HT20, 5180MHz)**




**Fig. 45 Band Edges (802.11n-HT20, 5320MHz)**



**Fig. 46 Band Edges (802.11n-HT20, 5500MHz)**




**Fig. 47 Band Edges (802.11n-HT40, 5190MHz)**




**Fig. 48 Band Edges (802.11n-HT40, 5310MHz)**

RE-Power\_5.45G-5.5GHz




**Fig. 49 Band Edges (802.11n-HT40, 5510MHz)**


RE-Power\_5.125G-5.175GHz



**Fig. 50 Band Edges (802.11ac-HT80, 5210MHz)**



**Fig. 51 Band Edges (802.11ac-HT80, 5290MHz)**



**Fig. 52 Band Edges (802.11ac-HT80, 5530MHz)**

## A.6. Transmitter Spurious Emission

### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.407	-27 dBm/MHz

The measurement is made according to KDB 789033

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

### Limit in restricted band:

Frequency of emission (MHz)	Field strength(dBμV/m)	Measurement distance(m)
30-88	40.0	3
88-216	43.5	3
216-960	46.0	3
Above 960	54.0	3

Note: for frequency range below 960MHz, the limit in 15.209 is defined in 10m test distance. The limit used above is calculated from 10m to 3m

### Measurement uncertainty:

Expanded measurement uncertainty for this test item is U =3.9 dB, k=2.

### Measurement Results:



802.11a mode

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11a	36(5180MHz)	1 GHz ~ 6 GHz	Fig.53	P
		6 GHz ~ 18 GHz	Fig.54	P
	40(5200MHz)	30 MHz ~1 GHz	Fig.55	P
		1 GHz ~ 6 GHz	Fig.56	P
		6 GHz ~ 18 GHz	Fig.57	P
		18 GHz ~ 26.5 GHz	Fig.58	P
		26.5 GHz ~ 40 GHz	Fig.59	P
	48(5240MHz)	1 GHz ~ 6 GHz	Fig.60	P
		6 GHz ~ 18 GHz	Fig.61	P
	52(5260MHz)	1 GHz ~ 6 GHz	Fig.62	P
		6 GHz ~ 18 GHz	Fig.63	P
	56(5280MHz)	30 MHz ~1 GHz	Fig.64	P
		1 GHz ~ 6 GHz	Fig.65	P
		6 GHz ~ 18 GHz	Fig.66	P
		18 GHz ~ 26.5 GHz	Fig.67	P
		26.5 GHz ~ 40 GHz	Fig.68	P
	64(5320MHz)	1 GHz ~ 6 GHz	Fig.69	P
		6 GHz ~ 18 GHz	Fig.70	P
	100(5500MHz)	1 GHz ~ 6 GHz	Fig.71	P
		6 GHz ~ 18 GHz	Fig.72	P
	120(5600MHz)	30 MHz ~1 GHz	Fig.73	P
		1 GHz ~ 6 GHz	Fig.74	P
		6 GHz ~ 18 GHz	Fig.75	P
		18 GHz ~ 26.5 GHz	Fig.76	P
		26.5 GHz ~ 40 GHz	Fig.77	P
	140(5700MHz)	1 GHz ~ 6 GHz	Fig.78	P
		6 GHz ~ 18 GHz	Fig.79	P

**802.11n-HT20 mode**

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n -HT20	36(5180MHz)	1 GHz ~ 6 GHz	Fig.80	P
		6 GHz ~ 18 GHz	Fig.81	P
	40(5200MHz)	30 MHz ~1 GHz	Fig.82	P
		1 GHz ~ 6 GHz	Fig.83	P
		6 GHz ~ 18 GHz	Fig.84	P
		18 GHz ~ 26.5 GHz	Fig.85	P
	48(5240MHz)	26.5 GHz ~ 40 GHz	Fig.86	P
		1 GHz ~ 6 GHz	Fig.87	P
	52(5260MHz)	6 GHz ~ 18 GHz	Fig.88	P
		1 GHz ~ 6 GHz	Fig.89	P
	56(5280MHz)	6 GHz ~ 18 GHz	Fig.90	P
		30 MHz ~1 GHz	Fig.91	P
		1 GHz ~ 6 GHz	Fig.92	P
		6 GHz ~ 18 GHz	Fig.93	P
		18 GHz ~ 26.5 GHz	Fig.94	P
	64(5320MHz)	26.5 GHz ~ 40 GHz	Fig.95	P
		1 GHz ~ 6 GHz	Fig.96	P
	100(5500MHz)	6 GHz ~ 18 GHz	Fig.97	P
		1 GHz ~ 6 GHz	Fig.98	P
	120(5600MHz)	6 GHz ~ 18 GHz	Fig.99	P
		30 MHz ~1 GHz	Fig.100	P
		1 GHz ~ 6 GHz	Fig.101	P
		6 GHz ~ 18 GHz	Fig.102	P
		18 GHz ~ 26.5 GHz	Fig.103	P
	140(5700MHz)	26.5 GHz ~ 40 GHz	Fig.104	P
		1 GHz ~ 6 GHz	Fig.105	P
		6 GHz ~ 18 GHz	Fig.106	P

**802.11n-HT40 mode**

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11n HT40	38(5190MHz)	30 MHz ~1 GHz	Fig.107	P
		1 GHz ~ 6 GHz	Fig.108	P
		6 GHz ~ 18 GHz	Fig.109	P
		18 GHz ~ 26.5 GHz	Fig.110	P
		26.5 GHz ~ 40 GHz	Fig.111	P
	46(5230MHz)	1 GHz ~ 6 GHz	Fig.112	P
		6 GHz ~ 18 GHz	Fig.113	P
	54(5270MHz)	1 GHz ~ 6 GHz	Fig.114	P
		6 GHz ~ 18 GHz	Fig.115	P
		18 GHz ~ 26.5 GHz	Fig.116	P
	62(5310MHz)	30 MHz ~1 GHz	Fig.117	P
		1 GHz ~ 6 GHz	Fig.118	P
		6 GHz ~ 18 GHz	Fig.119	P
	102(5510MHz)	1 GHz ~ 6 GHz	Fig.120	P
		6 GHz ~ 18 GHz	Fig.121	P
	118(5590MHz)	30 MHz ~1 GHz	Fig.122	P
		1 GHz ~ 6 GHz	Fig.123	P
		6 GHz ~ 18 GHz	Fig.124	P
18 GHz ~ 26.5 GHz		Fig.125	P	
134(5670MHz)	1 GHz ~ 6 GHz	Fig.126	P	
	6 GHz ~ 18 GHz	Fig.127	P	

**802.11ac-HT80 mode**

Mode	Channel	Frequency Range	Test Results	Conclusion
802.11ac HT80	42(5210MHz)	1 GHz ~ 6 GHz	Fig.128	P
		6 GHz ~ 18 GHz	Fig.129	P
	58(5290MHz)	30 MHz ~1 GHz	Fig.130	P
		1 GHz ~ 6 GHz	Fig.131	P
		6 GHz ~ 18 GHz	Fig.132	P
		18 GHz ~ 26.5 GHz	Fig.133	P
		26.5 GHz ~ 40 GHz	Fig.134	P
	106(5530MHz)	1 GHz ~ 6 GHz	Fig.135	P
		6 GHz ~ 18 GHz	Fig.136	P

**Conclusion: PASS**

**Note:**

A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

$P_{Mea}$  is the field strength recorded from the instrument.

The measurement results are obtained as described below:

$$\text{Result} = P_{Mea} + A_{Rpl} = P_{Mea} + \text{Cable Loss} + \text{Antenna Factor}$$

**802.11a**

The worse case is measured in channel 56

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P <sub>Mea</sub> (dBuV/m)	Polarization
17985.000	55.5	-17.7	45.6	27.6	V
17961.000	54.9	-17.7	45.6	27.0	V
17953.500	54.9	-17.7	45.6	27.0	V
17997.000	54.6	-17.7	45.6	26.7	H
17991.000	54.6	-17.7	45.6	26.7	V
17989.500	54.5	-17.7	45.6	26.6	V

**802.11n-HT20**

The worse case is measured in channel 140

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P <sub>Mea</sub> (dBuV/m)	Polarization
17991.000	56.6	-17.7	45.6	28.7	V
17997.000	56.6	-17.7	45.6	28.7	V
17952.000	56.0	-17.7	45.6	28.1	V
17964.000	55.9	-17.7	45.6	28.0	V
17820.000	55.8	-18.5	45.6	28.7	V
17928.000	55.4	-17.7	45.6	27.5	V

**802.11n-HT40**

The worse case is measured in channel 62

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P <sub>Mea</sub> (dBuV/m)	Polarization
5354.830	54.4	-34.8	34.6	54.6	V
17995.500	55.9	-17.7	45.6	28.0	V
17997.000	55.4	-17.7	45.6	27.5	V
17998.500	55.2	-17.7	45.6	27.3	V
17959.500	55.2	-17.7	45.6	27.3	V
17920.500	55.1	-17.7	45.6	27.2	H

**802.11ac-HT80**

The worse case is measured in channel 58

Frequency(MHz)	Result (dBuV/m)	Cable Loss	Antenna Factor	P <sub>Mea</sub> (dBuV/m)	Polarization
5351.756	54.8	-34.8	34.6	55.000	V
17773.500	55.7	-18.5	45.6	28.600	V
17992.500	55.5	-17.7	45.6	27.600	H
17989.500	55.4	-17.7	45.6	27.500	V
17982.000	55.3	-17.7	45.6	27.400	V
18000.000	55.1	-17.7	44.5	28.300	V

Test graphs as below:




Fig. 53 Radiated Spurious Emission (802.11a, ch36, 1 GHz-6 GHz)







Fig. 54 Radiated Spurious Emission (802.11a, ch36, 6 GHz-18 GHz)




**Fig. 55 Radiated Spurious Emission (802.11a, ch40, 30 MHz-1 GHz)**




**Fig. 56 Radiated Spurious Emission (802.11a, ch40, 1 GHz-6 GHz)**




**Fig. 57 Radiated Spurious Emission (802.11a, ch40, 6 GHz-18 GHz)**



**Fig. 58 Radiated Spurious Emission (802.11a, ch40, 18 GHz-26.5 GHz)**




**Fig. 59 Radiated Spurious Emission (802.11a, ch40, 26.5 GHz-40 GHz)**




**Fig. 60 Radiated Spurious Emission (802.11a, ch48, 1 GHz-6 GHz)**







**Fig. 61 Radiated Spurious Emission (802.11a, ch48, 6 GHz-18 GHz)**




**Fig. 62 Radiated Spurious Emission (802.11a, ch52, 1 GHz-6 GHz)**




**Fig. 63 Radiated Spurious Emission (802.11a, ch52, 6 GHz-18 GHz)**




**Fig. 64 Radiated Spurious Emission (802.11a, ch56, 30 MHz-1 GHz)**




**Fig. 65 Radiated Spurious Emission (802.11a, ch56, 1 GHz-6 GHz)**




**Fig. 66 Radiated Spurious Emission (802.11a, ch56, 6 GHz-18 GHz)**




**Fig. 67 Radiated Spurious Emission (802.11a, ch56, 18 GHz-26.5 GHz)**




**Fig. 68 Radiated Spurious Emission (802.11a, ch56, 26.5 GHz-40 GHz)**




**Fig. 69 Radiated Spurious Emission (802.11a, ch64, 1 GHz-6 GHz)**




**Fig. 70 Radiated Spurious Emission (802.11a, ch64, 6 GHz-18 GHz)**




**Fig. 71 Radiated Spurious Emission (802.11a, ch100, 1 GHz-6 GHz)**




**Fig. 72 Radiated Spurious Emission (802.11a, ch100, 6 GHz-18 GHz)**




**Fig. 73 Radiated Spurious Emission (802.11a, ch120, 30 MHz-1 GHz)**



**Fig. 74 Radiated Spurious Emission (802.11a, ch120, 1 GHz-6 GHz)**




**Fig. 75 Radiated Spurious Emission (802.11a, ch120, 6 GHz-18 GHz)**




**Fig. 76 Radiated Spurious Emission (802.11a, ch120, 18 GHz-26.5 GHz)**







**Fig. 77 Radiated Spurious Emission (802.11a, ch120, 26.5 GHz-40 GHz)**




**Fig. 78 Radiated Spurious Emission (802.11a, ch140, 1 GHz-6 GHz)**




**Fig. 79 Radiated Spurious Emission (802.11a, ch140, 6 GHz-18 GHz)**




**Fig. 80 Radiated Spurious Emission (802.11n-HT20, ch36, 1 GHz-6 GHz)**




**Fig. 81 Radiated Spurious Emission (802.11n-HT20, ch36, 6 GHz-18 GHz)**




**Fig. 82 Radiated Spurious Emission (802.11n-HT20, ch40, 30 MHz-1 GHz)**




**Fig. 83 Radiated Spurious Emission (802.11n-HT20, ch40, 1 GHz-6 GHz)**



**Fig. 84 Radiated Spurious Emission (802.11n-HT20, ch40, 6 GHz-18 GHz)**



**Fig. 85 Radiated Spurious Emission (802.11n-HT20, ch40, 18 GHz-26.5 GHz)**



**Fig. 86 Radiated Spurious Emission (802.11n-HT20, ch40, 26.5 GHz-40 GHz)**




Fig. 87 Radiated Spurious Emission (802.11n-HT20, ch48, 1 GHz-6 GHz)




Fig. 88 Radiated Spurious Emission (802.11n-HT20, ch48, 6 GHz-18 GHz)