



FCC 47 CFR PART 15 SUBPART E

CERTIFICATION TEST REPORT

FOR

GSM/WCDMA/LTE + BLUETOOTH + DTS/UNII a/b/g/n/ac + ANT+ and NFC

FCC ID: PY7-PM0791

REPORT NUMBER: 15J20225-E5

ISSUE DATE: MAY 5, 2015

**Prepared for
SONY MOBILE COMMUNICATIONS, INC.
1-8-15 KONAN, MINATO-KU
TOKYO, 108-0075 JAPAN**

**Prepared by
UL VERIFICATION SERVICES INC.
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888**



NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	05/05/15	Initial Issue	CHOON OOI

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	7
2. TEST METHODOLOGY	8
3. FACILITIES AND ACCREDITATION	8
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. SAMPLE CALCULATION	8
4.3. MEASUREMENT UNCERTAINTY.....	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT	9
5.2. MAXIMUM OUTPUT POWER.....	9
5.3. DESCRIPTION OF AVAILABLE ANTENNAS	13
5.4. WORST-CASE CONFIGURATION AND MODE	15
5.5. DESCRIPTION OF TEST SETUP.....	16
6. TEST AND MEASUREMENT EQUIPMENT	18
7. SUMMARY TABLE	19
8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	20
8.1. ON TIME AND DUTY CYCLE RESULTS.....	20
8.2. DUTY CYCLE PLOTS	20
9. MEASUREMENT METHOD.....	21
10. ANTENNA PORT TEST RESULTS	22
10.1. 6 dB BANDWIDTH	22
10.1.1. 802.11a MODE IN THE 5.8 GHz BAND.....	22
10.1.2. 802.11n HT20 MODE IN THE 5.8 GHz BAND	22
10.1.3. 802.11n HT40 MODE IN THE 5.8 GHz BAND	22
10.1.4. 802.11ac HT80 MODE IN THE 5.8 GHz BAND	22
10.1.5. 802.11a MODE THE CHANNEL 144	22
10.1.6. 802.11n HT20 MODE THE CHANNEL 144.....	23
10.1.7. 802.11n HT40 MODE THE CHANNEL 142.....	23
10.1.8. 802.11ac HT80 MODE IN THE 5.8 GHz BAND	23
10.1.9. 6 dB BANDWIDTH MID CH PLOTS.....	23
10.2. 26 dB BANDWIDTH	24
10.2.1. 802.11a MODE IN THE 5.2 GHz BAND.....	24
10.2.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND	24
10.2.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND	24
10.2.4. 802.11ac HT80 MODE IN THE 5.2 GHz BAND	24
10.2.5. 802.11a MODE IN THE 5.3 GHz BAND.....	24

10.2.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	24
10.2.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	24
10.2.8.	802.11ac HT80 MODE IN THE 5.3 GHz BAND	24
10.2.9.	802.11a MODE IN THE 5.5 GHz BAND	25
10.2.10.	802.11n HT20 MODE IN THE 5.5 GHz BAND	25
10.2.11.	802.11n HT40 MODE IN THE 5.5 GHz BAND	25
10.2.12.	802.11ac HT80 MODE IN THE 5.5 GHz BAND	25
10.2.13.	802.11a MODE IN THE 5.8 GHz BAND	25
10.2.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	25
10.2.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	25
10.2.16.	802.11ac HT80 MODE IN THE 5.8 GHz BAND	25
10.2.17.	26 dB BANDWIDTH PLOTS	25
10.3.	99% BANDWIDTH	26
10.3.1.	802.11a MODE IN THE 5.2 GHz BAND	26
10.3.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	26
10.3.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	26
10.3.4.	802.11ac HT80 MODE IN THE 5.2 GHz BAND	26
10.3.5.	802.11a MODE IN THE 5.3 GHz BAND	26
10.3.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	26
10.3.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	26
10.3.8.	802.11ac HT80 MODE IN THE 5.3 GHz BAND	26
10.3.9.	802.11a MODE IN THE 5.5 GHz BAND	27
10.3.10.	802.11n HT20 MODE IN THE 5.5 GHz BAND	27
10.3.11.	802.11n HT40 MODE IN THE 5.5 GHz BAND	27
10.3.12.	802.11ac HT80 MODE IN THE 5.5 GHz BAND	27
10.3.13.	802.11a MODE IN THE 5.8 GHz BAND	27
10.3.14.	802.11n HT20 MODE IN THE 5.8 GHz BAND	27
10.3.15.	802.11n HT40 MODE IN THE 5.8 GHz BAND	27
10.3.16.	802.11ac HT80 MODE IN THE 5.8 GHz BAND	27
10.3.17.	99% BANDWIDTH PLOTS	27
10.4.	OUTPUT POWER AND PPSD	28
10.4.1.	802.11a MODE IN THE 5.2 GHz BAND	31
10.4.2.	802.11n HT20 MODE IN THE 5.2 GHz BAND	31
10.4.3.	802.11n HT40 MODE IN THE 5.2 GHz BAND	31
10.4.4.	802.11ac HT80 MODE IN THE 5.2 GHz BAND	31
10.4.5.	802.11a MODE IN THE 5.3 GHz BAND	31
10.4.6.	802.11n HT20 MODE IN THE 5.3 GHz BAND	31
10.4.7.	802.11n HT40 MODE IN THE 5.3 GHz BAND	31
10.4.8.	802.11ac HT80 MODE IN THE 5.3 GHz BAND	31
10.4.9.	802.11a MODE IN THE 5.5 GHz BAND	31
10.4.10.	802.11n HT20 MODE IN THE 5.5 GHz BAND	31
10.4.11.	802.11n HT40 MODE IN THE 5.5 GHz BAND	32
10.4.12.	802.11ac HT80 MODE IN THE 5.5 GHz BAND	32
10.4.13.	802.11a MODE STRADDLE CHANNEL 144	32
10.4.14.	802.11n HT20 MODE STRADDLE CHANNEL 144	32
10.4.15.	802.11n HT40 MODE STRADDLE CHANNEL 142	33
10.4.16.	802.11ac80 MODE STRADDLE CHANNEL 138	33
10.4.17.	802.11a MODE IN THE 5.8 GHz BAND	34
10.4.18.	802.11n HT20 MODE IN THE 5.8 GHz BAND	34
10.4.19.	802.11n HT40 MODE IN THE 5.8 GHz BAND	34
10.4.20.	802.11ac HT80 MODE IN THE 5.8 GHz BAND	34
10.4.21.	OUTPUT POWER AND PPSD PLOTS	34

11. TRANSMITTER ABOVE 1 GHz.....	35
11.1. 5.2 GHz.....	36
11.1.1. TX ABOVE 1 GHz 802.11a MODE IN THE 5.2 GHz BAND	36
11.1.2. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.2 GHz BAND.....	36
11.1.3. TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.2 GHz BAND.....	36
11.1.4. TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.2 GHz BAND.....	36
11.2. 5.3 GHz.....	36
11.2.1. TX ABOVE 1 GHz 802.11a MODE IN THE 5.3 GHz BAND	36
11.2.2. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.3 GHz BAND.....	36
11.2.3. TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.3 GHz BAND.....	36
11.2.4. TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.3 GHz BAND.....	36
11.3. 5.5-5.6 GHz.....	37
11.3.1. TX ABOVE 1 GHz 802.11a MODE IN THE 5.5 GHz BAND	37
11.3.2. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.5 GHz BAND.....	37
11.3.3. TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.5 GHz BAND.....	37
11.3.4. TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.5 GHz BAND.....	37
11.4. 5.8 GHz.....	37
11.4.1. TX ABOVE 1 GHz 802.11a MODE IN THE 5.8 GHz BAND	37
11.4.2. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.8 GHz BAND.....	37
11.4.3. TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.8 GHz BAND.....	37
11.4.4. TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.8 GHz BAND.....	37
12. WORST-CASE BELOW 1 GHz (in the 5.3 GHz Band).....	37
13. AC POWER LINE CONDUCTED EMISSIONS.....	38
14. DYNAMIC FREQUENCY SELECTION.....	39
14.1. OVERVIEW.....	39
14.1.1. LIMITS.....	39
14.1.2. TEST AND MEASUREMENT SYSTEM.....	43
14.1.3. SETUP OF EUT.....	46
14.1.4. DESCRIPTION OF EUT	47
14.2. RESULTS FOR 20 MHz BANDWIDTH.....	49
14.2.1. TEST CHANNEL	49
14.2.2. RADAR WAVEFORM AND TRAFFIC.....	49
14.2.3. OVERLAPPING CHANNEL TESTS.....	49
14.2.4. MOVE AND CLOSING TIME	49
14.3. RESULTS FOR 40 MHz BANDWIDTH.....	50
14.3.1. TEST CHANNEL	50
14.3.2. RADAR WAVEFORM AND TRAFFIC.....	50
14.3.3. OVERLAPPING CHANNEL TESTS.....	50
14.3.4. MOVE AND CLOSING TIME	50
14.3.5. 10-MINUTE BEACON MONITORING PERIOD	50
14.4. RESULTS FOR 80 MHz BANDWIDTH.....	51
14.4.1. TEST CHANNEL	51
14.4.2. RADAR WAVEFORM AND TRAFFIC.....	51
14.4.3. OVERLAPPING CHANNEL TESTS.....	51
14.4.4. MOVE AND CLOSING TIME	51
14.4.5. 10-MINUTE BEACON MONITORING PERIOD	52

15. SETUP PHOTOS.....	53
------------------------------	-----------

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SONY MOBILE COMMUNICATIONS, INC.

EUT DESCRIPTION: GSM/WCDMA/LTE + BLUETOOTH, DTS/UNII a/b/g/n/ac + ANT+ and NFC

SERIAL NUMBER: CB5A24D6BV (Radiated)

DATE TESTED: APRIL 24 – MAY 5, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 Part 15 Subpart E	Pass

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For
UL Verification Services Inc. By:

Tested By:



CHOON OOI
CONSUMER TECHNOLOGY DIVISION
PROJECT LEAD
UL Verification Services Inc.



CHARLES VERGONIO
CONSUMER TECHNOLOGY DIVISION
LAB ENGINEER
UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.4-2009. 789033 D02 General UNII Test Procedures New Rules v01

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
☒ Chamber A	☐ Chamber F
☐ Chamber B	☐ Chamber G
☒ Chamber C	☐ Chamber H

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://ts.nist.gov/standards/scopes/2000650.htm>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

$$\begin{aligned}\text{Field Strength (dBuV/m)} &= \text{Measured Voltage (dBuV)} + \text{Antenna Factor (dB/m)} + \\ &\text{Cable Loss (dB)} - \text{Preamp Gain (dB)} \\ 36.5 \text{ dBuV} + 18.7 \text{ dB/m} + 0.6 \text{ dB} - 26.9 \text{ dB} &= 28.9 \text{ dBuV/m}\end{aligned}$$

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	3.52 dB
Radiated Disturbance, 30 to 40000 MHz	4.94 dB

Uncertainty figures are valid to a confidence level of 95%.

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a GSM/WCDMA/LTE + BLUETOOTH, DTS/UNII a/b/g/n/ac + ANT+ and NFC

The model FCC ID: PY7-PM0791 shares the same enclosure and circuit board as mode FCC ID: PY7-PM0793. The unlicensed radios (WLAN/BT/NFC/ANT+) including antenna and GPS receiver, are identical between the two units.

After confirming through preliminary radiated emissions that the performance of the FCC ID: PY7-PM0793 data remains representative of this model (FCC ID: PY7-PM0791), FCC ID: PY7-PM0791 leveraged test data from FCC ID: PY7-PM0793.

5.2. MAXIMUM OUTPUT POWER

The transmitter has a maximum total conducted output power as follows:

Frequency Range (MHz)	Mode	Total Output Power (dBm)	Total Output Power (mW)
5180-5240	802.11a	14.34	27.16
5180-5240	802.11n HT20	14.11	25.76
5190-5230	802.11n HT40	14.1	25.70
5210	802.11ac HT80	14.2	26.30
5260-5320	802.11a	14.44	27.80
5260-5320	802.11n HT20	14.43	27.73
5270-5310	802.11n HT40	14.4	27.54
5290	802.11ac HT80	14.26	26.67
5500-5700	802.11a	14.83	30.41
5720	802.11a	13.524	22.51
5500-5700	802.11n HT20	15.07	32.14
5720	802.11n HT20	13.324	21.50
5510-5670	802.11n HT40	14.81	30.27
5710	802.11n HT40	13.568	22.74
5530	802.11ac HT80	14.12	25.82
5690	802.11ac HT80	14.37	27.35
5745-5825	802.11a	14.9	30.90
5745-5825	802.11n HT20	14.88	30.76
5755-5795	802.11n HT40	14.54	28.44
5775	802.11ac HT80	14.65	29.17

The transmitter has average conducted output power (measured by power meter) as follows:

Band (GHz)	Mode	Data Rate	Ch #	Freq. (MHz)	Avg Pwr (dBm)	SAR Test (Yes/No)
UNII-1	802.11a	6 Mbps	36	5180	10.7	Yes
			40	5200	10.7	
			44	5220	10.9	
			48	5240	10.9	
	802.11n (HT20)	6.5 Mbps	36	5180	10.8	Yes
			40	5200	10.8	
			44	5220	10.8	
			48	5240	10.7	
	802.11n (HT40)	13.5 Mbps	38	5190	10.8	Yes
			46	5230	10.8	
	802.11ac (VHT20)	6.5 Mbps	36	5180	10.8	Yes
			40	5200	10.9	
			44	5220	10.8	
			48	5240	10.8	
	802.11ac (VHT40)	13.5 Mbps	38	5190	10.6	Yes
			46	5230	10.7	
	802.11ac (VHT80)	29.3 Mbps	42	5210	10.9	Yes
UNII-2A	802.11a	6 Mbps	52	5260	10.9	Yes
			56	5280	10.8	
			60	5300	10.9	
			64	5320	10.7	
	802.11n (HT20)	6.5 Mbps	52	5260	11.0	Yes
			56	5280	10.6	
			60	5300	10.7	
			64	5320	10.8	
	802.11n (HT40)	13.5 Mbps	54	5270	11.0	Yes
			62	5310	10.7	
	802.11ac (VHT20)	6.5 Mbps	52	5260	10.8	Yes
			56	5280	10.7	
			60	5300	10.6	
			64	5320	10.9	
	802.11ac (VHT40)	13.5 Mbps	54	5270	11.0	Yes
			62	5310	10.7	
	802.11ac (VHT80)	29.3 Mbps	58	5290	10.6	Yes
UNII-2C	802.11a	6 Mbps	100	5500	11.0	Yes
			104	5520	11.0	
			108	5540	11.3	
			112	5560	11.4	

			116	5580	11.5						
			120	5600	11.5						
			124	5620	11.4						
			128	5640	11.4						
								132	5660	11.4	
								136	5680	11.4	
								140	5700	11.4	
								144	5720	11.4	
	802.11n (HT20)	6.5 Mbps	100	5500	11.4	Yes					
			104	5520	11.2						
			108	5540	11.4						
			112	5560	11.4						
			116	5580	11.4						
			120	5600	11.5						
			124	5620	11.3						
			128	5640	11.4						
			132	5660	11.3						
			136	5680	11.3						
			140	5700	11.2						
			144	5720	11.2						
	802.11n (HT40)	13.5 Mbps	102	5510	11.2	Yes					
			110	5550	11.3						
			118	5590	11.4						
			126	5630	11.4						
			134	5670	11.4						
			142	5710	11.4						
	802.11ac (VHT20)	6.5 Mbps	100	5500	11.2	Yes					
			104	5520	11.2						
			108	5540	11.3						
			112	5560	11.4						
			116	5580	11.3						
			120	5600	11.4						
			124	5620	11.4						
			128	5640	11.4						
			132	5660	11.4						
			136	5680	11.5						
			140	5700	11.3						
			144	5720	11.1						
	802.11ac (VHT40)	13.5 Mbps	102	5510	11.3	Yes					
			110	5550	11.4						
			118	5590	11.4						
			126	5630	11.5						
			134	5670	11.5						
			142	5710	11.4						

	802.11ac (VHT80)	29.3 Mbps	106	5530	11.2	Yes
			122	5610	11.3	
			138	5690	11.1	
UNII-3 or §15.247	802.11a	6 Mbps	149	5745	10.8	Yes
			153	5765	10.8	
			157	5785	10.8	
			161	5805	10.6	
			165	5825	10.8	
	802.11n (HT20)	6.5 Mbps	149	5745	11.0	Yes
			153	5765	10.9	
			157	5785	11.0	
			161	5805	10.6	
			165	5825	10.9	
	802.11n (HT40)	13.5 Mbps	151	5755	10.8	Yes
			159	5795	10.9	
	802.11ac (VHT20)	6.5 Mbps	149	5745	11.0	Yes
			153	5765	11.0	
			157	5785	10.9	
			161	5805	10.8	
			165	5825	10.9	
	802.11ac (VHT40)	13.5 Mbps	151	5755	10.8	Yes
			159	5795	10.9	
	802.11ac (VHT80)	29.3 Mbps	155	5775	10.7	Yes

5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes an FPCB antenna, please refer to section 10.4 for antenna gain information.

List of test reduction and modes covering other modes:

Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range (MHz)	Mode	Covered by
5180 - 5240	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5180 - 5240	802.11HT20 1TX	802.11n HT20 2TX CDD
5180 - 5240	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5180 - 5240	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5180 - 5240	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5180 - 5240	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5190 - 5230	802.11n HT40 1TX	802.11n HT40 2TX CDD
5190 - 5230	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5190 - 5230	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5190 - 5230	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5190 - 5230	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5210	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5210	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range (MHz)	Mode	Covered by
5260 - 5320	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5260 - 5320	802.11HT20 1TX	802.11n HT20 2TX CDD
5260 - 5320	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5260 - 5320	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5260 - 5320	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5260 - 5320	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5270 - 5310	802.11n HT40 1TX	802.11n HT40 2TX CDD
5270 - 5310	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5270 - 5310	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5270 - 5310	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5270 - 5310	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5290	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5290	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range (MHz)	Mode	Covered by
5500 - 5720	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5500 - 5720	802.11HT20 1TX	802.11n HT20 2TX CDD
5500 - 5720	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5500 - 5720	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5500 - 5720	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5500 - 5720	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5510 - 5710	802.11n HT40 1TX	802.11n HT40 2TX CDD
5510 - 5710	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5510 - 5710	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5510 - 5710	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5510 - 5710	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5530-5690	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5530-5690	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

Authorized Frequency Band (Antenna port & Radiated Testing)		
Frequency Range (MHz)	Mode	Covered by
5745 - 5825	802.11a legacy 1TX/STBC 2TX	802.11a 2TX CDD
5745 - 5825	802.11HT20 1TX	802.11n HT20 2TX CDD
5745 - 5825	802.11HT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5745 - 5825	802.11ac VHT20 1TX	802.11n HT20 2TX CDD
5745 - 5825	802.11ac VHT20 2TX STBC/SDM	802.11n HT20 2TX CDD
5745 - 5825	802.11ac VHT20 2TX CDD/Tx BF	802.11n HT20 2TX CDD
5755 - 5795	802.11n HT40 1TX	802.11n HT40 2TX CDD
5755 - 5795	802.11n HT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5755 - 5795	802.11ac VHT40 1TX	802.11n HT40 2TX CDD
5755 - 5795	802.11ac VHT40 2TX STBC/SDM	802.11n HT40 2TX CDD
5755 - 5795	802.11ac VHT40 2TX CDD/Tx BF	802.11n HT40 2TX CDD
5775	802.11ac VHT80 1TX	802.11ac VHT80 2TX CDD
5775	802.11ac VHT80 2TX STBC/SDM/Tx BF	802.11ac VHT80 2TX CDD

5.4. WORST-CASE CONFIGURATION AND MODE

Radiated emission and power line conducted emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that the X orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in the X orientation.

Based on the baseline scan, the worst-case data rates were:

802.11a mode: 6 Mbps

802.11n HT20mode: MCS0

802.11n HT40mode: MCS0

802.11ac VHT80mode: MCS0

5.5. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List				
Description	Manufacturer	Model	Serial Number	FCC ID
AC Adapter	SONY	EP880	3514W 01 S08328	N/A
Earphone	SONY	MH410C	N/A	N/A


I/O CABLES

I/O Cable List						
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	DC Power	1	Mini-USB	Shielded	1.2m	N/A
2	Audio	1	Mini-Jack	Unshielded	1.0m	N/A

TEST SETUP

The EUT is setup as a stand-alone device.

SETUP DIAGRAM FOR TESTS



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List				
Description	Manufacturer	Model	Asset	Cal Due
Spectrum Analyzer, 44 GHz	Agilent / HP	E4446A	C01069	12/20/15
Spectrum Analyzer, 9KHz-40GHz	HP	8564E	C00986	04/01/15
EMI Test Receiver, 9 kHz-7 GHz	R & S	ESCI 7	100773	08/15/15
Peak Power Meter	Agilent / HP	E4416A	C00963	12/13/15
Peak / Average Power Sensor	Agilent / HP	E9327A	C00964	12/13/15
Antenna, Horn, 18GHz	EMCO	3115	C00783	10/25/15
Antenna, Horn, 18- 26 GHz	ARA	MWH-1826/B	C00946	11/12/15
Antenna, Horn, 26-40 GHz	ARA	MWH-2640	C00891	06/28/15
Antenna, Bilog, 30MHz-1 GHz	Sunol Sciences	JB1	T243	12/08/15
RF Preamplifier, 100KHz -> 1300MHz	HP	TBD	C00825	06/01/15
RF Preamplifier, 1GHz - 18GHz	Miteq	NSP4000-SP2	924343	09/03/15
RF Preamplifier, 1GHz - 26.5GHz	HP	8449B	F00351	06/27/15
AC Power Supply, 2,500VA 45-500Hz	Elgar-Ametek	CW2501M	F00013	CNR
RF Preamplifier, 1GHz - 18GHz	Miteq	AFS42-00101800-25-S-42	1818466	05/09/15
Attenuator / Switch driver	HP	11713A	F00204	CNR
Low Pass Filter 3GHz	Micro-Tronics	LPS17541	F00219	05/23/15
High Pass Filter 5GHz	Micro-Tronics	HPS17542	F00222	05/22/15
High Pass Filter 6GHz	Micro-Tronics	HPM17543	F00224	05/22/15

Test Software List			
Description	Manufacturer	Model	Version
Radiated Software	UL	UL EMC	Version 9.5, 07/22/14
Conducted Software	UL	UL EMC	Version 9.5, 05/17/14
CLT Software	UL	UL RF	Version 1.0, 02/02/15
Antenna Port Software	UL	UL RF	Version 2.1.1.1, 1/20/15

7. SUMMARY TABLE

FCC Part Section	Test Description	Test Limit	Test Condition	Test Result	Worst Case
15.407 (a)	Occupied Band width (26dB)	N/A	Conducted	Pass	82.5MHz
14.407	6dB Band width	>500KHz		Pass	76.08MHz
15.407 (a)(2)	TX Cond. Power 5.15-2.25, 5.25-5.35 & 5.47-5.725	<24dBm or 11+10Log(OBW)		Pass	15.07dBm
15.407 (a)(3)	TX Cond. Power 5.725-5.850	< 30dBm or 17+10Log(OBW)		Pass	14.88dBm
15.407 (a)(5)	PSD (5.2,5.3,5.5GHz)	<11dBm		Pass	3.49dBm
15.407 (a)(5)	PSD	30dBm per 500kHz		Pass	1.25dBm
15.207 (a)	AC Power Line conducted emissions	Section 10	Radiated	Pass	44.76dBuV(AV)
15.407 (b) & 15.209	Radiated Spurious Emission	< 54dBuV/m		Pass	49.66dBuV/m
15.407 (h)(2)	Dynamic Frequency Selection	N/A	Radiated / Conducted	Pass	N/A

8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None; for reporting purposes only.

PROCEDURE

KDB 789033 Zero-Span Spectrum Analyzer Method.

8.1. ON TIME AND DUTY CYCLE RESULTS

Please refer to UNII test report of FCC ID: PY7-PM0793.

8.2. DUTY CYCLE PLOTS

Please refer to UNII test report of FCC ID: PY7-PM0793.

9. MEASUREMENT METHOD

789033 D02 General UNII Test Procedures New Rules v01

The Duty Cycle is less than 98% and consistent therefore KDB 789033 Method SA-2 is used for power and PPSD

The Duty Cycle is less than 98% and consistent, KDB 789033 Method AD with Power RMS Averaging and duty cycle correction is used.

Straddle Channels: KDB 644545 D01 v01r02

MIMO Device: KDB 662911 v02r01

10. ANTENNA PORT TEST RESULTS

10.1. 6 dB BANDWIDTH

LIMITS

FCC §15.407

The minimum 6 dB bandwidth shall be at least 500 kHz.

TEST PROCEDURE

Reference to 789033 D02 General UNII Test Procedures New Rules v01: The transmitter output is connected to a spectrum analyzer with the RBW set to 100kHz, the VBW $\geq 3 \times$ RBW, peak detector and max hold.

RESULTS

10.1.1. 802.11a MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.1.2. 802.11n HT20 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.1.3. 802.11n HT40 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.1.4. 802.11ac HT80 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.1.5. 802.11a MODE THE CHANNEL 144

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.1.6. 802.11n HT20 MODE THE CHANNEL 144

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.1.7. 802.11n HT40 MODE THE CHANNEL 142

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.1.8. 802.11ac HT80 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.1.9. 6 dB BANDWIDTH MID CH PLOTS

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2. 26 dB BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

10.2.1. 802.11a MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.4. 802.11ac HT80 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.5. 802.11a MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.6. 802.11n HT20 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.7. 802.11n HT40 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.8. 802.11ac HT80 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.9. 802.11a MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.10. 802.11n HT20 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.11. 802.11n HT40 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.12. 802.11ac HT80 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.13. 802.11a MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.14. 802.11n HT20 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.15. 802.11n HT40 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.16. 802.11ac HT80 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.2.17. 26 dB BANDWIDTH PLOTS

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3. 99% BANDWIDTH

LIMITS

None; for reporting purposes only.

RESULTS

10.3.1. 802.11a MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.4. 802.11ac HT80 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.5. 802.11a MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.6. 802.11n HT20 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.7. 802.11n HT40 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.8. 802.11ac HT80 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.9. 802.11a MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.10. 802.11n HT20 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.11. 802.11n HT40 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.12. 802.11ac HT80 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.13. 802.11a MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.14. 802.11n HT20 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.15. 802.11n HT40 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.16. 802.11ac HT80 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.3.17. 99% BANDWIDTH PLOTS

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4. OUTPUT POWER AND PPSD

LIMITS

FCC §15.407 (a) (1) (2) (3)

For the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26-dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 4 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

DIRECTIONAL ANTENNA GAIN

The TX chains are uncorrelated and the antenna gain is unequal among the chains. The directional gain is:

5180-5320MHz

Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Uncorrelated Chains Directional Gain (dBi)
-0.90	-2.30	-1.54

The TX chains are correlated and the antenna gain is unequal among the chains. The directional gain is:

5180-5320MHz

Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Correlated Chains Directional Gain (dBi)
-0.90	-2.30	1.44

5500-5700MHz

Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Uncorrelated Chains Directional Gain (dBi)
-0.90	-1.30	-1.10

The TX chains are correlated and the antenna gain is unequal among the chains. The directional gain is:

5500-5700MHz

Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Correlated Chains Directional Gain (dBi)
-0.90	-1.30	1.91

5725-5850MHz

Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Uncorrelated Chains Directional Gain (dBi)
-2.10	-2.10	-2.10

The TX chains are correlated and the antenna gain is unequal among the chains. The directional gain is:

5725-5850MHz

Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Correlated Chains Directional Gain (dBi)
-2.10	-2.10	0.91

RESULTS

10.4.1. 802.11a MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.2. 802.11n HT20 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.3. 802.11n HT40 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.4. 802.11ac HT80 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.5. 802.11a MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.6. 802.11n HT20 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.7. 802.11n HT40 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.8. 802.11ac HT80 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.9. 802.11a MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.10. 802.11n HT20 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.11. 802.11n HT40 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.12. 802.11ac HT80 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.13. 802.11a MODE STRADDLE CHANNEL 144

UNII-2C BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

UNII-3 BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

AVERAGE OUTPUT POWER (WHOLE FUNDAMENTAL)

Results

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.14. 802.11n HT20 MODE STRADDLE CHANNEL 144

UNII-2C BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

UNII-3 BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

AVERAGE OUTPUT POWER (WHOLE FUNDAMENTAL)

Results

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.15. 802.11n HT40 MODE STRADDLE CHANNEL 142

UNII-2C BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

UNII-3 BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

AVERAGE OUTPUT POWER (WHOLE FUNDAMENTAL

Results

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.16. 802.11ac80 MODE STRADDLE CHANNEL 138

UNII-2C BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

UNII-3 BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

AVERAGE OUTPUT POWER (WHOLE FUNDAMENTAL

Results

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.17. 802.11a MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.18. 802.11n HT20 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.19. 802.11n HT40 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.20. 802.11ac HT80 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

10.4.21. OUTPUT POWER AND PPSD PLOTS

Please refer to UNII test report of FCC ID: PY7-PM0793.

11. TRANSMITTER ABOVE 1 GHz

LIMITS

FCC §15.205 and §15.209

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

Reference to KDB 789033 UNII part H) 6) d) Method AD:

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 3 MHz for peak measurements and add duty cycle factor to the reading offset for average measurements.

The spectrum from 30 MHz to 40 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

11.1. 5.2 GHz

11.1.1. TX ABOVE 1 GHz 802.11a MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.1.2. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.1.3. TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.1.4. TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.2 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.2. 5.3 GHz

11.2.1. TX ABOVE 1 GHz 802.11a MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.2.2. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.2.3. TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.2.4. TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.3 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.3. 5.5-5.6 GHz

11.3.1. TX ABOVE 1 GHz 802.11a MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.3.2. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.3.3. TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.3.4. TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.5 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.4. 5.8 GHz

11.4.1. TX ABOVE 1 GHz 802.11a MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.4.2. TX ABOVE 1 GHz 802.11n HT20 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.4.3. TX ABOVE 1 GHz 802.11n HT40 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

11.4.4. TX ABOVE 1 GHz 802.11ac HT80 MODE IN THE 5.8 GHz BAND

Please refer to UNII test report of FCC ID: PY7-PM0793.

12. WORST-CASE BELOW 1 GHz (in the 5.3 GHz Band)

Please refer to UNII test report of FCC ID: PY7-PM0793.

13. AC POWER LINE CONDUCTED EMISSIONS

LIMITS

FCC §15.207 (a)

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80 cm above the horizontal ground plane. The EUT is configured in accordance with ANSI C63.4.

The receiver is set to a resolution bandwidth of 9 kHz. Peak detection is used unless otherwise noted as quasi-peak or average.

Line conducted data is recorded for both NEUTRAL and HOT lines.

RESULTS

Please refer to UNII test report of FCC ID: PY7-PM0793.6 WORST EMISSIONS

14. DYNAMIC FREQUENCY SELECTION

14.1. OVERVIEW

14.1.1. LIMITS

INDUSTRY CANADA

IC RSS-210 is closely harmonized with FCC Part 15 DFS rules. The deviations are as follows:

RSS-210 Issue 8 A9.3

Note: For the band 5600–5650 MHz, no operation is permitted.

Until further notice, devices subject to this annex shall not be capable of transmitting in the band 5600–5650 MHz. This restriction is for the protection of Environment Canada weather radars operating in this band.

FCC

§15.407 (h), FCC KDB 905462 D02 “COMPLIANCE MEASUREMENT PROCEDURES FOR UNLICENSED-NATIONAL INFORMATION INFRASTRUCTURE DEVICES OPERATING IN THE 5250-5350 MHz AND 5470-5725 MHz BANDS INCORPORATING DYNAMIC FREQUENCY SELECTION” and KDB 905462 D03 “U-NII CLIENT DEVICES WITHOUT RADAR DETECTION CAPABILITY”.

Table 1: Applicability of DFS requirements prior to use of a channel

Requirement	Operational Mode		
	Master	Client (without radar detection)	Client (with radar detection)
Non-Occupancy Period	Yes	Not required	Yes
DFS Detection Threshold	Yes	Not required	Yes
Channel Availability Check Time	Yes	Not required	Not required
U-NII Detection Bandwidth	Yes	Not required	Yes

Table 2: Applicability of DFS requirements during normal operation

Requirement	Operational Mode		
	Master	Client (without DFS)	Client (with DFS)
DFS Detection Threshold	Yes	Not required	Yes
Channel Closing Transmission Time	Yes	Yes	Yes
Channel Move Time	Yes	Yes	Yes
U-NII Detection Bandwidth	Yes	Not required	Yes

Additional requirements for devices with multiple bandwidth modes	Master Device or Client with Radar DFS	Client (without DFS)
<i>U-NII Detection Bandwidth and Statistical Performance Check</i>	All BW modes must be tested	Not required
<i>Channel Move Time and Channel Closing Transmission Time</i>	Test using widest BW mode available	Test using the widest BW mode available for the link
<i>All other tests</i>	Any single BW mode	Not required
Note: Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in all 20 MHz channel blocks and a null frequency between the bonded 20 MHz channel blocks.		

Table 3: Interference Threshold values, Master or Client incorporating In-Service Monitoring

Maximum Transmit Power	Value (see notes)
E.I.R.P. $\geq$ 200 mill watt	-64 dBm
E.I.R.P. < 200 mill watt and power spectral density < 10 dBm/MHz	-62 dBm
E.I.R.P. < 200 mill watt that do not meet power spectral density requirement	-64 dBm
Note 1: This is the level at the input of the receiver assuming a 0 dBi receive antenna Note 2: Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response. Note 3: E.I.R.P. is based on the highest antenna gain. For MIMO devices refer to KDB publication 662911 D01.	

Table 4: DFS Response requirement values

Parameter	Value
<i>Non-occupancy period</i>	30 minutes
<i>Channel Availability Check Time</i>	60 seconds
<i>Channel Move Time</i>	10 seconds (See Note 1)
<i>Channel Closing Transmission Time</i>	200 milliseconds + approx. 60 milliseconds over remaining 10 second period. (See Notes 1 and 2)
<i>U-NII Detection Bandwidth</i>	Minimum 100% of the U- NII 99% transmission power bandwidth. (See Note 3)
Note 1: <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. Note 2: The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions. Note 3: During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.	

Table 5 – Short Pulse Radar Test Waveforms

Radar Type	Pulse Width (usec)	PRI (usec)	Pulses	Minimum Percentage of Successful Detection	Minimum Trials
0	1	1428	18	See Note 1	See Note 1
1	1	Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in table 5a	Roundup: $\{(1/360) \times (19 \times 10^6 \text{ PRI}_{\text{usec}})\}$	60%	30
		Test B: 15 unique PRI values randomly selected within the range of 518-3066 usec. With a minimum increment of 1 usec, excluding PRI values selected in Test A			
2	1-5	150-230	23-29	60%	30
3	6-10	200-500	16-18	60%	30
4	11-20	200-500	12-16	60%	30
Aggregate (Radar Types 1-4)				80%	120
Note 1: Short Pulse Radar Type 0 should be used for the <i>Detection Bandwidth</i> test, <i>Channel Move Time</i> , and <i>Channel Closing Time</i> tests.					

Table 6 – Long Pulse Radar Test Signal


Radar Waveform Type	Pulse Width (μsec)	Chirp Width (MHz)	PRI (μsec)	Pulses per Burst	Number of Bursts	Minimum Percentage of Successful Detection	Minimum Trials
5	50-100	5-20	1000-2000	1-3	8-20	80%	30

Table 7 – Frequency Hopping Radar Test Signal

Radar Waveform Type	Pulse Width (μsec)	PRI (μsec)	Pulses per Hop	Hopping Rate (kHz)	Hopping Sequence Length (msec)	Minimum Percentage of Successful Detection	Minimum Trials
6	1	333	9	0.333	300	70%	30

14.1.2. TEST AND MEASUREMENT SYSTEM

RADIATED METHOD SYSTEM BLOCK DIAGRAM



SYSTEM OVERVIEW

The short pulse and long pulse signal generating system utilizes the NTIA software. The Vector Signal Generator has been validated by the NTIA. The hopping signal generating system utilizes the CCS simulated hopping method and system, which has been validated by the DoD, FCC and NTIA. The software selects waveform parameters from within the bounds of the signal type on a random basis using uniform distribution.

The short pulse types 1, 2, 3 and 4, and the long pulse type 5 parameters are randomized at run-time.

The hopping type 6 pulse parameters are fixed while the hopping sequence is based on the August 2005 NTIA Hopping Frequency List. The initial starting point randomized at run-time and each subsequent starting point is incremented by 475. Each frequency in the 100-length segment is compared to the boundaries of the EUT Detection Bandwidth and the software creates a hopping burst pattern in accordance with Section 7.4.1.3 Method #2 Simulated Frequency Hopping Radar Waveform Generating Subsystem of KDB 905462 D02. The frequency of the signal generator is incremented in 1 MHz steps from F_L to F_H for each successive trial. This incremental sequence is repeated as required to generate a minimum of 30 total trials and to maintain a uniform frequency distribution over the entire Detection Bandwidth.

The signal monitoring equipment consists of a spectrum analyzer. The aggregate ON time is calculated by multiplying the number of bins above a threshold during a particular observation period by the dwell time per bin, with the analyzer set to peak detection and max hold.

SYSTEM CALIBRATION

A 50-ohm load is connected in place of the spectrum analyzer, and the spectrum analyzer is connected to a horn antenna via a coaxial cable, with the reference level offset set to (horn antenna gain – coaxial cable loss). The signal generator is set to CW mode. The amplitude of the signal generator is adjusted to yield a level of –64 dBm as measured on the spectrum analyzer.

Without changing any of the instrument settings, the spectrum analyzer is reconnected to the Common port of the Spectrum Analyzer Combiner/Divider. The Reference Level Offset of the spectrum analyzer is adjusted so that the displayed amplitude of the signal is –64 dBm.

The spectrum analyzer displays the level of the signal generator as received at the antenna ports of the Master Device. The interference detection threshold may be varied from the calibrated value of –64 dBm and the spectrum analyzer will still indicate the level as received by the Master Device.

ADJUSTMENT OF DISPLAYED TRAFFIC LEVEL

A link is established between the Master and Slave and the distance between the units is adjusted as needed to provide a suitable received level at the Master and Slave devices. The video test file is streamed to generate WLAN traffic. The monitoring antenna is adjusted so that the WLAN traffic level, as displayed on the spectrum analyzer, is at lower amplitude than the radar detection threshold.


TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the DFS tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Asset Number	Cal Due
Spectrum Analyzer, 26.5 GHz	Agilent / HP	E4440A	C01178	09/05/15
Vector Signal Generator, 20GHz	Agilent / HP	E8267C	C01066	09/03/15

14.1.3. SETUP OF EUT

RADIATED METHOD EUT TEST SETUP



SUPPORT EQUIPMENT

The following support equipment was utilized for the DFS tests documented in this report:

PERIPHERAL SUPPORT EQUIPMENT LIST				
Description	Manufacturer	Model	Serial Number	FCC ID
802.11ac Dual Band Wireless Access Point (Master Device)	Cisco	AIR-CAP3702E-A-K9	FTX181570A6	LDK102087
P.O.E. Injector (Master)	Phihong	POE30U-560(G)	PHI170102N2	DoC
Notebook PC (Controller)	Lenovo	Type 4236-B92	PB-HEX04 12/05	DoC
AC Adapter (Controller PC)	Lenovo	42T4418	11S42T4418Z1ZG WG08R90M	DoC

14.1.4. DESCRIPTION OF EUT

For FCC the EUT operates over the 5250-5350 MHz and 5470-5725 MHz ranges.

The EUT is a Slave Device without Radar Detection.

The highest power level within these bands is 11.74 dBm EIRP in the 5250-5350 MHz band and 12.27 dBm EIRP in the 5470-5725 MHz band.

The highest gain antenna assembly utilized with the EUT has a gain of -2.7 dBi in the 5250-5350 MHz band and -2.8 dBi in the 5470-5725 MHz band. The lowest gain antenna assembly utilized with the EUT has a gain of -2.7 dBi in the 5250-5350 MHz band and -2.8 dBi in the 5470-5725 MHz band.

Two identical antennas are utilized to meet the diversity and MIMO operational requirements.

The rated output power of the Master unit is > 23dBm (EIRP). Therefore the required interference threshold level is -64 dBm. After correction for procedural adjustments, the required radiated threshold at the antenna port is $-64 + 1 = -63$ dBm.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm. The tested level is lower than the required level hence it provides a margin to the limit.

The EUT uses two transmitter/receiver chains, each connected to an antenna to perform radiated tests.

WLAN traffic that meets or exceeds the minimum required loading was generated by transferring a data stream from the controller/server PC to the EUT using iPerf version 2.0.5 software package.

TPC is not required since the maximum EIRP is less than 500 mW (27 dBm).

The EUT utilizes the 802.11ac architecture. Three nominal channel bandwidths are implemented: 20 MHz, 40 MHz and 80 MHz.

The software installed in the access point is AP3G2-K9W7-M version 15.2(4)JB4.

UNIFORM CHANNEL SPREADING

This is requirement not applicable to Slave Devices.

OVERVIEW OF MASTER DEVICE WITH RESPECT TO §15.407 (h) REQUIREMENTS

The Master Device is a Cisco Access Point, FCC ID: LDK102087. The minimum antenna gain for the Master Device is 6 dBi.

The rated output power of the Master unit is $> 23\text{dBm}$ (EIRP). Therefore the required interference threshold level is -64 dBm . After correction for procedural adjustments, the required radiated threshold at the antenna port is $-64 + 1 = -63\text{ dBm}$.

The calibrated radiated DFS Detection Threshold level is set to -64 dBm . The tested level is lower than the required level hence it provides a margin to the limit.

14.2. RESULTS FOR 20 MHz BANDWIDTH

14.2.1. TEST CHANNEL

All tests were performed at a channel center frequency of 5500 MHz.

14.2.2. RADAR WAVEFORM AND TRAFFIC

Please refer to UNII test report of FCC ID: PY7-PM0793

CHANNEL LOADING

Please refer to UNII test report of FCC ID: PY7-PM0793.

14.2.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

14.2.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS

Please refer to UNII test report of FCC ID: PY7-PM0793.

14.3. RESULTS FOR 40 MHz BANDWIDTH

14.3.1. TEST CHANNEL

All tests were performed at a channel center frequency of 5510 MHz.

14.3.2. RADAR WAVEFORM AND TRAFFIC

Please refer to UNII test report of FCC ID: PY7-PM0793.

14.3.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

14.3.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS

Please refer to UNII test report of FCC ID: PY7-PM0793.

14.3.5. 10-MINUTE BEACON MONITORING PERIOD

RESULTS

Please refer to UNII test report of FCC ID: PY7-PM0793.

14.4. RESULTS FOR 80 MHz BANDWIDTH

14.4.1. TEST CHANNEL

All tests were performed at a channel center frequency of 5530 MHz.

14.4.2. RADAR WAVEFORM AND TRAFFIC

Please refer to UNII test report of FCC ID: PY7-PM0793

14.4.3. OVERLAPPING CHANNEL TESTS

RESULTS

These tests are not applicable.

14.4.4. MOVE AND CLOSING TIME

REPORTING NOTES

The reference marker is set at the end of last radar pulse.

The delta marker is set at the end of the last WLAN transmission following the radar pulse. This delta is the channel move time.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =
(Number of analyzer bins showing transmission) * (dwell time per bin)

The observation period over which the aggregate time is calculated begins at (Reference Marker + 200 msec) and ends no earlier than (Reference Marker + 10 sec).

RESULTS

Please refer to UNII test report of FCC ID: PY7-PM0793

14.4.5. 10-MINUTE BEACON MONITORING PERIOD

RESULTS

Please refer to UNII test report of FCC ID: PY7-PM0793.