**CETECOM™****CETECOM ICT Services**
consulting - testing - certification >>>

TEST REPORT

Test report no.: 1-6965/13-12-12-A

Deutsche
Akkreditierungsstelle
D-PL-12076-01-01

Testing laboratory

CETECOM ICT Services GmbH

Untertuerkheimer Strasse 6 – 10

66117 Saarbruecken / Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

Internet: <http://www.cetecom.com>e-mail: ict@cetecom.com**Accredited Testing Laboratory:**

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2005) by the Deutsche Akkreditierungsstelle GmbH (DAkkS)

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number: D-PL-12076-01-01

Area of Testing:

Radio Communications & EMC (RCE)

Applicant

Sony Mobile Communications AB

Nya Vattentorget

22188 Lund / SWEDEN

Phone: +46 46 19 30 00

Fax: -/-

Contact: Mikael Nilsson

e-mail: Micke.nilsson@sonymobile.com

Phone: +46 7 03 22 75 03

Manufacturer

Sony Mobile Communications AB

Nya Vattentorget

22188 Lund / SWEDEN

Test standard/s

47 CFR Part 15

Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item:**Tablet PC GPRS/EGPRS 850/900/1800/1900; UMTS HSPA FDD/TDD; LTE FDD1/3/17/18; LTE TDD41; CDMA 2K C00/C06; WLAN b/g/n/a/ac; BT 4.0; RFID; A-GPS****FCC ID:****PY7TM-0044****Frequency:**

DTS band 5725 MHz to 5850 MHz

(lowest channel 149 – 5745 MHz; highest channel 165 – 5825 MHz)

Technology tested:

WLAN (OFDM/a – mode; n/ac HT20 / HT40 – mode and ac HT80 – mode)

Antenna:

Integrated antenna

Power supply:

3.7 V DC by Li - polymer battery

Temperature range:

-30°C to +60°C

This test report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorised:Andreas Luckenbill
Expert**Test performed:**Marco Bertolino
Testing Manager

1 Table of contents

1	Table of contents	2
2	General information	3
2.1	Notes and disclaimer	3
2.2	Application details.....	3
3	Test standard/s	3
3.1	Measurement guidance.....	3
4	Test environment.....	4
5	Test item	4
5.1	Additional information	4
6	Test laboratories sub-contracted	4
7	Description of the test setup	5
7.1	Radiated measurements chamber F.....	5
7.2	Radiated measurements chamber C	6
7.3	Radiated measurements 12.75 GHz to 40 GHz	7
7.4	AC conducted	8
8	Summary of measurement results	9
9	Additional comments	10
10	Measurement results	11
10.1	TX spurious emissions radiated.....	11
10.2	RX spurious emissions radiated	41
10.3	Spurious emissions radiated < 30 MHz	45
10.4	Spurious emissions conducted < 30 MHz	47
11	Test equipment and ancillaries used for tests	50
12	Observations	51
Annex A	Document history	52
Annex B	Further information.....	52
Annex C	Accreditation Certificate	53

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM ICT Services GmbH.

The testing service provided by CETECOM ICT Services GmbH has been rendered under the current "General Terms and Conditions for CETECOM ICT Services GmbH".

CETECOM ICT Services GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CETECOM ICT Services GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CETECOM ICT Services GmbH test report include or imply any product or service warranties from CETECOM ICT Services GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CETECOM ICT Services GmbH.

All rights and remedies regarding vendor's products and services for which CETECOM ICT Services GmbH has prepared this test report shall be provided by the party offering such products or services and not by CETECOM ICT Services GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

2.2 Application details

Date of receipt of order:	2013-12-19
Date of receipt of test item:	2014-02-17
Start of test:	2014-02-17
End of test:	2014-02-24
Person(s) present during the test:	-/-

3 Test standard/s

Test standard	Date	Test standard description
47 CFR Part 15	-/-	Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

3.1 Measurement guidance

DTS : KDB 558074	2013-04	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
------------------	---------	---

4 Test environment

Temperature:	T_{nom}	+22 °C during room temperature tests
	T_{max}	+60 °C during high temperature tests
	T_{min}	-30 °C during low temperature tests
Relative humidity content:		43 %
Barometric pressure:		not relevant for this kind of testing
Power supply:	V_{nom}	3.7 V DC by Li - polymer battery
	V_{max}	4.2 V
	V_{min}	3.3 V

5 Test item

Kind of test item :	Tablet PC GPRS/EGPRS 850/900/1800/1900; UMTS HSPA FDDI/III/V; LTE FDD1/3/17/18; LTE TDD41; CDMA 2K C00/C06; WLAN b/g/n/a/ac; BT 4.0; RFID; A-GPS
S/N serial number :	Radiated units: CB5126DAHf; CB5126DAHx
HW hardware status :	AP1
SW software status :	RF test software!
Frequency band [MHz] :	DTS band 5725 MHz to 5850 MHz (lowest channel 149 – 5745 MHz; highest channel 165 – 5825 MHz)
Type of radio transmission :	OFDM
Use of frequency spectrum :	
Type of modulation :	BPSK, QPSK, 16 – QAM; 64 – QAM and 256 – QAM
Number of channels :	5
Antenna :	Integrated antenna
Power supply :	3.7 V DC by Li - polymer battery
Temperature range :	-30°C to +60 °C

5.1 Additional information

Test setup- and EUT-photos are included in test report: 1-6965/13-12-01_AnnexA
 1-6965/13-12-01_AnnexB
 1-6965/13-12-01_AnnexD


6 Test laboratories sub-contracted

None

7 Description of the test setup

7.1 Radiated measurements chamber F


The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Equipment table:


Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom
Switch-Unit	3488A	HP Meßtechnik	2719A14505	300000368
DC power supply, 60Vdc, 50A, 1200 W	6032A	HP Meßtechnik	2920A04466	300000580
EMI Test Receiver	ESCI 3	R&S	100083	300003312
Amplifier	JS42-00502650-28-5A	MITEQ	1084532	300003379
Antenna Tower	Model 2175	ETS-LINDGREN	64762	300003745
Positioning Controller	Model 2090	ETS-LINDGREN	64672	300003746
Turntable Interface-Box	Model 105637	ETS-LINDGREN	44583	300003747
TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	295	300003787

7.2 Radiated measurements chamber C




Equipment table:

Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom
MXE EMI Receiver 20 Hz bis 26,5 GHz	N9038A	Agilent Technologies	MY51210197	300004405
Highpass Filter	WHKX7.0/18G-8SS	Wainwright	18	300003789
Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	8812-3088	300001032
Active Loop Antenna	6502	EMCO	8905-2342	300000256
Anechoic chamber	FAC 3/5m	MWB / TDK	87400/02	300000996
Switch / Control Unit	3488A	HP Meßtechnik	*	300000199
Switch / Control Unit	3488A	HP Meßtechnik	2719A15013	300001156
Isolating Transformer	MPL IEC625 Bus Regeltrenntravo	Erfi	91350	300001155
Three-Way Power Splitter, 50 Ohm	11850C	HP Meßtechnik		300000997
Amplifier	js42-00502650-28-5a	Parzich GMBH	928979	300003143

7.3 Radiated measurements 12.75 GHz to 40 GHz**Equipment table:**

Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom
Std. Gain Horn Antenna 12.4 to 18.0 GHz	639	Narda	8402	300000787
Std. Gain Horn Antenna 18.0 to 26.5 GHz	638	Narda	8205	300002442
Microwave System Amplifier, 0.5-26.5 GHz	83017A	HP Meßtechnik	00419	300002268
Std. Gain Horn Antenna 26.5-40.0 GHz	V637	Narda	7911	300001751
Broadband Low Noise Amplifier 18-50 GHz	CBL18503070-XX	CERNEX	19338	300004273
Spectrum Analyzer 20 Hz - 50 GHz	FSU50	R&S	200012	300003443
Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517

7.4 AC conducted



Equipment table:

Equipment	Type	Manufacturer	Serial No.	INV. No Cetecom
MXE EMI Receiver 20 Hz bis 26,5 GHz	N9038A	Agilent Technologies	MY51210197	300004405
Isolating Transformer	MPL IEC625 Bus Regeltrenntravo	Erft	91350	300001155
Switch / Control Unit	3488A	HP Meßtechnik	*	300000199
Switch / Control Unit	3488A	HP Meßtechnik	2719A15013	300001168
Artificial Mains 9 kHz to 30 MHz	ESH3-Z5	R&S	828576/020	300001210

8 Summary of measurement results



No deviations from the technical specifications were ascertained



There were deviations from the technical specifications ascertained

TC Identifier	Description	Verdict	Date	Remark
RF-Testing	CFR Part 15	Passed	2014-03-17	Delta tests according to manufacturer test plan!

Test specification clause	Test case	Temperature conditions	Power source voltages	Mode	Pass	Fail	NA	NP	Remark
§15.247(b)(4)	Antenna gain	Nominal	Nominal	OFDM	☐	☐	☐	☒	-/-
§15.247(e)	Power spectral density DTS clause 10.2	Nominal	Nominal	OFDM	☐	☐	☐	☒	-/-
§15.247(a)(2)	Spectrum bandwidth - 6dB bandwidth DTS clause 8.2	Nominal	Nominal	OFDM	☐	☐	☐	☒	-/-
§15.247(a)(2)	Spectrum bandwidth - 20dB bandwidth	Nominal	Nominal	OFDM	☐	☐	☐	☒	-/-
§15.247(b)(3)	Maximum output power DTS clause 9.1.2	Nominal	Nominal	OFDM	☐	☐	☐	☒	-/-
§15.247(d)	Band edge compliance conducted DTS clause 13.2.1	Nominal	Nominal	OFDM	☐	☐	☐	☒	-/-
§15.247(d)	TX spurious emissions conducted DTS clause 11.1 & 2	Nominal	Nominal	OFDM	☐	☐	☐	☒	-/-
§15.247(d)	TX spurious emissions radiated	Nominal	Nominal	OFDM	☒	☐	☐	☐	complies
§15.109	RX spurious emissions radiated	Nominal	Nominal	-/-	☒	☐	☐	☐	complies
§15.209(a)	TX spurious emissions radiated < 30 MHz	Nominal	Nominal	OFDM	☒	☐	☐	☐	complies
§15.107(a) §15.207	Conducted emissions < 30 MHz	Nominal	Nominal	OFDM	☒	☐	☐	☐	complies

Note: NA = Not Applicable; NP = Not Performed

9 Additional comments

Reference documents: Main report: 1-6965/13-05-18-A / PY7TM-0040 (conducted values)

Special test descriptions: None

Configuration descriptions: None

Test mode:

- ☐ No test mode available.
Iperf was used to ping another device with the largest support packet size
- ☒ Special software is used.
EUT is transmitting pseudo random data by itself

10 Measurement results

10.1 TX spurious emissions radiated

Description:

Measurement of the radiated spurious emissions in transmit mode. The measurement is performed at the lowest, middle and highest channel. The measurement is repeated for all modulations.

Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak / RMS
Sweep time:	Auto
Resolution bandwidth:	F > 1 GHz: 1 MHz F < 1 GHz: 100 kHz
Video bandwidth:	3 x RBW Re-measurement: 10 Hz / 3 MHz
Span:	30 MHz to 40 GHz
Trace-Mode:	Max Hold
Measured Modulation	☒ OFDM a – mode ☒ OFDM n/ac – mode HT20 ☒ OFDM n/ac – mode HT40 ☒ OFDM ac – mode HT80

The modulation with the highest output power was used to perform the transmitter spurious emissions. If spurious were detected a re-measurement was performed on the detected frequency with each modulation.

Limits:

FCC		
TX Spurious Emissions Radiated		
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).		
Frequency (MHz)	Field Strength (dBμV/m)	Measurement distance
30 - 88	30.0	10
88 – 216	33.5	10
216 – 960	36.0	10
Above 960	54.0	3

Results: OFDM / a – mode

TX Spurious Emissions Radiated [dBμV/m]								
OFDM / a – mode								
5745 MHz			5785 MHz			5825 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
All detected peak emissions above 1 GHz are below the average limit. See plots!			All detected peak emissions above 1 GHz are below the average limit. See plots!			All detected peak emissions above 1 GHz are below the average limit. See plots!		
Measurement uncertainty			± 3 dB					

Results: OFDM / n/ac – mode HT20

TX Spurious Emissions Radiated [dBμV/m]								
OFDM / n/ac HT20 – mode								
5745 MHz			5785 MHz			5825 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
All detected peak emissions above 1 GHz are below the average limit. See plots!			All detected peak emissions above 1 GHz are below the average limit. See plots!			All detected peak emissions above 1 GHz are below the average limit. See plots!		
Measurement uncertainty			± 3 dB					

Results: OFDM / n/ac – mode HT40

TX Spurious Emissions Radiated [dBμV/m]					
OFDM / n/ac HT40 – mode					
5755 MHz			5795 MHz		
F [MHz]	Detector	Level [dBμV/m]	F [MHz]	Detector	Level [dBμV/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.			For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
All detected peak emissions above 1 GHz are below the average limit. See plots!			All detected peak emissions above 1 GHz are below the average limit. See plots!		
Measurement uncertainty			± 3 dB		

Results: OFDM / ac – mode HT80

TX Spurious Emissions Radiated [dB μ V/m]		
OFDM / ac – mode HT80		
5775 MHz		
F [MHz]	Detector	Level [dB μ V/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
All detected peak emissions above 1 GHz are below the average limit. See plots!		
Measurement uncertainty	± 3 dB	

Result: **Passed**

Note: The limit was recalculated with 20 dB / decade (Part 15.31) for all radiated spurious emissions 30 MHz to 1 GHz from 3 meter limit to a 10 meter distance. (40dB/decade for emissions < 30MHz)


Plots: OFDM / a – mode**Plot 1:** Lowest channel, 30 MHz to 1 GHz, vertical & horizontal polarization**Common Information**

Serial Number: CB5126DAHf
 Test Description: FCC part 15 class B
 Operating Conditions: WLAN TX a-mode Ch. 149
 Operator Name: Wolsdorfer
 Comment: battery powered



Scan Setup: STAN_Fin [EMI radiated]



Hardware Setup: Electric Field (NOS)
 Receiver: [ESCI 3]
 Level Unit: dBμV/m

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.939650	15.7	1000.0	120.000	134.0	V	270.0	12.7	14.3	30.0	
36.015750	13.1	1000.0	120.000	135.0	V	175.0	13.1	16.9	30.0	
307.771800	11.5	1000.0	120.000	112.0	V	10.0	14.8	24.5	36.0	
499.049850	15.5	1000.0	120.000	98.0	V	180.0	18.7	20.5	36.0	
735.400650	20.5	1000.0	120.000	170.0	H	170.0	23.3	15.5	36.0	
926.406150	22.4	1000.0	120.000	170.0	V	0.0	25.3	13.6	36.0	

Plot 2: Lowest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization**Plot 3:** Lowest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization

Plot 4: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization**Plot 5:** Lowest channel, 26 GHz to 40 GHz, vertical & horizontal polarization

Plot 6: Middle channel, 30 MHz to 1 GHz, vertical & horizontal polarization


Common Information

Serial Number: CB5126DAHf
 Test Description: FCC part 15 class B
 Operating Conditions: WLAN TX a-mode Ch. 157
 Operator Name: Wolsdorfer
 Comment: battery powered

Scan Setup: STAN_Fin [EMI radiated]



Hardware Setup: Electric Field (NOS)
 Receiver: [ESCI 3]
 Level Unit: dBμV/m



Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.760250	15.0	1000.0	120.000	133.0	V	190.0	12.7	15.0	30.0	
41.339850	10.2	1000.0	120.000	98.0	H	85.0	13.4	19.8	30.0	
438.741900	14.1	1000.0	120.000	170.0	H	265.0	17.5	21.9	36.0	
733.482300	20.6	1000.0	120.000	170.0	H	100.0	23.3	15.4	36.0	
915.190500	22.3	1000.0	120.000	98.0	H	-3.0	25.2	13.7	36.0	
332.940000	13.7	1000.0	120.000	157.0	V	217.0	15.6	22.3	36.0	

Plot 7: Middle channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization**Plot 8:** Middle channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization

Plot 9: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization**Plot 10:** Middle channel, 26 GHz to 40 GHz, vertical & horizontal polarization

Plot 11: Highest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


Common Information

Serial Number: CB5126DAHf
 Test Description: FCC part 15 class B
 Operating Conditions: WLAN TX a-mode Ch. 165
 Operator Name: Wolsdorfer
 Comment: battery powered

Scan Setup: STAN_Fin [EMI radiated]



Hardware Setup: Electric Field (NOS)
 Receiver: [ESCI 3]
 Level Unit: dBμV/m



Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.552350	14.6	1000.0	120.000	127.0	V	280.0	12.7	15.4	30.0	
51.032550	10.5	1000.0	120.000	132.0	V	100.0	13.3	19.5	30.0	
317.432700	11.6	1000.0	120.000	170.0	H	170.0	15.1	24.4	36.0	
637.800900	18.2	1000.0	120.000	170.0	V	177.0	21.0	17.8	36.0	
732.840900	20.5	1000.0	120.000	170.0	V	80.0	23.3	15.5	36.0	
936.057300	22.4	1000.0	120.000	170.0	H	0.0	25.3	13.6	36.0	

Plot 12: Highest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization**Plot 13:** Highest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization

Plot 14: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization**Plot 15:** Highest channel, 26 GHz to 40 GHz, vertical & horizontal polarization


Plots: OFDM / n/ac HT20 – mode**Plot 1:** Lowest channel, 30 MHz to 1 GHz, vertical & horizontal polarization**Common Information**

Serial Number: CB5126DAHf
 Test Description: FCC part 15 class B
 Operating Conditions: WLAN TX n-mode (HT 20) Ch. 149
 Operator Name: Wolsdorfer
 Comment: battery powered



Scan Setup: STAN_Fin [EMI radiated]



Hardware Setup: Electric Field (NOS)
 Receiver: [ESCI 3]
 Level Unit: dBμV/m

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
41.259000	10.3	1000.0	120.000	170.0	H	0.0	13.4	19.7	30.0	
291.927600	11.0	1000.0	120.000	105.0	V	190.0	14.3	25.0	36.0	
509.977800	20.6	1000.0	120.000	98.0	V	10.0	18.8	15.4	36.0	
629.725800	18.2	1000.0	120.000	98.0	H	280.0	21.0	17.8	36.0	
734.849550	20.6	1000.0	120.000	147.0	V	182.0	23.3	15.4	36.0	
928.326450	22.3	1000.0	120.000	132.0	H	2.0	25.3	13.7	36.0	

Plot 2: Lowest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization**Plot 3:** Lowest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization

Plot 4: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization**Plot 5:** Lowest channel, 26 GHz to 40 GHz, vertical & horizontal polarization

Plot 6: Middle channel, 30 MHz to 1 GHz, vertical & horizontal polarization


Common Information

Serial Number: CB5126DAHf
 Test Description: FCC part 15 class B
 Operating Conditions: WLAN TX n-mode (HT 20) Ch. 157
 Operator Name: Wolsdorfer
 Comment: battery powered

Scan Setup: STAN_Fin [EMI radiated]



Hardware Setup: Electric Field (NOS)
 Receiver: [ESCI 3]
 Level Unit: dBμV/m



Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
35.771400	10.4	1000.0	120.000	170.0	H	270.0	13.1	19.6	30.0	
45.111600	10.1	1000.0	120.000	170.0	H	100.0	13.3	19.9	30.0	
418.388400	13.8	1000.0	120.000	170.0	V	10.0	17.2	22.2	36.0	
669.645150	18.9	1000.0	120.000	170.0	H	-3.0	21.7	17.1	36.0	
732.882150	20.5	1000.0	120.000	170.0	H	265.0	23.3	15.5	36.0	
871.723350	22.2	1000.0	120.000	170.0	H	10.0	24.8	13.8	36.0	

Plot 7: Middle channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization**Plot 8:** Middle channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization

Plot 9: Middle channel, 18 GHz to 26 GHz, vertical & horizontal polarization**Plot 10:** Middle channel, 26 GHz to 40 GHz, vertical & horizontal polarization

Plot 11: Highest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


Common Information

Serial Number: CB5126DAHf
 Test Description: FCC part 15 class B
 Operating Conditions: WLAN TX n-mode (HT 20) Ch. 165
 Operator Name: Wolsdorfer
 Comment: battery powered

Scan Setup: STAN_Fin [EMI radiated]



Hardware Setup: Electric Field (NOS)
 Receiver: [ESCI 3]
 Level Unit: dBμV/m



Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
36.584850	10.1	1000.0	120.000	162.0	H	190.0	13.2	19.9	30.0	
45.247350	10.2	1000.0	120.000	98.0	H	93.0	13.3	19.8	30.0	
310.300350	11.4	1000.0	120.000	170.0	H	10.0	14.8	24.6	36.0	
642.396150	18.2	1000.0	120.000	170.0	H	92.0	21.1	17.8	36.0	
889.471500	22.3	1000.0	120.000	170.0	V	2.0	25.1	13.7	36.0	
930.474600	22.5	1000.0	120.000	170.0	H	171.0	25.3	13.5	36.0	

Plot 12: Highest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization**Plot 13:** Highest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization

Plot 14: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization**Plot 15:** Highest channel, 26 GHz to 40 GHz, vertical & horizontal polarization


Plots: OFDM / n/ac HT40 – mode**Plot 1:** Lowest channel, 30 MHz to 1 GHz, vertical & horizontal polarization**Common Information**

Serial Number: CB5126DAHf
 Test Description: FCC part 15 class B
 Operating Conditions: WLAN TX n-mode (HT 40) Ch. 151
 Operator Name: Wolsdorfer
 Comment: battery powered



Scan Setup: STAN_Fin [EMI radiated]



Hardware Setup: Electric Field (NOS)
 Receiver: [ESCI 3]
 Level Unit: dBμV/m

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.962750	13.1	1000.0	120.000	162.0	V	280.0	12.7	16.9	30.0	
36.451350	10.2	1000.0	120.000	143.0	H	92.0	13.1	19.8	30.0	
333.441000	12.1	1000.0	120.000	170.0	H	88.0	15.6	23.9	36.0	
529.669200	16.8	1000.0	120.000	119.0	V	260.0	19.1	19.2	36.0	
735.277950	20.6	1000.0	120.000	98.0	V	265.0	23.3	15.4	36.0	
932.500500	22.4	1000.0	120.000	170.0	H	280.0	25.3	13.6	36.0	

Plot 2: Lowest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization**Plot 3:** Lowest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization

Plot 4: Lowest channel, 18 GHz to 26 GHz, vertical & horizontal polarization**Plot 5:** Lowest channel, 26 GHz to 40 GHz, vertical & horizontal polarization

Plot 6: Highest channel, 30 MHz to 1 GHz, vertical & horizontal polarization


Common Information

Serial Number: CB5126DAHf
 Test Description: FCC part 15 class B
 Operating Conditions: WLAN TX n-mode (HT 40) Ch. 159
 Operator Name: Wolsdorfer
 Comment: battery powered

Scan Setup: STAN_Fin [EMI radiated]



Hardware Setup: Electric Field (NOS)
 Receiver: [ESCI 3]
 Level Unit: dBμV/m



Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.683150	13.8	1000.0	120.000	170.0	V	100.0	12.7	16.2	30.0	
39.268800	10.0	1000.0	120.000	152.0	V	177.0	13.4	20.0	30.0	
49.476900	9.6	1000.0	120.000	170.0	H	261.0	13.4	20.4	30.0	
639.527250	18.2	1000.0	120.000	120.0	H	171.0	21.0	17.8	36.0	
700.354500	19.8	1000.0	120.000	170.0	H	182.0	22.5	16.2	36.0	
930.413850	22.4	1000.0	120.000	170.0	H	100.0	25.3	13.6	36.0	

Plot 7: Highest channel, 1 GHz to 12.75 GHz, vertical & horizontal polarization**Plot 8:** Highest channel, 12.75 GHz to 18 GHz, vertical & horizontal polarization

Plot 9: Highest channel, 18 GHz to 26 GHz, vertical & horizontal polarization**Plot 10:** Highest channel, 26 GHz to 40 GHz, vertical & horizontal polarization


Plots: OFDM / ac HT80 – mode**Plot 1:** 30 MHz to 1 GHz, vertical & horizontal polarization**Common Information**

Serial Number: CB5126DAHf
 Test Description: FCC part 15 class B
 Operating Conditions: WLAN TX ac-mode (HT 80) Ch. 155
 Operator Name: Wolsdorfer
 Comment: battery powered



Scan Setup: STAN_Fin [EMI radiated]



Hardware Setup: Electric Field (NOS)
 Receiver: [ESCI 3]
 Level Unit: dBμV/m

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.610250	13.5	1000.0	120.000	170.0	V	90.0	12.7	16.5	30.0	
46.075500	12.2	1000.0	120.000	170.0	V	280.0	13.3	17.8	30.0	
458.459850	14.5	1000.0	120.000	170.0	V	-4.0	17.8	21.5	36.0	
558.357450	18.1	1000.0	120.000	170.0	H	270.0	19.6	17.9	36.0	
722.599350	20.3	1000.0	120.000	160.0	V	10.0	23.0	15.7	36.0	
936.331800	22.4	1000.0	120.000	170.0	H	-5.0	25.3	13.6	36.0	

Plot 2: 1 GHz to 12.75 GHz, vertical & horizontal polarization**Plot 3:** 12.75 GHz to 18 GHz, vertical & horizontal polarization

Plot 4: 18 GHz to 26 GHz, vertical & horizontal polarization**Plot 5:** 26 GHz to 40 GHz, vertical & horizontal polarization

10.2 RX spurious emissions radiated

Description:

Measurement of the radiated spurious emissions in idle/receive mode. The results are valid for both modes.

Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak / RMS
Sweep time:	Auto
Resolution bandwidth:	F > 1 GHz: 1 MHz F < 1 GHz: 100 kHz
Video bandwidth:	3 x RBW Re-measurement: 10 Hz / 3 MHz
Span:	30 MHz to 40 GHz
Trace-Mode:	Max Hold

Limits:

FCC		
RX Spurious Emissions Radiated		
Frequency (MHz)	Field Strength (dB μ V/m)	Measurement distance
30 - 88	30.0	10
88 – 216	33.5	10
216 – 960	36.0	10
Above 960	54.0	3

Results:

RX Spurious Emissions Radiated [dB μ V/m]		
F [MHz]	Detector	Level [dB μ V/m]
For emissions below 1 GHz, please take a look at the table below the 1 GHz plot.		
All detected peak emissions above 1 GHz are below the average limit. See plots!		
Measurement uncertainty	± 3 dB	

Result: Passed.

Note: The limit was recalculated with 20 dB / decade (Part 15.31) for all radiated spurious emissions 30 MHz to 1 GHz from 3 meter limit to a 10 meter distance. (40dB/decade for emissions < 30MHz)


Plots: RX / Idle – mode**Plot 1:** 30 MHz to 1 GHz, vertical & horizontal polarization**Common Information**

Serial Number: CB5126DAHf
 Test Description: FCC part 15 class B
 Operating Conditions: WLAN RX
 Operator Name: Hennemann
 Comment: battery powered



Scan Setup: STAN_Fin [EMI radiated]



Hardware Setup: Electric Field (NOS)
 Receiver: [ESCI 3]
 Level Unit: dBμV/m

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
30 MHz - 2 GHz	60 kHz	QPK	120 kHz	1 s	20 dB

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.703100	15.2	1000.0	120.000	98.0	V	100.0	12.7	14.8	30.0	
40.063950	10.7	1000.0	120.000	170.0	V	178.0	13.4	19.3	30.0	
46.012500	10.7	1000.0	120.000	98.0	V	-10.0	13.3	19.3	30.0	
704.545950	19.9	1000.0	120.000	170.0	H	100.0	22.6	16.1	36.0	
794.278350	20.9	1000.0	120.000	170.0	V	100.0	23.8	15.1	36.0	
910.534050	22.3	1000.0	120.000	154.0	V	10.0	25.2	13.7	36.0	

Plot 2: 1 GHz to 12.75 GHz, vertical & horizontal polarization**Plot 3:** 12.75 GHz to 18 GHz, vertical & horizontal polarization

Plot 4: 18 GHz to 26 GHz, vertical & horizontal polarization**Plot 5:** 26 GHz to 40 GHz, vertical & horizontal polarization

10.3 Spurious emissions radiated < 30 MHz

Description:

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The EUT is set to mid channel. This measurement is representative for all channels and modes. If peaks are found the lowest channel and the highest channel will be measured too. The measurement is performed with the data rate producing the highest output power. The limits are recalculated to a measurement distance of 3 m with 40 dB/decade according CFR Part 2.

Measurement:

Measurement parameter	
Detector:	Peak / Quasi Peak
Sweep time:	Auto
Video bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Resolution bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace-Mode:	Max Hold

Limits:

FCC		
TX Spurious Emissions Radiated < 30 MHz		
Frequency (MHz)	Field Strength (dBμV/m)	Measurement distance
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30


Results:

TX Spurious Emissions Radiated < 30 MHz [dBμV/m]		
F [MHz]	Detector	Level [dBμV/m]
No peaks detected.		
Measurement uncertainty	± 3 dB	

Result: Passed


Plots: TX mode

Plot 1: 9 kHz to 30 MHz



Plots: RX / Idle – mode

Plot 1: 9 kHz to 30 MHz



10.4 Spurious emissions conducted < 30 MHz

Description:

Measurement of the conducted spurious emissions in transmit mode below 30 MHz. The EUT is set to mid channel. If peaks are found the lowest channel and the highest channel will be measured too. The measurement is performed with the data rate producing the highest output power. Both power lines, phase and neutral line, are measured. Found peaks are re-measured with average and quasi peak detection to show compliance to the limits.

Measurement:

Measurement parameter	
Detector:	Peak - Quasi Peak / Average
Sweep time:	Auto
Video bandwidth:	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz
Resolution bandwidth:	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz
Span:	9 kHz to 30 MHz
Trace-Mode:	Max Hold

Limits:



FCC		
TX Spurious Emissions Conducted < 30 MHz		
Frequency (MHz)	Quasi-Peak (dBμV/m)	Average (dBμV/m)
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30.0	60	50

*Decreases with the logarithm of the frequency


Results:

TX Spurious Emissions Conducted < 30 MHz [dBμV/m]		
F [MHz]	Detector	Level [dBμV/m]
No peaks detected.		
Measurement uncertainty	± 3 dB	


Result: Passed

Plots:**Plot 1: TX mode, 150 kHz to 30 MHz, phase line****Plot 2: TX mode, 150 kHz to 30 MHz, neutral line**

Plot 3: RX / Idle – mode, 150 kHz to 30 MHz, phase line



Plot 4: RX / Idle – mode, 150 kHz to 30 MHz, neutral line



11 Test equipment and ancillaries used for tests

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, rf-generating and signalling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).

No.	Lab / Item	Equipment	Type	Manufact.	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	45	Switch-Unit	3488A	HP Meßtechnik	2719A14505	300000368	g		
2	50	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP Meßtechnik	2920A04466	300000580	ne		
3	n. a.	EMI Test Receiver	ESCI 3	R&S	100083	300003312	k	27.01.2014	27.01.2015
4	n. a.	Antenna Tower	Model 2175	ETS-LINDGREN	64762	300003745	izw		
5	n. a.	Positioning Controller	Model 2090	ETS-LINDGREN	64672	300003746	izw		
6	n. a.	Turntable Interface-Box	Model 105637	ETS-LINDGREN	44583	300003747	izw		
7	n. a.	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	295	300003787	k	12.04.2012	12.04.2014
8	n. a.	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	8812-3088	300001032	vIKII	08.05.2013	08.05.2015
9	n. a.	Anechoic chamber	FAC 3/5m	MWB / TDK	87400/02	300000996	ev		
10	n. a.	Switch / Control Unit	3488A	HP Meßtechnik	*	300000199	ne		
11	n. a.	Switch / Control Unit	3488A	HP Meßtechnik	2719A15013	300001156	ne		
12	9	Isolating Transformer	MPL IEC625 Bus Regeltrennt ravo	Erfi	91350	300001155	ne		
13	n. a.	Three-Way Power Splitter, 50 Ohm	11850C	HP Meßtechnik		300000997	ne		
14	90	Active Loop Antenna 10 kHz to 30 MHz	6502	Kontron Psychotech	8905-2342	300000256	k	13.06.2013	13.06.2015
15	n. a.	Amplifier	js42-00502650-28-5a	Parzich GMBH	928979	300003143	ne		
16	n. a.	MXE EMI Receiver 20 Hz bis 26,5 GHz	N9038A	Agilent Technologies	MY51210197	300004405	k	21.02.2013	21.02.2015
17	11b	Microwave System Amplifier, 0,5-26,5 GHz	83017A	HP Meßtechnik	00419	300002268	ev		
18	A026	Std. Gain Horn Antenna 12.4 to 18.0 GHz	639	Narda	8402	300000787	k	22.07.2013	22.07.2015
19	A029	Std. Gain Horn Antenna 18.0 to 26.5 GHz	638	Narda	8205	300002442	k	19.07.2013	19.07.2015
20	A031	Std. Gain Horn Antenna 26.5 to 40.0 GHz	637	Narda		300000510	k	19.07.2013	19.07.2015
21	n. a.	Broadband Low Noise Amplifier 18-50 GHz	CBL18503 070-XX	CERNEX	19338	300004273	ne		
22	n. a.	Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517	k	21.01.2014	21.01.2015

Agenda: Kind of Calibration

k	calibration / calibrated	EK	limited calibration
ne	not required (k, ev, izw, zw not required)	zw	cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlk!	Attention: extended calibration interval		
NK!	Attention: not calibrated	*)	next calibration ordered / currently in progress

12 Observations

No observations exceeding those reported with the single test cases have been made.

Annex A Document history

Version	Applied changes	Date of release
	Initial release	2014-02-26
A	Editorial change	2014-03-17

Annex B Further information**Glossary**


AVG	-	Average
DUT	-	Device under test
EMC	-	Electromagnetic Compatibility
EN	-	European Standard
EUT	-	Equipment under test
ETSI	-	European Telecommunications Standard Institute
FCC	-	Federal Communication Commission
FCC ID	-	Company Identifier at FCC
HW	-	Hardware
IC	-	Industry Canada
Inv. No.	-	Inventory number
N/A	-	Not applicable
PP	-	Positive peak
QP	-	Quasi peak
S/N	-	Serial number
SW	-	Software

Annex C Accreditation Certificate

Front side of certificate



Back side of certificate



Note:

The current certificate including annex is published on our website (see link below) or may be received from CETECOM ICT Services on request.

<http://www.cetecom.com/eu/de/cetecom-group/europa/deutschland-saarbruecken/akkreditierungen.html>