


## GSM 850

Frequency: 824.2 MHz; Duty Cycle: 1:2.60016; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used:  $f = 825 \text{ MHz}$ ;  $\sigma = 1.005 \text{ S/m}$ ;  $\epsilon_r = 53.663$ ;  $\rho = 1000 \text{ kg/m}^3$   
 DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(8.77, 8.77, 8.77); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI-B v5.0; Type: QDOVA001BB; Serial: 1215

**Rear/GPRS\_3 Slot\_Ch. 128\_Sensor ON/Area Scan (11x17x1):** Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (measured) = 1.73 W/kg

**Rear/GPRS\_3 Slot\_Ch. 128\_Sensor ON/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm  
 Reference Value = 41.92 V/m; Power Drift = 0.02 dB  
 Peak SAR (extrapolated) = 2.42 W/kg  
**SAR(1 g) = 1.29 W/kg; SAR(10 g) = 0.752 W/kg**  
 Maximum value of SAR (measured) = 1.70 W/kg



0 dB = 1.70 W/kg = 2.30 dBW/kg

## GSM 1900

Frequency: 1909.8 MHz; Duty Cycle: 1:4.00037; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used:  $f = 1910 \text{ MHz}$ ;  $\sigma = 1.51 \text{ S/m}$ ;  $\epsilon_r = 51.865$ ;  $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(6.9, 6.9, 6.9); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI-B v5.0; Type: QDOVA001BB; Serial: 1215

**Rear/GPRS\_2 Slot\_Ch. 810\_Sensor ON/Area Scan (11x17x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.77 W/kg


**Rear/GPRS\_2 Slot\_Ch. 810\_Sensor ON/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 34.13 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 2.57 W/kg

**SAR(1 g) = 1.24 W/kg; SAR(10 g) = 0.570 W/kg**

Maximum value of SAR (measured) = 1.60 W/kg



0 dB = 1.60 W/kg = 2.04 dBW/kg

## W-CDMA Band V

Frequency: 846.6 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used (interpolated):  $f = 846.6 \text{ MHz}$ ;  $\sigma = 1.028 \text{ S/m}$ ;  $\epsilon_r = 53.445$ ;  $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(8.77, 8.77, 8.77); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI-B v5.0; Type: QDOVA001BB; Serial: 1215

### Rear/Rel.99\_RMC\_12.2\_kbps Ch.4233\_Sensor ON/Area Scan (11x17x1): Measurement grid:

$dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.32 W/kg

### Rear/Rel.99\_RMC\_12.2\_kbps Ch.4233\_Sensor ON/Zoom Scan (5x5x7)/Cube 0: Measurement grid:

$dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 35.46 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 2.25 W/kg

**SAR(1 g) = 1.18 W/kg; SAR(10 g) = 0.680 W/kg**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.62 W/kg



0 dB = 1.62 W/kg = 2.10 dBW/kg

## W-CDMA Band IV

Frequency: 1732.6 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used (interpolated):  $f = 1732.6$  MHz;  $\sigma = 1.502$  S/m;  $\epsilon_r = 51.626$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(7.13, 7.13, 7.13); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI v5.0 (A); Type: QDOVA001BB; Serial: 1213

### Rear/Rel.99\_RMC\_12.2\_kbps Ch.1413\_Sensor ON/Area Scan (11x17x1): Measurement grid:

dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.57 W/kg

### Rear/Rel.99\_RMC\_12.2\_kbps Ch.1413\_Sensor ON/Zoom Scan (5x5x7)/Cube 0: Measurement grid:

grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 32.78 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 2.72 W/kg

**SAR(1 g) = 1.33 W/kg; SAR(10 g) = 0.667 W/kg**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.81 W/kg



0 dB = 1.81 W/kg = 2.58 dBW/kg

## W-CDMA Band II

Frequency: 1880 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used:  $f = 1880 \text{ MHz}$ ;  $\sigma = 1.481 \text{ S/m}$ ;  $\epsilon_r = 51.976$ ;  $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(6.9, 6.9, 6.9); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI-B v5.0; Type: QDOVA001BB; Serial: 1215

### Rear/Rel. 99\_RMC 12.2 kbps\_Ch 9400\_Sensor ON/Area Scan (11x17x1): Measurement grid:

$dx=15\text{mm}$ ,  $dy=15\text{mm}$

Maximum value of SAR (measured) = 1.20 W/kg

### Rear/Rel. 99\_RMC 12.2 kbps\_Ch 9400\_Sensor ON/Zoom Scan (5x5x7)/Cube 0: Measurement grid:


grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 30.68 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 2.51 W/kg

**SAR(1 g) = 1.2 W/kg; SAR(10 g) = 0.566 W/kg**

Maximum value of SAR (measured) = 1.61 W/kg



0 dB = 1.61 W/kg = 2.07 dBW/kg

## LTE Band 2

Frequency: 1900 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used:  $f = 1900 \text{ MHz}$ ;  $\sigma = 1.5 \text{ S/m}$ ;  $\epsilon_r = 51.902$ ;  $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(6.9, 6.9, 6.9); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI-B v5.0; Type: QDOVA001BB; Serial: 1215

**Rear/QPSK\_RB 50/50\_Ch.19100\_Sensor ON/Area Scan (11x17x1):** Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.08 W/kg

**Rear/QPSK\_RB 50/50\_Ch.19100\_Sensor ON/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:


dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.98 V/m; Power Drift = 0.06 dB

Peak SAR (extrapolated) = 2.41 W/kg

**SAR(1 g) = 1.2 W/kg; SAR(10 g) = 0.565 W/kg**

Maximum value of SAR (measured) = 1.70 W/kg



0 dB = 1.70 W/kg = 2.30 dBW/kg

## LTE Band 4

Frequency: 1732.5 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used (interpolated):  $f = 1732.5$  MHz;  $\sigma = 1.502$  S/m;  $\epsilon_r = 51.627$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(7.13, 7.13, 7.13); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI v5.0 (A); Type: QDOVA001BB; Serial: 1213

**Rear/QPSK\_RB 50/24\_Ch.20175\_Sensor ON/Area Scan (11x17x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.57 W/kg

**Rear/QPSK\_RB 50/24\_Ch.20175\_Sensor ON/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm


Reference Value = 32.94 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 2.81 W/kg

**SAR(1 g) = 1.35 W/kg; SAR(10 g) = 0.673 W/kg**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.94 W/kg



0 dB = 1.94 W/kg = 2.88 dBW/kg

## LTE Band 5

Frequency: 844 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used (interpolated):  $f = 844 \text{ MHz}$ ;  $\sigma = 1.018 \text{ S/m}$ ;  $\epsilon_r = 53.541$ ;  $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(8.77, 8.77, 8.77); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI-B v5.0; Type: QDOVA001BB; Serial: 1215

### Rear (8\_18)/QPSK\_RB 25/0\_Ch.20600\_Sensor ON/Area Scan (7x7x1): Measurement grid:

$dx=15\text{mm}$ ,  $dy=15\text{mm}$

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.51 W/kg

### Rear (8\_18)/QPSK\_RB 25/0\_Ch.20600\_Sensor ON/Zoom Scan (5x5x7)/Cube 0: Measurement grid:

grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$


Reference Value = 38.96 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.49 W/kg

**SAR(1 g) = 1.26 W/kg; SAR(10 g) = 0.719 W/kg**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.74 W/kg



0 dB = 1.74 W/kg = 2.41 dBW/kg

## LTE Band 7

Frequency: 2560 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C

Medium parameters used:  $f = 2560$  MHz;  $\sigma = 2.182$  S/m;  $\epsilon_r = 50.381$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(6.44, 6.44, 6.44); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI-B v5.0; Type: QDOVA001BB; Serial: 1215

### Rear/QPSK\_RB 1/49\_Ch 21350 Sensoring ON/Area Scan (11x17x1): Measurement grid:

$dx=15$ mm,  $dy=15$ mm

Maximum value of SAR (measured) = 1.46 W/kg

### Rear/QPSK\_RB 1/49\_Ch 21350 Sensoring ON/Zoom Scan (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm,  $dy=5$ mm,  $dz=5$ mm

Reference Value = 26.03 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.62 W/kg

**SAR(1 g) = 1.02 W/kg; SAR(10 g) = 0.491 W/kg**

Maximum value of SAR (measured) = 1.51 W/kg



0 dB = 1.51 W/kg = 1.79 dBW/kg

## LTE Band 13

Frequency: 782 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used (interpolated):  $f = 782 \text{ MHz}$ ;  $\sigma = 1.001 \text{ S/m}$ ;  $\epsilon_r = 53.749$ ;  $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(8.79, 8.79, 8.79); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI-B v5.0; Type: QDOVA001BB; Serial: 1215

**Rear/QPSK\_RB 50/0\_Ch.23230\_Sensor ON/Area Scan (11x17x1):** Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.10 W/kg

**Rear/QPSK\_RB 50/0\_Ch.23230\_Sensor ON/Zoom Scan (5x5x7)/Cube 0:** Measurement grid:

dx=8mm, dy=8mm, dz=5mm


Reference Value = 33.63 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.91 W/kg

**SAR(1 g) = 1 W/kg; SAR(10 g) = 0.582 W/kg**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.36 W/kg



0 dB = 1.36 W/kg = 1.34 dBW/kg

## LTE Band 17

Frequency: 710 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used:  $f = 710 \text{ MHz}$ ;  $\sigma = 0.929 \text{ S/m}$ ;  $\epsilon_r = 54.455$ ;  $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(8.79, 8.79, 8.79); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI-B v5.0; Type: QDOVA001BB; Serial: 1215

**Rear/QPSK\_RB 1/0\_Ch.23790\_Sensor ON/Area Scan (11x17x1):** Measurement grid: dx=15mm, dy=15mm  
 Maximum value of SAR (measured) = 1.23 W/kg


**Rear/QPSK\_RB 1/0\_Ch.23790\_Sensor ON/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 37.02 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.47 W/kg

**SAR(1 g) = 1.23 W/kg; SAR(10 g) = 0.698 W/kg**

Maximum value of SAR (measured) = 1.72 W/kg



0 dB = 1.72 W/kg = 2.36 dBW/kg

## Wi-Fi 2.4 GHz (b Mode)

Frequency: 2462 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used (interpolated):  $f = 2462$  MHz;  $\sigma = 2.032$  S/m;  $\epsilon_r = 50.725$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(6.67, 6.67, 6.67); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI-B v5.0; Type: QDOVA001BB; Serial: 1215

**Rear/802.11b\_Ch.11\_MIMO\_Sensor ON/Area Scan (13x9x1):** Measurement grid: dx=12mm, dy=12mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.36 W/kg

**Rear/802.11b\_Ch.11\_MIMO\_Sensor ON/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.91 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 3.21 W/kg

**SAR(1 g) = 1.03 W/kg; SAR(10 g) = 0.425 W/kg**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 1.62 W/kg


**Rear/802.11b\_Ch.11\_MIMO\_Sensor ON/Zoom Scan 2 (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 25.91 V/m; Power Drift = -0.17 dB

Peak SAR (extrapolated) = 2.16 W/kg

**SAR(1 g) = 0.883 W/kg; SAR(10 g) = 0.329 W/kg**

[Info: Interpolated medium parameters used for SAR evaluation.](#)



0 dB = 1.36 W/kg = 1.34 dBW/kg

## Wi-Fi 5 GHz

Frequency: 5200 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used:  $f = 5200 \text{ MHz}$ ;  $\sigma = 5.292 \text{ S/m}$ ;  $\epsilon_r = 47.768$ ;  $\rho = 1000 \text{ kg/m}^3$


DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1352; Calibrated: 9/11/2013
- Probe: EX3DV4 - SN3929; ConvF(4.19, 4.19, 4.19); Calibrated: 5/9/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Phantom: ELI A (v5.0); Type: QDOVA001BB; Serial: S/n:1212

**Edge 3/802.11a\_Ch.40\_MIMO/Area Scan (8x15x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
 Maximum value of SAR (measured) = 2.71 W/kg

**Edge 3/802.11a\_Ch.40\_MIMO/Zoom Scan (7x7x12)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  
 $dz=2\text{mm}$   
 Reference Value = 22.68 V/m; Power Drift = -0.02 dB  
 Peak SAR (extrapolated) = 5.48 W/kg  
**SAR(1 g) = 1.26 W/kg; SAR(10 g) = 0.337 W/kg**  
 Maximum value of SAR (measured) = 2.72 W/kg

**Edge 3/802.11a\_Ch.40\_MIMO/Zoom Scan 2 (7x7x12)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  
 $dz=2\text{mm}$   
 Reference Value = 22.68 V/m; Power Drift = -0.02 dB  
 Peak SAR (extrapolated) = 4.93 W/kg  
**SAR(1 g) = 1.13 W/kg; SAR(10 g) = 0.315 W/kg**  
 Maximum value of SAR (measured) = 2.48 W/kg



0 dB = 2.48 W/kg = 3.94 dBW/kg

## Wi-Fi 5 GHz

Frequency: 5260 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used:  $f = 5260 \text{ MHz}$ ;  $\sigma = 5.356 \text{ S/m}$ ;  $\epsilon_r = 47.687$ ;  $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1352; Calibrated: 9/11/2013
- Probe: EX3DV4 - SN3929; ConvF(4.04, 4.04, 4.04); Calibrated: 5/9/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection)
- Phantom: ELI A (v5.0); Type: QDOVA001BB; Serial: S/n:1212

**Edge 3/802.11a\_Ch.52\_MIMO/Area Scan (8x15x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
 Maximum value of SAR (measured) = 2.58 W/kg

**Edge 3/802.11a\_Ch.52\_MIMO/Zoom Scan (7x7x12)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=2\text{mm}$

Reference Value = 21.78 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 5.17 W/kg

**SAR(1 g) = 1.19 W/kg; SAR(10 g) = 0.314 W/kg**

Maximum value of SAR (measured) = 2.54 W/kg


**Edge 3/802.11a\_Ch.52\_MIMO/Zoom Scan 2 (7x7x12)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  $dz=2\text{mm}$

Reference Value = 21.78 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 4.80 W/kg

**SAR(1 g) = 1.11 W/kg; SAR(10 g) = 0.314 W/kg**

Maximum value of SAR (measured) = 2.35 W/kg



0 dB = 2.35 W/kg = 3.71 dBW/kg

## Wi-Fi 5 GHz

Frequency: 5580 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used:  $f = 5580 \text{ MHz}$ ;  $\sigma = 5.951 \text{ S/m}$ ;  $\epsilon_r = 47.106$ ;  $\rho = 1000 \text{ kg/m}^3$


DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1352; Calibrated: 9/11/2013
- Probe: EX3DV4 - SN3929; ConvF(3.66, 3.66, 3.66); Calibrated: 5/9/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Phantom: ELI A (v5.0); Type: QDOVA001BB; Serial: S/n:1212

**Rear/802.11a\_Ch.116\_MIMO/Area Scan (14x9x1):** Measurement grid:  $dx=10\text{mm}$ ,  $dy=10\text{mm}$   
 Maximum value of SAR (measured) = 1.85 W/kg

**Rear/802.11a\_Ch.116\_MIMO/Zoom Scan (7x7x12)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  
 $dz=2\text{mm}$   
 Reference Value = 17.49 V/m; Power Drift = 0.02 dB  
 Peak SAR (extrapolated) = 5.52 W/kg  
**SAR(1 g) = 0.937 W/kg; SAR(10 g) = 0.288 W/kg**  
 Maximum value of SAR (measured) = 2.12 W/kg

**Rear/802.11a\_Ch.116\_MIMO/Zoom Scan 2 (7x7x12)/Cube 0:** Measurement grid:  $dx=4\text{mm}$ ,  $dy=4\text{mm}$ ,  
 $dz=2\text{mm}$   
 Reference Value = 17.49 V/m; Power Drift = 0.02 dB  
 Peak SAR (extrapolated) = 3.06 W/kg  
**SAR(1 g) = 0.453 W/kg; SAR(10 g) = 0.167 W/kg**  
 Maximum value of SAR (measured) = 0.977 W/kg



0 dB = 0.977 W/kg = -0.10 dBW/kg

## Wi-Fi 5 GHz

Frequency: 5825 MHz; Duty Cycle: 1:1; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used:  $f = 5825 \text{ MHz}$ ;  $\sigma = 6.293 \text{ S/m}$ ;  $\epsilon_r = 46.684$ ;  $\rho = 1000 \text{ kg/m}^3$

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1352; Calibrated: 9/11/2013
- Probe: EX3DV4 - SN3929; ConvF(3.9, 3.9, 3.9); Calibrated: 5/9/2014;
- Sensor-Surface: 2mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 2mm (Mechanical Surface Detection)
- Phantom: ELI A (v5.0); Type: QDOVA001BB; Serial: S/n:1212

**Rear/802.11a\_Ch.165\_MIMO/Area Scan (14x9x1):** Measurement grid: dx=10mm, dy=10mm  
 Maximum value of SAR (measured) = 0.990 W/kg

**Rear/802.11a\_Ch.165\_MIMO/Zoom Scan (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 12.53 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 3.43 W/kg

**SAR(1 g) = 0.547 W/kg; SAR(10 g) = 0.181 W/kg**

Maximum value of SAR (measured) = 1.20 W/kg


**Rear/802.11a\_Ch.165\_MIMO/Zoom Scan 2 (7x7x12)/Cube 0:** Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 12.53 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.47 W/kg

**SAR(1 g) = 0.195 W/kg; SAR(10 g) = 0.087 W/kg**

Maximum value of SAR (measured) = 0.439 W/kg



0 dB = 0.439 W/kg = -3.58 dBW/kg

## Bluetooth 2.4 GHz

Frequency: 2441 MHz; Duty Cycle: 1:1.29033; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C  
 Medium parameters used (interpolated):  $f = 2441$  MHz;  $\sigma = 2.008$  S/m;  $\epsilon_r = 50.787$ ;  $\rho = 1000$  kg/m<sup>3</sup>

DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1380; Calibrated: 7/23/2014
- Probe: EX3DV4 - SN3773; ConvF(6.67, 6.67, 6.67); Calibrated: 4/22/2014;
- Sensor-Surface: 2.5mm (Mechanical Surface Detection)
- Phantom: ELI-B v5.0; Type: QDOVA001BB; Serial: 1215

**Rear/DH5\_GFSK\_Ch.39/Area Scan (13x9x1):** Measurement grid: dx=12mm, dy=12mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.339 W/kg

**Rear/DH5\_GFSK\_Ch.39/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 13.17 V/m; Power Drift = -0.11 dB

Peak SAR (extrapolated) = 0.519 W/kg

**SAR(1 g) = 0.166 W/kg; SAR(10 g) = 0.061 W/kg**

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.287 W/kg



0 dB = 0.287 W/kg = -5.42 dBW/kg