



Test Setup photos for HD-1 SAR Compliance Test Report

Test report no.: **Template version: Testing laboratory:** Salo SAR 0917 03 11.0

TCC Nokia Copenhagen Lab. 1790 COPENHAGEN V, DENMARK

TCC Nokia Salo Laboratory

P.O.Box 86

FIN-24101 SALO, FINLAND

Date of report: **Number of pages:**

Client:

2009-04-23

Nokia Corporation

PL/P.O. Box 407 Itämerenkatu 11-13 FIN-00180 HELSINKI

FINLAND

Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 36227

Responsible test engineer:

Measurements made by:

Virpi Tuominen

Leif Klysner

person:

Product contact

Mikko Lyytikäinen

Tested device:

HD-1

PYAHD-1 FCC ID:

IC: 661V-HD1

Supplement reports:

Salo_SAR_0917_02

Testing has been carried out in accordance with:

47CFR §2.1093

Radiofreguency Radiation Exposure Evaluation: Portable Devices

FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01)

Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency

Electromagnetic Fields

RSS-102

Evaluation Procedure for Mobile and Portable Radio Transmitters with Respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields

IEEE 1528 - 2003

IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices:

Measurement Technique

Documentation:

The documentation of the testing performed on the tested devices is archived for 15 years at

TCC Nokia.

Test results:

The tested device complies with the requirements in respect of all parameters subject to the **test.** The test results and statements relate only to the items tested. The test report shall not

be reproduced except in full, without written approval of the laboratory.

Date and signatures:

For the contents:





CONTENTS

1.	SUMI	MARY OF SAR TEST REPORT	3
	1.1	TEST DETAILS	.3
	1.2	PICTURE OF THE DEVICE	.3
2.	TEST	POSITIONS	3
	21	RODY WORN CONFIGURATION	2





1. SUMMARY OF SAR TEST REPORT

1.1 Test Details

Period of test	2009-04-17 to 2009-04-23
SN, HW and SW numbers of	SN: 0634028913113T00109, HW: B4, SW: 2.21, DUT: 25220
tested device	
Batteries used in testing	HD-1 power supply
Headsets used in testing	HS-83, DUT: 25523
Other accessories used in	-
testing	
State of sample	Prototype unit
Notes	-

1.2 Picture of the Device







2. TEST POSITIONS

2.1 Body Worn Configuration

The device was placed below and touching the flat section of the phantom. The device was oriented with a total of four sides facing the phantom to find the highest results.







Photo of the device in "Top facing phantom" position



Photo of the device in "Back facing phantom" position



Photo of the device in "Side facing phantom" position