

# RF EXPOSURE REPORT

**REPORT NO.:** SA971230A02

**MODEL NO.:** HF-510

**VERSION:** HW:0.31, SW:0.33, MV:0.3, Proto:3.21

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT :** Nokia Corporation

**ADDRESS :** Elektroniikkatie 10 P.O. Box 300, Salo, 90230, Finland

**ISSUED BY :** Bureau Veritas Consumer Products Services (H.K.)  
Ltd., Taoyuan Branch

**LAB ADDRESS :** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,  
Taipei Hsien, 244 Taiwan

## Conclusion

No Evaluation Required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)		Pout (mW)
Conducted Power	2.95	1.972
EIRP Power	5.80	3.802

**\*Note:** The antenna is Printed antenna with 2.85dBi gain

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 3.802mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold

**---END---**