

FCC Part 22/24 Compliance Test Report

Test Report no.:	FCC22&24_RM-1045_28.docx	Date of Report:	07-May-2014
Number of pages:	11	Customer's Contact person:	Tia Melava
Testing laboratory:	TCC Nokia Tampere Laboratory P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880	Customer:	Nokia Corporation P.O.Box(86) Joensuunkatu 7H / Kiila 1B FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 45220
FCC listing no.:	94436		
IC recognition no.:	661AK-1		
Tested devices/ accessories:	Phone RM-1045		
FCC ID:	PYARM-1045	IC:	661R-RM1045
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Parts 22/24 , TIA-603-C-2004 and IC standards, RSS-GEN (Issue 3, December 2010), RSS-132 (Issue 2, September 2005). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Hannu Söderholm, Specialist, EMC

1. Summary for FCC Part 22 Compliance Test Report

Date of receipt	23-Apr-2014
Testing completed	19-Apr-2014
The customer's contact person	Tia Melava
Test Plan referred to	T:\Projects\RM-1045\TestPlan\RS_Testplan_RM-1045.xlsm
Notes	-
Document name	T:\Projects\RM-1045\EMC\FCC22&24_RM-1045_28.docx

1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:

GSM/WCDMA/WLAN/Bluetooth

The EUT is tested with maximum rated TX power.

Devices under tests

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-1045	004402478600780	1004		02061.00037.14145.00001	43160

1.2. Summary of Test Results

GSM 850:

Section in CFR 47	Section in RSS-GEN or RSS-132	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	-
§22.913(a)	4.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	-
§22.917(a)	4.5	Band edge compliance	-
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	-
§22.917(a), §2.1053	4.5	Spurious radiated emissions	-
§2.1055(a)	4.3	Frequency stability, temperature variation	-
§2.1055(d)	4.3	Frequency stability, voltage variation	-

GSM 1900:

Section in CFR 47	Section in RSS-GEN or RSS-133	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	-
§24.232(b)	6.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	-
§24.238(a)	6.5	Band edge compliance	-
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	-
§24.238(a), §2.1053	6.5	Spurious radiated emissions	-
§2.1055(a)	6.3	Frequency stability, temperature variation	-
§2.1055(d)	6.3	Frequency stability, voltage variation	-

WCDMA 1900:

Section in CFR 47	Section in RSS-GEN or RSS-133	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	-
§24.232(b)	6.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	-
§24.238(a)	6.5	Band edge compliance	-
§24.238(a), §2.1051	6.5	Spurious emissions at antenna terminals	-
§24.238(a), §2.1053	6.5	Spurious radiated emissions	-
§2.1055(a)	6.3	Frequency stability, temperature variation	-
§2.1055(d)	6.3	Frequency stability, voltage variation	-

WCDMA 850:

Section in CFR 47	Section in RSS-GEN or RSS-132	Name of the test	Result
§2.1046(a), 22.913(a)	4.4	Conducted RF output power	-
§22.913(a)	4.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	-
§22.917(a)	4.5	Band edge compliance	-
§22.917(a), §2.1051	4.5	Spurious emissions at antenna terminals	-
§22.917(a), §2.1053	4.5	Spurious radiated emissions	-
§2.1055(a)	4.3	Frequency stability, temperature variation	-
§2.1055(d)	4.3	Frequency stability, voltage variation	-

LTE7:

Section in CFR 47	Section in RSS-GEN or RSS-139	Name of the test	Result
§2.1046(a)	6.4	Conducted RF output power	-
§27.50(h)(2)	6.4	Radiated RF output power	PASSED
§2.1049(h)	4.6.1	99 % occupied bandwidth	-
§27.53(l)	6.5	Band edge compliance	-
§27.53(h), §2.1051	6.5	Spurious emissions at antenna terminals	-
§27.53(l), §2.1053	6.5	Spurious radiated emissions	-
§27.54	6.3	Frequency stability, temperature variation	-
§27.54	6.3	Frequency stability, voltage variation	-

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Nokia Laboratory.

CONTENTS


1. Summary for FCC Part 22 Compliance Test Report	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	3
2. Radiated RF output power (FCC §22.913(a), §27.50(h)(2), §24.232(b), RSS-132 4.4, RSS-133 6.4, RSS-139 6.4)....	6
2.2. Test method and limit	6
2.3. GSM 850 test results, Antenna 1	7
2.4. GSM 850 test results, Antenna 2	7
2.5. GSM 850 E-GPRS (MSC9) test results, Antenna 1	7
2.6. GSM 850 E-GPRS (MSC9) test results, Antenna 2	7
2.7. GSM 1900 test results, Antenna 1	8
2.8. GSM 1900 test results, Antenna 2	8
2.9. GSM 1900 E-GPRS (MSC9) test results, Antenna 1	8
2.10. GSM 1900 E-GPRS (MSC9) test results, Antenna 2	8
2.11. WCDMA 1900 test results	9
2.12. WCDMA 850 test results	9
2.13. LTE7 test results	9
3. Test Equipment.....	10
3.1. Conducted measurements	10
3.2. Radiated measurements	11

2. Radiated RF output power

(FCC §22.913(a), §27.50(h)(2), §24.232(b), RSS-132 4.4, RSS-133 6.4, RSS-139 6.4)

EUT with DUT number	RM-1045, DUT 43160
Accessories with DUT numbers	-
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 45 / 100.7
Date of measurements	28-Apr-2014
Measured by	Hannu Söderholm

2.1.1 Test setup



2.2. Test method and limit

The measurement is made according to TIA-603-C-2004 as follows:

The measurement is performed in the Anechoic Chamber with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system. The turntable is rotated 360 degrees and this is repeated for both horizontal and vertical receive antenna polarizations.

The EUT is placed on a nonconductive plate at 170 cm height.

The substitution method is used. The measurement results are obtained as described below:

$$P[\text{dBm}] = P_{\text{SUBST TX}} + P_{\text{MEAS}} - P_{\text{SUBST RX}} - L_{\text{SUBST CABLES}} + G_{\text{SUBST TX ANT}}$$

Where $P_{\text{SUBST TX}}$ is signal generator level. P_{MEAS} is measured power level from the EUT. $P_{\text{SUBST RX}}$ is measured power level in substitute measurement. $L_{\text{SUBST CABLE}}$ is the loss of the cable between the signal generator and the substitution antenna and $G_{\text{SUBST TX ANT}}$ is substitution antenna gain.

Limits for radiated RF output power measurements

Frequency range [MHz]	Limit [W]	Limit [dBm]
824 - 849	7 ERP	38.5

2.3. GSM 850 test results, Antenna 1

RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
128 / 824.2	28.11	0.647	-3.82	31.93	HORIZONTAL	PASSED
190 / 836.6	26.78	0.476	-4.23	31.01	HORIZONTAL	PASSED
251 / 848.8	25.3	0.339	-5.09	30.39	HORIZONTAL	PASSED

2.4. GSM 850 test results, Antenna 2

RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
128 / 824.2	25	0.316	-6.93	31.93	HORIZONTAL	PASSED
190 / 836.6	23.65	0.232	-8.47	32.12	VERTICAL	PASSED
251 / 848.8	23.78	0.239	-7.56	31.34	VERTICAL	PASSED

2.5. GSM 850 E-GPRS (MSC9) test results, Antenna 1

RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
128 / 824.2	24	0.251	-8.29	32.29	VERTICAL	PASSED
190 / 836.6	22.82	0.191	-9.3	32.12	VERTICAL	PASSED
251 / 848.8	21.21	0.132	-10.13	31.34	VERTICAL	PASSED

2.6. GSM 850 E-GPRS (MSC9) test results, Antenna 2

RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
128 / 824.2	20.34	0.108	-11.95	32.29	VERTICAL	PASSED
190 / 836.6	19.1	0.081	-13.02	32.12	VERTICAL	PASSED
251 / 848.8	24.63	0.29	-6.71	31.34	VERTICAL	PASSED

2.7. GSM 1900 test results, Antenna 1

RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
512 / 1850.2	29.08	0.809	-13.54	42.62	HORIZONTAL	PASSED
661 / 1880	29.11	0.814	-13.56	42.67	VERTICAL	PASSED
810 / 1909.8	28.67	0.736	-14.01	42.68	VERTICAL	PASSED

2.8. GSM 1900 test results, Antenna 2

RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
512 / 1850.2	21.49	0.141	-21.13	42.62	HORIZONTAL	PASSED
661 / 1880	21.21	0.132	-21.27	42.48	HORIZONTAL	PASSED
810 / 1909.8	21.48	0.14	-21.2	42.68	VERTICAL	PASSED

2.9. GSM 1900 E-GPRS (MSC9) test results, Antenna 1

RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
512 / 1850.2	24.76	0.3	-17.86	42.62	HORIZONTAL	PASSED
661 / 1880	24.01	0.252	-18.47	42.48	HORIZONTAL	PASSED
810 / 1909.8	23.03	0.201	-19.51	42.54	HORIZONTAL	PASSED

2.10. GSM 1900 E-GPRS (MSC9) test results, Antenna 2

RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
512 / 1850.2	22.14	0.164	-20.48	42.62	HORIZONTAL	PASSED
661 / 1880	21.91	0.155	-20.76	42.67	VERTICAL	PASSED
810 / 1909.8	21.37	0.137	-21.31	42.68	VERTICAL	PASSED

2.11. WCDMA 1900 test results

RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
9262 / 1852.4	22.16	0.164	-20.47	42.63	HORIZONTAL	PASSED
9400 / 1880	21.51	0.142	-20.97	42.48	HORIZONTAL	PASSED
9538 / 1907.6	20.89	0.123	-21.62	42.51	HORIZONTAL	PASSED

2.12. WCDMA 850 test results

RMS detector

Channel / f _c [MHz]	ERP [dBm]	ERP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
4132 / 826.4	18.18	0.066	-14.45	32.63	VERTICAL	PASSED
4175 / 835	18.31	0.068	-14.08	32.39	VERTICAL	PASSED
4233 / 846.6	17.23	0.053	-14.12	31.35	VERTICAL	PASSED

2.13. LTE7 test results

FDD, CBW 5MHz, QPSK, 1RB mid, RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
20775 / 2502.5	22	0.158	-24.5	46.5	HORIZONTAL	PASSED
21100 / 2535	22.23	0.167	-24.63	46.86	HORIZONTAL	PASSED
21425 / 2567.5	22.18	0.165	-24.71	46.89	HORIZONTAL	PASSED

FDD, CBW 5MHz, 16QAM, 1RB mid, RMS detector

Channel / f _c [MHz]	EIRP [dBm]	EIRP [W]	P _{MEAS} [dBm]	A _{TOT} [dB]	Polarisation	Results
20775 / 2502.5	21.7	0.148	-24.85	46.55	VERTICAL	PASSED
21100 / 2535	21.75	0.149	-25.24	46.99	VERTICAL	PASSED
21425 / 2567.5	22.45	0.176	-24.44	46.89	HORIZONTAL	PASSED

3. Test Equipment

3.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM38112	Power supply	6632A	Agilent	22/24/27, 15C, 15E
TM38114	Power supply	6632A	Agilent	22/24/27, 15C, 15E
TM37773	Communication Tester	CMU200	R&S	22/24/27, 15B
TM30600	Impulse limiter	ESH3-Z2	R&S	15C, 15B
TM26490	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
TM26491	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
TM37610	Spectrum Analyzer	FSU26	R&S	22/24/27, 15C, 15E
TM23007	Oscilloscope	TDS684B	Tektronix	15E
TM22806	Battery	BAT 20/E	Fiskars	15C, 15B
TM22805	UPS	PS 20/1.2	Fiskars	15C, 15B
-	Temperature and humidity logger	175-H2	Testo	15C, 15B
-	Temperature and humidity logger	175-H2	Testo	22/24/27, 15C
-	Air pressure and temperature logger	635-2	Testo	22/24/27, 15C, 15B
-	Air pressure sensor	0638-1835	Testo	22/24/27, 15C, 15B
-	Temperature test chamber	VT 4002	Vötsch	22/24/27
2001	Bluetooth tester	CBT	R&S	15C, 15B
2009	LISN 50 µH	ENV216	R&S	15C, 15B
2010	LISN 50 µH	ENV216	R&S	15C, 15B
2012	Power splitter	11667B	Agilent	22/24/27, 15C
2013	Attenuator	8493C	Agilent	22/24/27, 15C
2014	Attenuator	8493C	Agilent	22/24/27, 15C
2019	Power splitter	ZN2PD-9G-S+	Mini-Circuits	15E
2020	Power splitter	ZN2PD-9G-S+	Mini-Circuits	15E
2021	Communication Tester	CMW500	R&S	22/24/27
2022	Communication Tester	CMU200	R&S	22/24/27
2023	Spectrum Analyzer	ESMI-RF	R&S	15B/15C
2024	Analyzer display unit	ESAI-D	R&S	15B/15C
2026	Signal Generator	SMF 100A	R&S	22/24/27, 15C, 15E, 15B

3.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	Antenna	BBHA 9120 D	Schwarzbeck	22/24/27, 15C
TM37678	Communication Tester	CMU200	R&S	22/24/27, 15B
TM38845	Receiver	ESIB 26	R&S	22/24/27, 15C, 15E, 15B
-	Antenna	HL562	R&S	22/24/27, 15C, 15E, 15B
-	Turntable	2188	EMCO	22/24/27, 15C, 15E, 15B
-	Turntable controller	2090	EMCO	22/24/27, 15C, 15E, 15B
-	RF system panel	OSP130	R&S	22/24/27, 15C, 15E, 15B
-	Mini mast	2075-2	ETS Lindgren	22/24/27, 15C, 15B
TM38843	Mini mast	2075	Emco	22/24/27, 15C, 15B
TM38842	Antenna mast controller	2090	Emco	22/24/27, 15C, 15B
TM30643	LISN 50 µH	LISN-5-20-2	FCC	22/24/27, 15C, 15B
TM30644	LISN 50 µH	LISN-5-20-2	FCC	22/24/27, 15C, 15B
-	Temperature and humidity logger	175-H2	Testo	22/24/27, 15C, 15B
-	Air pressure and temperature logger	635-2	Testo	22/24/27, 15C, 15B
-	Air pressure sensor	0638-1835	Testo	22/24/27, 15C, 15B
TM37523	Preamplifier	AMF-4D-10M-3G-25-20P	Miteq	22/24/27, 15C, 15B
TM37498	Preamplifier	AMF-5D-020180-26-10P	Miteq	22/24/27, 15C, 15B
TM30599	Semi anechoic chamber	UNKNOWN	TDK	22/24/27, 15C, 15B
TM22638	Power supply	OL63743-901	-	22/24/27, 15C, 15E, 15B
TM38066	High pass filter	WHKX3.0/18G-12SS	Wainwright	22/24/27, 15C, 15E, 15B
2028	High pass filter	WHKX 1.0/15G-12SS	Wainwright	22/24/27, 15C, 15E, 15B
TM37545	Tunable notch filter	800.0/960.0-0.2/40-8SSK	Wainwright	22
TM26512	Tunable notch filter	WRCD1850/1910-0.2/40-10SSK	Wainwright	24
-	Band reject filter	WRCG1877/1883-1870/1890-40/6EE	Wainwright	24
-	Band reject filter	WRCG1729.4/1735.4-1722.4/1742.4-40/6SS	Wainwright	27
TM23892	Controller	G-1000SDX	Yaesu	22/24/27, 15C, 15E
2001	Bluetooth tester	CBT	R&S	15C, 15B
6023	Antenna	VUBA 9117	Schwarzbeck	22/24/27
2021	Communication Tester	CMW500	R&S	22/24/27
2025	Antenna	HFH2-Z2	R&S	15C
2026	Signal Generator	SMF 100A	R&S	22/24/27, 15C, 15E, 15B
2052	Antenna	BBHA 9120 D	Schwarzbeck	22/24/27, 15C, 15B, 15E
-	Antenna	QSH18S20	Q-Par	22/24/27, 15C, 15B, 15E
-	Antenna	QSH20S20	Q-Par	22/24/27, 15C, 15B, 15E
-	Antenna	QSH20S20	Q-Par	22/24/27, 15C, 15B, 15E