





Setup photos for HAC RF Emissions and T-Coil Test Report

Test report no.: HAC_Photo_RM-1105_03 Date of report: 2015-09-24

Template version: 4.0 Number of pages: 3

Testing laboratory: TCC Microsoft Salo Laboratory **Client:** Microsoft P.O.Box 303 P.O.Box 303

Joensuunkatu 7E Joensuunkatu 7

FIN-24101 SALO, FINLAND
Tel. +358 71 800 8000
Tel. +358 71 80 44122
Fax. +358 71 80 44122
Fax. +358 71 80 44122

Responsible test Janne Hirsimäki Product contact person: Jari Rontu

Tested devices: RM-1105

FCC ID: PYARM-1105 IC: -

Supplement reports: RF_RM-1105_01, T-Coil_RM-1105_02

Testing has been

accordance with: ANSI C63.19-2011

American National Standard for Methods of Measurement of Compatibility between

Wireless Communications Devices and Hearing Aids

CTIA Test Plan for Hearing Aid Compatibility, Revision 3.0, November 2013

Documentation: The documentation of the testing performed on the tested devices is archived for 15

years at TCC Microsoft.

Test results: The tested device complies with the requirements in respect of all parameters subject

to the test. The test results and statements relate only to the items tested. The test report

shall not be reproduced except in full, without written approval of the laboratory.

Date and signatures:

For the contents:

by:

carried out in

HAC Photo Report HAC_Photo_RM-1105_03 Applicant: Microsoft RM-1105




CTIA Authorized Test Lab



		_
CONTENTS		
1.1	PICTURE OF DEVICE	3
1.2	Test Positions	3
1.2	1 Scan area centered at the acoustic output	_







1.1 Picture of Device



1.2 Test Positions

1.2.1 Scan area centered at the acoustic output

The device was positioned such that Device Reference plane was touching the bottom of the Test Arch. The scan is centered at the acoustic output by aligning the acoustic output with the intersection of the Test Arch's middle bar and dielectric wire.




Photo of the device positioned under Test Arch