

**Setup photos for HAC RF Emissions
and T-Coil Test Report**

Test report no.:	HAC_Photo_RM-1116_03	Date of report:	2015-09-23
Template version:	4.0	Number of pages:	3
Testing laboratory:	TCC Microsoft Salo Laboratory P.O.Box 303 Joensuunkatu 7E FIN-24101 SALO, FINLAND Tel. +358 71 800 8000 Fax. +358 71 80 44122	Client:	Microsoft P.O.Box 303 Joensuunkatu 7 FIN-24101 SALO, FINLAND Tel. +358 71 800 8000 Fax. +358 71 80 44122
Responsible test engineer:	Janne Hirsimäki	Product contact person:	Tia Melava
Measurements made by:	Sami Savela		
Tested devices:	RM-1116		
FCC ID:	PYARM-1116	IC:	661X-RM1116
Supplement reports:	RF_RM-1116_01, T-Coil_RM-1116_02		
Testing has been carried out in accordance with:	<p>ANSI C63.19-2011 American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids</p> <p>CTIA Test Plan for Hearing Aid Compatibility, Revision 3.0, November 2013</p>		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at TCC Microsoft.		
Test results:	<p>The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.</p>		

Date and signatures:

For the contents:



CONTENTS

1.1 PICTURE OF DEVICE3

1.2 TEST POSITIONS.....3

 1.2.1 Scan area centered at the acoustic output3

1.1 Picture of Device



1.2 Test Positions

1.2.1 Scan area centered at the acoustic output

The device was positioned such that Device Reference plane was touching the bottom of the Test Arch. The scan is centered at the acoustic output by aligning the acoustic output with the intersection of the Test Arch's middle bar and dielectric wire.



Photo of the device positioned under Test Arch