

FCC Part 15B Compliance Test Report

Test Report no.:	FCC15B_RM-1127_03.docx	Date of Report:	08-Oct-2015
Number of pages:	13	Customer's Contact person:	Tero Huhtala
Testing laboratory:	TCC Microsoft Beijing Laboratory Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550	Customer:	Microsoft P.O. Box 403 Visiokatu 4 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880
FCC listing no.:	975940		
IC recognition no.:	661AH-1		
Tested devices/ accessories:	Phone RM-1127 / Cover CC-3097 / Battery Samsung BL-T5A / AC Charger AC-18U / Headset WH-108		
FCC ID:	PYARM-1127	IC:	
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart B, ANSI C63.4 (2014), CISPR 22 and IC standards, RSS-GEN (Issue 4, November 2014), RSS-132 (Issue 3, January 2013), RSS-133 (Issue 6, January 2013), RSS-199 (Issue 2, October 2014). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Microsoft.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Timo Raiskio, System Manager, EMC

1. Summary for FCC Part 15B Compliance Test Report

Date of receipt	15-Jun-2015
Testing completed	06-Aug-2015
The customer's contact person	Tero Huhtala
Test Plan referred to	T:\Projects\RM-1127\TestPlan\RS_TestPlan_RM-1127_EMCC_FCC.xlsm
Notes	-
Document name	FCC15B_RM-1127_03.docx

1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:
GSM/WCDMA/WLAN/Bluetooth
The EUT is tested with maximum rated TX power.

Devices under tests

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-1127	004402742167830	1500	-	01065.00000.15265.37000	500106
Cover	CC-3097	-	-	-	-	500129
Battery	Samsung BL-T5A	5241525213V10200110;0670778	PWB Ver.1.1	-	-	500114
AC-Charger	AC-18U	4818715115100100661;0675735	-	-	-	500124
Headset	WH-108	-	-	-	-	500121

1.2. Summary of Test Results

GSM 850:

Section in CFR 47	Section in RSS-GEN	Name of the test	Result
15.107, a	8.8	AC powerline conducted emissions	NP
15.109, a	6.1	Radiated emissions	PASSED

GSM 1900:

Section in CFR 47	Section in RSS-GEN	Name of the test	Result
15.107, a	8.8	AC powerline conducted emissions	NP
15.109, a	6.1	Radiated emissions	PASSED

LTE7:

Section in CFR 47	Section in RSS-GEN	Name of the test	Result
15.107, a	8.8	AC powerline conducted emissions	NP
15.109, a	6.1	Radiated emissions	PASSED

PASSED
FAILED
NP

The EUT complies with the essential requirements in the standard.
The EUT does not comply with the essential requirements in the standard.
The test was not performed by the TCC Microsoft Laboratory.


CONTENTS

1. Summary for FCC Part 15B Compliance Test Report.....	2
1.1. EUT and Accessory Information.....	2
1.2. Summary of Test Results	2
2. Radiated emissions (FCC 15.109, a, RSS-132 6.1, RSS-133 6.1, RSS-199 6.1)	4
2.2. Test method and limit	4
2.3. GSM 850 test results; FM Radio on	6
2.4. GSM 1900 test results, GPS active	7
2.5. LTE7 test results, GPS active.....	8
3. Test Equipment.....	11
3.1. Conducted measurements	11
3.2. Radiated measurements	11

2. Radiated emissions
(FCC 15.109, a, RSS-132 6.1, RSS-133 6.1, RSS-199 6.1)

EUT with DUT number	RM-1128, DUT 500106
Accessories with DUT numbers	CC-3097, DUT 500129 ; Samsung BL-T5A, DUT 500114; AC-18U, DUT 500124; WH-108, DUT 500121
Operation Voltage [V] / [Hz]	115 / 60
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	21 / 63 / 100.1
Date of measurements	03-Aug-2015
Measured by	Gao Sherina

2.1.1 Test setup



2.2. Test method and limit

The measurement is made according to ANSI C63.4-2014 as follows:

The measurement is performed in the Semi-Anechoic Chamber with conducting metal floor.

The measurement distance is 3 m.

The EUT is placed on a nonconductive plate at 80 cm height.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [dB\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + A_F - G_{PREAMP}$).

CISPR 22 and FCC Part 15 Class B limits (3 m measurement distance)

Frequency range [MHz]	Quasi peak limit [dBμV/m]	Average limit [dBμV/m]	Peak limit [dBμV/m]
30 - 230	40	-	-
230 – 1000	47	-	-
1000 - 3000	-	50	70
Above 3000	-	54	74

2.3. GSM 850 test results; FM Radio on

The examined frequency range was 30MHz – 8GHz

RX mode, channel 128 / 869.2 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
3478.5	41.18	114.551	42.18	-1	74	32.82	PASSED
6951.7	55.86	620.869	47.16	8.7	74	18.14	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
3478.5	28.19	25.674	29.19	-1	54	25.81	PASSED
6951.7	43.26	145.546	34.56	8.7	54	10.74	PASSED

RX mode, channel 190 / 881.6 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
30.27	15.66	6.067	26.86	-11.2	40	24.34	PASSED
47.886	13.4	4.677	36.2	-22.8	40	26.6	PASSED
97.986	20.69	10.827	44.59	-23.9	40	19.31	PASSED
144.008	25.44	18.707	50.24	-24.8	40	14.56	PASSED
228.027	27.27	23.094	50.17	-22.9	40	12.73	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
3524.6	41.48	118.577	41.88	-0.4	74	32.52	PASSED
7053.6	48.8	275.423	38.8	10	74	25.2	PASSED
7817.436	49.67	304.439	38.77	10.9	74	24.33	PASSED
7822.846	50.11	320.258	39.11	11	74	23.89	PASSED
7843.991	50.5	334.965	39.5	11	74	23.5	PASSED
7860.218	50.23	324.713	39.13	11.1	74	23.77	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
3524.6	28.43	26.394	28.83	-0.4	54	25.57	PASSED
7053.6	35.82	61.802	25.82	10	54	18.18	PASSED
7817.436	36.76	68.865	25.86	10.9	54	17.24	PASSED
7822.846	36.94	70.307	25.94	11	54	17.06	PASSED
7843.991	37.04	71.121	26.04	11	54	16.96	PASSED
7860.218	37.2	72.444	26.1	11.1	54	16.8	PASSED

RX mode, channel 251 / 893.8 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
3573.3	41.9	124.451	42.7	-0.8	74	32.1	PASSED
7150.2	49.55	300.262	39.15	10.4	74	24.45	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
3573.3	28.01	25.148	28.81	-0.8	54	25.99	PASSED
7150.2	36.01	63.168	25.61	10.4	54	17.99	PASSED

2.4. GSM 1900 test results, GPS active

The examined frequency range was 30MHz – 8GHz

RX mode, channel 512 / 1930.2 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
3859.2	41.54	119.399	41.84	-0.3	74	32.46	PASSED
7721	49.66	304.089	39.06	10.6	74	24.34	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
3859.2	28.1	25.41	28.4	-0.3	54	25.9	PASSED
7721	36.45	66.451	25.85	10.6	54	17.55	PASSED

RX mode, channel 661 / 1960.0 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
34.44	21.17	11.442	35.17	-14	40	18.83	PASSED
41.031	17.44	7.447	35.74	-18.3	40	22.56	PASSED
41.726	21.03	11.259	39.83	-18.8	40	18.97	PASSED
228.447	27.69	24.238	50.49	-22.8	40	12.31	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
3918.6	41.03	112.59	41.33	-0.3	74	32.97	PASSED
7836.677	50.37	329.989	39.37	11	74	23.63	PASSED
7840.9	50.01	316.592	39.01	11	74	23.99	PASSED
7850.9	50.11	320.258	39.11	11	74	23.89	PASSED
7855.71	50.32	328.095	39.32	11	74	23.68	PASSED
7862.125	50.4	331.131	39.3	11.1	74	23.6	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
3918.6	27.77	24.462	28.07	-0.3	54	26.23	PASSED
7836.677	37.05	71.203	26.05	11	54	16.95	PASSED
7840.9	37.01	70.876	26.01	11	54	16.99	PASSED
7850.9	37.04	71.121	26.04	11	54	16.96	PASSED
7855.71	37.14	71.945	26.14	11	54	16.86	PASSED
7862.125	37.2	72.444	26.1	11.1	54	16.8	PASSED

RX mode, channel 810 / 1989.8 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
3979.4	40.58	106.905	40.68	-0.1	74	33.42	PASSED
7960.2	50.31	327.718	38.81	11.5	74	23.69	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
3979.4	27.57	23.906	27.67	-0.1	54	26.43	PASSED
7960.2	37.36	73.79	25.86	11.5	54	16.64	PASSED

2.5. LTE7 test results, GPS active

The examined frequency range was 30MHz – 8GHz

RX mode, channel 2775 / 2622.5 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
5244.3	45.61	190.766	44.11	1.5	74	28.39	PASSED
7868.9	49.98	315.5	38.78	11.2	74	24.02	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
5244.3	32.88	44.055	31.38	1.5	54	21.12	PASSED
7868.9	37.32	73.451	26.12	11.2	54	16.68	PASSED

RX mode, channel 3100 / 2655 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
35.23	16.14	6.412	30.74	-14.6	40	23.86	PASSED
41.456	18.61	8.521	37.21	-18.6	40	21.39	PASSED
140.802	18.4	8.318	43	-24.6	40	21.6	PASSED
143.988	26.01	19.976	50.81	-24.8	40	13.99	PASSED
148.805	17.46	7.464	42.46	-25	40	22.54	PASSED
150.401	27.07	22.568	52.17	-25.1	40	12.93	PASSED
153.607	26.25	20.535	51.35	-25.1	40	13.75	PASSED
228.847	27.32	23.227	50.12	-22.8	40	12.68	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
5310	45.71	192.975	44.31	1.4	74	28.29	PASSED
7827.357	50.04	317.687	39.04	11	74	23.96	PASSED
7843.185	50.11	320.258	39.11	11	74	23.89	PASSED
7858.216	50.84	348.337	39.74	11.1	74	23.16	PASSED
7864.23	50.28	326.588	39.18	11.1	74	23.72	PASSED
7966.7	51.29	366.86	39.79	11.5	74	22.71	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
5310	32.98	44.566	31.58	1.4	54	21.02	PASSED
7827.357	36.97	70.55	25.97	11	54	17.03	PASSED
7843.185	37.03	71.04	26.03	11	54	16.97	PASSED
7858.216	37.17	72.194	26.07	11.1	54	16.83	PASSED
7864.23	37.25	72.862	26.15	11.1	54	16.75	PASSED
7966.7	37.39	74.046	25.89	11.5	54	16.61	PASSED

RX mode, channel 3425 / 2687.5 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Limit [dB μ V/m]	Margin	Results
5375.1	45.73	193.419	44.03	1.7	74	28.27	PASSED
8064.3	51.13	360.164	39.43	11.7	74	22.87	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
5375.1	32.82	43.752	31.12	1.7	54	21.18	PASSED
8064.3	38.06	79.983	26.36	11.7	54	15.94	PASSED

3. Test Equipment

3.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	EMC32 Test Software	R&S	22/24/27, 15C, 15B
BJPCHW0020	DC Power supply	Hp6632B	HP	22/24/27, 15C
BJPCPT0040	Receiver	ESCS30	R&S	15C,15B
BJPCPT0069	LISN 50 μH	ESH3-Z5	R&S	15C,15B
BJPCTC0323	Signal Generator	SMR 27	R&S	22/24/27, 15C, 15B
BJPCPT0073	Signal Generator	SMR 20	R&S	22/24/27, 15C, 15B
BJPCPT0191	Pulse Limiter	ESH3-Z2	R&S	15C,15B
BJPCPT0208	UPS	PULSAR RX10	Merlin gerin	15C.15B
BJPCTC0001	DIGITAL CAMERA	PC1015	CANON	15C.15R
BJPCTC0017	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0062	AC Power source	6812B	Hp	15C.15B
BJPCTC0067	Bluetooth Tester	CBT	R&S	22/24/27, 15C
BJPCTC0082	Humidity and Temperature Sensor	175-H2	Testo	15B,15C
BJPCTC0088	Absolut pressure meter	testo 511	Testo	22/24/27, 15B,15C
BJPCTC0089	Tempreture Test chamber	VT4002	Votsch industrietechnik	22/24/27, 15C
BJPCTC0090	FSP spectrum analyzer	FSP30	R&S	22/24/27, 15C
BJPCTC0094	GPIB-RS232 convertor	GPIB-RS232	NI	22/24/27, 15C
BJPCTC0112	Power Splitter	11667B	Agilent	22/24/27, 15C
BJPCTC0127	AC Power source	SOYI-500VA	SOYI	15B 15C
BJPCTC0128	Communication antenna	JTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0129	Communication antenna	JTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0131	Communication tester	CMW500	R&S	22/24/27 15B 15C
BJPCTC0136	Communication antenna	JTXLB-880-NF	A-INFOMW	15B 15C
BJPCTC0306	Power Splitter	11667B	Agilent	22/24/27, 15C
BJPCTC0305	GPIB converter	GPIB-RS232	NI	22/24/27, 15C
BJPCTC0304	Spectrum Analyser	FSV30	R&S	22/24/27, 15C
BJPCTC0309	GPIB-RS232 convertor	RS232	NI	22/24/27, 15C
BJPCTC0307	Dual channel battery/charger simulator	2306	KEITHLEY	22/24/27, 15C
BJPCTC0308	Dual channel battery/charger simulator	2306	KEITHLEY	22/24/27, 15C
BJPCTC0352	Signal Generator 20GHz	MG3692B	Anritsu	22/24/27, 15C
BJBDATC0169	Tempreture Test chamber	VT4002	Votsch	22/24/27, 15C
BJPCTC0334	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0342	Communication Tester	CMU200	R&S	15B, 15C
BJPCTC0343	Power Splitter	1167A	Agilent	EN300328
BJPCTC0344	Power Splitter	1167A	Agilent	EN300328
BJPCTC0345	Power Splitter	1167A	Agilent	EN300328
BJPCTC0346	Attenuator	8496A	Agilent	EN300328
BJPCTC0347	Directional Coupler	4226-20	Narda	EN300328
BJPCTC0348	Signal generator	E4438C	Agilent	EN300328
BJPCTC0336	Signal Generator	SMP22	R&S	22/24/27, 15C
BJPCTC0357	Signal Generator	SMB100A	R&S	-

3.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	EMC32 Test Software	R&S	22/24/27, 15C, 15B
BJPCPT0072	Receiver	ESIB26	R&S	22/24/27, 15C, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
BJPCPT0150	High Pass Filter	WHKS1200-10SS	Wainwright	22/24/27, 15C, 15B
BJPCPT0151	Band Reject Filter	WRCD1880/2000-0.2/40-5SSK	Wainwright	24, 15B
BJPCPT0154	Band Reject Filter	WRCT2402/2480-2400/2483.5-30-20SS	Wainwright	15C, 15B
BJPCPT0166	Antenna	VUBA 9117	Swarzbeck	22/24/27
BJPCPT0208	UPS	PULSAR RX10	Merlin gerin	15C.15B
BJPCTC0001	DIGITAL CAMERA	PC1015	CANON	15C.15R
BJPCTC0007	Antenna	HL562	R&S	22/24/27, 15C, 15B
BJPCTC0029	Antenna	HF906	R&S	22/24/27, 15C, 15B
BJPCTC0034	Band Reject Filter	WRCT 800/880-0.2/40-5SSK	Wainwright	22, 15B
BJPCTC0049	Preamplifier	Bima 0118-1A-Bt	Bonn	22/24/27, 15C, 15B
BJPCTC0055	Communication Tester	CMU200	R&S	22/24/27,15C,15B
BJPCTC0058	Bluetooth Tester	CBT	R&S	15C, 15B
BJPCTC0062	AC Power source	6812B	Hp	15C.15B
BJPCTC0064	Band Reject Filter	WRCG1877/1883-1870/1890-40/6SS	Wainwright	24, 15B
BJPCTC0071	Multi-Device Controller	2090	EMCO	22/24/27, 15C, 15B
BJPCTC0072	Anechoic Chamber	3 m Semi / Full Anechoic Chamber	ETS	22/24/27, 15C, 15B
BJPCTC0073	MAST	Model-TR/POL	ETS	22/24/27, 15C, 15B
BJPCTC0074	MAST	Model 2070-2	ETS	22/24/27, 15C, 15B
BJPCTC0075	Turntable	Model 2188	ETS-EMCO	22/24/27, 15C, 15B
BJPCTC0081	Humidity and Temperature Sensor	175-H2	Testo	15B, 15C
BJPCTC0088	Absolut pressure meter	testo 511	Testo	22/24/27, 15B,15C
BJPCTC0124	Attenuator	SA18N200W-40	Fairview Microwave	-
BJPCTC0125	Loop Antenna	HFH2-Z2	R&S	15C
BJPCTC0126	Tripod	FHU-Z	R&S	15C
BJPCTC0128	Communication antenna	JTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0129	Communication antenna	JTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0131	Communication tester	CMW500	R&S	22/24/27 15B 15C
BJPCTC0133	Open Swith and contril unit	OSP 150	R&S	15B,15C
BJPCTC0134	Open Swith and contril unit	OSP 150	R&S	15B,15C
BJPCTC0135	Open Swith and contril unit	OSP 130	R&S	15B,15C
BJPCTC0136	Communication antenna	JTXLB-880-NF	A-INFOMW	15B 15C
BJPCTC0171	Broad-band Horn Antenna	BBHA9120 D	SCHWARZBECK MESS - ELEKTRONIK	22/24/27, 15C, 15B
BJPCTC0310	Horn Antenna	QSH20SMA	Q-par	22/24/27, 15C, 15B
BJPCTC0311	Horn Antenna	QSH18SMA	Q-par	22/24/27, 15C, 15B
BJPCTC0312	Relay Switch Unit	-	-	22/24/27, 15C, 15B
BJPCTC0313	High Pass Filter	WHKX1.0/15G-12SS	Wainwright	22/24/27, 15C, 15B
BJPCTC0314	High Pass Filter	WHKX8.0/18G-88SS	Wainwright	22/24/27, 15C, 15B
BJPCTC0315	High Pass Filter	WHKX3.0/18G-12SS	Wainwright	22/24/27, 15C, 15B
BJPCTC0316	Preamplifier	AMT-5F-18002550-25-108	-	22/24/27, 15C, 15B
BJPCTC0317	Preamplifier	AMF-6D-02001800-29-20P	-	22/24/27, 15C, 15B
BJPCTC0350	Preamplifier	AMF-4D-01000800-30-29P	Miteq	22/24/27, 15C, 15B
BJPCTC0324	Preamplifier	AFS4-00100300-20-23P-6	Miteq	22/24/27, 15C, 15B
BJPCTC0329	Relay Switch Unit	-	-	22/24/27, 15C, 15B
BJPCTC0334	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0342	Communication Tester	CMU200	R&S	15B, 15C
BJPCTC0349	Preamplifier	AMF-4D-01000800-30-79P	Miteq	22/24/27, 15C, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
BJPCTC0350	Preamplifier	AMF-4D-01000800-30-29P	Miteg	22/24/27, 15C, 15B
BJPCTC0351	Preamplifier	AFS4-00101800	-	22/24/27, 15C, 15B
BJPCTC0113	Receiver	ESI B26	R&S	22/24/27, 15B, 15C