

FCC Part 15B Compliance Test Report

Test Report no.:	Tre_FCC_0644_03.doc	Date of Report:	6.11.2006
Number of pages:	16	Customer's Contact person:	Timo Seppälä
Testing laboratory:	TCC Nokia Tampere Laboratory P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880	Customer:	Nokia Corporation P.O. Box 86 Joensuunkatu 7 FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 44277
FCC listing no.:	94436		
IC recognition no.:	3608		
Tested devices/ accessories:	GSM phone RM-208 / Battery BL-5F, AC charger AC-4, Data cable CA-53, Laptop IBM Thinkpad T22, AC adapter 02K6543, Printer HP deskjet 1600CC3540A, Digital camera FUJI DS-7, Serial cable for camera, Parallel cable for printer		
FCC ID:	PYARM-208	IC:	661V-RM208
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart B, ANSI C63.4 (2003), ICES-003, CISPR 22 and IC standards RSS-132, RSS-133 and RSS-210. Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Jari Jantunen, System Manager

1. Summary for FCC Part 15B Compliance Test Report

Date of receipt	31.10.2006
Testing completed	3.11.2006
The customer's contact person	Timo Seppälä
Test Plan referred to	\EMC\TESTPLAN\
Notes	-
Document name	T:\Projects\RM-208\EMC\Results\FCC\Tre_FCC_0644_03.doc

1.1. EUT and Accessory Information

The EUT is a 5-band (GSM850/900/1800/1900 and WCDMA Band I) mobile phone with GPRS, EGPRS, Bluetooth and WLAN. GSM bands are tested in idle mode. Bluetooth and WLAN are tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
GSM phone	RM-208	004400941721597	0404	-	1.0633.06.00	40850
Battery	BL-5F	-	-	-	-	40853
AC Charger	AC-4	-	3.22	0.3	-	40857
Data cable	CA-53	-	WK05/2006	4.0	-	40859
Laptop	IBM Thinkpad T22	555V2PT	-	-	-	40201
AC Adapter	02K6543	-	-	-	-	40202
Printer	HP deskjet 1600CC3540A	USB8302546	-	-	-	40077
Digital camera	FUJI DS-7	7102516	-	-	-	40076
Serial cable for camera	-	-	-	-	-	40088
Parallel cable for printer	-	-	-	-	-	40087

1.2. Summary of Test Results

GSM 850:

Section in CFR 47	Section in ICES-003 (RSS-132)	Name of the test	Result
15.107, a	5.3	AC powerline conducted emissions	PASSED
15.109, a	5.5 (6.6)	Radiated emissions	PASSED

GSM 1900:

Section in CFR 47	Section in ICES-003 (RSS-133)	Name of the test	Result
15.107, a	5.3	AC powerline conducted emissions	PASSED
15.109, a	5.5 (9)	Radiated emissions	PASSED

Bluetooth:

Section in CFR 47	Section in ICES-003	Name of the test	Result
15.107, a	5.3	AC powerline conducted emissions	PASSED
15.109, a	5.5	Radiated emissions	PASSED

WLAN:

Section in CFR 47	Section in ICES-003	Name of the test	Result
15.107, a	5.3	AC powerline conducted emissions	PASSED
15.109, a	5.5	Radiated emissions	PASSED

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Nokia Tampere Laboratory.


CONTENTS

1. Summary for FCC Part 15B Compliance Test Report.....	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results.....	2
2. AC powerline conducted emissions (FCC §15.107, ICES-003 section 5.3).....	5
2.1. Test setup	5
2.2. Test method and limit.....	5
2.3. GSM 850 Test results	6
2.4. GSM 1900 Test results	7
2.5. Bluetooth Test results	8
2.6. WLAN Test results	9
3. Radiated emissions (FCC §15.109, ICES-003 section 5.5, RSS-132 6.6, RSS-133 9) 10	
3.1. Test setup	10
3.2. Test method and limit.....	10
3.3. GSM 850 Test results	11
3.4. GSM 1900 Test results	12
3.5. Bluetooth Test results	13
3.6. WLAN Test results	14
4. Test Equipment.....	16
4.1. Conducted measurements	16
4.2. Radiated measurements	16

2. AC powerline conducted emissions (FCC §15.107, ICES-003 section 5.3)

EUT with DUT number	RM-208 DUT 40850
Accessories with DUT numbers	BL-5F DUT 40853, AC-4 DUT 40857, CA-53 DUT 40859, IBM Thinkpad T22 DUT 40201, 02K6543 DUT 40202, HP deskjet 1600CC3540A DUT 40077, FUJI DS-7 DUT 40076, Serial cable for camera DUT 40088, Parallel cable for printer DUT 40087
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	Continuous data transfer was active between the phone and the computer during the test.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 52 / 100.5
Date of measurements	2.11.2006
Measured by	Jari Jantunen

2.1. Test setup



2.2. Test method and limit

The measurement is made according to ANSI C63.4-2003 as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$


Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.

CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

2.3. GSM 850 Test results

RX mode, channel 190 / 881.6 MHz



Quasi peak (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
0.375000	49.70	L1	PASSED
0.755000	50.70	L1	PASSED
1.130000	49.00	L1	PASSED
2.065000	31.00	L1	PASSED
2.625000	39.60	L1	PASSED
2.850000	28.40	L1	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.380000	38.50	L1	PASSED
0.760000	32.30	L1	PASSED
1.135000	32.90	L1	PASSED
1.510000	32.40	L1	PASSED
2.065000	22.30	L1	PASSED
2.630000	32.80	L1	PASSED
3.005000	31.40	L1	PASSED
4.240000	26.50	L1	PASSED

2.4. GSM 1900 Test results

RX mode, channel 661 / 1960.0 MHz



Quasi peak (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
0.375000	46.50	L1	PASSED
0.750000	42.60	L1	PASSED
0.940000	42.60	L1	PASSED
1.130000	47.50	L1	PASSED
2.120000	36.60	N	PASSED
2.190000	37.20	N	PASSED
2.355000	36.10	L1	PASSED
2.505000	36.40	L1	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.375000	41.50	L1	PASSED
0.750000	41.00	L1	PASSED
0.950000	30.50	L1	PASSED
1.145000	19.20	N	PASSED
2.350000	16.40	L1	PASSED
2.630000	29.20	L1	PASSED
2.840000	20.20	L1	PASSED
3.000000	30.70	L1	PASSED

2.5. Bluetooth Test results

TX mode, channel 40 / 2442 MHz



Quasi peak (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
0.730000	38.50	L1	PASSED
0.905000	34.60	L1	PASSED
1.105000	41.00	L1	PASSED
1.475000	38.60	L1	PASSED
2.895000	24.80	L1	PASSED
3.890000	25.30	L1	PASSED
4.065000	25.60	L1	PASSED
4.220000	25.80	L1	PASSED

Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.370000	43.00	L1	PASSED
0.740000	44.60	L1	PASSED
0.925000	39.20	L1	PASSED
1.110000	39.80	L1	PASSED
2.635000	28.00	L1	PASSED
2.825000	27.20	L1	PASSED
3.015000	28.60	L1	PASSED
22.500000	30.80	L1	PASSED

2.6. WLAN Test results

RX mode, channel 7 / 2442 MHz



Quasi peak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.655000	37.60	L1	PASSED
1.070000	39.90	L1	PASSED
1.695000	43.40	L1	PASSED
1.980000	44.00	L1	PASSED
2.255000	44.30	L1	PASSED
2.625000	41.60	L1	PASSED
3.710000	41.50	L1	PASSED
4.280000	39.20	L1	PASSED

Average (RBW: 9 kHz)


Frequency [MHz]	U [dBμV]	Line	Result
0.190000	38.30	N	PASSED
0.375000	31.80	L1	PASSED
1.555000	30.80	L1	PASSED
1.975000	32.10	L1	PASSED
2.110000	31.80	L1	PASSED
2.530000	31.60	L1	PASSED
4.415000	30.40	L1	PASSED
4.925000	28.50	N	PASSED

3. Radiated emissions

(FCC §15.109, ICES-003 section 5.5, RSS-132 6.6, RSS-133 9)

EUT with DUT number	RM-208 DUT 40850
Accessories with DUT numbers	BL-5F DUT 40853, AC-4 DUT 40857, CA-53 DUT 40859, IBM Thinkpad T22 DUT 40201, 02K6543 DUT 40202, HP deskjet 1600CC3540A DUT 40077, FUJI DS-7 DUT 40076, Serial cable for camera DUT 40088, Parallel cable for printer DUT 40087
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	Continuous data transfer was active between the phone and the computer during the test.
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 52 / 100.5
Date of measurements	2.11.2006
Measured by	Jari Jantunen

3.1. Test setup



3.2. Test method and limit

The measurement is made according to ANSI C63.4-2003as follows:

The measurement is performed in the Semi-Anechoic Chamber with conducting metal floor.
The measurement distance is 3 m.

The EUT is placed on a nonconductive plate at 80 cm height.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement results are obtained as described below:

$$E [\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + AF - G_{PREAMP}$).

CISPR 22 and FCC Part 15 Class B limits (3 m measurement distance)

Frequency range [MHz]	Quasi peak limit [dBμV/m]	Average limit [dBμV/m]	Peak limit [dBμV/m]
30 – 230	40	-	-
230 – 1000	47	-	-
Above 1000	-	54	74

3.3. GSM 850 Test results

RX mode, channel 128 / 869.2 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3476.800000	38.60	85.11	43.70	-5.10	VERTICAL	PASSED
6953.600000	44.40	165.96	43.50	0.90	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3476.800000	26.20	20.42	31.30	-5.10	HORIZONTAL	PASSED
6953.600000	30.40	33.11	29.50	0.90	HORIZONTAL	PASSED

RX mode, channel 190 / 881.6 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3526.400000	39.00	89.13	43.80	-4.80	VERTICAL	PASSED
7052.800000	41.50	118.85	40.70	0.80	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3526.400000	26.30	20.65	31.10	-4.80	HORIZONTAL	PASSED
7052.800000	28.60	26.92	27.80	0.80	HORIZONTAL	PASSED

RX mode, channel 251 / 893.8 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3575.200000	39.90	98.86	44.50	-4.60	HORIZONTAL	
7150.400000	41.40	117.49	39.90	1.50	HORIZONTAL	

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3575.200000	26.20	20.42	30.80	-4.60	HORIZONTAL	
7150.400000	28.50	26.61	27.00	1.50	HORIZONTAL	

3.4. GSM 1900 Test results

RX mode, channel 512 / 1930.2 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3860.000000	41.00	112.20	43.40	-2.40	HORIZONTAL	PASSED
7720.000000	43.10	142.89	40.40	2.70	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3860.000000	27.80	24.55	30.20	-2.40	HORIZONTAL	PASSED
7720.000000	29.80	30.90	27.10	2.70	HORIZONTAL	PASSED

RX mode, channel 661 / 1960.0 MHz

Quasi peak (RBW: 120 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
32.002405	32.10	40.27	58.50	-26.40	VERTICAL	PASSED
36.012024	36.00	63.10	64.30	-28.30	VERTICAL	PASSED
48.036072	37.60	75.86	71.60	-34.00	VERTICAL	PASSED
54.769539	29.00	28.18	66.50	-37.50	VERTICAL	PASSED
501.302004	34.90	55.59	62.80	-27.90	HORIZONTAL	PASSED
597.294389	29.20	28.84	55.20	-26.00	VERTICAL	PASSED

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3920.000000	40.50	105.93	42.90	-2.40	HORIZONTAL	PASSED
7840.000000	43.40	147.91	40.60	2.80	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3920.000000	27.60	23.99	30.00	-2.40	HORIZONTAL	PASSED
7840.000000	29.80	30.90	27.00	2.80	VERTICAL	PASSED

RX mode, channel 810 / 1989.8 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3980.000000	40.10	101.16	42.80	-2.70	HORIZONTAL	PASSED
7960.000000	43.10	142.89	40.00	3.10	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
3980.000000	27.70	24.27	30.40	-2.70	HORIZONTAL	PASSED
7960.000000	30.10	31.99	27.00	3.10	HORIZONTAL	PASSED

3.5. Bluetooth Test results

TX mode, channel 0 / 2402 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	41.80	123.03	43.50	-1.70	HORIZONTAL	PASSED
7206.000000	42.00	125.89	40.30	1.70	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4804.000000	27.60	23.99	29.30	-1.70	VERTICAL	PASSED
7206.000000	28.90	27.86	27.20	1.70	HORIZONTAL	PASSED

TX mode, channel 40 / 2442 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4882.000000	40.80	109.65	42.40	-1.60	HORIZONTAL	PASSED
7323.000000	42.60	134.90	40.30	2.30	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Polarisation	Result
4882.000000	27.60	23.99	29.20	-1.60	HORIZONTAL	PASSED
7323.000000	29.80	30.90	27.50	2.30	HORIZONTAL	PASSED

TX mode, channel 78 / 2480 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4960.000000	40.70	108.39	41.90	-1.20	HORIZONTAL	PASSED
7440.000000	43.60	151.36	40.90	2.70	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4960.000000	27.80	24.55	29.00	-1.20	HORIZONTAL	PASSED
7440.000000	29.90	31.26	27.20	2.70	VERTICAL	PASSED

3.6. WLAN Test results

RX mode, channel 1

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4824.000000	40.70	108.39	42.40	-1.70	HORIZONTAL	PASSED
7236.000000	42.30	130.32	40.30	2.00	VERTICAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4824.000000	27.10	22.65	28.80	-1.70	VERTICAL	PASSED
7236.000000	29.30	29.17	27.30	2.00	HORIZONTAL	PASSED

RX mode, channel 7 / 2442 MHz

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4884.000000	41.00	112.20	42.60	-1.60	VERTICAL	PASSED
7326.000000	42.60	134.90	40.30	2.30	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4884.000000	28.10	25.41	29.70	-1.60	VERTICAL	PASSED
7326.000000	29.90	31.26	27.60	2.30	HORIZONTAL	PASSED

RX mode, channel 11

Peak (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4924.000000	40.40	104.71	41.80	-1.40	HORIZONTAL	PASSED
7386.000000	43.00	141.25	40.40	2.60	HORIZONTAL	PASSED

Average (RBW: 1 MHz)

Frequency [MHz]	E [dB μ V/m]	E [μ V/m]	U _{RX} [dB μ V]	A _{TOT} [dB]	Polarisation	Result
4924.000000	28.10	25.41	29.50	-1.40	VERTICAL	PASSED
7386.000000	30.00	31.62	27.40	2.60	HORIZONTAL	PASSED

4. Test Equipment

4.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM37610	Spectrum analyzer	FSU	R&S	22/24, 15C
TM37678	Radio communication tester	CMU-200	R&S	22/24, 15C
	Attenuator 10 dB	6251.17.A	Huber+Suhner AG	22/24, 15C
TM37499	Power splitter	11667A	Agilent	22/24, 15C
	Temperature chamber	VT4002	Vötsch	22/24, 15C
TM38112	DC power supply	6632A	Agilent	22/24, 15C
TM38111	Multimeter	34401A	Agilent	22/24, 15C
	EMI Test receiver	ESPC	R&S	15C, 15B
TM37773	Radio communication tester	CMU-200	R&S	15C, 15B
TM38631	Signal generator	83640L	Agilent	15C, 15B
TM38114	DC power supply	6632A	Agilent	15C, 15B
TM22835	Multimeter	87	Fluke	15C, 15B
TM30600	Pulse Limiter	ESH3-Z2	R&S	15C, 15B
TM26490	LISN 50 µH	ESH3-Z5/	R&S	15C, 15B
TM30636	LISN 50 µH	L2-16/	PMM	15C, 15B

4.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM30599	3m semi-anechoic chamber		TDK	22/24, 15C, 15B
TM38845	EMI receiver	ESI 40	R&S	22/24, 15C, 15B
TM37498	Preamplifier	AMF-5D-020180-26-10P	MITEQ	22/24, 15C, 15B
TM37523	Preamplifier	AMF-4D-10M-3G-25-20P	MITEQ	22/24, 15C, 15B
TM37516	Biconilog antenna	HL562	R&S	22/24, 15C, 15B
TM26496	Double ridged waveguide antenna	3115	EMCO	22/24, 15C, 15B
TM39158	Horn antenna	3116	EMCO	22/24, 15C, 15B
TM26492	Reference dipole set	UHAP/VHAP	Schwarzbeck	22/24, 15C, 15B
TM37501	Dipole antenna	3125-870	EMCO	22/24
TM37502	Dipole antenna	3125-1880	EMCO	22/24
TM37773	Radio communication tester	CMU-200	R&S	22/24, 15C, 15B
TM38631	Signal generator	83640L	Agilent	22/24, 15C, 15B
TM38066	High pass filter	4HC3000/18000-3-KK	Trilithic	22/24, 15C, 15B
	High pass filter	WHK2010-10SS	Trilithic	22/24, 15C, 15B
	Low pass filter	WLK1750-10SS	Trilithic	22/24, 15C, 15B
TM26511	Tunable notch filter	WRCA870	Wainwright	22/24
TM38215	Tunable notch filter	WRCD1850/1910-0.2/40	Wainwright	22/24
TM38214	Band reject filter	WRCT 2402/2480-2400/2483.5-30	Wainwright	15C
TM30642	Turntable controller	HD-100	Deisel	22/24, 15C, 15B
TM26500	Turntable	DS412	Deisel	22/24, 15C, 15B
TM38842	Antenna mast controller	2090	EMCO	22/24, 15C, 15B
TM38843	Antenna mast	2075	EMCO	22/24, 15C, 15B
TM38114	DC power supply	6632A	Agilent	22/24, 15C, 15B
TM22835	Multimeter	87	Fluke	22/24, 15C, 15B