

Setup photos for HAC RF Emissions Test Report

Test report no.:	Salo_HAC_0812_12	Date of report:	2008-03-28
Template version:	1.0	Number of pages:	4
Testing laboratory:	TCC Salo P.O. Box 86 Joensuunkatu 7H / Kiila 1B FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 45220	Client:	Nokia Corporation P.O. Box 86 Joensuunkatu 7 FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 44277
Responsible test engineer:	Ari Orte	Product contact person:	Tia Melava
Measurements made by:	Ari Orte		
Tested devices:	RM-345		
FCC ID:	PYARM-345		
Supplement reports:	Salo_HAC_0812_11		
Testing has been carried out in accordance with:	ANSI C63.19-2006 American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test results:	The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.		
Date and signatures:			
For the contents:			

CONTENTS

1.1	TEST DETAILS.....	3
1.2	PICTURE OF DEVICE	3
1.3	TEST POSITIONS.....	4
1.3.1	<i>Scan area centered at the acoustic output.....</i>	<i>4</i>

1.1 Test Details

Period of test	2008-03-07 to 2008-03-12
SN, HW, SW and DUT numbers of tested device	SN: 352944/02/000604/8, HW: 0520, SW: 07.49.2, DUT: 12600
Batteries used in testing	BL-4U, DUT: 12601, 12602
State of sample	Prototype unit
Notes	AWF = -5 for GSM, 0 for WCDMA

1.2 Picture of Device



Slide closed



Slide open

1.3 Test Positions

1.3.1 Scan area centered at the acoustic output

The device was positioned such that Device Reference plane was touching the bottom of the Test Arch. The scan is centered at the acoustic output by aligning the acoustic output with the intersection of the Test Arch's middle bar and dielectric wire.



Device positioned under Test Arch