

Test setup photos for HAC Test Report

Test report no.:	Salo_HAC_0851_07	Date of report:	2008-12-19
Template version:	4.0	Number of pages:	4
Testing laboratory:	TCC Nokia Salo Laboratory P.O.Box 86 Joensuunkatu 7H / Kiila 1B FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 45220	Client:	Nokia Corporation P.O. Box 86 Joensuunkatu 7 FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 44277
Responsible test engineer:	Janne Hirsimäki	Product contact person:	Kari O. Koskela
Measurements made by:	Janne Hirsimäki		
Tested devices:	RM-413		
FCC ID:	PYARM-413	IC:	661V-RM413
Supplement reports:	Salo_HAC_0851_03		
Testing has been carried out in accordance with:	ANSI C63.19-2007 American National Standard for Methods of Measurement of Compatibility between Wireless Communications Devices and Hearing Aids		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test results:	The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.		
Date and signatures:			
For the contents:			

CONTENTS

1. SUMMARY OF HAC RF EMISSION TEST REPORT	3
1.1 TEST DETAILS.....	3
1.2 PICTURE OF DEVICE	3
1.3 TEST POSITIONS.....	4
1.3.1 <i>Scan area centered at the acoustic output</i>	4

1. SUMMARY OF HAC RF EMISSION TEST REPORT

1.1 Test Details

Period of test	2008-11-28 to 2008-12-16
SN, HW, SW and DUT numbers of tested device	SN: 356814/02/000031/5, HW: 0420, SW: 008.38.1, DUT: 13289
Batteries used in testing	BL-4U, DUT: 13323
State of sample	
Notes	AWF = -5 for GSM, 0 for WCDMA

1.2 Picture of Device



Flip closed



Flip open

1.3 Test Positions

1.3.1 Scan area centered at the acoustic output

The device was positioned such that Device Reference plane was touching the bottom of the Test Arch. The scan is centered at the acoustic output by aligning the acoustic output with the intersection of the Test Arch's middle bar and dielectric wire.



Photo of the device positioned under Test Arch