

SAR Compliance Test Report

Test report no.:	Salo_SAR_0804_14	Date of report:	2008-01-29
Template version:	8.0	Number of pages:	85
Testing laboratory:	TCC Nokia Copenhagen Lab. Frederikskaj, 1790 COPENHAGEN V, DENMARK TCC Nokia Salo Laboratory Joensuunkatu 7H 24101 SALO, FINLAND	Client:	Nokia Corporation P.O. Box 86 Joensuunkatu 7 FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 44277
Responsible test engineer:	Virpi Tuominen	Product contact person:	Tia Melava
Measurements made by:	Leif Klysner, Jesper Nielsen, Janne Hirsimäki		
Tested device:	RM-420		
FCC ID:	PYARM-420	IC:	661V-RM420
Supplement reports:	Cph_SAR_0803_10 for RM-343 / FCC ID: PYARM-343 / IC: 661V-RM343, Salo_SAR_0804_15		
Testing has been carried out in accordance with:	47CFR §2.1093 Radiofrequency Radiation Exposure Evaluation: Portable Devices FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01) Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields RSS-102 Evaluation Procedure for Mobile and Portable Radio Transmitters with Respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields IEEE 1528 - 2003 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Technique		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test results:	The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.		

Date and signatures:

For the contents:

CONTENTS

1. SUMMARY OF SAR TEST REPORT	3
1.1 TEST DETAILS.....	3
1.2 MAXIMUM RESULTS.....	3
1.2.1 Head Configuration.....	3
1.2.2 Body Worn Configuration	4
1.2.3 Maximum Drift	4
1.2.4 Measurement Uncertainty	4
2. DESCRIPTION OF THE DEVICE UNDER TEST.....	5
2.1 DESCRIPTION OF THE ANTENNA	5
3. TEST CONDITIONS	5
3.1 TEMPERATURE AND HUMIDITY	5
3.2 TEST SIGNAL, FREQUENCIES AND OUTPUT POWER	6
4. DESCRIPTION OF THE TEST EQUIPMENT	6
4.1 MEASUREMENT SYSTEM AND COMPONENTS	6
4.1.1 Isotropic E-field Probe Type ES3DV3	9
4.2 PHANTOMS	10
4.3 TISSUE SIMULANTS	11
4.3.1 Tissue Simulant Recipes	11
4.3.2 System Checking	12
4.3.3 Tissue Simulants used in the Measurements.....	14
5. DESCRIPTION OF THE TEST PROCEDURE	15
5.1 DEVICE HOLDER.....	15
5.2 TEST POSITIONS.....	15
5.2.1 Against Phantom Head.....	15
5.2.2 Body Worn Configuration	16
5.3 SCAN PROCEDURES	16
5.4 SAR AVERAGING METHODS.....	16
6. MEASUREMENT UNCERTAINTY	17
7. RESULTS	18
APPENDIX A: SYSTEM CHECKING SCAN	24
APPENDIX B: MEASUREMENT SCANS.....	32
APPENDIX C: RELEVANT PAGES FROM PROBE CALIBRATION REPORT(S)	84
APPENDIX D: RELEVANT PAGES FROM DIPOLE VALIDATION KIT REPORT(S)	85

1. SUMMARY OF SAR TEST REPORT

1.1 Test Details

Period of test	2008-01-10 to 2008-01-21
SN, HW and SW numbers of tested device	SN: 004401/01/436959/5, HW: 0303, SW: 07.45.3, DUT: 27580 SN: 004401/01/437252/4, HW: 0303, SW: 07.45.3, DUT: 27579 SN: 004401/01/728454/4, HW: 0330, SW: 07.45.3, DUT: 12451
Batteries used in testing	BL-4U, DUT: 27581, 27582, 27583, 27584, 27585, 27586, 12446, 12447
Headsets used in testing	HS-47, DUT: 27567, 12443
Other accessories used in testing	-
State of sample	Prototype unit
Notes	-

1.2 Maximum Results

The maximum measured SAR values for Head configuration and Body Worn configuration are given in section 1.2.1 and 1.2.2 respectively. The device conforms to the requirements of the standard(s) when the maximum measured SAR value is less than or equal to the limit.

1.2.1 Head Configuration

Mode	Ch / f (MHz)	Radiated power	Position	Measured SAR value (1g avg)	Scaled* SAR value (1g avg)	SAR limit (1g avg)	Result
WCDMA850	4175 / 835.0	15.5 dBm ERP	Right, Cheek	0.371 W/kg	0.42 W/kg	1.6 W/kg	PASSED
2-slot GPRS850**	251 / 848.8	24.1 dBm ERP	Right, Cheek	0.380 W/kg	0.43 W/kg	1.6 W/kg	PASSED
3-slot GPRS1900**	512 / 1850.2	27.3 dBm EIRP	Right, Cheek	0.905 W/kg	1.01 W/kg	1.6 W/kg	PASSED
WLAN2450**	11 / 2462.0	21.7 dBm EIRP	Right, Tilt	0.406 W/kg	0.45 W/kg	1.6 W/kg	PASSED
WCDMA850 + WLAN2450	-	-	Right, Tilt	0.678 W/kg	0.76 W/kg	1.6 W/kg	PASSED
2-slot GPRS850 + WLAN2450**	-	-	Right, Cheek	0.665 W/kg	0.74 W/kg	1.6 W/kg	PASSED
3-slot GPRS1900 + WLAN2450**	-	-	Right, Cheek	1.190 W/kg	1.33 W/kg	1.6 W/kg	PASSED

1.2.2 Body Worn Configuration

Mode	Ch / f (MHz)	Radiated power	Separation distance	Measured SAR value (1g avg)	Scaled* SAR value (1g avg)	SAR limit (1g avg)	Result
WCDMA850	4233 / 846.6	13.8 dBm ERP	2.2 cm	0.314 W/kg	0.35 W/kg	1.6 W/kg	PASSED
2-slot GPRS850**	251 / 848.8	24.1 dBm ERP	2.2 cm	0.321 W/kg	0.36 W/kg	1.6 W/kg	PASSED
3-slot GPRS1900**	512 / 1850.2	27.3 dBm EIRP	2.2 cm	0.251 W/kg	0.28 W/kg	1.6 W/kg	PASSED
WLAN2450**	7 / 2442.0	20.8 dBm EIRP	2.2 cm	0.079 W/kg	0.09 W/kg	1.6 W/kg	PASSED
WCDMA850 + WLAN2450	-	-	2.2 cm	0.393 W/kg	0.44 W/kg	1.6 W/kg	PASSED
2-slot GPRS850 + WLAN2450**	-	-	2.2 cm	0.400 W/kg	0.45 W/kg	1.6 W/kg	PASSED
3-slot GPRS1900 + WLAN2450**	-	-	2.2 cm	0.327 W/kg	0.37 W/kg	1.6 W/kg	PASSED

*SAR values are scaled up by 12% to cover measurement drift.

**SAR values taken from Cph_SAR_0803_10 for RM-343 /FCC ID: PYARM-343 / IC ID: 661V-RM343.

1.2.3 Maximum Drift

Maximum drift covered by 12% scaling up of the SAR values	Maximum drift during measurements
0.5dB	0.50 dB

1.2.4 Measurement Uncertainty

Expanded Uncertainty (k=2) 95%	± 25.8%
--------------------------------	---------

2. DESCRIPTION OF THE DEVICE UNDER TEST

Device category	Portable
Exposure environment	General population / uncontrolled

Modes of Operation	Bands	Modulation Mode	Duty Cycle	Transmitter Frequency Range (MHz)
GSM	850 1900	GMSK	1/8	824 – 849 1850 – 1910
GPRS	850 1900	GMSK	1/8 to 3/8	824 – 849 1850 – 1910
EGPRS	850 1900	GMSK / 8PSK	1/8 to 3/8	824 – 849 1850 – 1910
WCDMA	850 (Band V)		1	824 - 849
BT	2450	GFSK	1	2402 – 2480
WLAN	2450	11Mbps QPSK	1	2412 – 2462

Outside of USA and Canada, the transmitter of the device is capable of operating also in GSM/GPRS/EGPRS900, GSM/GPRS/EGPRS1800 and WCDMA2100 bands which are not part of this filing.

This device has Voice-over-IP/Dual Transfer Mode capability for use at the ear. Therefore, SAR for multi slot GPRS mode was evaluated against the head profile of the phantom.

2.1 Description of the Antenna

The device has an internal antenna.

3. TEST CONDITIONS

3.1 Temperature and Humidity

Ambient temperature (°C):	20.5 to 22.5
Ambient humidity (RH %):	35 to 55

3.2 Test Signal, Frequencies and Output Power

The device was put into operation by using a call tester except for testing WLAN2450 where control software was used. Communication between the device and the call tester was established by air link.

The device output power was set to maximum power level for all tests; a fully charged battery was used for every test sequence.

In all operating bands the measurements were performed on lowest, middle and highest channels.

The radiated output power of the device was measured by a separate test laboratory on the same unit(s) as used for SAR testing.

The transmission mode of the device in all WCDMA tests was configured to 12.2kbps RMC with all TPC bits set as "1".

Some of the SAR results, SAR plots and test details given in this report are duplicated from the earlier report Cph_SAR_0803_10 for RM-343 / FCC ID: PYARM-343 / IC ID: 661V-RM343. The difference between RM-420 and RM-343 is that RM-420 has had WCDMA900 components removed and WCDMA850 components added.

4. DESCRIPTION OF THE TEST EQUIPMENT

4.1 Measurement System and Components

The measurements were performed using an automated near-field scanning system, DASY4, manufactured by Schmid & Partner Engineering AG (SPEAG) in Switzerland. The SAR extrapolation algorithm used in all measurements was the 'advanced extrapolation' algorithm.

The following table lists calibration dates of SPEAG components:

Test Equipment	Serial Number	Calibration interval	Calibration expiry
DAE3	339	12 months	2008-06
DAE4	682	12 months	2008-08
DAE4	710	12 months	2008-10
DAE4	728	12 months	2008-02
E-field Probe ES3DV3	3116	12 months	2008-08
E-field Probe ES3DV3	3117	12 months	2008-08
E-field Probe ES3DV3	3119	12 months	2008-10
E-field Probe ET3DV6	1396	12 months	2008-02
Dipole Validation Kit, D835V2	480	24 months	2009-05
Dipole Validation Kit, D835V2	4d042	24 months	2008-09
Dipole Validation Kit, D1900V2	5d026	24 months	2008-02
Dipole Validation Kit, D2450V2	750	24 months	2008-02
DASY4 software	Version 4.7	-	-

Additional test equipment used in testing:

Test Equipment	Model	Serial Number	Calibration interval	Calibration expiry
Signal Generator	SME06	848650/011	36 months	2008-07
Signal Generator	SML03	101265	12 months	2008-07
Amplifier	2100-BBS3Q8CCJ	1003	-	-
Amplifier	ZHL-42 (SMA)	N072095-5	12 months	2008-07
Power Meter	NRP	100808	24 months	2008-03
Power Sensor	NRP-Z51	100412	24 months	2008-03
Power Meter	NRVS	849305/028	12 months	2008-07
Power Sensor	NRV-Z32	839176/020	12 months	2008-07
Call Tester	4400M	0411216	-	-
Call Tester	CMU 200	103293	-	-
Call Tester	CMU 200	104983	-	-
BT Tester	CBT	100263	-	-
Vector Network Analyzer	AT8753ES	MY40001091	12 months	2008-08
Dielectric Probe Kit	HP85070B	US33020403	-	-
Vector Network Analyzer	8753E	US38432928	12 months	2008-07
Dielectric Probe Kit	85070B	US33020420	-	-

4.1.1 Isotropic E-field Probe Type ET3DV6

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., butyl diglycol)
Calibration	Calibration certificate in Appendix C
Frequency	10 MHz to 3 GHz (dosimetry); Linearity: ± 0.2 dB (30 MHz to 3 GHz)
Optical Surface Detection	± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic Range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm Tip length: 16 mm Body diameter: 12 mm Tip diameter: 6.8 mm Distance from probe tip to dipole centers: 2.7 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms

4.1.2 Isotropic E-field Probe Type ES3DV3

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., butyl diglycol)
Calibration	Calibration certificate in Appendix C
Frequency	10 MHz to 4 GHz (dosimetry); Linearity: ± 0.2 dB (30 MHz to 4 GHz)
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in HSL (rotation normal to probe axis)
Dynamic Range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm Tip length: 20 mm Body diameter: 12 mm Tip diameter: 3.9 mm Distance from probe tip to dipole centers: 2.0 mm
Application	General dosimetry up to 4 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms

4.2 Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin-headed "SAM Phantom", manufactured by SPEAG. The phantom conforms to the requirements of IEEE 1528 - 2003.

System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.

The SPEAG device holder (see Section 5.1) was used to position the device in all tests whilst a tripod was used to position the validation dipoles against the flat section of phantom.

4.3 Tissue Simulants

Recommended values for the dielectric parameters of the tissue simulants are given in IEEE 1528 - 2003 and FCC Supplement C to OET Bulletin 65. All tests were carried out using simulants whose dielectric parameters were within $\pm 5\%$ of the recommended values. All tests were carried out within 24 hours of measuring the dielectric parameters.

The depth of the tissue simulant was 15.0 ± 0.5 cm measured from the ear reference point during system checking and device measurements.

4.3.1 Tissue Simulant Recipes

The following recipe(s) were used for Head and Body tissue simulant(s):

800MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	51.50	69.25
Tween 20	47.35	30.00
Salt	1.15	0.75

800MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	39.74	55.97
HEC	0.25	1.21
Sugar	58.31	41.76
Preservative	0.15	0.27
Salt	1.55	0.79

1900MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	54.88	69.02
Butyl Diglycol	44.91	30.76
Salt	0.21	0.22

2450MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	56.0	70.20
Tween 20	44.0	29.62
Salt	-	0.18

4.3.2 System Checking

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulants were measured every day using the dielectric probe kit and the network analyser. A system check measurement was made following the determination of the dielectric parameters of the simulant, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system checking results (dielectric parameters and SAR values) are given in the table below.

System checking, head tissue simulant

f [MHz]	Description	SAR [W/kg], 1g	Dielectric Parameters		Temp [°C]
			ϵ_r	σ [S/m]	
835	Reference result	2.29	41.6	0.90	
	± 10% window	2.06 – 2.52			
	2008-01-15	2.34	40.7	0.91	21.0
	2008-01-16	2.37	40.7	0.91	21.0
835	Reference result	2.33	42.2	0.90	
	± 10% window	2.10 - 2.56			
	2008-01-16	2.43	41.9	0.91	21.6
1900	Reference result	9.83	39.4	1.42	
	± 10% window	8.85 - 10.81			
	2008-01-10	10.5	40.2	1.45	21.5
2450	Reference result	13.7	38.5	1.79	
	± 10% window	12.3 - 15.1			
	2008-01-14	13.3	38.9	1.88	22.0

System checking, body tissue simulant

f [MHz]	Description	SAR [W/kg], 1g	Dielectric Parameters		Temp [°C]
			ϵ_r	σ [S/m]	
835	Reference result	2.45	53.8	0.98	
	± 10% window	2.20 - 2.70			
	2008-01-21	2.43	53.1	0.96	21.9
1900	Reference result	10.0	54.8	1.54	
	± 10% window	9.0 - 11.0			
	2008-01-17	10.5	52.5	1.52	21.2
2450	Reference result	13.5	53.8	1.97	
	± 10% window	12.1 - 14.9			
	2008-01-18	14.3	52.0	2.04	21.6

Plots of the system checking scans are given in Appendix A.

4.3.3 Tissue Simulants used in the Measurements

Head tissue simulant measurements

f [MHz]	Description	Dielectric Parameters		Temp [°C]
		ϵ_r	σ [S/m]	
836	Recommended value	41.5	0.90	
	± 5% window	39.4 – 43.6	0.86 – 0.95	
	2008-01-15	40.7	0.91	21.0
	2008-01-16	40.7	0.91	21.0
	2008-01-16	41.9	0.91	21.6
1880	Recommended value	40.0	1.40	
	± 5% window	38.0 – 42.0	1.33 – 1.47	
	2008-01-10	40.3	1.43	21.5
2442	Recommended value	39.2	1.79	
	± 5% window	37.3 – 41.2	1.70 – 1.88	
	2008-01-14	39.0	1.87	22.0

Body tissue simulant measurements

f [MHz]	Description	Dielectric Parameters		Temp [°C]
		ϵ_r	σ [S/m]	
836	Recommended value	55.2	0.97	
	± 5% window	52.4 – 58.0	0.92 – 1.02	
	2008-01-16	54.5	1.00	21.0
	2008-01-21	53.1	0.96	21.9
1880	Recommended value	53.3	1.52	
	± 5% window	50.6 – 56.0	1.44 – 1.60	
	2008-01-17	52.5	1.49	21.2
2442	Recommended value	52.7	1.94	
	± 5% window	50.1 – 55.3	1.85 – 2.04	
	2008-01-18	52.0	2.03	21.6

5. DESCRIPTION OF THE TEST PROCEDURE

5.1 Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the Dasy system.



Device holder supplied by SPEAG

A Nokia designed spacer (illustrated below) was used to position the device within the SPEAG holder. The spacer positions the device so that the holder has minimal effect on the test results but still holds the device securely. The spacer was removed before the tests.



Nokia spacer

5.2 Test Positions

5.2.1 Against Phantom Head

Measurements were made in “cheek” and “tilt” positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2003 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".

5.2.2 Body Worn Configuration

The device was placed in the SPEAG holder using the Nokia spacer and placed below the flat section of the phantom. The distance between the device and the phantom was kept at the separation distance indicated in Section 1.2.2 using a separate flat spacer that was removed before the start of the measurements. The device was oriented with its antenna facing the phantom since this orientation gives higher results.

5.3 Scan Procedures

First, area scans were used for determination of the field distribution. Next, a zoom scan, a minimum of 5x5x7 points covering a volume of at least 30x30x30mm, was performed around the highest E-field value to determine the averaged SAR value. Drift was determined by measuring the same point at the start of the area scan and again at the end of the zoom scan.

5.4 SAR Averaging Methods

The maximum SAR value was averaged over a cube of tissue using interpolation and extrapolation.

The interpolation, extrapolation and maximum search routines within Dasy4 are all based on the modified Quadratic Shepard's method (Robert J. Renka, "Multivariate Interpolation Of Large Sets Of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988, pp. 139-148).

The interpolation scheme combines a least-square fitted function method with a weighted average method. A trivariate 3-D / bivariate 2-D quadratic function is computed for each measurement point and fitted to neighbouring points by a least-square method. For the zoom scan, inverse distance weighting is incorporated to fit distant points more accurately. The interpolating function is finally calculated as a weighted average of the quadratics.

In the zoom scan, the interpolation function is used to extrapolate the Peak SAR from the deepest measurement points to the inner surface of the phantom.

6. MEASUREMENT UNCERTAINTY

Table 6.1 – Measurement uncertainty evaluation

Uncertainty Component	Section in IEEE 1528	Tol. (%)	Prob Dist	Div	G_i	$G_i \cdot u_i$ (%)	v_i
Measurement System							
Probe Calibration	E2.1	±5.9	N	1	1	±5.9	∞
Axial Isotropy	E2.2	±4.7	R	√3	$(1-c_p)^{1/2}$	±1.9	∞
Hemispherical Isotropy	E2.2	±9.6	R	√3	$(c_p)^{1/2}$	±3.9	∞
Boundary Effect	E2.3	±1.0	R	√3	1	±0.6	∞
Linearity	E2.4	±4.7	R	√3	1	±2.7	∞
System Detection Limits	E2.5	±1.0	R	√3	1	±0.6	∞
Readout Electronics	E2.6	±1.0	N	1	1	±1.0	∞
Response Time	E2.7	±0.8	R	√3	1	±0.5	∞
Integration Time	E2.8	±2.6	R	√3	1	±1.5	∞
RF Ambient Conditions - Noise	E6.1	±3.0	R	√3	1	±1.7	∞
RF Ambient Conditions - Reflections	E6.1	±3.0	R	√3	1	±1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	±0.4	R	√3	1	±0.2	∞
Probe Positioning with respect to Phantom Shell	E6.3	±2.9	R	√3	1	±1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E5	±3.9	R	√3	1	±2.3	∞
Test sample Related							
Test Sample Positioning	E4.2	±6.0	N	1	1	±6.0	11
Device Holder Uncertainty	E4.1	±5.0	N	1	1	±5.0	7
Output Power Variation - SAR drift measurement	6.6.3	±0.0	R	√3	1	±0.0	∞
Phantom and Tissue Parameters							
Phantom Uncertainty (shape and thickness tolerances)	E3.1	±4.0	R	√3	1	±2.3	∞
Conductivity Target - tolerance	E3.2	±5.0	R	√3	0.64	±1.8	∞
Conductivity - measurement uncertainty	E3.3	±5.5	N	1	0.64	±3.5	5
Permittivity Target - tolerance	E3.2	±5.0	R	√3	0.6	±1.7	∞
Permittivity - measurement uncertainty	E3.3	±2.9	N	1	0.6	±1.7	5
Combined Standard Uncertainty			RSS			±12.9	116
Coverage Factor for 95%			k=2				
Expanded Uncertainty						±25.8	

7. RESULTS

The measured Head SAR values for the test device are tabulated below:

850MHz Head SAR results

Option used	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 128 824.2 MHz	Ch 190 836.6 MHz	Ch 251 848.8 MHz
GSM	Power		24.1 dBm	25.0 dBm	24.3 dBm
Slide closed	Left	Cheek	-	0.137	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
2-slot GPRS	Power		23.5 dBm	24.6 dBm	24.1 dBm
Slide closed	Left	Cheek	-	0.242	-
		Tilt	-	0.180	-
	Right	Cheek	0.242	0.322	0.380
		Tilt	-	0.205	-
2-slot GPRS	Power		21.2 dBm	23.3 dBm	25.3 dBm
Slide open	Left	Cheek	-	0.249	-
		Tilt	-	0.170	-
	Right	Cheek	-	0.312	-
		Tilt	-	0.184	-
3-slot GPRS	Power		21.9 dBm	22.8 dBm	22.2 dBm
Slide closed	Left	Cheek	-	0.235	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
2-slot 8PSK EGPRS	Power		15.6 dBm	16.2 dBm	15.5 dBm
Slide closed	Left	Cheek	-	-	-
		Tilt	-	-	-
	Right	Cheek	-	-	0.077
		Tilt	-	-	-
2-slot GPRS Slide closed	Right Cheek, BT active		-	-	0.373

(850MHz Table continues)

(850MHz Table continues)

Option used	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 4132 826.4 MHz	Ch 4175 835.0 MHz	Ch 4233 846.6 MHz
WCDMA	Power		12.2 dBm	13.3 dBm	13.8 dBm
Slide closed	Left	Cheek	-	0.290	-
		Tilt	-	0.254	-
	Right	Cheek	-	0.353	-
		Tilt	-	0.272	-
WCDMA	Power		13.4 dBm	15.5 dBm	15.7 dBm
Slide open	Left	Cheek	-	0.297	-
		Tilt	-	0.218	-
	Right	Cheek	0.236	0.360	0.314
		Tilt	-	0.242	-
WCDMA Slide open	Right Cheek, BT active		-	0.371	-

1900MHz Head SAR results

Option used	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 512 1850.2 MHz	Ch 661 1880.0 MHz	Ch 810 1909.8 MHz
GSM	Power		28.7 dBm	28.2 dBm	28.0 dBm
Slide closed	Left	Cheek	-	0.248	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
2-slot GPRS	Power		28.4 dBm	27.9 dBm	27.4 dBm
Slide closed	Left	Cheek	-	0.448	-
		Tilt	-	-	-
	Right	Cheek	-	-	-
		Tilt	-	-	-
3-slot GPRS	Power		27.3 dBm	26.7 dBm	26.6 dBm
Slide closed	Left	Cheek	-	0.507	-
		Tilt	-	0.441	-
	Right	Cheek	0.905	0.773	0.566
		Tilt	-	0.314	-
3-slot GPRS	Power		28.3 dBm	27.6 dBm	27.7 dBm
Slide open	Left	Cheek	-	0.189	-
		Tilt	-	0.320	-
	Right	Cheek	-	0.458	-
		Tilt	-	0.361	-
3-slot 8PSK EGPRS	Power		24.7 dBm	24.4 dBm	24.0 dBm
Slide closed	Left	Cheek	-	-	-
		Tilt	-	-	-
	Right	Cheek	0.373	-	-
		Tilt	-	-	-
3-slot GPRS Slide closed	Right Cheek, BT active		0.888	-	-

2450MHz Head SAR results

Option used	Test configuration		SAR, averaged over 1g (W/kg)		
			Ch 1 2412.0 MHz	Ch 7 2442.0 MHz	Ch 11 2462.0 MHz
WLAN	Power		22.9 dBm	20.8 dBm	21.7 dBm
Slide closed	Left	Cheek	-	0.303	-
		Tilt	-	0.345	-
	Right	Cheek	-	0.285	-
		Tilt	0.357	0.360	0.406
WLAN	Power		18.5 dBm	16.7 dBm	19.3 dBm
Slide open	Left	Cheek	-	0.074	-
		Tilt	-	0.055	-
	Right	Cheek	-	0.048	-
		Tilt	-	0.046	-

The measured Body SAR values for the test device are tabulated below:

850MHz Body SAR results

Option used	Test configuration	SAR, averaged over 1g (W/kg)		
		Ch 128 824.2 MHz	Ch 190 836.6 MHz	Ch 251 848.8 MHz
2-slot GPRS	Power	23.5 dBm	24.6 dBm	24.1 dBm
Slide closed	Without headset	0.161	0.235	0.311
	Headset HS-47	0.131	0.193	0.275
Slide closed	Without headset, BT active	-	-	0.321
Option used	Test configuration	SAR, averaged over 1g (W/kg)		
		Ch 4132 826.4 MHz	Ch 4175 835.0 MHz	Ch 4233 846.6 MHz
WCDMA	Power	12.2 dBm	13.3 dBm	13.8 dBm
Slide closed	Without headset	0.188	0.282	0.314
	Headset HS-47	0.150	0.218	0.260
Slide closed	Without headset, BT active	-	-	0.304

1900MHz Body SAR results

Option used	Test configuration	SAR, averaged over 1g (W/kg)		
		Ch 512 1850.2 MHz	Ch 661 1880.0 MHz	Ch 810 1909.8 MHz
3-slot GPRS	Power	27.3 dBm	26.7 dBm	26.6 dBm
Slide closed	Without headset	0.243	0.208	0.148
	Headset HS-47	0.244	0.205	0.146
Slide closed	Headset HS-47, BT active	0.251	-	-

2450MHz Body SAR results

Option used	Test configuration	SAR, averaged over 1g (W/kg)		
		Ch 1 2412.0 MHz	Ch 7 2442.0 MHz	Ch 11 2462.0 MHz
WCDMA	Power	22.9 dBm	20.8 dBm	21.7 dBm
Slide closed	Without headset	0.076	0.079	0.071
	Headset HS-47	0.067	0.076	0.072

Simultaneous transmissions: Combined SAR results

Test configuration	WLAN 2450	WCDMA 850	GSM850	GSM1900	WLAN + WCDMA 850	WLAN + GSM850	WLAN + GSM1900
Head: Left, Cheek	0.303	0.297	0.249	0.507	0.600	0.552	0.810
Head: Left, Tilt	0.345	0.254	0.180	0.441	0.599	0.525	0.786
Head: Right, Cheek	0.285	0.371	0.380	0.905	0.656	0.665	1.190
Head: Right, Tilt	0.406	0.272	0.205	0.361	0.678	0.611	0.767
Body: Without Headset	0.079	0.314	0.321	0.243	0.393	0.400	0.322
Body: Headset HS-47	0.076	0.260	0.275	0.251	0.336	0.351	0.327

Combining the maximum SAR values of WLAN2450 and the cellular bands tends to overestimate the SAR value since their maxima do not necessarily occur in the same location.

Plots of the Measurement scans are given in Appendix B.

APPENDIX A: SYSTEM CHECKING SCAN

Date/Time: 2008-01-15 11:08:03

Test Laboratory: TCC Nokia

Type: D835V2; Serial: 480

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 19.9C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.91$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.86, 6.86, 6.86); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.54 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.3 V/m


Peak SAR (extrapolated) = 3.46 W/kg

SAR(1 g) = 2.34 mW/g

SAR(10 g) = 1.54 mW/g

Power Drift = 0.010 dB

Maximum value of SAR (measured) = 2.55 mW/g



Date/Time: 2008-01-16 10:02:55

Test Laboratory: TCC Nokia

Type: D835V2; Serial: 480

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 21.6C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.909$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.86, 6.86, 6.86); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.53 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.6 V/m


Peak SAR (extrapolated) = 3.53 W/kg

SAR(1 g) = 2.37 mW/g

SAR(10 g) = 1.55 mW/g

Power Drift = 0.014 dB

Maximum value of SAR (measured) = 2.57 mW/g



Date/Time: 2008-01-16 14:42:34

Test Laboratory: TCC Nokia
Type: D835V2; Serial: 4d042

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.909 \text{ mho/m}$; $\epsilon_r = 41.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x121x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 2.63 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 54.5 V/m


Peak SAR (extrapolated) = 3.62 W/kg

SAR(1 g) = 2.43 mW/g

SAR(10 g) = 1.59 mW/g

Power Drift = -0.075 dB

Maximum value of SAR (measured) = 2.63 mW/g



Date/Time: 2008-01-10 12:17:37

Test Laboratory: TCC Nokia
Type: D1900V2; Serial: 5d026

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.45$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=10mm, Pin=250mW/Area Scan (71x71x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 11.7 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 90.4 V/m


Peak SAR (extrapolated) = 19.7 W/kg

SAR(1 g) = 10.5 mW/g

SAR(10 g) = 5.4 mW/g

Power Drift = -0.021 dB

Maximum value of SAR (measured) = 11.9 mW/g



Date/Time: 2008-01-14 18:06:06

Test Laboratory: TCC Nokia

Type: D2450V2; Serial: 750

Communication System: CW2450

Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: Head 2450; Medium Notes: Medium Temperature: 22.0 C

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.88$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.43, 4.43, 4.43); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2007-08-29
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=10mm, Pin=250mW/Area Scan (71x71x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 15.3 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 75.4 V/m

Peak SAR (extrapolated) = 28.4 W/kg

SAR(1 g) = 13.3 mW/g

SAR(10 g) = 6.15 mW/g

Power Drift = 0.065 dB

Maximum value of SAR (measured) = 15.0 mW/g



Date/Time: 2008-01-21 15:20:36

Test Laboratory: TCC Nokia
Type: D835V2; Serial: 4d042

Communication System: CW835

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Body 850; Medium Notes: Medium Temperature: 21.9 C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.959$ mho/m; $\epsilon_r = 53.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.74, 5.74, 5.74); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 5; Type: Twin Phantom; Serial: TP-1412
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 2.63 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 46.2 V/m


Peak SAR (extrapolated) = 3.52 W/kg

SAR(1 g) = 2.43 mW/g

SAR(10 g) = 1.61 mW/g

Power Drift = -0.031 dB

Maximum value of SAR (measured) = 2.63 mW/g



Date/Time: 2008-01-17 12:13:33

Test Laboratory: TCC Nokia
Type: D1900V2; Serial: 5d026

Communication System: CW1900

Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: Body 1900; Medium Notes: Medium Temperature: 21.2 C

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.52$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3119; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2007-10-24
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn710; Calibrated: 2007-10-16
- Phantom: SAM 8; Type: SAM Twin Phantom; Serial: TP-1408
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=10mm, Pin=250mW/Area Scan (71x71x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 12.2 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 68.4 V/m


Peak SAR (extrapolated) = 18.9 W/kg

SAR(1 g) = 10.5 mW/g

SAR(10 g) = 5.55 mW/g

Power Drift = 0.063 dB

Maximum value of SAR (measured) = 12.0 mW/g



Date/Time: 2008-01-18 18:48:10

Test Laboratory: TCC Nokia

Type: D2450V2; Serial: 750

Communication System: CW2450

Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: Body 2450; Medium Notes: Medium Temperature: $t=21.6$ C

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.04$ mho/m; $\epsilon_r = 52$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(4.12, 4.12, 4.12); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

d=10mm, Pin=250mW/Area Scan (71x71x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 16.9 mW/g

d=10mm, Pin=250mW/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 73.3 V/m

Peak SAR (extrapolated) = 29.7 W/kg

SAR(1 g) = 14.3 mW/g

SAR(10 g) = 6.63 mW/g

Power Drift = -0.010 dB

Maximum value of SAR (measured) = 16.1 mW/g



APPENDIX B: MEASUREMENT SCANS

Date/Time: 2008-01-16 15:38:03

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: GSM850

Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.149 mW/g

Cheek position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 4.98 V/m


Peak SAR (extrapolated) = 0.183 W/kg

SAR(1 g) = 0.137 mW/g

SAR(10 g) = 0.101 mW/g

Power Drift = 0.007 dB

Maximum value of SAR (measured) = 0.145 mW/g



Date/Time: 2008-01-16 15:55:27

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.267 mW/g

Cheek position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.75 V/m


Peak SAR (extrapolated) = 0.327 W/kg

SAR(1 g) = 0.242 mW/g

SAR(10 g) = 0.180 mW/g

Power Drift = -0.246 dB

Maximum value of SAR (measured) = 0.256 mW/g



Date/Time: 2008-01-16 16:49:19

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.193 mW/g

Tilt position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.8 V/m


Peak SAR (extrapolated) = 0.234 W/kg

SAR(1 g) = 0.180 mW/g

SAR(10 g) = 0.134 mW/g

Power Drift = -0.257 dB

Maximum value of SAR (measured) = 0.191 mW/g



Date/Time: 2008-01-16 19:05:33

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 848.8 MHz; Duty Cycle: 1:4.2

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used: $f = 849$ MHz; $\sigma = 0.924$ mho/m; $\epsilon_r = 41.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - High - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.421 mW/g

Cheek position - High - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.60 V/m


Peak SAR (extrapolated) = 0.492 W/kg

SAR(1 g) = 0.380 mW/g

SAR(10 g) = 0.279 mW/g

Power Drift = -0.224 dB

Maximum value of SAR (measured) = 0.395 mW/g



SAR Report

Salo_SAR_0804_14

Applicant: Nokia Corporation

Type: RM-420

Copyright © 2008 TCC Nokia

Date/Time: 2008-01-16 17:59:54

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.9$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.217 mW/g

Tilt position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.7 V/m


Peak SAR (extrapolated) = 0.263 W/kg

SAR(1 g) = 0.205 mW/g

SAR(10 g) = 0.152 mW/g

Power Drift = -0.021 dB

Maximum value of SAR (measured) = 0.216 mW/g



Date/Time: 2008-01-16 17:09:02

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide open/Area Scan (51x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.275 mW/g

Cheek position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 5.55 V/m


Peak SAR (extrapolated) = 0.348 W/kg

SAR(1 g) = 0.249 mW/g

SAR(10 g) = 0.180 mW/g

Power Drift = -0.209 dB

Maximum value of SAR (measured) = 0.265 mW/g



Date/Time: 2008-01-16 17:23:53

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle - Slide open/Area Scan (51x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.181 mW/g

Tilt position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.84 V/m


Peak SAR (extrapolated) = 0.209 W/kg

SAR(1 g) = 0.170 mW/g

SAR(10 g) = 0.130 mW/g

Power Drift = -0.226 dB

Maximum value of SAR (measured) = 0.177 mW/g



Date/Time: 2008-01-16 18:12:06

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.9$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide open/Area Scan (51x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.346 mW/g

Cheek position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 5.78 V/m

Peak SAR (extrapolated) = 0.424 W/kg


SAR(1 g) = 0.312 mW/g

SAR(10 g) = 0.225 mW/g

Power Drift = -0.019 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.336 mW/g



Date/Time: 2008-01-16 18:26:58

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.9$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle - Slide open/Area Scan (51x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.198 mW/g

Tilt position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.90 V/m


Peak SAR (extrapolated) = 0.236 W/kg

SAR(1 g) = 0.184 mW/g

SAR(10 g) = 0.136 mW/g

Power Drift = -0.130 dB

Maximum value of SAR (measured) = 0.196 mW/g



Date/Time: 2008-01-16 16:33:33

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:2.8

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used (interpolated): $f = 836.6$ MHz; $\sigma = 0.912$ mho/m; $\epsilon_r = 41.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.259 mW/g

Cheek position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.76 V/m


Peak SAR (extrapolated) = 0.323 W/kg

SAR(1 g) = 0.235 mW/g

SAR(10 g) = 0.174 mW/g

Power Drift = -0.192 dB

Maximum value of SAR (measured) = 0.251 mW/g



Date/Time: 2008-01-16 19:49:26

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot 8PSK EGPRS850

Frequency: 848.8 MHz; Duty Cycle: 1:4.2

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used: $f = 849$ MHz; $\sigma = 0.924$ mho/m; $\epsilon_r = 41.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - High - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.095 mW/g

Cheek position - High - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 2.98 V/m

Peak SAR (extrapolated) = 0.111 W/kg


SAR(1 g) = 0.077 mW/g

SAR(10 g) = 0.055 mW/g

Power Drift = -0.086 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.111 mW/g



Date/Time: 2008-01-16 19:24:25

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 848.8 MHz; Duty Cycle: 1:4.2

Medium: Head 850; Medium Notes: Medium Temperature: 21.6 C

Medium parameters used: $f = 849$ MHz; $\sigma = 0.924$ mho/m; $\epsilon_r = 41.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(6.01, 6.01, 6.01); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 1; Type: Twin Phantom; Serial: TP-1215
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - High - Slide closed - BT active/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.413 mW/g

Cheek position - High - Slide closed - BT active/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.65 V/m


Peak SAR (extrapolated) = 0.490 W/kg

SAR(1 g) = 0.373 mW/g

SAR(10 g) = 0.272 mW/g

Power Drift = 0.009 dB

Maximum value of SAR (measured) = 0.391 mW/g



Date/Time: 2008-01-15 18:02:12

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 21.2C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.91$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.86, 6.86, 6.86); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position – Middle - Slide closed/Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.311 mW/g

Cheek position – Middle - Slide closed /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.52 V/m


Peak SAR (extrapolated) = 0.364 W/kg

SAR(1 g) = 0.290 mW/g

SAR(10 g) = 0.219 mW/g

Power Drift = -0.100 dB

Maximum value of SAR (measured) = 0.304 mW/g



Date/Time: 2008-01-15 18:15:34

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 21.2C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.91$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.86, 6.86, 6.86); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position – Middle - Slide closed/Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.263 mW/g

Tilt position – Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.9 V/m


Peak SAR (extrapolated) = 0.331 W/kg

SAR(1 g) = 0.254 mW/g

SAR(10 g) = 0.187 mW/g

Power Drift = 0.003 dB

Maximum value of SAR (measured) = 0.271 mW/g



Date/Time: 2008-01-16 10:43:37

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 21.4C

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.909 \text{ mho/m}$; $\epsilon_r = 40.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.86, 6.86, 6.86); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position – Middle - Slide closed/Area Scan (41x81x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.387 mW/g

Cheek position – Middle - Slide closed /Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.86 V/m

Peak SAR (extrapolated) = 0.448 W/kg


SAR(1 g) = 0.353 mW/g

SAR(10 g) = 0.264 mW/g

Power Drift = 0.443 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.375 mW/g



Date/Time: 2008-01-16 10:57:23

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 21.4C

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.909 \text{ mho/m}$; $\epsilon_r = 40.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.86, 6.86, 6.86); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position – Middle - Slide closed/Area Scan (41x81x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.283 mW/g

Tilt position – Middle - Slide closed /Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.3 V/m


Peak SAR (extrapolated) = 0.345 W/kg

SAR(1 g) = 0.272 mW/g

SAR(10 g) = 0.202 mW/g

Power Drift = -0.081 dB

Maximum value of SAR (measured) = 0.284 mW/g



Date/Time: 2008-01-16 12:37:11

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 21.2C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.909$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.86, 6.86, 6.86); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position – Middle - Slide open/Area Scan (41x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.318 mW/g

Cheek position – Middle - Slide open /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.48 V/m


Peak SAR (extrapolated) = 0.378 W/kg

SAR(1 g) = 0.297 mW/g

SAR(10 g) = 0.225 mW/g

Power Drift = -0.207 dB

Maximum value of SAR (measured) = 0.310 mW/g



Date/Time: 2008-01-16 12:57:25

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 21.2C

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.909 \text{ mho/m}$; $\epsilon_r = 40.7$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.86, 6.86, 6.86); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position – Middle - Slide open/Area Scan (41x101x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.229 mW/g

Tilt position – Middle - Slide open /Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 13.1 V/m


Peak SAR (extrapolated) = 0.278 W/kg

SAR(1 g) = 0.218 mW/g

SAR(10 g) = 0.162 mW/g

Power Drift = -0.196 dB

Maximum value of SAR (measured) = 0.229 mW/g



Date/Time: 2008-01-16 12:01:16

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 21.2C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.909$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.86, 6.86, 6.86); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position – Middle - Slide open/Area Scan (41x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.389 mW/g

Cheek position – Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.28 V/m


Peak SAR (extrapolated) = 0.466 W/kg

SAR(1 g) = 0.360 mW/g

SAR(10 g) = 0.269 mW/g

Power Drift = -0.100 dB

Maximum value of SAR (measured) = 0.380 mW/g



Date/Time: 2008-01-16 12:19:19

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 21.2C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.909$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.86, 6.86, 6.86); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position – Middle - Slide open/Area Scan (41x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.252 mW/g

Tilt position – Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.7 V/m


Peak SAR (extrapolated) = 0.305 W/kg

SAR(1 g) = 0.242 mW/g

SAR(10 g) = 0.181 mW/g

Power Drift = -0.036 dB

Maximum value of SAR (measured) = 0.255 mW/g



Date/Time: 2008-01-16 14:33:06

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL850; Medium Notes: 21.2C

Medium parameters used: $f = 835$ MHz; $\sigma = 0.909$ mho/m; $\epsilon_r = 40.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.86, 6.86, 6.86); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 2; Type: Twin SAM 040 CA; Serial: TP - 1177
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position – Middle - Slide open – BT active/Area Scan (41x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.408 mW/g

Cheek position – Middle - Slide open – BT active /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.35 V/m


Peak SAR (extrapolated) = 0.474 W/kg

SAR(1 g) = 0.371 mW/g

SAR(10 g) = 0.279 mW/g

Power Drift = -0.113 dB

Maximum value of SAR (measured) = 0.388 mW/g



Date/Time: 2008-01-10 14:49:44

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: GSM1900

Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.264 mW/g

Cheek position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 5.00 V/m


Peak SAR (extrapolated) = 0.405 W/kg

SAR(1 g) = 0.248 mW/g

SAR(10 g) = 0.146 mW/g

Power Drift = -0.071 dB

Maximum value of SAR (measured) = 0.266 mW/g



Date/Time: 2008-01-10 15:06:38

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:4.2

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.481 mW/g

Cheek position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.83 V/m


Peak SAR (extrapolated) = 0.728 W/kg

SAR(1 g) = 0.448 mW/g

SAR(10 g) = 0.264 mW/g

Power Drift = -0.209 dB

Maximum value of SAR (measured) = 0.490 mW/g



Date/Time: 2008-01-10 15:30:00

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.546 mW/g

Cheek position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.30 V/m


Peak SAR (extrapolated) = 0.840 W/kg

SAR(1 g) = 0.507 mW/g

SAR(10 g) = 0.299 mW/g

Power Drift = -0.267 dB

Maximum value of SAR (measured) = 0.549 mW/g



Date/Time: 2008-01-10 15:49:14

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.525 mW/g

Tilt position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.8 V/m


Peak SAR (extrapolated) = 0.738 W/kg

SAR(1 g) = 0.441 mW/g

SAR(10 g) = 0.257 mW/g

Power Drift = -0.277 dB

Maximum value of SAR (measured) = 0.470 mW/g



Date/Time: 2008-01-10 18:05:05

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1850.2 MHz; Duty Cycle: 1:2.8

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 40.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Low - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.03 mW/g

Cheek position - Low - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.43 V/m


Peak SAR (extrapolated) = 1.36 W/kg

SAR(1 g) = 0.905 mW/g

SAR(10 g) = 0.542 mW/g

Power Drift = -0.075 dB

Maximum value of SAR (measured) = 0.968 mW/g



SAR Report

Salo_SAR_0804_14

Applicant: Nokia Corporation

Type: RM-420

Copyright © 2008 TCC Nokia

Date/Time: 2008-01-10 17:20:30

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.382 mW/g

Tilt position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.7 V/m


Peak SAR (extrapolated) = 0.470 W/kg

SAR(1 g) = 0.314 mW/g

SAR(10 g) = 0.200 mW/g

Power Drift = -0.044 dB

Maximum value of SAR (measured) = 0.329 mW/g



Date/Time: 2008-01-10 16:07:30

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide open/Area Scan (51x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.208 mW/g

Cheek position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.64 V/m


Peak SAR (extrapolated) = 0.280 W/kg

SAR(1 g) = 0.189 mW/g

SAR(10 g) = 0.119 mW/g

Power Drift = -0.221 dB

Maximum value of SAR (measured) = 0.205 mW/g



Date/Time: 2008-01-10 16:22:22

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle - Slide open/Area Scan (51x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.386 mW/g

Tilt position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.6 V/m


Peak SAR (extrapolated) = 0.498 W/kg

SAR(1 g) = 0.320 mW/g

SAR(10 g) = 0.189 mW/g

Power Drift = -0.132 dB

Maximum value of SAR (measured) = 0.348 mW/g



Date/Time: 2008-01-10 17:32:53

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide open/Area Scan (51x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.524 mW/g

Cheek position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 4.74 V/m


Peak SAR (extrapolated) = 0.734 W/kg

SAR(1 g) = 0.458 mW/g

SAR(10 g) = 0.266 mW/g

Power Drift = -0.071 dB

Maximum value of SAR (measured) = 0.506 mW/g



Date/Time: 2008-01-10 17:49:57

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:2.8

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.43$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle - Slide open/Area Scan (51x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.459 mW/g

Tilt position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 10.9 V/m


Peak SAR (extrapolated) = 0.530 W/kg

SAR(1 g) = 0.361 mW/g

SAR(10 g) = 0.221 mW/g

Power Drift = -0.213 dB

Maximum value of SAR (measured) = 0.392 mW/g



Date/Time: 2008-01-10 19:08:23

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot 8PSK EGPRS1900

Frequency: 1850.2 MHz; Duty Cycle: 1:2.8

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 40.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Low - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.454 mW/g

Cheek position - Low - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.31 V/m


Peak SAR (extrapolated) = 0.670 W/kg

SAR(1 g) = 0.373 mW/g

SAR(10 g) = 0.196 mW/g

Power Drift = -0.007 dB

Maximum value of SAR (measured) = 0.447 mW/g



Date/Time: 2008-01-10 18:32:53

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1850.2 MHz; Duty Cycle: 1:2.8

Medium: Head 1900; Medium Notes: Medium Temperature: 21.5 C

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 40.4$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.05, 5.05, 5.05); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 3; Type: Twin Phantom; Serial: TP-1302
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Low - Slide closed - BT active/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.02 mW/g

Cheek position - Low - Slide closed - BT active/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.21 V/m


Peak SAR (extrapolated) = 1.34 W/kg

SAR(1 g) = 0.888 mW/g

SAR(10 g) = 0.539 mW/g

Power Drift = -0.244 dB

Maximum value of SAR (measured) = 0.950 mW/g



Date/Time: 2008-01-14 19:02:56

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/436959/5

Communication System: WLAN2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: Head 2450; Medium Notes: Medium Temperature: 22.0 C

Medium parameters used: $f = 2442$ MHz; $\sigma = 1.87$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.43, 4.43, 4.43); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2007-08-29
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide closed/Area Scan (81x151x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.339 mW/g

Cheek position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.1 V/m

Peak SAR (extrapolated) = 0.696 W/kg


SAR(1 g) = 0.303 mW/g

SAR(10 g) = 0.150 mW/g

Power Drift = 0.049 dB

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.343 mW/g



Date/Time: 2008-01-14 19:23:01

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/436959/5

Communication System: WLAN2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: Head 2450; Medium Notes: Medium Temperature: 22.0 C

Medium parameters used: $f = 2442$ MHz; $\sigma = 1.87$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.43, 4.43, 4.43); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2007-08-29
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle - Slide closed/Area Scan (81x151x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.395 mW/g

Tilt position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 13.6 V/m


Peak SAR (extrapolated) = 0.647 W/kg

SAR(1 g) = 0.345 mW/g

SAR(10 g) = 0.170 mW/g

Power Drift = -0.063 dB

Maximum value of SAR (measured) = 0.399 mW/g



Date/Time: 2008-01-14 20:29:25

Test Laboratory: TCC Nokia
Type: RM-343; Serial: 004401/01/436959/5

Communication System: WLAN2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: Head 2450; Medium Notes: Medium Temperature: 22.0 C

Medium parameters used: $f = 2442$ MHz; $\sigma = 1.87$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.43, 4.43, 4.43); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2007-08-29
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide closed/Area Scan (81x151x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.336 mW/g

Cheek position - Middle - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 12.8 V/m


Peak SAR (extrapolated) = 0.517 W/kg

SAR(1 g) = 0.285 mW/g

SAR(10 g) = 0.149 mW/g

Power Drift = -0.494 dB

Maximum value of SAR (measured) = 0.315 mW/g



Date/Time: 2008-01-14 22:16:03

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/436959/5

Communication System: WLAN2450

Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: Head 2450; Medium Notes: Medium Temperature: 22.0 C

Medium parameters used: $f = 2462$ MHz; $\sigma = 1.89$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.43, 4.43, 4.43); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2007-08-29
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - High - Slide closed/Area Scan (81x151x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.476 mW/g

Tilt position - High - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 14.1 V/m


Peak SAR (extrapolated) = 0.791 W/kg

SAR(1 g) = 0.406 mW/g

SAR(10 g) = 0.194 mW/g

Power Drift = -0.126 dB

Maximum value of SAR (measured) = 0.459 mW/g



Date/Time: 2008-01-14 19:38:49

Test Laboratory: TCC Nokia
Type: RM-343; Serial: 004401/01/436959/5

Communication System: WLAN2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: Head 2450; Medium Notes: Medium Temperature: 22.0 C

Medium parameters used: $f = 2442$ MHz; $\sigma = 1.87$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.43, 4.43, 4.43); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2007-08-29
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide open/Area Scan (81x181x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.078 mW/g

Cheek position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 4.33 V/m


Peak SAR (extrapolated) = 0.177 W/kg

SAR(1 g) = 0.074 mW/g

SAR(10 g) = 0.029 mW/g

Power Drift = 0.500 dB

Maximum value of SAR (measured) = 0.092 mW/g



Date/Time: 2008-01-14 20:04:07

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/436959/5

Communication System: WLAN2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: Head 2450; Medium Notes: Medium Temperature: 22.0 C

Medium parameters used: $f = 2442$ MHz; $\sigma = 1.87$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.43, 4.43, 4.43); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2007-08-29
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle - Slide open/Area Scan (81x181x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.066 mW/g

Tilt position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 5.15 V/m


Peak SAR (extrapolated) = 0.102 W/kg

SAR(1 g) = 0.055 mW/g

SAR(10 g) = 0.027 mW/g

Power Drift = 0.077 dB

Maximum value of SAR (measured) = 0.062 mW/g



Date/Time: 2008-01-14 21:26:20

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/436959/5

Communication System: WLAN2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: Head 2450; Medium Notes: Medium Temperature: 22.0 C

Medium parameters used: $f = 2442$ MHz; $\sigma = 1.87$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.43, 4.43, 4.43); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2007-08-29
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Cheek position - Middle - Slide open/Area Scan (51x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.051 mW/g

Cheek position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 4.75 V/m


Peak SAR (extrapolated) = 0.088 W/kg

SAR(1 g) = 0.048 mW/g

SAR(10 g) = 0.025 mW/g

Power Drift = 0.097 dB

Maximum value of SAR (measured) = 0.051 mW/g



Date/Time: 2008-01-14 21:41:05

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/436959/5

Communication System: WLAN2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: Head 2450; Medium Notes: Medium Temperature: 22.0 C

Medium parameters used: $f = 2442$ MHz; $\sigma = 1.87$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3116; Probe Notes:
- ConvF(4.43, 4.43, 4.43); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn682; Calibrated: 2007-08-29
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Tilt position - Middle - Slide open/Area Scan (51x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.049 mW/g

Tilt position - Middle - Slide open/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 4.53 V/m


Peak SAR (extrapolated) = 0.089 W/kg

SAR(1 g) = 0.046 mW/g

SAR(10 g) = 0.023 mW/g

Power Drift = 0.011 dB

Maximum value of SAR (measured) = 0.053 mW/g



Date/Time: 2008-01-21 16:54:43

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 848.8 MHz; Duty Cycle: 1:4.2

Medium: Body 850; Medium Notes: Medium Temperature: 21.9 C

Medium parameters used: $f = 849$ MHz; $\sigma = 0.974$ mho/m; $\epsilon_r = 53$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.74, 5.74, 5.74); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 5; Type: Twin Phantom; Serial: TP-1412
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - High - No Accessory - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.330 mW/g

Body - High - No Accessory - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 7.93 V/m


Peak SAR (extrapolated) = 0.399 W/kg

SAR(1 g) = 0.311 mW/g

SAR(10 g) = 0.227 mW/g

Power Drift = 0.010 dB

Maximum value of SAR (measured) = 0.328 mW/g



Date/Time: 2008-01-21 17:05:21

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 848.8 MHz; Duty Cycle: 1:4.2

Medium: Body 850; Medium Notes: Medium Temperature: 21.9 C

Medium parameters used: $f = 849$ MHz; $\sigma = 0.974$ mho/m; $\epsilon_r = 53$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.74, 5.74, 5.74); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 5; Type: Twin Phantom; Serial: TP-1412
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - High - HS-47 - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.295 mW/g

Body - High - HS-47 - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 6.97 V/m


Peak SAR (extrapolated) = 0.353 W/kg

SAR(1 g) = 0.275 mW/g

SAR(10 g) = 0.201 mW/g

Power Drift = 0.042 dB

Maximum value of SAR (measured) = 0.291 mW/g



Date/Time: 2008-01-21 17:52:01

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 2-slot GPRS850

Frequency: 848.8 MHz; Duty Cycle: 1:4.2

Medium: Body 850; Medium Notes: Medium Temperature: 21.9 C

Medium parameters used: $f = 849$ MHz; $\sigma = 0.974$ mho/m; $\epsilon_r = 53$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(5.74, 5.74, 5.74); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used)) Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 5; Type: Twin Phantom; Serial: TP-1412
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - High - No Accessory - Slide closed - BT active/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.348 mW/g

Body - High - No Accessory - Slide closed - BT active/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.24 V/m


Peak SAR (extrapolated) = 0.414 W/kg

SAR(1 g) = 0.321 mW/g

SAR(10 g) = 0.234 mW/g

Power Drift = -0.324 dB

Maximum value of SAR (measured) = 0.339 mW/g



SAR Report

Salo_SAR_0804_14

Applicant: Nokia Corporation

Type: RM-420

Copyright © 2008 TCC Nokia

Date/Time: 2008-01-16 16:37:53

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium: M850; Medium Notes: 21.1C

Medium parameters used: $f = 847$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 54.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.62, 6.62, 6.62); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – High - Slide closed - No accessory /Area Scan (51x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.330 mW/g

Body Measurement – High - Slide closed - No accessory/Zoom Scan (5x5x7)/Cube 0: Measurement grid:

dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.40 V/m



Peak SAR (extrapolated) = 0.401 W/kg

SAR(1 g) = 0.314 mW/g

SAR(10 g) = 0.231 mW/g

Power Drift = -0.007 dB

Maximum value of SAR (measured) = 0.332 mW/g



SAR Report

Salo_SAR_0804_14

Applicant: Nokia Corporation

Type: RM-420

Copyright © 2008 TCC Nokia

Date/Time: 2008-01-16 16:24:12

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium: M850; Medium Notes: 21.1C

Medium parameters used: $f = 847 \text{ MHz}$; $\sigma = 1 \text{ mho/m}$; $\epsilon_r = 54.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.62, 6.62, 6.62); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – High – Slide closed - HS-47/Area Scan (51x91x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 0.275 mW/g

Body Measurement – High – Slide closed - HS-47/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 6.79 V/m


Peak SAR (extrapolated) = 0.331 W/kg

SAR(1 g) = 0.260 mW/g

SAR(10 g) = 0.190 mW/g

Power Drift = 0.189 dB

Maximum value of SAR (measured) = 0.273 mW/g



Date/Time: 2008-01-16 16:58:15

Test Laboratory: TCC Nokia

Type: RM-420; Serial: 004401/01/728454/4

Communication System: WCDMA850

Frequency: 846.6 MHz; Duty Cycle: 1:1

Medium: M850; Medium Notes: 21.1C

Medium parameters used: $f = 847$ MHz; $\sigma = 1$ mho/m; $\epsilon_r = 54.4$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1396; Probe Notes:
- ConvF(6.62, 6.62, 6.62); Calibrated: 2007-02-12
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE4 Sn728; Calibrated: 2007-02-13
- Phantom: SAM 3; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body Measurement – High - Slide closed - No accessory – BT active /Area Scan (51x91x1): Measurement grid:
dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.321 mW/g

Body Measurement – High - Slide closed - No accessory – BT active/Zoom Scan (5x5x7)/Cube 0: Measurement grid:
dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 8.16 V/m


Peak SAR (extrapolated) = 0.385 W/kg

SAR(1 g) = 0.304 mW/g

SAR(10 g) = 0.223 mW/g

Power Drift = 0.126 dB

Maximum value of SAR (measured) = 0.322 mW/g



Date/Time: 2008-01-17 19:59:46

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1850.2 MHz; Duty Cycle: 1:2.8

Medium: Body 1900; Medium Notes: Medium Temperature: 21.2 C

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3119; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2007-10-24
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn710; Calibrated: 2007-10-16
- Phantom: SAM 8; Type: SAM Twin Phantom; Serial: TP-1408
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Low - No Accessory - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.263 mW/g

Body - Low - No Accessory - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.33 V/m


Peak SAR (extrapolated) = 0.348 W/kg

SAR(1 g) = 0.243 mW/g

SAR(10 g) = 0.161 mW/g

Power Drift = -0.104 dB

Maximum value of SAR (measured) = 0.261 mW/g



Date/Time: 2008-01-17 19:36:36

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1850.2 MHz; Duty Cycle: 1:2.8

Medium: Body 1900; Medium Notes: Medium Temperature: 21.2 C

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3119; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2007-10-24
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn710; Calibrated: 2007-10-16
- Phantom: SAM 8; Type: SAM Twin Phantom; Serial: TP-1408
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Low - HS-47 - Slide closed/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.265 mW/g

Body - Low - HS-47 - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.37 V/m


Peak SAR (extrapolated) = 0.346 W/kg

SAR(1 g) = 0.244 mW/g

SAR(10 g) = 0.163 mW/g

Power Drift = -0.091 dB

Maximum value of SAR (measured) = 0.260 mW/g



Date/Time: 2008-01-17 20:25:27

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/437252/4

Communication System: 3-slot GPRS1900

Frequency: 1850.2 MHz; Duty Cycle: 1:2.8

Medium: Body 1900; Medium Notes: Medium Temperature: 21.2 C

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 52.6$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3119; Probe Notes:
- ConvF(5.02, 5.02, 5.02); Calibrated: 2007-10-24
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn710; Calibrated: 2007-10-16
- Phantom: SAM 8; Type: SAM Twin Phantom; Serial: TP-1408
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Low - HS-47 - Slide closed - BT active/Area Scan (51x101x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.275 mW/g

Body - Low - HS-47 - Slide closed - BT active/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 9.46 V/m


Peak SAR (extrapolated) = 0.365 W/kg

SAR(1 g) = 0.251 mW/g

SAR(10 g) = 0.167 mW/g

Power Drift = -0.244 dB

Maximum value of SAR (measured) = 0.267 mW/g



Date/Time: 2008-01-18 19:20:03

Test Laboratory: TCC Nokia
Type: RM-343; Serial: 004401/01/436959/5

Communication System: WLAN2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: Body 2450; Medium Notes: Medium Temperature: $t=21.6$ C

Medium parameters used: $f = 2442$ MHz; $\sigma = 2.03$ mho/m; $\epsilon_r = 52$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(4.12, 4.12, 4.12); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Middle - No Accessory - Slide closed/Area Scan (51x101x1): Measurement grid: $dx=15$ mm, $dy=15$ mm
Maximum value of SAR (interpolated) = 0.086 mW/g

Body - Middle - No Accessory - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 3.88 V/m


Peak SAR (extrapolated) = 0.136 W/kg

SAR(1 g) = 0.079 mW/g

SAR(10 g) = 0.047 mW/g

Power Drift = -0.035 dB

Maximum value of SAR (measured) = 0.085 mW/g



Date/Time: 2008-01-18 19:33:19

Test Laboratory: TCC Nokia

Type: RM-343; Serial: 004401/01/436959/5

Communication System: WLAN2450

Frequency: 2442 MHz; Duty Cycle: 1:1

Medium: Body 2450; Medium Notes: Medium Temperature: $t=21.6$ C

Medium parameters used: $f = 2442$ MHz; $\sigma = 2.03$ mho/m; $\epsilon_r = 52$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV3 - SN3117; Probe Notes:
- ConvF(4.12, 4.12, 4.12); Calibrated: 2007-08-29
- Sensor-Surface: 4mm (Mechanical Surface Detection (Locations From Previous Scan Used))Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn339; Calibrated: 2007-06-12
- Phantom: SAM 4; Type: Twin Phantom; Serial: TP-1410
- Measurement SW: DASY4, V4.7 Build 55; Postprocessing SW: SEMCAD, V1.8 Build 176

Body - Middle - HS-47 - Slide closed/Area Scan (51x101x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (interpolated) = 0.082 mW/g

Body - Middle - HS-47 - Slide closed/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=7.5$ mm, $dy=7.5$ mm, $dz=5$ mm

Reference Value = 3.26 V/m

Peak SAR (extrapolated) = 0.133 W/kg

SAR(1 g) = 0.076 mW/g

SAR(10 g) = 0.045 mW/g

Power Drift = 0.188 dB

Maximum value of SAR (measured) = 0.082 mW/g

