

FCC RF EXPOSURE REPORT

FCC ID: PZ3-B2004Z100

Project No. : 1706C259
Equipment : PrimexSmart-SyncPersonal SeriesLCD Clock
Model : B13550
Applicant : Primex Wireless, Inc.
Address : 965 Wells Street, Lake Geneva, WI, 53147.
U.S.A.

According: : FCC Guidelines for Human Exposure IEEE
C95.1 & FCC Part 2.1091

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	PCB Antenna	N/A	0

TEST RESULTS

EUT :	PrimexSmart-SyncPersonal SeriesLCD Clock	Model Name :	B13550
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		

LE

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
0	1.0000	-0.38	0.9162	0.00018	1	Complies

Note: the calculated distance is 20 cm.