

# **FCC RF EXPOSURE REPORT**

**FCC ID: PZ3-SSD**

**Project No. : 1611C060**  
**Equipment : Primex Smart-Sync Digital Clock**  
**Model : B11980, B12028, B11923, B11924, B11980-G,**  
**B12028-G, B11923-G, B11924-G**  
**Applicant : Primex Wireless Inc.**  
**Address : 965 WellsSt Lake Geneva Wisconsin United**  
**States 53147**

**According: : FCC Guidelines for Human Exposure IEEE**  
**C95.1**

**B T L I N C .**

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

## MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	PCB	N/A	0

## TEST RESULTS

EUT :	Primex Smart-Sync Digital Clock	Model Name :	B11980
Temperature :	22°C	Relative Humidity:	56 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	CH00, CH19 , CH39 - 1Mbps		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
0	1.0000	-0.72	0.8472	0.00017	1	Complies
0	1.0000	0.95	1.2445	0.00025	1	Complies
0	1.0000	1.64	1.4588	0.00029	1	Complies

Note: the calculated distance is 20 cm.