



# FCC PART 15.247

## TEST REPORT

For

### Summer Infant, Inc.

582 Great Road, North Smithfield, Rhode Island, 02896, USA

**FCC ID: PZK-0223R**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Baby Monitor with Internet Device (Monitor Unit)
<b>Test Engineer:</b> <u>Leon Chen</u>	<i>leon chen</i>
<b>Report Number:</b> <u>RSZ110519002-15.247A</u>	
<b>Report Date:</b> <u>2011-09-30</u>	
<b>Reviewed By:</b> <u>Merry Zhao</u> EMC Engineer	<i>merry.zhao</i>
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP\* or any agency of the Federal Government.

\* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

**TABLE OF CONTENTS**

**GENERAL INFORMATION.....4**

    PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....4

    OBJECTIVE .....4

    RELATED SUBMITTAL(S)/GRANT(S).....4

    TEST METHODOLOGY .....4

    TEST FACILITY .....4

**SYSTEM TEST CONFIGURATION.....6**

    DESCRIPTION OF TEST CONFIGURATION .....6

    EUT EXERCISE SOFTWARE .....6

    EQUIPMENT MODIFICATIONS .....6

    CONFIGURATION OF TEST SETUP .....6

    BLOCK DIAGRAM OF TEST SETUP .....6

**SUMMARY OF TEST RESULTS .....7**

**FCC §15.247 (i) & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE).....8**

    STANDARD APPLICABLE .....8

    TEST DATA .....8

**FCC §15.203 – ANTENNA REQUIREMENT .....9**

    APPLICABLE STANDARD .....9

    ANTENNA CONNECTOR CONSTRUCTION .....9

**FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....10**

    APPLICABLE STANDARD .....10

    MEASUREMENT UNCERTAINTY .....10

    EUT SETUP .....10

    EMI TEST RECEIVER SETUP.....11

    TEST EQUIPMENT LIST AND DETAILS.....11

    TEST PROCEDURE .....11

    TEST RESULTS SUMMARY .....11

    TEST DATA .....11

**FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....14**

    APPLICABLE STANDARD .....14

    MEASUREMENT UNCERTAINTY .....14

    EUT SETUP .....14

    EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....15

    TEST EQUIPMENT LIST AND DETAILS.....15

    TEST PROCEDURE .....15

    CORRECTED AMPLITUDE & MARGIN CALCULATION .....15

    TEST RESULTS SUMMARY .....16

    TEST DATA .....16

**FCC §15.247(a) (1) - CHANNEL SEPARATION TEST .....19**

    APPLICABLE STANDARD .....19

    TEST EQUIPMENT LIST AND DETAILS.....19

    TEST PROCEDURE .....19

    TEST DATA .....19

**FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING.....22**

APPLICABLE STANDARD .....22  
 TEST EQUIPMENT LIST AND DETAILS.....22  
 TEST PROCEDURE .....22  
 TEST DATA .....22

**FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST .....25**  
 APPLICABLE STANDARD .....25  
 TEST EQUIPMENT LIST AND DETAILS.....25  
 TEST PROCEDURE .....25  
 TEST DATA .....25

**FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME).....27**  
 APPLICABLE STANDARD .....27  
 TEST EQUIPMENT LIST AND DETAILS.....27  
 TEST PROCEDURE .....27  
 TEST DATA .....27

**FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT .....30**  
 APPLICABLE STANDARD .....30  
 TEST EQUIPMENT LIST AND DETAILS.....30  
 TEST PROCEDURE .....30  
 TEST DATA .....30

**FCC §15.247(d) - BAND EDGES TESTING .....33**  
 APPLICABLE STANDARD .....33  
 TEST EQUIPMENT LIST AND DETAILS.....33  
 TEST PROCEDURE .....33  
 TEST DATA .....34

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Summer Infant, Inc.*'s product, model number: *02230R (FCC ID: PZK-0223R)* (the "EUT") in this report is a monitor unit of *Baby Monitor with Internet Device*, which was measured approximately: 10.5 cm (L) x 6.3 cm (W) x 1.8 cm (H), rated input voltage: DC 3.7 V battery or DC 6V from adapter.

AC/DC Adapter Information:  
Model: AD050600550;  
Input: AC 120V 250mA 60Hz;  
Output: DC 6V 550mA

*\* All measurement and test data in this report was gathered from production sample serial number: 1105105 (Assigned by BACL, Shenzhen). The EUT was received on 2011-05-19.*

### Objective

This Type approval report is prepared on behalf of *Summer Infant, Inc.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

Submitted with the part of a system with FCC ID: PZK-0223M and FCC ID: PZK-0223T.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

### Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in an engineering mode which was selected by manufacturer.


### EUT Exercise Software

N/A.


### Equipment Modifications

No modification was made to the unit tested.

### Configuration of Test Setup



### Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.247 (i), §1.1307 (b)(1), §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

**FCC §15.247 (i) & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Standard Applicable**

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mw/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz  
 \* = Plane-wave equivalent power density

**Test Data**

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where:

- S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)
- P = power input to the antenna (in appropriate units, e.g., mW).
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally *numeric* gain.
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Maximum peak output power at antenna input terminal: 18.68 (dBm)  
 Maximum peak output power at antenna input terminal: 73.80 (mW)  
 Prediction distance: >20 (cm)  
 Predication frequency: 2466.200 (MHz)  
 Antenna Gain (typical): 0 (dBi)  
 Maximum Antenna Gain: 1 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.0147 (mW/cm<sup>2</sup>)  
 MPE limit for general population exposure at prediction frequency: 1.0 (mW/cm<sup>2</sup>)

**Result:**

The device meets the MPE at 20 cm distance.



---

## **FCC §15.203 – ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to FCC §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### **Antenna Connector Construction**

The EUT has a monopole antenna connect to RF board, which in accordance to section 15.203, the maximum gain is 0 dBi; please refer to the internal photos.

**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard


FCC §15.207

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Shenzhen) is  $\pm 2.4$  dB (k=2, 95% level of confidence).

### EUT Setup



- Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

## EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<i>Frequency Range</i>	<i>IF B/W</i>
150 kHz – 30 MHz	9 kHz

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2011-03-03	2012-03-02
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2011-03-09	2012-03-08
SCHWARZBECK	MESS-ELEKTRONIK	NTFM 8136	8136164	2010-10-26	2011-10-25
Com-Power	L.I.S.N.	LI-200	12208	N/A	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratory Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the monitor was connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

**3.93 dB at 0.525 MHz** in the **Line** conducted mode

## Test Data


### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	48 %
<b>ATM Pressure:</b>	100.0 kPa

*The testing was performed by Leon Chen on 2011-08-27.*

Test Mode: Charging&operating

AC 120 V, 60 Hz, Line:



Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/QP/Ave.)
0.525	42.07	10.10	46.00	3.93	Ave.
0.525	49.69	10.10	56.00	6.31	QP
2.590	39.39	10.10	46.00	6.61	Ave.
2.020	48.92	10.10	56.00	7.08	QP
2.015	36.24	10.10	46.00	9.76	Ave.
2.610	45.59	10.10	56.00	10.41	QP
0.160	45.15	10.10	55.71	10.56	Ave.
0.160	53.25	10.10	65.71	12.46	QP
0.210	40.81	10.10	54.29	13.48	Ave.
0.210	50.52	10.10	64.29	13.77	QP
0.265	38.63	10.10	52.71	14.08	Ave.
0.265	47.50	10.10	62.71	15.21	QP

**AC 120V, 60 Hz, Neutral:**



Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/QP/Ave.)
2.680	39.36	10.10	46.00	6.64	Ave.
2.060	37.84	10.10	46.00	8.16	Ave.
0.515	36.74	10.10	46.00	9.26	Ave.
2.680	46.69	10.10	56.00	9.31	QP
0.515	46.25	10.10	56.00	9.75	QP
0.160	45.47	10.10	55.71	10.24	Ave.
0.210	44.05	10.10	54.29	10.24	Ave.
0.160	54.27	10.10	65.71	11.44	QP
2.050	44.42	10.10	56.00	11.58	QP
1.055	32.15	10.10	46.00	13.85	Ave.
1.055	41.80	10.10	56.00	14.20	QP
0.210	49.54	10.10	64.29	14.75	QP

## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

### Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is  $\pm 4.0$  dB ( $k=2$ , 95% level of confidence).

### EUT Setup



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>	<i>Detector</i>
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	PK

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2011-08-02	2012-08-02
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-07-05	2012-07-04
HP	Amplifier	2VA-213+	T-E27H	2011-03-08	2012-03-08
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Rohde&Schwarz	Signal Analyzer	FSIQ 26	609358	2011-07-08	2012-07-07

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

## Test Procedure

For the radiated emissions test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz and peak and Average detection modes for frequencies above 1GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247, with the worst margin reading of:

### Below 1GHz:

**5.9 dB** at **101.033500 MHz** in the **Horizontal** polarization

### Above 1 GHz:

**1.98 dB** at **4932.40 MHz** in the **Horizontal** polarization at High channel

## Test Data

### Environmental Conditions


<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	100.0kPa

*The testing was performed by Leon Chen on 2011-08-27.*



**Below 1 GHz:**

*Test Mode: Transmitting*



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Ant. Height (cm)	Ant. Polarity (H/V)	Turntable Position (deg)	Correction Factor (dB)	Limit (dBµV/m)	Margin (dB)
101.033500	37.6	399.0	H	4.0	-14.5	43.5	5.9
102.767000	36.8	299.0	H	4.0	-14.3	43.5	6.7
184.117750	34.4	100.0	H	4.0	-15.1	43.5	9.1
799.210000	36.2	161.0	V	4.0	-0.8	46.0	9.2
148.015500	33.7	100.0	V	45.0	-13.8	43.5	9.8
140.999750	32.0	100.0	V	102.0	-13.2	43.5	11.5

**Above 1 GHz:**

Indicated		Detector (PK/Ave.)	Table Angle Degree	Test Antenna		Correction Factor			FCC Part 15.247/15.209			
Frequency (MHz)	S.A. Reading (dBµV)			Height (m)	Polar (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. (dB)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Comment
Low Channel (2408.825 MHz)												
4817.65	56.37	PK	180	1.4	H	36.1	4.30	26.79	69.98	74	4.02	Harmonic
4817.65	56.02	PK	180	1.1	V	34.5	4.30	26.79	68.03	74	5.97	Harmonic
4817.65	32.70	Ave.	160	1.4	H	36.1	4.30	26.79	46.31	54	7.69	Harmonic
2389.279	59.69	PK	30	1.2	V	28.6	3.03	26.84	64.48	74	9.52	Spurious
2389.279	59.56	PK	20	1.2	H	28.7	3.03	26.84	64.45	74	9.55	Spurious
4817.65	32.29	Ave.	150	1.1	V	34.5	4.30	26.79	44.3	54	9.7	Harmonic
2389.279	31.43	Ave.	0	1.0	H	28.7	3.03	26.84	36.32	54	17.68	Spurious
2389.279	30.50	Ave.	0	1.0	V	28.6	3.03	26.84	35.29	54	18.71	Spurious
Middle Channel (2435.825 MHz)												
4871.65	54.65	PK	180	1.8	H	36.2	4.36	26.79	68.42	74	5.58	Harmonic
4871.65	54.30	PK	180	1.1	V	34.7	4.36	26.79	66.57	74	7.43	Harmonic
4871.65	26.81	Ave.	175	1.8	H	36.2	4.36	26.79	40.58	54	13.42	Harmonic
4871.65	26.51	Ave.	185	1.1	V	34.7	4.36	26.79	38.78	54	15.22	Harmonic
High Channel (2466.20 MHz)												
4932.40	57.81	PK	20	1.2	H	36.6	4.40	26.79	72.02	74	1.98*	Harmonic
4932.40	57.43	PK	0	1.2	V	33.8	4.40	26.79	68.84	74	5.16	Harmonic
4932.40	34.16	Ave.	0	1.0	H	36.6	4.40	26.79	48.37	54	5.63	Harmonic
4932.40	33.78	Ave.	20	1.0	V	33.8	4.40	26.79	45.19	54	8.81	Harmonic
2484.28	48.36	PK	10	1.0	H	28.7	3.20	26.85	53.41	74	20.59	Spurious
2484.28	46.53	PK	0	1.2	V	28.6	3.20	26.85	51.48	74	22.52	Spurious
2484.28	21.09	Ave.	0	1.0	H	28.7	3.20	26.85	26.14	54	27.86	Spurious
2484.28	19.22	Ave.	0	1.0	V	28.6	3.20	26.85	24.17	54	29.83	Spurious

\*Within measurement uncertainty.

## FCC §15.247(a) (1) - CHANNEL SEPARATION TEST

### Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Procedure

1. Set the EUT in Operating mode, spectrum Bandwidth was set at 100 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another truce
3. Measure the channel separation.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

\* The testing was performed by Leon Chen on 2011-08-17.

**Test Result:** Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
Low Channel	2408.825	3.376	2.48	Pass
Adjacency Channel	2412.200			
Mid Channel	2435.825	3.392	2.64	
Adjacency Channel	2432.450			
High Channel	2466.200	3.376	2.60	
Adjacency Channel	2464.025			


Please refer to the following plots.

Low Channel




Date: 17.AUG.2011 19:24:07

### Middle Channel



Date: 17.AUG.2011 19:26:06

### High Channel



Date: 17.AUG.2011 19:28:25

## FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING

### Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa

\* *The testing was performed by Leon Chen on 2011-08-17.*

**Test Result:** Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2408.825	3.720
Middle	2435.825	3.960
High	2466.200	3.900


Please refer to the following plots.

**Low Channel**




Date: 17.AUG.2011 18:50:38

### Middle Channel



Date: 17.AUG.2011 18:54:34

### High Channel



Date: 17.AUG.2011 18:58:21



## **FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST**

### **Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### **Test Procedure**

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	100.9kPa

*The testing was performed by Leon Chen on 2011-08-17.*


**Test Result:** Compliance.

Please refer to following tables and plots

Test Mode: Operating

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.50	18	≥ 15

### Number of Hopping Channels



Date: 17.AUG.2011 19:20:08

## **FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME)**

### **Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

### **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### **Test Procedure**

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time= Time slot length \* hope rate/ number of hopping channels \* hopping NO.\*0.4 s

### **Test Data**

#### **Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	100.0kPa

*The testing was performed by Leon Chen on 2011-07-22.*

**Test Result:** Compliance.

Please refer to following tables and plots


Test Mode: Transmitting

Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
Low	0.204	0.0065	0.4	Pass
Middle	0.204	0.0065	0.4	Pass
High	0.204	0.0065	0.4	Pass

*Note: Dwell time = Pulse time (ms) × (160/2/18) × 18 \* 0.4 S*


Please refer to the following plots.

**Low Channel**




Date: 22.JUL.2011 00:26:51

### Middle Channel



Date: 22.JUL.2011 00:26:34

### High Channel



Date: 22.JUL.2011 00:50:31

## FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

### Applicable Standard

According to FCC §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.


### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.



### Test Data

#### Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.9kPa

\* The testing was performed by Leon Chen on 2011-08-17.


**Test Result:** Compliance.

Test Mode: Transmitting

Freq. (MHz)	Conducted Output Power		Part15.247 Limit (mW)
	(dBm)	(mW)	
2408.825	17.68	58.61	125
2435.825	18.38	68.87	125
2466.200	18.68	73.80	125


Note: The data above was tested in conducted mode.

Low Channel




Date: 17.AUG.2011 18:46:26

### Middle Channel



Date: 17.AUG.2011 18:45:37

### High Channel



Date: 17.AUG.2011 18:44:29



## **FCC §15.247(d) - BAND EDGES TESTING**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2010-11-11	2011-11-10

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in Operating mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	100.9kPa

\*The testing was performed by Leon Chen on 2011-08-17.


**Test Result:** Compliance.

Test Mode: Transmitting

Frequency (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)
2398.412	43.41	20
2504.960	49.02	20


Please refer to follow plots:

**Band Edge: Left Side**



Date: 17.AUG.2011 18:47:13

### Band Edge: Right Side



Date: 17.AUG.2011 18:48:05

\*\*\*\*\* END OF REPORT \*\*\*\*\*