



**CENTRE OF TESTING SERVICE
INTERNATIONAL**

OPERATE ACCORDING TO ISO/IEC 17025

FCC ID TEST REPORT

TEST REPORT NUMBER : CGZ3121019-00841-E



CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao,
Guangzhou, China.



TEST REPORT For FCC ID	
47 CFR PART 15 OCT, 2011	
Report Reference No.	CGZ3121019-00841-E
Date of issue	09 November 2012
Testing Laboratory Name	CETRE OF TESTING SERVICE CO., LTD.
Address	Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China.
Testing location/ procedure	Full application of Harmonised standards ☒ Partial application of Harmonised standards ☐ Other standard testing method ☐
Applicant's name	Elite Century Technology Ltd.
Address	Room 1302, 13/F, Mega Trade Center, 1 Mei Wan Street, Tsuen Wan, N. T. Hong Kong
Test specification	
Standard	47 CFR PART 15 OCT, 2011
Test Report Form No.	CTSEMC-1.0
TRF Originator	CENTRE OF TESTING SERVICE CO., LTD
Master TRF	Dated 2009-01
CENTRE OF TESTING SERVICE CO., LTD. All rights reserved.	
This publication may be reproduced in whole or in part for non-commercial purposes as long as the CENTRE OF TESTING SERVICE CO., LTD is acknowledged as copyright owner and source of the material. CENTRE OF TESTING SERVICE CO., LTD takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test item description	Water-proof Bluetooth Handfree Speaker
Trade Mark	neutac
Manufacturer	GuangZhou PanYu Elite Century Electronic Co., Ltd
Model/Type reference	BM-88P
Ratings	Battery 3.7V
Operating Frequency	2402MMHz ~2480.00MHz/ GFSK,π/4-DQPSK,8DPSK
Result	Positive

Compiled by:

Kate zhang / Fileadministrators

Supervised by:

Duke yang / Technique principal

Approved by:

Vincent yao / Manager

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

FCC ID -- T E S T R E P O R T

Test Report No. : CGZ3121019-00841-E

09 November 2012
Date of issue

Type / Model..... BM-88P

EUT..... Water-proof Bluetooth Handfree Speaker

Applicant..... Elite Century Technology Ltd.

Address..... Room 1302, 13/F, Mega Trade Center, 1 Mei Wan Street, Tsuen Wan, N.
T. Hong Kong

Telephone..... +852-26876059

Fax..... +852-26876045

Contact..... Abel Zhao

Manufacturer..... GuangZhou PanYu Elite Century Electronic Co., Ltd.

Address..... /

Telephone..... /

Fax..... /

Contact..... /

Test report holder..... GuangZhou PanYu Elite Century Electronic Co., Ltd.

Address..... /

Telephone..... /

Fax..... /

Contact..... /

Test Result according to the standards on page 1: PASSED

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

TABLE OF CONTENTS

Description	Page
1.TEST STANDARDS	5
2.SUMMARY	5
2.1 GENERAL REMARKS.....	5
2.2 FINAL ASSESSMENT	5
3.EQUIPMENT UNDER TEST	5
3.1 POWER SUPPLY SYSTEM UTILISED	5
3.2 SHORT DESCRIPTION OF THE EQUIPMENT UNDER TEST (EUT)	5
3.3 EUT OPERATION MODE	5
3.4 EUT CONFIGURATION	6
4.TEST ENVIRONMENT	7
4.1 ADDRESS OF THE TEST LABORATORY	7
4.2 TEST FACILITY	7
4.3 ENVIRONMENTAL CONDITIONS	7
4.4 DEFINITIONS OF SYMBOLS USED IN THIS TEST REPORT	7
4.5 STATEMENT OF THE MEASUREMENT UNCERTAINTY	7
4.6 MEASUREMENT UNCERTAINTY.....	8
5.SUMMARY OF STANDARDS AND RESULTS	8
5.1.DESCRPTION OF STANDARDS AND RESULTS	8
6.POWER LINE CONDUCTED EMISSION TEST	9
6.1.TEST EQUIPMENT.....	9
6.2. BLOCK DIAGRAM OF TEST SETUP	9
6.3. POWER LINE CONDUCTED EMISSION TEST LIMITS	9
6.4.TEST PROCEDURE	9
6.5. POWER LINE CONDUCTED EMISSION TEST RESULTS	9
7.RADIATED DISTURBANCE (ELECTRIC FIELD)	12
7.1.TEST EQUIPMENT.....	12
7.2.BLOCK DIAGRAM OF TEST SETUP	12
7.3.RADIATED EMISSION LIMIT :	13
7.4.TEST PROCEDURE	14
7.5.RADIATED EMISSION TEST RESULTS	14
9.BAND EDGE COMPLIANCE TEST	28
9.1. TEST EQUIPMENT.....	28
9.2. TEST INFORMATION.....	28
9.3. TEST PROCEDURE.....	28

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



9.4. TEST RESULTS28

10. 20 DB BANDWIDTH TEST33

10.1. TEST EQUIPMENT.....33

10.2. TEST INFORMATION.....33

10.3. TEST RESULTS33

11.DEVIATION TO TEST SPECIFICATIONS38

1. TEST STANDARDS

The tests were performed according to following standards:

- 47 CFR PART 15 OCT, 2011
- ANSI C63.4-2009

2. SUMMARY

2.1 GENERAL REMARKS

Date of receipt of test sample	19 October 2012
Testing commenced on	01 ~08 November 2012
Testing concluded on	09 November

2.2 FINAL ASSESSMENT

The FCC requirements pertaining to the technical standards and tested operation modes are

- - fulfilled.
- ☐ - **not** fulfilled.

The equipment under test

- - fulfils the FCC requirements cited on page 1.
- ☐ - **does not** fulfil the FCC requirements cited on page 1.

3. EQUIPMENT UNDER TEST

3.1 Power supply system utilised

Power supply voltage : ■ Battery 3.7V

3.2 Short description of the Equipment under Test (EUT)

Number of tested samples: 1

Serial number: Prototype

3.3 EUT operation mode

The equipment under test was operated during the measurement under the following conditions:

- ☐ - Standby
- ☐ TX- Y position
- ☐ TX- Zposition
- TX- X position
- Charging

Operation mode 1:TX-X Position Low (2402MHz) , TX-X Position Middle (2441MHz) ,
TX-X Position High (2480MHz)

Operation mode 2: Charging

Note:Operation mode 1 TX -X position of EUT is the radiated test worst case; Operation mode 2 Charging is the conducted test worst case. so only these test results be recorded in the test report.

3.4 EUT configuration

3.4.1. Description of configuration (EUT)

Description	:	Water-proof Bluetooth Handfree Speaker
Model Number	:	BM-88P
Operation frequency	:	2402~ 2480 MHz ISM Band
Radio Technology	:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Modulation Technology	:	GFSK, $\pi/4$ -DQPSK, 8DPSK modulation
Antenna	:	PCB antenna, met requirement of FCC 15.203

3.4.2. Tested Supporting System Details

3.4.2.1. Monitor

M/N	:	E7722-f
S/N	:	CN-02W486-64180-3B7-01MP
Manufacturer	:	DELL
Power Cord	:	Unshielded, Detachable, 1.8m , 3Pin
FCC ID	:	By DoC

3.4.2.2 Personal Computer

M/N	:	DIMENSION 4600
S/N	:	CN-OTO486-42940-37M-00XB
Manufacturer	:	DELL
Power Cord	:	Unshielded, Detachable, 1.8m , 3Pin
FCC ID	:	By DoC

3.4.2.3. Keyboard

M/N	:	SK-8110
S/N	:	CN-07N244-71616-37T-B293
Manufacturer	:	DELL
Data Cable	:	Shielded, Detachable
FCC	:	By DoC

3.4.2.4. Mouse

M/N	:	M-UR69
S/N	:	LNA33029188
Manufacturer	:	DELL
Data Cable	:	Shielded, Detachable, 1.8m
FCC	:	By DoC

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

4. TEST ENVIRONMENT

4.1 Address of the test laboratory

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

4.2 Test facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L3394

CENTRE OF TESTING SERVICE CO., LTD has been assessed and proved to be in compliance with CNAS-CL01: 2006 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

IC-Registration No.: 8374A

The 3m Alternate Test Site of CENTRE OF TESTING SERVICE CO., LTD has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 8374A on June 6, 2011.

FCC-Registration No.: 971995

CENTRE OF TESTING SERVICE CO., LTD, EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration No.791995, July 13,2012.

4.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35 ° C
Humidity:	25~75 %
Atmospheric pressure:	86~106 kPa

4.4 Definitions of symbols used in this test report

- - The black square indicates that the listed condition, standard or equipment is applicable for this report.
- - The empty square indicates that the listed condition, standard or equipment is **not** applicable for this report.

4.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the CTS quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

4.6 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Conduction disturbance	150kHz~30MHz	$\pm 1.22\text{dB}$	(1)
Power disturbance	30MHz~300MHz	$\pm 1.38\text{dB}$	(1)
Radiation emission (3m)	30MHz~300MHz	$\pm 3.14\text{dB}$	(1)
	300MHz~1000MHz	$\pm 3.18\text{dB}$	(1)
	1GHz~26.5GHz	$\pm 3.54\text{dB}$	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

5. Summary of standards and results

5.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Conducted Emission Test	FCC Part 15 : 15.207 ANSI C63.4-2009	PASSED
Radiated Emission Test	FCC Part 15 C: 15.249 FCC Part 15 : 109 ANSI C63.4-2009	PASSED
Receiver Spurious Emission	FCC Part 15 C: 15.249 FCC Part 15 : 109 ANSI C63.4-2009	PASSED
20 dB Bandwidth test	FCC Part 15 C: 15.249 ANSI C63.4-2009	PASSED
Band Edge Compliance Test	FCC Part 15 C: 15.249 ANSI C63.4-2009	PASSED
N/A is an abbreviation for Not Applicable.		

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service

6. Power Line Conducted Emission Test

6.1. Test Equipment

Conducted Disturbance					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESHS10	842884/012	2011/11
2	Artificial Mains	ROHDE & SCHWARZ	ESH3-Z5	832479/025	2011/11
3	Artificial Mains	ROHDE & SCHWARZ	ESH3-Z5	832479/026	2011/11
4	Pulse Limiter	ROHDE & SCHWARZ	ESHSZ2	100301	2011/11
5	EMI Test Software	ROHDE & SCHWARZ	ESK1	N/A	2011/11

6.2. Block Diagram of Test Setup



(EUT: Water-proof Bluetooth Handfree Speaker)

6.3. Power Line Conducted Emission Test Limits

Standard:RSS-Gen:7.2.4,FCC Part 15 : 15.207,ANSI C63.4-2009

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

6.4. Test Procedure

The XBOX Power connected to the power mains through a line impedance stabilization network (L.I.S.N.#2). This provides a 50 ohm coupling impedance for the EUT. Please refer the block diagram of the test setup and photographs. The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.#1). Power on the PC and let it work normally, we use a keyboard test soft ware, let EUT working in test mode, then test it. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC Part 15C on Conducted Emission Test.

6.5. Power Line Conducted Emission Test Results

PASSED.

The frequency range from 150KHz~30MHz is investigated. Please see the following pages.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Test point:	L	Result:	☒ - passed
Frequency range:	0.15MHz~30MHz		☐ - not passed

EUT	Water-proof Bluetooth Handfree Speaker
Firm Name	Elite Century Technology Ltd.
Operating Condition	Charging by adaptor 120VAC 50/60Hz
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Test Date:	01~08 November 2012
Operator	Duke
MODEL NO	BM-88P



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.2020	9.99	32.01	42.00	63.52	-21.52	QP
2	0.2020	9.99	27.83	37.82	53.52	-15.70	AVG
3	4.3940	10.09	33.75	43.84	56.00	-12.16	QP
4	4.3940	10.09	20.65	30.74	46.00	-15.26	AVG
5	4.7340	10.11	33.05	43.16	56.00	-12.84	QP
6	4.7340	10.11	27.40	37.51	46.00	-8.49	AVG
7	6.6660	10.12	26.63	36.75	60.00	-23.25	QP
8	6.6660	10.12	18.07	28.19	50.00	-21.81	AVG
9	13.2980	10.17	26.24	36.41	60.00	-23.59	QP
10	13.2980	10.17	11.88	22.05	50.00	-27.95	AVG
11	19.8500	10.23	23.15	33.38	60.00	-26.62	QP
12	19.8500	10.23	16.26	26.49	50.00	-23.51	AVG
Remark: Other frequency mini margin all >10 dB of Limit							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)


Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Test point:	N	Result:	☒ - passed
Frequency range:	0.15MHz~30MHz		☐ - not passed



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.2060	9.99	29.61	39.60	63.37	-23.77	QP
2	0.2060	9.99	24.35	34.34	53.37	-19.03	AVG
3	4.3980	10.09	29.96	40.05	56.00	-15.95	QP
4	4.3980	10.09	22.12	32.21	46.00	-13.79	AVG
5	5.1900	10.12	31.61	41.73	60.00	-18.27	QP
6	5.1900	10.12	24.15	34.27	50.00	-15.73	AVG
7	6.5900	10.12	31.38	41.50	60.00	-18.50	QP
8	6.5900	10.12	18.68	28.80	50.00	-21.20	AVG
9	13.2980	10.17	33.81	43.98	60.00	-16.02	QP
10	13.2980	10.17	20.71	30.88	50.00	-19.12	AVG
11	15.3780	10.18	25.79	35.97	60.00	-24.03	QP
12	15.3780	10.18	13.46	23.64	50.00	-26.36	AVG

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service


7. Radiated disturbance (electric field)

7.1. Test Equipment


Radiated disturbance (electric field)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	100868	2011/11
2	Biconical Antenna	ROHDE & SCHWARZ	HK116	100221	2011/11
3	Log per Antenna	ROHDE & SCHWARZ	HL223	100226	2011/11
4	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2011/11
5	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2011/11
6	Loop Antenna	A.R.A	PLA-1030/B	1030	2011/11

7.2. Block Diagram of Test Setup

7.2.1 Block Diagram of connection between EUT and simulators



7.2.2 Anechoic Chamber Setup Diagram



7.3. Radiated Emission Limit :

Standard: FCC 15.249 , FCC 15.209.

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (μV/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24000-24250	250	2500

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other: 74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

- Remark:
- (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
 - (2) The smaller limit shall apply at the cross point between two frequency bands.
 - (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

7.4. Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2009 on radiated emission Test.

The frequency range from 30MHz to 1000MHz and above 1GHz. is investigated. Please see the following pages.

All measurements for radiated emissions within the restricted bands were performed using a Quasi-Peak detector with 120kHz RBW below 1GHz and a Peak and Average detector with 2MHz RBW above 1GHz,

All measurements for radiated emissions within the restricted bands were performed using a Quasi-Peak detector with 300kHz VBW below 1GHz and a Peak detector with 2MHz VBW above 1GHz, A average detector with 10Hz VBW above 1GHz

Pretest x, y, z position of EUT, final, select the worst case x position test and record the test results in the report.

The test modes (TX Mode) is tested in Anechoic Chamber and all the scanning waveforms are reported on section 7.5

7.5. Radiated Emission Test Results

PASSED.

The frequency range from 9KHz~30MHz, 30MHz to 230MHz, 230MHz to 1000MHz and above 1GHz. is investigated. Please see the following pages.



Test Mode:	TX –X Position Mode	Result:	☒ - passed
Frequency range:	9KHz~30MHz		☐ - not passed

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
Remark: The test result reading value is to low, margin all > 10dB of the limit.							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service

Channel:	TX -X Position Mode Low 2402MHz	Result:	☒ - passed
Test point:	Horizontal		☐ - not passed
Frequency range:	30MHz-26.5GHz		

EUT	Water-proof Bluetooth Handfree Speaker
Firm Name	Elite Century Technology Ltd.
Operating Condition	Battery 3.7V
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Test Date:	01~08 November 2012
Operator	Duke
MODEL NO	BM-88P

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2402.00	-26.11	118.12	92.01	114.00	-21.99	Peak
2	2402.00	-26.11	113.75	87.64	94.00	-6.36	AVG

80.0 dBuV/m



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	64.6293	-21.97	50.75	28.78	40.00	-11.22	QP
2	74.9098	-19.81	51.46	31.65	40.00	-8.35	QP
3	123.0661	-16.30	46.35	30.05	43.50	-13.45	QP
4	172.3046	-15.23	43.09	27.86	43.50	-15.64	QP
5	196.6533	-11.26	41.27	30.01	43.50	-13.49	QP
6	270.7816	-11.40	42.17	30.77	46.00	-15.23	QP

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	323.8477	-9.46	45.92	36.46	46.00	-9.54	QP
2	367.3347	-14.34	45.63	31.29	46.00	-14.71	QP
3	417.8357	-14.66	42.23	27.57	46.00	-18.43	QP
4	466.9339	-12.56	42.14	29.58	46.00	-16.42	QP
5	490.7816	-11.15	35.21	24.06	46.00	-21.94	QP
6	779.7595	-8.46	32.00	23.54	46.00	-22.46	QP

Remark: Other frequency mini margin all >10 dB of Limit

Above 1GHz

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	1705.411	-25.01	44.74	19.73	74.00	-54.27	peak
2	1705.411	-25.01	33.17	8.16	54.00	-45.84	AVG
3	4130.261	-10.33	36.31	25.98	74.00	-48.02	peak
4	4130.261	-10.33	22.69	12.36	54.00	-41.64	AVG
5	4659.319	-8.40	37.13	28.73	74.00	-45.27	peak
6	4659.319	-8.40	24.09	15.69	54.00	-38.31	AVG
7	4804.230	-9.48	35.85	26.37	74.00	-47.63	peak
8	4804.230	-9.48	22.70	13.22	54.00	-40.78	AVG
9	6444.890	-13.45	41.48	28.03	74.00	-45.97	peak
10	6444.890	-13.45	29.14	15.69	54.00	-38.31	AVG
11	8340.681	-15.60	38.65	23.05	74.00	-50.95	peak
12	8340.681	-15.60	26.62	11.02	54.00	-42.98	AVG

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Channel:	TX -X Position Mode Low 2402MHz	Result:	☒ - passed
Test point:	Vertical		☐ - not passed
Frequency range:	30MHzHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2402.00	-26.11	114.50	88.39	114.00	-25.61	Peak
2	2402.00	-26.11	109.68	83.57	94.00	-10.43	AVG



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	64.6293	-21.97	57.57	35.60	40.00	-4.40	QP
2	74.9098	-19.81	51.46	31.65	40.00	-8.35	QP
3	125.2305	-15.95	46.75	30.80	43.50	-12.70	QP
4	184.7495	-12.42	42.47	30.05	43.50	-13.45	QP
5	196.6533	-11.26	42.25	30.99	43.50	-12.51	QP
6	295.1303	-6.12	36.95	30.83	46.00	-15.17	QP

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	392.5852	-15.06	46.65	31.59	46.00	-14.41	QP
2	417.8357	-14.66	43.78	29.12	46.00	-16.88	QP
3	466.9339	-12.56	41.17	28.61	46.00	-17.39	QP
4	584.7695	-13.03	38.92	25.89	46.00	-20.11	QP
5	779.7595	-8.46	40.07	31.61	46.00	-14.39	QP
6	910.2204	-6.39	35.50	29.11	46.00	-16.89	QP

Remark: Other frequency mini margin all >10 dB of Limit

Above 1GHz

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2124.249	-26.75	48.87	22.12	74.00	-51.88	peak
2	2124.249	-26.75	37.19	10.44	54.00	-43.56	AVG
3	2873.747	-29.72	57.87	28.15	74.00	-45.85	peak
4	2873.747	-29.72	37.79	8.07	54.00	-45.93	AVG
5	6973.948	-29.11	54.47	25.36	74.00	-48.64	peak
6	6973.948	-29.11	40.58	11.47	54.00	-42.53	AVG
7	8142.285	-23.60	48.29	24.69	74.00	-49.31	peak
8	8142.285	-23.60	37.46	13.86	54.00	-40.14	AVG
9	9927.856	-15.74	47.22	31.48	74.00	-42.52	peak
10	9927.856	-15.74	36.27	20.53	54.00	-33.47	AVG
11	10501.002	-15.21	49.46	34.25	74.00	-39.75	peak
12	10501.002	-15.21	37.82	22.61	54.00	-31.39	AVG

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn


See Reverse For Terms And Conditions of Service

Channel:	TX-X Position Mode Middle 2441MHz	Result:	☒ - passed
Test point:	Horizontal		☐ - not passed
Frequency range:	30MHz-26.5GHz		

EUT	Water-proof Bluetooth Handfree Speaker
Firm Name	Elite Century Technology Ltd.
Operating Condition	Battery 3.7V
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Test Date:	01~08 November 2012
Operator	Duke
MODEL NO	BM-88P

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2441.00	-25.95	116.03	90.08	114.00	-23.92	Peak
2	2441.00	-25.95	112.67	86.72	94.00	-7.28	AVG

80.0 dBuV/m



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	64.6293	-21.97	55.64	33.67	40.00	-6.33	QP
2	74.9098	-19.81	50.13	30.32	40.00	-9.68	QP
3	125.2305	-15.95	45.91	29.96	43.50	-13.54	QP
4	166.8938	-15.75	41.15	25.40	43.50	-18.10	QP
5	270.7816	-11.40	47.62	36.22	46.00	-9.78	QP
6	295.1303	-6.12	42.22	36.10	46.00	-9.90	QP

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	367.3347	-14.34	46.12	31.78	46.00	-14.22	QP
2	417.8357	-14.66	43.48	28.82	46.00	-17.18	QP
3	466.9339	-12.56	41.88	29.32	46.00	-16.68	QP
4	490.7816	-11.15	34.51	23.36	46.00	-22.64	QP
5	584.7695	-13.03	34.32	21.29	46.00	-24.71	QP
6	845.6914	-10.37	34.43	24.06	46.00	-21.94	QP

Remark: Other frequency mini margin all >10 dB of Limit

Above 1GHz

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	4394.790	-6.44	35.61	29.17	74.00	-44.83	peak
2	4394.790	-6.44	24.80	18.36	54.00	-35.64	AVG
3	4879.760	-10.04	35.11	25.07	74.00	-48.93	peak
4	4879.760	-10.04	23.70	13.66	54.00	-40.34	AVG
5	5915.832	-12.90	38.03	25.13	74.00	-48.87	peak
6	5915.832	-12.90	26.92	14.02	54.00	-39.98	AVG
7	6687.375	-13.72	40.79	27.07	74.00	-46.93	peak
8	6687.375	-13.72	32.44	18.72	54.00	-35.28	AVG
9	6907.816	-13.97	41.74	27.77	74.00	-46.23	peak
10	6907.816	-13.97	29.10	15.13	54.00	-38.87	AVG
11	7591.182	-14.75	37.35	22.60	74.00	-51.40	peak
12	7591.182	-14.75	26.86	12.11	54.00	-41.89	AVG

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service


Channel:	TX -X Position Mode Middle 2441MHz	Result:	☒ - passed
Test point:	Vertical		☐ - not passed
Frequency range:	30MHzHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2441.00	-25.95	114.83	88.88	114.00	-25.12	Peak
2	2441.00	-25.95	109.70	83.75	94.00	-10.25	AVG



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	74.9098	-19.81	50.95	31.14	40.00	-8.86	QP
2	119.2786	-16.91	47.02	30.11	43.50	-13.39	QP
3	123.0661	-16.30	46.87	30.57	43.50	-12.93	QP
4	172.3046	-15.23	44.32	29.09	43.50	-14.41	QP
5	199.8998	-11.26	38.64	27.38	43.50	-16.12	QP
6	270.7816	-11.40	41.95	30.55	46.00	-15.45	QP

Remark: Other frequency mini margin all >10 dB of Limit



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	392.5852	-15.06	47.63	32.57	46.00	-13.43	QP
2	417.8357	-14.66	44.54	29.88	46.00	-16.12	QP
3	466.9339	-12.56	41.76	29.20	46.00	-16.80	QP
4	584.7695	-13.03	38.99	25.96	46.00	-20.04	QP
5	715.2305	-11.96	38.41	26.45	46.00	-19.55	QP
6	779.7595	-8.46	40.87	32.41	46.00	-13.59	QP

Remark: Other frequency mini margin all >10 dB of Limit

Above 1GHz

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	1837.675	-25.57	47.01	21.44	74.00	-52.56	peak
2	1837.675	-25.57	37.34	11.77	54.00	-42.23	AVG
3	2873.747	-29.72	50.23	20.51	74.00	-53.49	peak
4	2873.747	-29.72	38.28	8.56	54.00	-45.44	AVG
5	3226.453	-31.02	46.17	15.15	74.00	-58.85	peak
6	3226.453	-31.02	34.06	3.04	54.00	-50.96	AVG
7	6951.904	-29.21	51.92	22.71	74.00	-51.29	peak
8	6951.904	-29.21	41.27	12.06	54.00	-41.94	AVG
9	8869.739	-20.18	45.49	25.31	74.00	-48.69	peak
10	8869.739	-20.18	35.82	15.64	54.00	-38.36	AVG
11	10545.090	-15.19	47.33	32.14	74.00	-41.86	peak
12	10545.090	-15.19	37.64	22.45	54.00	-31.55	AVG

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471


E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Channel:	TX -X Position Mode High 2480MHz	Result:	☒ - passed
Test point:	Horizontal		☐ - not passed
Frequency range:	30MHz-26.5GHz		

EUT	Water-proof Bluetooth Handfree Speaker
Firm Name	Elite Century Technology Ltd.
Operating Condition	Battery 3.7V
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Test Date:	01~08 November 2012
Operator	Duke
MODEL NO	BM-88P

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2480.00	-25.13	114.73	89.60	114.00	-24.40	Peak
2	2480.00	-25.13	111.29	86.16	94.00	-7.84	AVG



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	74.9098	-19.81	49.74	29.93	40.00	-10.07	QP
2	112.7856	-17.95	46.01	28.06	43.50	-15.44	QP
3	119.2786	-16.91	47.54	30.63	43.50	-12.87	QP
4	172.3046	-15.23	52.17	36.94	43.50	-6.56	QP
5	196.6533	-11.26	48.61	37.35	43.50	-6.15	QP
6	270.7816	-11.40	48.21	36.81	46.00	-9.19	QP

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	367.3347	-14.34	44.72	30.38	46.00	-15.62	QP
2	417.8357	-14.66	41.12	26.46	46.00	-19.54	QP
3	454.3086	-13.31	42.54	29.23	46.00	-16.77	QP
4	466.9339	-12.56	43.05	30.49	46.00	-15.51	QP
5	688.5772	-13.79	35.57	21.78	46.00	-24.22	QP
6	779.7595	-8.46	33.46	25.00	46.00	-21.00	QP

Remark: Other frequency mini margin all >10 dB of Limit

Above 1GHz

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	4306.613	-6.19	35.06	28.87	74.00	-45.13	peak
2	4306.613	-6.19	25.55	19.36	54.00	-34.64	AVG
3	4681.363	-8.56	35.84	27.28	74.00	-46.72	peak
4	4681.363	-8.56	23.92	15.36	54.00	-38.64	AVG
5	5408.818	-12.52	37.38	24.86	74.00	-49.14	peak
6	5408.818	-12.52	24.65	12.13	54.00	-41.87	AVG
7	6114.229	-13.07	39.10	26.03	74.00	-47.97	peak
8	6114.229	-13.07	27.35	14.28	54.00	-39.72	AVG
9	6907.816	-13.97	40.73	26.76	74.00	-47.24	peak
10	6907.816	-13.97	29.34	15.37	54.00	-38.63	AVG
11	8252.505	-15.50	35.85	20.35	74.00	-53.65	peak
12	8252.505	-15.50	25.86	10.36	54.00	-43.64	AVG

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Channel:	TX -X Position Mode High 2480MHz	Result:	☒ - passed
Test point:	Vertical		☐ - not passed
Frequency range:	30MHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2480.00	-25.13	112.64	87.51	114.00	-26.49	Peak
2	2480.00	-25.13	109.15	84.02	94.00	-9.98	AVG



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	64.6293	-21.97	56.14	34.17	40.00	-5.83	QP
2	74.9098	-19.81	51.93	32.12	40.00	-7.88	QP
3	122.5250	-16.38	45.41	29.03	43.50	-14.47	QP
4	196.6533	-11.26	43.76	32.50	43.50	-11.00	QP
5	270.7816	-11.40	40.85	29.45	46.00	-16.55	QP
6	295.1303	-6.12	37.73	31.61	46.00	-14.39	QP

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	343.4870	-12.76	39.01	26.25	46.00	-19.75	QP
2	392.5852	-15.06	46.65	31.59	46.00	-14.41	QP
3	466.9339	-12.56	43.19	30.63	46.00	-15.37	QP
4	490.7816	-11.15	37.23	26.08	46.00	-19.92	QP
5	584.7695	-13.03	38.65	25.62	46.00	-20.38	QP
6	779.7595	-8.46	39.00	30.54	46.00	-15.46	QP

Remark: Other frequency mini margin all >10 dB of Limit

Above 1GHz

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	1815.631	-25.48	45.61	20.13	74.00	-53.87	peak
2	1815.631	-25.48	35.30	9.82	54.00	-44.18	AVG
3	2609.218	-28.74	50.48	21.74	74.00	-52.26	peak
4	2609.218	-28.74	37.93	9.19	54.00	-44.81	AVG
5	8120.240	-23.71	48.07	24.36	74.00	-49.64	peak
6	8120.240	-23.71	36.91	13.20	54.00	-40.80	AVG
7	9354.709	-17.89	44.37	26.48	74.00	-47.52	peak
8	9354.709	-17.89	35.29	17.40	54.00	-36.60	AVG
9	9773.547	-16.24	47.49	31.25	74.00	-42.75	peak
10	9773.547	-16.24	36.54	20.30	54.00	-33.70	AVG
11	10478.958	-15.22	47.37	32.15	74.00	-41.85	peak
12	10478.958	-15.22	37.85	22.63	54.00	-31.37	AVG

Remark: Other frequency mini margin all >10 dB of Limit

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

9. Band Edge Compliance test

9.1. Test Equipment

Band Edge Compliance test					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	10868	2011/11
2	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2011/11
3	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2011/11

9.2. Test Information

EUT	Water-proof Bluetooth Handfree Speaker
Firm Name	Elite Century Technology Ltd.
Operating Condition	Battery 3.7V
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Test Date:	01~08 November 2012
Operator	Duke
MODEL NO	BM-88P

9.3. Test procedure

- 1、The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2、Max hold the trace of the setp 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.

9.4. Test Results

PASSED.

The EUT operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.

Test Mode	Channel Marked Frequency	Test Result Highest Emission (dBuV/m)			
		Horizontal		Vertical	
		Peak	Average	Peak	Average
Low Channel	2390MHz	35.51	20.92	32.76	19.29
	2400MHz	64.93	60.39	61.54	56.59
High Channel	2483.5MHz	48.70	44.86	47.77	42.77
	2500MHz	33.72	17.87	33.28	17.55

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471


E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service




Band Edges(CH Low)
Detector mode:Peak

Polarity:Horizontal



Band Edges(CH Low)
Detector mode: Average

Polarity: Horizontal



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.


CENTRE OF TESTING SERVICE CO., LTD.
Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



Band Edges(CH Low)
Detector mode:Peak


Polarity:Vertical



Date: 8.NOV.2012 19:33:50

Band Edges(CH Low)
Detector mode:Average

Polarity:Vertical



Date: 8.NOV.2012 19:31:57

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471


E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



Band Edges(CH High)
Detector mode:Peak


Polarity:Horizontal



Date: 8.NOV.2012 19:39:49

Band Edges(CH High)
Detector mode:Average

Polarity:Horizontal




Date: 8.NOV.2012 19:46:57


Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China
Tel: +86-20-85543113 (32 lines) Fax: +86-20-38780406
Complaint line: +86-20-85533471 E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Band Edges(CH High)
Detector mode:Peak**Polarity:Vertical**

Date: 8.NOV.2012 19:41:31

Band Edges(CH High)
Detector mode:Average**Polarity:Vertical**

Date: 8.NOV.2012 19:43:57

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

10. 20 dB Bandwidth test

10.1. Test Equipment

20 dB Bandwidth test					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	10868	2011/12
2	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2011/12
3	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2011/12

10.2. Test Information

EUT	Water-proof Bluetooth Handfree Speaker
Firm Name	Elite Century Technology Ltd.
Operating Condition	Battery 3.7V
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Test Date:	01~08 November 2012
Operator	Duke
MODEL NO	BM-88P

10.3. Test Results

PASSED.

The testing data was attached in the next pages.

Channel		Frequency (MHz)	20dB Bandwidth (MHz)
Low	GFSK 1M	2402	0.813
Middle		2441	0.804
High		2480	0.822
Low	$\pi/4$ -DQPSK 2M	2402	1.212
Middle		2441	1.212
High		2480	1.218
Low	8DPSK 3M	2402	1.206
Middle		2441	1.206
High		2480	1.212

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

**20 dB Bandwidth (2402 MHz GFSK 1M)**

Date: 30.NOV.2012 12:39:19

20 dB Bandwidth (2441MHz GFSK 1M)

Date: 30.NOV.2012 12:41:09

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

20 dB Bandwidth (2480MHz GFSK 1M)

Date: 30.NOV.2012 12:43:55

20 dB Bandwidth (2402 MHz, $\pi/4$ -DQPSK 2M)

Date: 3.DEC.2012 13:37:45

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

20 dB Bandwidth (2441 MHz, $\pi/4$ -DQPSK 2M)

Date: 3.DEC.2012 13:39:07

20 dB Bandwidth (2480 MHz, $\pi/4$ -DQPSK 2M)

Date: 3.DEC.2012 13:39:51

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406


Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

20 dB Bandwidth (2402 MHz, 8DPSK 3M)

Date: 3.DEC.2012 13:13:50

20 dB Bandwidth (2441 MHz, 8DPSK 3M)

Date: 3.DEC.2012 13:15:13

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China


Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

20 dB Bandwidth (2480 MHz, 8DPSK 3M)

Date: 3.DEC.2012 13:15:53

11.Deviation to test specifications

The following identical model(s):

BW-201, BW-101, BW-202, BW-102

Belong to the tested device:

Product description: **Water-proof Bluetooth Handfree Speaker**
Model name: **BM-88P**

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.

Building F, Dachuang industrial park, No.379, Zhongshan Dadao, Guangzhou, China

Tel: +86-20-85543113 (32 lines)

Fax: +86-20-38780406

Complaint line: +86-20-85533471

E-mail: cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service