

## RF EXPOSURE REPORT

**REPORT NO.:** SA990705C23

BHT-XY, BHT-XY Series

**MODEL NO.:** (X=900~906 or 914 for marketing purpose; Y=BB, B or blank, BB with

Bluetooth function, B and blank without

Bluetooth function)

FCC ID: PZWBHT900

**ACCORDING:** FCC Guidelines for Human Exposure

**IEEE C95.1** 

**APPLICANT:** DENSO WAVE INCORPORATED

ADDRESS: 1, Yoshiike, Kusaki, Agui-cho, Chita-gun, Aichi,

Japan, 470-2297

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,

Taipei Hsien 244, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation required if power is below this threshold:

F(GHz)		mW	
Low	2.402	24.58	
High	2.480	24.50	

Maximum measured transmitter power:

Pout (dBr	Pout (mW)	
Conducted Power	1.3	1.3
EIRP Power	4.897	3.088

<sup>\*</sup>Note: The antenna is PCB antenna with 3.597dBi gain.

Threshold for no SAR evaluation is 24.58mW Transmitter power is 3.088mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold