

July 09, 2018

## TUNE-UP PROCEDURE FOR THE XPLORE L10 TABLET

The output power levels of the EUT are stored in the mobile broadband module (Sierra Wireless EM7565) and set at the factory during Sierra Wireless module manufacturing. There is no tune-up procedure except these factory default settings, listed below.

**Table 4-6: Conducted Tx (Transmit) Power Tolerances**

Bands	Conducted Tx power	Notes
<b>LTE</b>		
LTE bands 1,2,3,4,5,8,9,12,13,18,19,20,26,28,66	+23 dBm $\pm$ 1 dB	
LTE bands 7,30,41,42 <sup>a</sup> ,43 <sup>a</sup> , 48 <sup>a</sup>	+22 dBm $\pm$ 1 dB	
<b>UMTS</b>		
Band 1 (IMT 2100 12.2 kbps) Band 2 (UMTS 1900 12.2 kbps) Band 4 (AWS 1700/2100 12.2 kbps) Band 5 (UMTS 850 12.2 kbps) Band 6 (UMTS 800 12.2 kbps) Band 8 (UMTS 900 12.2 kbps) Band 9 (UMTS 1700 12.2 kbps) Band 19 (UMTS 800 12.2 kbps)	+23 dBm $\pm$ 1 dB	Connectorized (Class 3)

a. B42/B43/B48 disabled as of publication date, support pending regulatory approval

Sincerely yours,



David J Ball  
Sr. Regulatory and Compliance Specialist  
8601 Ranch Rd. 2222  
Building 2  
Austin, Texas 78730  
(512) 485-1556  
dball@xploretech.com