

Date / Time:	9/4/2003 10:23:36 AM	Position:	Lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore iX104 CDMA	Head Rotation:	0
Antenna:	integral	Test Frequency:	835
Shape File:	xplorgprslap.csv	Power Level:	maximum

Probe:	0106																				
Cal File:	106_835_BODY_CDMA																				
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.35</td> <td>0.35</td> <td>0.35</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table>		X	Y	Z	Air	415	805	371	DCP	20	20	20	Lin	0.35	0.35	0.35		7	7	7
		X	Y	Z																	
	Air	415	805	371																	
	DCP	20	20	20																	
Lin	0.35	0.35	0.35																		
	7	7	7																		
Amp Gain:	2																				
Averaging:	6																				
Batteries Replaced:	09/03/2003																				

Liquid:	850
Type:	Body
Conductivity:	0.986
Relative Permittivity:	55.4
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.073	0.073
Change during Scan (%):	-0.12	
Max E-field (V/m):	14.28	
Max SAR (W/kg):	1g	10g
	0.174	0.115

Location of Max (mm):	X	Y	Z
	75.1	-49.0	-174.7

AREA SCAN:

Scan Extent:	Min	Max	Steps
Y	50.0	-50.0	10.0
Z	-190.0	-100.0	10.0

Date / Time:	9/4/2003 10:50:14 AM	Position:	bystander 1.5cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore iX104 CDMA	Head Rotation:	0
Antenna:	integral	Test Frequency:	835
Shape File:	xplorgprsbystand.csv	Power Level:	maximum

Probe:	0106																				
Cal File:	106_835_BODY_CDMA																				
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.35</td> <td>0.35</td> <td>0.35</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table>		X	Y	Z	Air	415	805	371	DCP	20	20	20	Lin	0.35	0.35	0.35		7	7	7
		X	Y	Z																	
	Air	415	805	371																	
	DCP	20	20	20																	
Lin	0.35	0.35	0.35																		
	7	7	7																		
Amp Gain:	2																				
Averaging:	6																				
Batteries Replaced:	09/03/2003																				

Liquid:	850
Type:	Body
Conductivity:	0.986
Relative Permittivity:	55.4
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.186	0.185
Change during Scan (%):	-0.24	
Max E-field (V/m):	20.86	
Max SAR (W/kg)	1g	10g
	0.376	0.257

Location of Max (mm):	X	Y	Z
	75.0	13.0	-149.5

AREA SCAN:

Scan Extent:	Min	Max	Steps
Y	50.0	-50.0	10.0
Z	-190.0	-100.0	10.0

Date / Time:	9/4/2003 11:16:22 AM	Position:	bystander 1.5cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore iX104 CDMA	Head Rotation:	0
Antenna:	integral	Test Frequency:	825.25
Shape File:	xplorgprsbystand.csv	Power Level:	maximum

Probe:	0106																				
Cal File:	106_835_BODY_CDMA																				
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.35</td> <td>0.35</td> <td>0.35</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table>		X	Y	Z	Air	415	805	371	DCP	20	20	20	Lin	0.35	0.35	0.35		7	7	7
		X	Y	Z																	
	Air	415	805	371																	
	DCP	20	20	20																	
Lin	0.35	0.35	0.35																		
	7	7	7																		
Amp Gain:	2																				
Averaging:	6																				
Batteries Replaced:	09/03/2003																				

Liquid:	850
Type:	Body
Conductivity:	0.977
Relative Permittivity:	55.8
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.130	0.130
Change during Scan (%):	-0.06	
Max E-field (V/m):	17.53	
Max SAR (W/kg)	1g	10g
	0.262	0.180

Location of Max (mm):	X	Y	Z
	75.0	13.0	-149.5

AREA SCAN:

Scan Extent:	Min	Max	Steps
Y	50.0	-50.0	10.0
Z	-190.0	-100.0	10.0

Date / Time:	9/4/2003 11:43:05 AM	Position:	bystander 1.5cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore iX104 CDMA	Head Rotation:	0
Antenna:	integral	Test Frequency:	847.75
Shape File:	xplorgprsbystand.csv	Power Level:	maximum

Probe:	0106																				
Cal File:	106_835_BODY_CDMA																				
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.35</td> <td>0.35</td> <td>0.35</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table>		X	Y	Z	Air	415	805	371	DCP	20	20	20	Lin	0.35	0.35	0.35		7	7	7
		X	Y	Z																	
	Air	415	805	371																	
	DCP	20	20	20																	
Lin	0.35	0.35	0.35																		
	7	7	7																		
Amp Gain:	2																				
Averaging:	6																				
Batteries Replaced:	09/03/2003																				

Liquid:	850
Type:	Body
Conductivity:	0.992
Relative Permittivity:	55.3
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.161	0.161
Change during Scan (%):	-0.05	
Max E-field (V/m):	19.60	
Max SAR (W/kg)	1g	10g
	0.331	0.225

Location of Max (mm):	X	Y	Z
	75.0	12.0	-149.3

AREA SCAN:

Scan Extent:	Min	Max	Steps
Y	50.0	-50.0	10.0
Z	-190.0	-100.0	10.0

1900MHz:

Date / Time:	9/3/2003 3:32:01 PM	Position:	Lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore iX104 CDMA	Head Rotation:	0
Antenna:	integral	Test Frequency:	1880
Shape File:	xplorgprslap.csv	Power Level:	maximum

Probe:	0106																				
Cal File:	106_1900_BODY_CDMA																				
Cal Factors:	<table border="1"> <tr> <td></td> <td>X</td> <td>Y</td> <td>Z</td> </tr> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.47</td> <td>0.47</td> <td>0.47</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </table>		X	Y	Z	Air	415	805	371	DCP	20	20	20	Lin	0.47	0.47	0.47		7	7	7
		X	Y	Z																	
	Air	415	805	371																	
	DCP	20	20	20																	
Lin	0.47	0.47	0.47																		
	7	7	7																		
Amp Gain:	2																				
Averaging:	6																				
Batteries Replaced:	09/03/2003																				

Liquid:	1900
Type:	Body
Conductivity:	1.540
Relative Permittivity:	53.27
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.178	0.177
Change during Scan (%):	-0.69	
Max E-field (V/m):	21.08	
Max SAR (W/kg)	1g	10g
	0.573	0.346

Location of Max (mm):	X	Y	Z
	75.1	-40.0	-174.7

AREA SCAN:

Scan Extent:	Min	Max	Steps
Y	50.0	-50.0	10.0
Z	-190.0	-100.0	10.0

Date / Time:	9/3/2003 4:26:52 PM	Position:	bystander 1.5cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore iX104 CDMA	Head Rotation:	0
Antenna:	integral	Test Frequency:	1880
Shape File:	xplorgprsbystand.csv	Power Level:	maximum

Probe:	0106																				
Cal File:	106_1900_BODY_CDMA																				
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.47</td> <td>0.47</td> <td>0.47</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table>		X	Y	Z	Air	415	805	371	DCP	20	20	20	Lin	0.47	0.47	0.47		7	7	7
		X	Y	Z																	
	Air	415	805	371																	
	DCP	20	20	20																	
Lin	0.47	0.47	0.47																		
	7	7	7																		
Amp Gain:	2																				
Averaging:	6																				
Batteries Replaced:	09/03/2003																				

Liquid:	1900
Type:	Body
Conductivity:	1.540
Relative Permittivity:	53.27
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan	
	0.330	0.330	
Change during Scan (%)	0.22		
Max E-field (V/m):	29.60		
Max SAR (W/kg)	1g	10g	
	1.067	0.587	
Location of Max (mm):	X	Y	Z
	75.1	-2.0	-145.0

AREA SCAN:

Scan Extent:	Min	Max	Steps	
	Y	50.0	-50.0	10.0
	Z	-190.0	-100.0	10.0

Date / Time:	9/3/2003 4:52:34 PM	Position:	bystander 1.5cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore iX104 CDMA	Head Rotation:	0
Antenna:	integral	Test Frequency:	1851.25
Shape File:	xplorgprsbystand.csv	Power Level:	maximum

Probe:	0106																				
Cal File:	106_1900_BODY_CDMA																				
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.47</td> <td>0.47</td> <td>0.47</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table>		X	Y	Z	Air	415	805	371	DCP	20	20	20	Lin	0.47	0.47	0.47		7	7	7
		X	Y	Z																	
	Air	415	805	371																	
	DCP	20	20	20																	
Lin	0.47	0.47	0.47																		
	7	7	7																		
Amp Gain:	2																				
Averaging:	6																				
Batteries Replaced:	09/03/2003																				

Liquid:	1900
Type:	Body
Conductivity:	1.531
Relative Permittivity:	53.46
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.250	0.253
Change during Scan (%):	1.15	
Max E-field (V/m):	26.03	
Max SAR (W/kg)	1g	10g
	0.816	0.448

Location of Max (mm):	X	Y	Z
	75.1	-2.0	-145.0

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	50.0	-50.0	10.0
	Z	-190.0	-100.0	10.0

Date / Time:	9/3/2003 5:19:41 PM	Position:	bystander 1.5cm
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore iX104 CDMA	Head Rotation:	0
Antenna:	integral	Test Frequency:	1908.75
Shape File:	xplorgprsbystand.csv	Power Level:	maximum

Probe:	0106																				
Cal File:	106_1900_BODY_CDMA																				
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.47</td> <td>0.47</td> <td>0.47</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table>		X	Y	Z	Air	415	805	371	DCP	20	20	20	Lin	0.47	0.47	0.47		7	7	7
		X	Y	Z																	
	Air	415	805	371																	
	DCP	20	20	20																	
Lin	0.47	0.47	0.47																		
	7	7	7																		
Amp Gain:	2																				
Averaging:	6																				
Batteries Replaced:	09/03/2003																				

Liquid:	1900
Type:	Body
Conductivity:	1.551
Relative Permittivity:	53.06
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.176	0.176
Change during Scan (%):	0.10	
Max E-field (V/m):	21.85	
Max SAR (W/kg)	1g	10g
	0.576	0.317

Location of Max (mm):	X	Y	Z
	75.1	-2.0	-144.8

AREA SCAN:

Scan Extent:	Min	Max	Steps	
	Y	50.0	-50.0	10.0
	Z	-190.0	-100.0	10.0