

|                       |                             |                        |                       |
|-----------------------|-----------------------------|------------------------|-----------------------|
| <b>Date / Time:</b>   | 9/4/2003 1:27:03 PM         | <b>Position:</b>       | lap                   |
| <b>Filename:</b>      | *.txt                       | <b>Phantom:</b>        | HeadBox_new_spout.csv |
| <b>Device Tested:</b> | Xplore iX104 802.11b<br>KM8 | <b>Head Rotation:</b>  | 0                     |
| <b>Antenna:</b>       | integral                    | <b>Test Frequency:</b> | 2437                  |
| <b>Shape File:</b>    | xplor802lap.csv             | <b>Power Level:</b>    | maximum               |

| <b>Probe:</b>              | 0106  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|----------------------------|---|------|------|-----|---|------------|-----|-----|-----|------------|----|----|----|------------|------|------|------|--|---|---|---|
| <b>Cal File:</b>           | 106_2450_BODY_802_11  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Cal Factors:</b>        | <table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td><b>Air</b></td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td><b>DCP</b></td> <td>19</td> <td>19</td> <td>19</td> </tr> <tr> <td><b>Lin</b></td> <td>0.58</td> <td>0.58</td> <td>0.58</td> </tr> <tr> <td></td> <td>5</td> <td>5</td> <td>5</td> </tr> </tbody> </table> |      | X    | Y   | Z | <b>Air</b> | 415 | 805 | 371 | <b>DCP</b> | 19 | 19 | 19 | <b>Lin</b> | 0.58 | 0.58 | 0.58 |  | 5 | 5 | 5 |
|                            |   | X    | Y    | Z   |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | <b>Air</b>  | 415  | 805  | 371 |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | <b>DCP</b>  | 19   | 19   | 19  |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Lin</b>                 | 0.58  | 0.58 | 0.58 |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | 5   | 5    | 5    |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Amp Gain:</b>           | 2   |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Averaging:</b>          | 6   |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Batteries Replaced:</b> | 09/03/2003  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |

|                               |       |
|-------------------------------|-------|
| <b>Liquid:</b>                | 2400  |
| <b>Type:</b>                  | Body  |
| <b>Conductivity:</b>          | 1.945 |
| <b>Relative Permittivity:</b> | 51.5  |
| <b>Liquid Temp (deg C):</b>   | 22.0  |
| <b>Ambient Temp (deg C):</b>  | 22.0  |
| <b>Ambient RH (%):</b>        | 50    |
| <b>Density (kg/m3):</b>       | 1000  |
| <b>Software Version:</b>      | 0.420 |

**ZOOM SCAN RESULTS:**

|                                |                   |                 |
|--------------------------------|-------------------|-----------------|
| <b>Spot SAR (W/kg):</b>        | <b>Start Scan</b> | <b>End Scan</b> |
|                                | 0.008             | 0.008           |
| <b>Change during Scan (%):</b> | 0.00              |                 |
| <b>Max E-field (V/m):</b>      | 5.17              |                 |
| <b>Max SAR (W/kg)</b>          | <b>1g</b>         | <b>10g</b>      |
|                                | 0.041             | 0.023           |

  

|                              |          |          |          |
|------------------------------|----------|----------|----------|
| <b>Location of Max (mm):</b> | <b>X</b> | <b>Y</b> | <b>Z</b> |
|                              | 75.0     | -27.0    | -172.7   |

**AREA SCAN:**

|                     |            |            |              |
|---------------------|------------|------------|--------------|
| <b>Scan Extent:</b> | <b>Min</b> | <b>Max</b> | <b>Steps</b> |
| <b>Y</b>            | 50.0       | -50.0      | 10.0         |
| <b>Z</b>            | -190.0     | -100.0     | 10.0         |

|                       |                             |                        |                       |
|-----------------------|-----------------------------|------------------------|-----------------------|
| <b>Date / Time:</b>   | 9/4/2003 1:59:48 PM         | <b>Position:</b>       | bystander 1.5cm       |
| <b>Filename:</b>      | *.txt                       | <b>Phantom:</b>        | HeadBox_new_spout.csv |
| <b>Device Tested:</b> | Xplore iX104 802.11b<br>KM8 | <b>Head Rotation:</b>  | 0                     |
| <b>Antenna:</b>       | integral                    | <b>Test Frequency:</b> | 2437                  |
| <b>Shape File:</b>    | xplor802bystand.csv         | <b>Power Level:</b>    | maximum               |

| <b>Probe:</b>              | 0106  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|----------------------------|---|------|------|-----|---|------------|-----|-----|-----|------------|----|----|----|------------|------|------|------|--|---|---|---|
| <b>Cal File:</b>           | 106_2450_BODY_802_11  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Cal Factors:</b>        | <table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td><b>Air</b></td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td><b>DCP</b></td> <td>19</td> <td>19</td> <td>19</td> </tr> <tr> <td><b>Lin</b></td> <td>0.58</td> <td>0.58</td> <td>0.58</td> </tr> <tr> <td></td> <td>5</td> <td>5</td> <td>5</td> </tr> </tbody> </table> |      | X    | Y   | Z | <b>Air</b> | 415 | 805 | 371 | <b>DCP</b> | 19 | 19 | 19 | <b>Lin</b> | 0.58 | 0.58 | 0.58 |  | 5 | 5 | 5 |
|                            |   | X    | Y    | Z   |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | <b>Air</b>  | 415  | 805  | 371 |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | <b>DCP</b>  | 19   | 19   | 19  |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Lin</b>                 | 0.58  | 0.58 | 0.58 |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | 5   | 5    | 5    |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Amp Gain:</b>           | 2   |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Averaging:</b>          | 6   |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Batteries Replaced:</b> | 09/03/2003  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |

|                               |       |
|-------------------------------|-------|
| <b>Liquid:</b>                | 2400  |
| <b>Type:</b>                  | Body  |
| <b>Conductivity:</b>          | 1.945 |
| <b>Relative Permittivity:</b> | 51.5  |
| <b>Liquid Temp (deg C):</b>   | 22.0  |
| <b>Ambient Temp (deg C):</b>  | 22.0  |
| <b>Ambient RH (%):</b>        | 50    |
| <b>Density (kg/m3):</b>       | 1000  |
| <b>Software Version:</b>      | 0.420 |

**ZOOM SCAN RESULTS:**

|                                |                   |                 |
|--------------------------------|-------------------|-----------------|
| <b>Spot SAR (W/kg):</b>        | <b>Start Scan</b> | <b>End Scan</b> |
|                                | 0.022             | 0.022           |
| <b>Change during Scan (%):</b> | 0.00              |                 |
| <b>Max E-field (V/m):</b>      | 6.60              |                 |
| <b>Max SAR (W/kg)</b>          | <b>1g</b>         | <b>10g</b>      |
|                                | 0.072             | 0.042           |

  

|                              |          |          |          |
|------------------------------|----------|----------|----------|
| <b>Location of Max (mm):</b> | <b>X</b> | <b>Y</b> | <b>Z</b> |
|                              | 75.1     | 10.0     | -149.5   |

**AREA SCAN:**

|                     |            |            |              |
|---------------------|------------|------------|--------------|
| <b>Scan Extent:</b> | <b>Min</b> | <b>Max</b> | <b>Steps</b> |
| <b>Y</b>            | 50.0       | -50.0      | 10.0         |
| <b>Z</b>            | -190.0     | -100.0     | 10.0         |

|                       |                             |                        |                       |
|-----------------------|-----------------------------|------------------------|-----------------------|
| <b>Date / Time:</b>   | 9/4/2003 2:27:48 PM         | <b>Position:</b>       | bystander 1.5cm       |
| <b>Filename:</b>      | *.txt                       | <b>Phantom:</b>        | HeadBox_new_spout.csv |
| <b>Device Tested:</b> | Xplore iX104 802.11b<br>KM8 | <b>Head Rotation:</b>  | 0                     |
| <b>Antenna:</b>       | integral                    | <b>Test Frequency:</b> | 2412                  |
| <b>Shape File:</b>    | xplor802bystand.csv         | <b>Power Level:</b>    | maximum               |

| <b>Probe:</b>              | 0106  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|----------------------------|---|------|------|-----|---|------------|-----|-----|-----|------------|----|----|----|------------|------|------|------|--|---|---|---|
| <b>Cal File:</b>           | 106_2450_BODY_802_11  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Cal Factors:</b>        | <table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td><b>Air</b></td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td><b>DCP</b></td> <td>19</td> <td>19</td> <td>19</td> </tr> <tr> <td><b>Lin</b></td> <td>0.58</td> <td>0.58</td> <td>0.58</td> </tr> <tr> <td></td> <td>5</td> <td>5</td> <td>5</td> </tr> </tbody> </table> |      | X    | Y   | Z | <b>Air</b> | 415 | 805 | 371 | <b>DCP</b> | 19 | 19 | 19 | <b>Lin</b> | 0.58 | 0.58 | 0.58 |  | 5 | 5 | 5 |
|                            |   | X    | Y    | Z   |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | <b>Air</b>  | 415  | 805  | 371 |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | <b>DCP</b>  | 19   | 19   | 19  |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Lin</b>                 | 0.58  | 0.58 | 0.58 |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | 5   | 5    | 5    |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Amp Gain:</b>           | 2   |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Averaging:</b>          | 6   |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Batteries Replaced:</b> | 09/03/2003  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |

|                               |       |
|-------------------------------|-------|
| <b>Liquid:</b>                | 2400  |
| <b>Type:</b>                  | Body  |
| <b>Conductivity:</b>          | 1.932 |
| <b>Relative Permittivity:</b> | 51.6  |
| <b>Liquid Temp (deg C):</b>   | 22.0  |
| <b>Ambient Temp (deg C):</b>  | 22.0  |
| <b>Ambient RH (%):</b>        | 50    |
| <b>Density (kg/m3):</b>       | 1000  |
| <b>Software Version:</b>      | 0.420 |

**ZOOM SCAN RESULTS:**

|                                |                   |                 |
|--------------------------------|-------------------|-----------------|
| <b>Spot SAR (W/kg):</b>        | <b>Start Scan</b> | <b>End Scan</b> |
|                                | 0.020             | 0.020           |
| <b>Change during Scan (%):</b> | -2.76             |                 |
| <b>Max E-field (V/m):</b>      | 6.67              |                 |
| <b>Max SAR (W/kg):</b>         | <b>1g</b>         | <b>10g</b>      |
|                                | 0.073             | 0.043           |

  

|                              |          |          |          |
|------------------------------|----------|----------|----------|
| <b>Location of Max (mm):</b> | <b>X</b> | <b>Y</b> | <b>Z</b> |
|                              | 75.1     | 10.0     | -149.5   |

**AREA SCAN:**

|                     |            |            |              |
|---------------------|------------|------------|--------------|
| <b>Scan Extent:</b> | <b>Min</b> | <b>Max</b> | <b>Steps</b> |
| <b>Y</b>            | 50.0       | -50.0      | 10.0         |
| <b>Z</b>            | -190.0     | -100.0     | 10.0         |

|                       |                             |                        |                       |
|-----------------------|-----------------------------|------------------------|-----------------------|
| <b>Date / Time:</b>   | 9/4/2003 2:53:30 PM         | <b>Position:</b>       | bystander 1.5cm       |
| <b>Filename:</b>      | *.txt                       | <b>Phantom:</b>        | HeadBox_new_spout.csv |
| <b>Device Tested:</b> | Xplore iX104 802.11b<br>KM8 | <b>Head Rotation:</b>  | 0                     |
| <b>Antenna:</b>       | integral                    | <b>Test Frequency:</b> | 2462                  |
| <b>Shape File:</b>    | xplor802bystand.csv         | <b>Power Level:</b>    | maximum               |

| <b>Probe:</b>              | 0106  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|----------------------------|---|------|------|-----|---|------------|-----|-----|-----|------------|----|----|----|------------|------|------|------|--|---|---|---|
| <b>Cal File:</b>           | 106_2450_BODY_802_11  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Cal Factors:</b>        | <table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td><b>Air</b></td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td><b>DCP</b></td> <td>19</td> <td>19</td> <td>19</td> </tr> <tr> <td><b>Lin</b></td> <td>0.58</td> <td>0.58</td> <td>0.58</td> </tr> <tr> <td></td> <td>5</td> <td>5</td> <td>5</td> </tr> </tbody> </table> |      | X    | Y   | Z | <b>Air</b> | 415 | 805 | 371 | <b>DCP</b> | 19 | 19 | 19 | <b>Lin</b> | 0.58 | 0.58 | 0.58 |  | 5 | 5 | 5 |
|                            |   | X    | Y    | Z   |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | <b>Air</b>  | 415  | 805  | 371 |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | <b>DCP</b>  | 19   | 19   | 19  |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Lin</b>                 | 0.58  | 0.58 | 0.58 |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
|                            | 5   | 5    | 5    |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Amp Gain:</b>           | 2   |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Averaging:</b>          | 6   |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |
| <b>Batteries Replaced:</b> | 09/03/2003  |      |      |     |   |            |     |     |     |            |    |    |    |            |      |      |      |  |   |   |   |

|                               |       |
|-------------------------------|-------|
| <b>Liquid:</b>                | 2400  |
| <b>Type:</b>                  | Body  |
| <b>Conductivity:</b>          | 1.961 |
| <b>Relative Permittivity:</b> | 51.1  |
| <b>Liquid Temp (deg C):</b>   | 22.0  |
| <b>Ambient Temp (deg C):</b>  | 22.0  |
| <b>Ambient RH (%):</b>        | 50    |
| <b>Density (kg/m3):</b>       | 1000  |
| <b>Software Version:</b>      | 0.420 |

**ZOOM SCAN RESULTS:**

|                                |                   |                 |
|--------------------------------|-------------------|-----------------|
| <b>Spot SAR (W/kg):</b>        | <b>Start Scan</b> | <b>End Scan</b> |
|                                | 0.019             | 0.019           |
| <b>Change during Scan (%):</b> | -1.27             |                 |
| <b>Max E-field (V/m):</b>      | 6.51              |                 |
| <b>Max SAR (W/kg)</b>          | <b>1g</b>         | <b>10g</b>      |
|                                | 0.070             | 0.041           |

  

|                              |          |          |          |
|------------------------------|----------|----------|----------|
| <b>Location of Max (mm):</b> | <b>X</b> | <b>Y</b> | <b>Z</b> |
|                              | 75.1     | 9.0      | -149.5   |

**AREA SCAN:**

|                     |            |            |              |
|---------------------|------------|------------|--------------|
| <b>Scan Extent:</b> | <b>Min</b> | <b>Max</b> | <b>Steps</b> |
| <b>Y</b>            | 50.0       | -50.0      | 10.0         |
| <b>Z</b>            | -190.0     | -100.0     | 10.0         |