

Date / Time:	3/23/2004 1:20:47 PM	Position:	Lap
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore	Head Rotation:	0
Antenna:	internal	Test Frequency:	2437
Shape File:	xplor802lap.csv	Power Level:	max

Probe:	0106																
Cal File:	106_2450_BODY_802_11																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>19</td> <td>19</td> <td>19</td> </tr> <tr> <td>Lin</td> <td>0.585</td> <td>0.585</td> <td>0.585</td> </tr> </tbody> </table>		X	Y	Z	Air	415	805	371	DCP	19	19	19	Lin	0.585	0.585	0.585
		X	Y	Z													
	Air	415	805	371													
	DCP	19	19	19													
Lin	0.585	0.585	0.585														
Amp Gain:	32																
Averaging:	6																
Batteries Replaced:	03/23/04																

Liquid:	2450
Type:	Body
Conductivity:	1.927
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.001	0.001
Change during Scan (%):	0.18	
Max E-field (V/m):	2.30	
Max SAR (W/kg)	1g	10g
	0.007	0.003

Location of Max (mm):	X	Y	Z
	75.0	-36.0	-172.8

AREA SCAN:

Scan Extent:	Min	Max	Steps
Y	-80.0	20.0	10.0
Z	-200.0	-120.0	10.0

Date / Time:	3/23/2004 1:49:10 PM	Position:	rear bystander touching phantom
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore	Head Rotation:	0
Antenna:	internal	Test Frequency:	2437
Shape File:	xplor802bystand.csv	Power Level:	max

Probe:	0106																
Cal File:	106_2450_BODY_802_11																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>19</td> <td>19</td> <td>19</td> </tr> <tr> <td>Lin</td> <td>0.585</td> <td>0.585</td> <td>0.585</td> </tr> </tbody> </table>		X	Y	Z	Air	415	805	371	DCP	19	19	19	Lin	0.585	0.585	0.585
		X	Y	Z													
	Air	415	805	371													
	DCP	19	19	19													
Lin	0.585	0.585	0.585														
Amp Gain:	32																
Averaging:	6																
Batteries Replaced:	03/23/04																

Liquid:	2450
Type:	Body
Conductivity:	1.927
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.005	0.005
Change during Scan (%):	0.00	
Max E-field (V/m):	4.85	
Max SAR (W/kg)	1g	10g
	0.033	0.016

Location of Max (mm):	X	Y	Z
	75.0	0.0	-148.8

AREA SCAN:

Scan Extent:	Min	Max	Steps
Y	-20.0	80.0	10.0
Z	-200.0	-120.0	10.0

Date / Time:	3/23/2004 2:15:30 PM	Position:	rear bystander touching phantom
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore	Head Rotation:	0
Antenna:	internal	Test Frequency:	2412
Shape File:	xplor802bystand.csv	Power Level:	max

Probe:	0106																
Cal File:	106_2450_BODY_802_11																
Cal Factors:	<table border="1"> <tr> <td></td> <td>X</td> <td>Y</td> <td>Z</td> </tr> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>19</td> <td>19</td> <td>19</td> </tr> <tr> <td>Lin</td> <td>0.585</td> <td>0.585</td> <td>0.585</td> </tr> </table>		X	Y	Z	Air	415	805	371	DCP	19	19	19	Lin	0.585	0.585	0.585
		X	Y	Z													
	Air	415	805	371													
	DCP	19	19	19													
Lin	0.585	0.585	0.585														
Amp Gain:	32																
Averaging:	6																
Batteries Replaced:	03/23/04																

Liquid:	2450
Type:	Body
Conductivity:	1.861
Relative Permittivity:	50.96
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.017	0.017
Change during Scan (%):	-0.08	
Max E-field (V/m):	7.08	
Max SAR (W/kg)	1g	10g
	0.071	0.038

Location of Max (mm):	X	Y	Z
	75.0	0.0	-149.9

AREA SCAN:

Scan Extent:	Min	Max	Steps
Y	-20.0	80.0	10.0
Z	-200.0	-120.0	10.0

Date / Time:	3/23/2004 2:59:28 PM	Position:	rear bystander touching phantom
Filename:	*.txt	Phantom:	HeadBox_new_spout.csv
Device Tested:	Xplore	Head Rotation:	0
Antenna:	internal	Test Frequency:	2462
Shape File:	xplor802bystand.csv	Power Level:	max

Probe:	0106																
Cal File:	106_2450_BODY_802_11																
Cal Factors:	<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>19</td> <td>19</td> <td>19</td> </tr> <tr> <td>Lin</td> <td>0.585</td> <td>0.585</td> <td>0.585</td> </tr> </tbody> </table>		X	Y	Z	Air	415	805	371	DCP	19	19	19	Lin	0.585	0.585	0.585
		X	Y	Z													
	Air	415	805	371													
	DCP	19	19	19													
Lin	0.585	0.585	0.585														
Amp Gain:	32																
Averaging:	6																
Batteries Replaced:	03/23/04																

Liquid:	2450
Type:	Body
Conductivity:	1.968
Relative Permittivity:	50.80
Liquid Temp (deg C):	22.0
Ambient Temp (deg C):	22.0
Ambient RH (%):	50
Density (kg/m3):	1000
Software Version:	0.420

ZOOM SCAN RESULTS:

Spot SAR (W/kg):	Start Scan	End Scan
	0.013	0.013
Change during Scan (%):	0.00	
Max E-field (V/m):	6.58	
Max SAR (W/kg)	1g	10g
	0.065	0.037

Location of Max (mm):	X	Y	Z
	75.0	1.0	-150.1

AREA SCAN:

Scan Extent:		Min	Max	Steps
	Y	-20.0	80.0	10.0
	Z	-200.0	-120.0	10.0