

| | | | |
|-----------------------|----------------------|------------------------|-----------------------|
| Date / Time: | 9/4/2003 10:23:36 AM | Position: | Lap |
| Filename: | *.txt | Phantom: | HeadBox_new_spout.csv |
| Device Tested: | Xplore iX104 CDMA | Head Rotation: | 0 |
| Antenna: | integral | Test Frequency: | 835 |
| Shape File: | xplorgprslap.csv | Power Level: | maximum |

| | | | | | | | | | | | | | | | | | | | | | |
|----------------------------|--|----------|----------|----------|----------|------------|-----|-----|-----|------------|----|----|----|------------|------|------|------|--|---|---|---|
| Probe: | 0106 | | | | | | | | | | | | | | | | | | | | |
| Cal File: | 106_835_BODY_CDMA | | | | | | | | | | | | | | | | | | | | |
| Cal Factors: | <table border="1"> <tr> <td></td> <td>X</td> <td>Y</td> <td>Z</td> </tr> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.35</td> <td>0.35</td> <td>0.35</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </table> | | X | Y | Z | Air | 415 | 805 | 371 | DCP | 20 | 20 | 20 | Lin | 0.35 | 0.35 | 0.35 | | 7 | 7 | 7 |
| | | X | Y | Z | | | | | | | | | | | | | | | | | |
| | Air | 415 | 805 | 371 | | | | | | | | | | | | | | | | | |
| | DCP | 20 | 20 | 20 | | | | | | | | | | | | | | | | | |
| Lin | 0.35 | 0.35 | 0.35 | | | | | | | | | | | | | | | | | | |
| | 7 | 7 | 7 | | | | | | | | | | | | | | | | | | |
| Amp Gain: | 2 | | | | | | | | | | | | | | | | | | | | |
| Averaging: | 6 | | | | | | | | | | | | | | | | | | | | |
| Batteries Replaced: | 09/03/2003 | | | | | | | | | | | | | | | | | | | | |

| | |
|-------------------------------|-------|
| Liquid: | 850 |
| Type: | Body |
| Conductivity: | 0.986 |
| Relative Permittivity: | 55.4 |
| Liquid Temp (deg C): | 22.0 |
| Ambient Temp (deg C): | 22.0 |
| Ambient RH (%): | 50 |
| Density (kg/m3): | 1000 |
| Software Version: | 0.420 |

ZOOM SCAN RESULTS:

| | | |
|--------------------------------|-------------------|-----------------|
| Spot SAR (W/kg): | Start Scan | End Scan |
| | 0.073 | 0.073 |
| Change during Scan (%): | -0.12 | |
| Max E-field (V/m): | 14.28 | |
| Max SAR (W/kg) | 1g | 10g |
| | 0.174 | 0.115 |

| | | | |
|------------------------------|----------|----------|----------|
| Location of Max (mm): | X | Y | Z |
| | 75.1 | -49.0 | -174.7 |

AREA SCAN:

| | | | | |
|---------------------|----------|------------|------------|--------------|
| Scan Extent: | | Min | Max | Steps |
| | Y | 50.0 | -50.0 | 10.0 |
| | Z | -190.0 | -100.0 | 10.0 |

| | | | |
|-----------------------|----------------------|------------------------|-----------------------|
| Date / Time: | 9/4/2003 10:50:14 AM | Position: | bystander 1.5cm |
| Filename: | *.txt | Phantom: | HeadBox_new_spout.csv |
| Device Tested: | Xplore iX104 CDMA | Head Rotation: | 0 |
| Antenna: | integral | Test Frequency: | 835 |
| Shape File: | xplorgprsbystand.csv | Power Level: | maximum |

| Probe: | 0106 | | | | | | | | | | | | | | | | | | | | |
|----------------------------|---|------|------|-----|---|------------|-----|-----|-----|------------|----|----|----|------------|------|------|------|--|---|---|---|
| Cal File: | 106_835_BODY_CDMA | | | | | | | | | | | | | | | | | | | | |
| Cal Factors: | <table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.35</td> <td>0.35</td> <td>0.35</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table> | | X | Y | Z | Air | 415 | 805 | 371 | DCP | 20 | 20 | 20 | Lin | 0.35 | 0.35 | 0.35 | | 7 | 7 | 7 |
| | | X | Y | Z | | | | | | | | | | | | | | | | | |
| | Air | 415 | 805 | 371 | | | | | | | | | | | | | | | | | |
| | DCP | 20 | 20 | 20 | | | | | | | | | | | | | | | | | |
| Lin | 0.35 | 0.35 | 0.35 | | | | | | | | | | | | | | | | | | |
| | 7 | 7 | 7 | | | | | | | | | | | | | | | | | | |
| Amp Gain: | 2 | | | | | | | | | | | | | | | | | | | | |
| Averaging: | 6 | | | | | | | | | | | | | | | | | | | | |
| Batteries Replaced: | 09/03/2003 | | | | | | | | | | | | | | | | | | | | |

| | |
|-------------------------------|-------|
| Liquid: | 850 |
| Type: | Body |
| Conductivity: | 0.986 |
| Relative Permittivity: | 55.4 |
| Liquid Temp (deg C): | 22.0 |
| Ambient Temp (deg C): | 22.0 |
| Ambient RH (%): | 50 |
| Density (kg/m3): | 1000 |
| Software Version: | 0.420 |

ZOOM SCAN RESULTS:

| | | | |
|--------------------------------|-------------------|-----------------|----------|
| Spot SAR (W/kg): | Start Scan | End Scan | |
| | 0.186 | 0.185 | |
| Change during Scan (%): | -0.24 | | |
| Max E-field (V/m): | 20.86 | | |
| Max SAR (W/kg) | 1g | 10g | |
| | 0.376 | 0.257 | |
| Location of Max (mm): | X | Y | Z |
| | 75.0 | 13.0 | -149.5 |

AREA SCAN:

| | | | | |
|---------------------|------------|------------|--------------|------|
| Scan Extent: | Min | Max | Steps | |
| | Y | 50.0 | -50.0 | 10.0 |
| | Z | -190.0 | -100.0 | 10.0 |

| | | | |
|-----------------------|----------------------|------------------------|-----------------------|
| Date / Time: | 9/4/2003 11:16:22 AM | Position: | bystander 1.5cm |
| Filename: | *.txt | Phantom: | HeadBox_new_spout.csv |
| Device Tested: | Xplore iX104 CDMA | Head Rotation: | 0 |
| Antenna: | integral | Test Frequency: | 825.25 |
| Shape File: | xplorgprsbystand.csv | Power Level: | maximum |

| Probe: | 0106 | | | | | | | | | | | | | | | | | | | | |
|----------------------------|---|------|------|-----|---|------------|-----|-----|-----|------------|----|----|----|------------|------|------|------|--|---|---|---|
| Cal File: | 106_835_BODY_CDMA | | | | | | | | | | | | | | | | | | | | |
| Cal Factors: | <table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.35</td> <td>0.35</td> <td>0.35</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table> | | X | Y | Z | Air | 415 | 805 | 371 | DCP | 20 | 20 | 20 | Lin | 0.35 | 0.35 | 0.35 | | 7 | 7 | 7 |
| | | X | Y | Z | | | | | | | | | | | | | | | | | |
| | Air | 415 | 805 | 371 | | | | | | | | | | | | | | | | | |
| | DCP | 20 | 20 | 20 | | | | | | | | | | | | | | | | | |
| Lin | 0.35 | 0.35 | 0.35 | | | | | | | | | | | | | | | | | | |
| | 7 | 7 | 7 | | | | | | | | | | | | | | | | | | |
| Amp Gain: | 2 | | | | | | | | | | | | | | | | | | | | |
| Averaging: | 6 | | | | | | | | | | | | | | | | | | | | |
| Batteries Replaced: | 09/03/2003 | | | | | | | | | | | | | | | | | | | | |

| | |
|-------------------------------|-------|
| Liquid: | 850 |
| Type: | Body |
| Conductivity: | 0.977 |
| Relative Permittivity: | 55.8 |
| Liquid Temp (deg C): | 22.0 |
| Ambient Temp (deg C): | 22.0 |
| Ambient RH (%): | 50 |
| Density (kg/m3): | 1000 |
| Software Version: | 0.420 |

ZOOM SCAN RESULTS:

| | | |
|--------------------------------|-------------------|-----------------|
| Spot SAR (W/kg): | Start Scan | End Scan |
| | 0.130 | 0.130 |
| Change during Scan (%): | -0.06 | |
| Max E-field (V/m): | 17.53 | |
| Max SAR (W/kg) | 1g | 10g |
| | 0.262 | 0.180 |

| | | | |
|------------------------------|----------|----------|----------|
| Location of Max (mm): | X | Y | Z |
| | 75.0 | 13.0 | -149.5 |

AREA SCAN:

| | | | |
|---------------------|------------|------------|--------------|
| Scan Extent: | Min | Max | Steps |
| Y | 50.0 | -50.0 | 10.0 |
| Z | -190.0 | -100.0 | 10.0 |

| | | | |
|-----------------------|----------------------|------------------------|-----------------------|
| Date / Time: | 9/4/2003 11:43:05 AM | Position: | bystander 1.5cm |
| Filename: | *.txt | Phantom: | HeadBox_new_spout.csv |
| Device Tested: | Xplore iX104 CDMA | Head Rotation: | 0 |
| Antenna: | integral | Test Frequency: | 847.75 |
| Shape File: | xplorgprsbystand.csv | Power Level: | maximum |

| Probe: | 0106 | | | | | | | | | | | | | | | | | | | | |
|----------------------------|---|------|------|-----|---|------------|-----|-----|-----|------------|----|----|----|------------|------|------|------|--|---|---|---|
| Cal File: | 106_835_BODY_CDMA | | | | | | | | | | | | | | | | | | | | |
| Cal Factors: | <table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.35</td> <td>0.35</td> <td>0.35</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table> | | X | Y | Z | Air | 415 | 805 | 371 | DCP | 20 | 20 | 20 | Lin | 0.35 | 0.35 | 0.35 | | 7 | 7 | 7 |
| | | X | Y | Z | | | | | | | | | | | | | | | | | |
| | Air | 415 | 805 | 371 | | | | | | | | | | | | | | | | | |
| | DCP | 20 | 20 | 20 | | | | | | | | | | | | | | | | | |
| Lin | 0.35 | 0.35 | 0.35 | | | | | | | | | | | | | | | | | | |
| | 7 | 7 | 7 | | | | | | | | | | | | | | | | | | |
| Amp Gain: | 2 | | | | | | | | | | | | | | | | | | | | |
| Averaging: | 6 | | | | | | | | | | | | | | | | | | | | |
| Batteries Replaced: | 09/03/2003 | | | | | | | | | | | | | | | | | | | | |

| | |
|-------------------------------|-------|
| Liquid: | 850 |
| Type: | Body |
| Conductivity: | 0.992 |
| Relative Permittivity: | 55.3 |
| Liquid Temp (deg C): | 22.0 |
| Ambient Temp (deg C): | 22.0 |
| Ambient RH (%): | 50 |
| Density (kg/m3): | 1000 |
| Software Version: | 0.420 |

ZOOM SCAN RESULTS:

| | | |
|--------------------------------|-------------------|-----------------|
| Spot SAR (W/kg): | Start Scan | End Scan |
| | 0.161 | 0.161 |
| Change during Scan (%): | -0.05 | |
| Max E-field (V/m): | 19.60 | |
| Max SAR (W/kg): | 1g | 10g |
| | 0.331 | 0.225 |

| | | | |
|------------------------------|----------|----------|----------|
| Location of Max (mm): | X | Y | Z |
| | 75.0 | 12.0 | -149.3 |

AREA SCAN:

| | | | |
|---------------------|------------|------------|--------------|
| Scan Extent: | Min | Max | Steps |
| Y | 50.0 | -50.0 | 10.0 |
| Z | -190.0 | -100.0 | 10.0 |

1900MHz:

| | | | |
|-----------------------|---------------------|------------------------|-----------------------|
| Date / Time: | 9/3/2003 3:32:01 PM | Position: | Lap |
| Filename: | *.txt | Phantom: | HeadBox_new_spout.csv |
| Device Tested: | Xplore iX104 CDMA | Head Rotation: | 0 |
| Antenna: | integral | Test Frequency: | 1880 |
| Shape File: | xplorgprslap.csv | Power Level: | maximum |

| | | | | | | | | | | | | | | | | | | | | | |
|----------------------------|--|----------|----------|----------|----------|------------|-----|-----|-----|------------|----|----|----|------------|------|------|------|--|---|---|---|
| Probe: | 0106 | | | | | | | | | | | | | | | | | | | | |
| Cal File: | 106_1900_BODY_CDMA | | | | | | | | | | | | | | | | | | | | |
| Cal Factors: | <table border="1"> <tr> <td></td> <td>X</td> <td>Y</td> <td>Z</td> </tr> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.47</td> <td>0.47</td> <td>0.47</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </table> | | X | Y | Z | Air | 415 | 805 | 371 | DCP | 20 | 20 | 20 | Lin | 0.47 | 0.47 | 0.47 | | 7 | 7 | 7 |
| | | X | Y | Z | | | | | | | | | | | | | | | | | |
| | Air | 415 | 805 | 371 | | | | | | | | | | | | | | | | | |
| | DCP | 20 | 20 | 20 | | | | | | | | | | | | | | | | | |
| Lin | 0.47 | 0.47 | 0.47 | | | | | | | | | | | | | | | | | | |
| | 7 | 7 | 7 | | | | | | | | | | | | | | | | | | |
| Amp Gain: | 2 | | | | | | | | | | | | | | | | | | | | |
| Averaging: | 6 | | | | | | | | | | | | | | | | | | | | |
| Batteries Replaced: | 09/03/2003 | | | | | | | | | | | | | | | | | | | | |

| | |
|-------------------------------|-------|
| Liquid: | 1900 |
| Type: | Body |
| Conductivity: | 1.540 |
| Relative Permittivity: | 53.27 |
| Liquid Temp (deg C): | 22.0 |
| Ambient Temp (deg C): | 22.0 |
| Ambient RH (%): | 50 |
| Density (kg/m3): | 1000 |
| Software Version: | 0.420 |

ZOOM SCAN RESULTS:

| | | |
|--------------------------------|-------------------|-----------------|
| Spot SAR (W/kg): | Start Scan | End Scan |
| | 0.178 | 0.177 |
| Change during Scan (%): | -0.69 | |
| Max E-field (V/m): | 21.08 | |
| Max SAR (W/kg) | 1g | 10g |
| | 0.573 | 0.346 |

| | | | |
|------------------------------|----------|----------|----------|
| Location of Max (mm): | X | Y | Z |
| | 75.1 | -40.0 | -174.7 |

AREA SCAN:

| | | | |
|---------------------|------------|------------|--------------|
| Scan Extent: | Min | Max | Steps |
| Y | 50.0 | -50.0 | 10.0 |
| Z | -190.0 | -100.0 | 10.0 |

| | | | |
|-----------------------|----------------------|------------------------|-----------------------|
| Date / Time: | 9/3/2003 4:26:52 PM | Position: | bystander 1.5cm |
| Filename: | *.txt | Phantom: | HeadBox_new_spout.csv |
| Device Tested: | Xplore iX104 CDMA | Head Rotation: | 0 |
| Antenna: | integral | Test Frequency: | 1880 |
| Shape File: | xplorgprsbystand.csv | Power Level: | maximum |

| Probe: | 0106 | | | | | | | | | | | | | | | | | | | | |
|----------------------------|---|------|------|-----|---|------------|-----|-----|-----|------------|----|----|----|------------|------|------|------|--|---|---|---|
| Cal File: | 106_1900_BODY_CDMA | | | | | | | | | | | | | | | | | | | | |
| Cal Factors: | <table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.47</td> <td>0.47</td> <td>0.47</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table> | | X | Y | Z | Air | 415 | 805 | 371 | DCP | 20 | 20 | 20 | Lin | 0.47 | 0.47 | 0.47 | | 7 | 7 | 7 |
| | | X | Y | Z | | | | | | | | | | | | | | | | | |
| | Air | 415 | 805 | 371 | | | | | | | | | | | | | | | | | |
| | DCP | 20 | 20 | 20 | | | | | | | | | | | | | | | | | |
| Lin | 0.47 | 0.47 | 0.47 | | | | | | | | | | | | | | | | | | |
| | 7 | 7 | 7 | | | | | | | | | | | | | | | | | | |
| Amp Gain: | 2 | | | | | | | | | | | | | | | | | | | | |
| Averaging: | 6 | | | | | | | | | | | | | | | | | | | | |
| Batteries Replaced: | 09/03/2003 | | | | | | | | | | | | | | | | | | | | |

| | |
|-------------------------------|-------|
| Liquid: | 1900 |
| Type: | Body |
| Conductivity: | 1.540 |
| Relative Permittivity: | 53.27 |
| Liquid Temp (deg C): | 22.0 |
| Ambient Temp (deg C): | 22.0 |
| Ambient RH (%): | 50 |
| Density (kg/m3): | 1000 |
| Software Version: | 0.420 |

ZOOM SCAN RESULTS:

| | | | |
|-------------------------------|-------------------|-----------------|----------|
| Spot SAR (W/kg): | Start Scan | End Scan | |
| | 0.330 | 0.330 | |
| Change during Scan (%) | 0.22 | | |
| Max E-field (V/m): | 29.60 | | |
| Max SAR (W/kg) | 1g | 10g | |
| | 1.067 | 0.587 | |
| Location of Max (mm): | X | Y | Z |
| | 75.1 | -2.0 | -145.0 |

AREA SCAN:

| | | | | |
|---------------------|------------|------------|--------------|------|
| Scan Extent: | Min | Max | Steps | |
| | Y | 50.0 | -50.0 | 10.0 |
| | Z | -190.0 | -100.0 | 10.0 |

| | | | |
|-----------------------|----------------------|------------------------|-----------------------|
| Date / Time: | 9/3/2003 4:52:34 PM | Position: | bystander 1.5cm |
| Filename: | *.txt | Phantom: | HeadBox_new_spout.csv |
| Device Tested: | Xplore iX104 CDMA | Head Rotation: | 0 |
| Antenna: | integral | Test Frequency: | 1851.25 |
| Shape File: | xplorgprsbystand.csv | Power Level: | maximum |

| Probe: | 0106 | | | | | | | | | | | | | | | | | | | | |
|----------------------------|---|------|------|-----|---|------------|-----|-----|-----|------------|----|----|----|------------|------|------|------|--|---|---|---|
| Cal File: | 106_1900_BODY_CDMA | | | | | | | | | | | | | | | | | | | | |
| Cal Factors: | <table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> <th>Z</th> </tr> </thead> <tbody> <tr> <td>Air</td> <td>415</td> <td>805</td> <td>371</td> </tr> <tr> <td>DCP</td> <td>20</td> <td>20</td> <td>20</td> </tr> <tr> <td>Lin</td> <td>0.47</td> <td>0.47</td> <td>0.47</td> </tr> <tr> <td></td> <td>7</td> <td>7</td> <td>7</td> </tr> </tbody> </table> | | X | Y | Z | Air | 415 | 805 | 371 | DCP | 20 | 20 | 20 | Lin | 0.47 | 0.47 | 0.47 | | 7 | 7 | 7 |
| | | X | Y | Z | | | | | | | | | | | | | | | | | |
| | Air | 415 | 805 | 371 | | | | | | | | | | | | | | | | | |
| | DCP | 20 | 20 | 20 | | | | | | | | | | | | | | | | | |
| Lin | 0.47 | 0.47 | 0.47 | | | | | | | | | | | | | | | | | | |
| | 7 | 7 | 7 | | | | | | | | | | | | | | | | | | |
| Amp Gain: | 2 | | | | | | | | | | | | | | | | | | | | |
| Averaging: | 6 | | | | | | | | | | | | | | | | | | | | |
| Batteries Replaced: | 09/03/2003 | | | | | | | | | | | | | | | | | | | | |

| | |
|-------------------------------|-------|
| Liquid: | 1900 |
| Type: | Body |
| Conductivity: | 1.531 |
| Relative Permittivity: | 53.46 |
| Liquid Temp (deg C): | 22.0 |
| Ambient Temp (deg C): | 22.0 |
| Ambient RH (%): | 50 |
| Density (kg/m3): | 1000 |
| Software Version: | 0.420 |

ZOOM SCAN RESULTS:

| | | |
|--------------------------------|-------------------|-----------------|
| Spot SAR (W/kg): | Start Scan | End Scan |
| | 0.250 | 0.253 |
| Change during Scan (%): | 1.15 | |
| Max E-field (V/m): | 26.03 | |
| Max SAR (W/kg) | 1g | 10g |
| | 0.816 | 0.448 |

| | | | |
|------------------------------|----------|----------|----------|
| Location of Max (mm): | X | Y | Z |
| | 75.1 | -2.0 | -145.0 |

AREA SCAN:

| | | | |
|---------------------|------------|------------|--------------|
| Scan Extent: | Min | Max | Steps |
| Y | 50.0 | -50.0 | 10.0 |
| Z | -190.0 | -100.0 | 10.0 |

| | | | |
|-----------------------|----------------------|------------------------|-----------------------|
| Date / Time: | 9/3/2003 5:19:41 PM | Position: | bystander 1.5cm |
| Filename: | *.txt | Phantom: | HeadBox_new_spout.csv |
| Device Tested: | Xplore iX104 CDMA | Head Rotation: | 0 |
| Antenna: | integral | Test Frequency: | 1908.75 |
| Shape File: | xplorgprsbystand.csv | Power Level: | maximum |

Probe: 0106
Cal File: 106_1900_BODY_CDMA

| | X | Y | Z |
|------------|------|------|------|
| Air | 415 | 805 | 371 |
| DCP | 20 | 20 | 20 |
| Lin | 0.47 | 0.47 | 0.47 |
| | 7 | 7 | 7 |

Cal Factors:

Amp Gain: 2
Averaging: 6
Batteries Replaced: 09/03/2003

Liquid: 1900
Type: Body
Conductivity: 1.551
Relative Permittivity: 53.06
Liquid Temp (deg C): 22.0
Ambient Temp (deg C): 22.0
Ambient RH (%): 50
Density (kg/m3): 1000
Software Version: 0.420

ZOOM SCAN RESULTS:

| | | |
|--------------------------------|-------------------|-----------------|
| Spot SAR (W/kg): | Start Scan | End Scan |
| | 0.176 | 0.176 |
| Change during Scan (%): | 0.10 | |
| Max E-field (V/m): | 21.85 | |
| Max SAR (W/kg) | 1g | 10g |
| | 0.576 | 0.317 |

| | | | |
|------------------------------|----------|----------|----------|
| Location of Max (mm): | X | Y | Z |
| | 75.1 | -2.0 | -144.8 |

AREA SCAN:

| | | | |
|---------------------|------------|------------|--------------|
| Scan Extent: | Min | Max | Steps |
| Y | 50.0 | -50.0 | 10.0 |
| Z | -190.0 | -100.0 | 10.0 |