



FCC Test Report

Test report no.: EMC_678FCC15.247_2004_BT+WLAN+CDMA

FCC Part 15.247 / CANADA RSS-210
EUT Tablet PC with
BT module Model: TM60M665
WLAN Model: 2200BG
CDMA module Model: AC555
IC ID: 4596A-iX104WBC



TTI-P-G 081/94-A0

Accredited according to **ISO/IEC 17025**



**Bluetooth Qualification
Test Facility
(BQTF)**



FCC listed # 101450

IC recognized # 3925

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: info@cetecomusa.com ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2113686

Board of Directors: Dr. Harald Ansorge, Dr. Klaus Matkey, Hans Peter May

Table of Contents

1	General information
1.1	Notes
1.2	Testing laboratory
1.3	Details of applicant
1.4	Application details
1.5	Test item
1.6	Test standards
2	Technical test
2.1	Summary of test results
2.2	Test report
1	General information
1.1	Notes

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM Inc USA.

TEST REPORT PREPARED BY:**EMC Engineer: Harpreet Sidhu****1.2 Testing laboratory****CETECOM Inc.****411 Dixon Landing Road, Milpitas, CA-95035, USA****Phone: +1 408 586 6200 Fax: +1 408 586 6299****E-mail: lothar.schmidt@cetecomusa.com****Internet: www.cetecom.com**

1.3 Details of applicant

Name : **Xplore Technologies**
Street : **14000 Summit Road, Suite 900**
City / Zip Code : **Austin, TX 78728**
Country : **USA**
Contact : **Douglas L. Fowler**
Telephone : **+1 512 336 7797**
Tele-fax : **+1 512 336 7791**
e-mail : dfowler@xploretech.com

1.4 Application details

Date of receipt test item : 2004-06-21
Date of test : 2004-06-21/22/23/29

1.5 Test item

Manufacturer : Applicant
Model No. : iX104-TM60+2200, iX104-TM60+AC55x,
iX104-2200+AC55x, iX104-TM60+2200+AC55x
Description : **Tablet PC with BT module, WLAN, GSM module**
FCC-ID : Q2GIX104-124, Q2GIX104-126,
Q2GIX104-128, Q2GIX104-130
IC ID : 4596A-iX104WBC

Additional information

Test Sample ID : PARIS
Frequency : 2402MHz – 2480MHz for BT
2412MHz – 2462MHz for WLAN
825.25MHz – 847.75MHz for CDMA 850,
1851.25MHz – 1908.75MHz for CDMA 1900
Type of modulation : FHSS, DSSS & OFDM, OQPSK
Antenna : Embedded
Power supply : via host Tablet PC
Extreme temp. Tolerance : -30°C to +50°C

1.6 Test standards: **FCC Part 15 §15.247 (DA00-705) / RSS 210**

SUMMARY OF TEST REPORT

This test report is valid for collocation combination of different radios under following FCC ID's and model #'s

FCC ID: Q2GIX104-124	EUT Model: iX104-TM60+2200	(BT+WLAN)
FCC ID: Q2GIX104-126	EUT Model: iX104-TM60+AC55x	(BT+CDMA)
FCC ID: Q2GIX104-128	EUT Model: iX104-2200+ AC55x	(WLAN+CDMA)
FCC ID: Q2GIX104-130	EUT Model: iX104-TM60+2200+AC55x	(BT+WLAN+CDMA)

For ease of testing all radios (BT, WLAN & CDMA) were set to transmit at under-mentioned channels. Testing is done against FCC15.247 limits. CDMA mode was tested in both 850 & 1900 bands along with BT & WLAN respectively. Test report carries only worst case plots.

<u>Transmitter</u>	<u>Channel Freq.</u>
CDMA 850	ch-383 836.5MHz
CDMA 1900	ch-600 1880MHz
BT	ch-79 2480MHz
WLAN	ch-1 2412MHz

2 Technical test**2.1 Summary of test results**

No deviations from the technical specification(s) were ascertained in the course of the tests Performed	
Final Verdict: (only "passed" if all single measurements are "passed")	Passed

Technical responsibility for area of testing:

2004-07-08 EMC & Radio Lothar Schmidt (Manager)**Date****Section****Name****Signature****Responsible for test report and project leader:**

2004-07-08 EMC & Radio Harpreet Sidhu (EMC Engineer)**Date****Section****Name****Signature**

2.2 Test report

TEST REPORT

Test report no.: EMC_678FCC15.247_2004_BT+WLAN+CDMA

TEST REPORT REFERENCE

LIST OF MEASUREMENTS		PAGE
EMISSION LIMITATIONS	§ 15.247 (c) (1)	8
CONDUCTED EMISSIONS	§ 15.107/207	17
RECEIVER SPURIOUS RADIATION	§ 15.209	18
TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS		24
BLOCK DIAGRAMS		25

EMISSION LIMITATIONS
Transmitter (Radiated)

§ 15.247 (c) (1)

LIMITS

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions that fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

NOTE:

1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 3 and 26.5 GHz very short cable connections to the antenna was used to minimize the noise level.
2. Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.
3. All measurements are done in peak mode unless specified with plots.

Results for the radiated measurements below 30MHz according § 15.33

Frequency	Measured values	Remarks
9KHz – 30MHz	No emissions found, caused by the EUT	This is valid for all the tested channels

EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

Transmit at Lowest channel Frequency			
Frequency (MHz)	Level (dBμV/m)		
	Peak	Quasi-Peak	Average
See plots			
Transmit at Middle channel Frequency			
Frequency (MHz)	Level (dBμV/m)		
	Peak	Quasi-Peak	Average
See plots			
Transmit at Highest channel Frequency			
Frequency (MHz)	Level (dBμV/m)		
	Peak	Quasi-Peak	Average
See plots			

EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)


30MHz – 1GHz

Antenna: horizontal

CDMA 850+BT+WLAN

Note: Peak above the limit line is the carrier freq. of CDMA 850 @ ch-383

SWEEP TABLE:		"Spuri hi 30-1G"			
Short Description:		30MHz-1GHz			
Start	Stop	Detector	Meas. Time	RBW	Transducer
Frequency	Frequency			VBW	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	3141-#1186



EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)


30MHz – 1GHz

Antenna: vertical

CDMA 850+BT+WLAN

Note: Peak above the limit line is the carrier freq. of CDMA 850 @ ch-383

SWEEP TABLE:		"Spuri hi 30-1G"			
Short Description:		30MHz-1GHz			
Start	Stop	Detector	Meas. Time	RBW	Transducer
Frequency	Frequency			VBW	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	3141-#1186




EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)

30MHz – 1GHz**Antenna: vertical****CDMA1900+BT+WLAN**

SWEEP TABLE: "Spuri hi 30-1G"
Short Description: 30MHz-1GHz

Start	Stop	Detector	Meas. Time	RBW	VBW	Transducer
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz		3141-#1186



EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)

30MHz – 1GHz


Antenna: horizontal

CDMA 1900+BT+WLAN

SWEEP TABLE: "Spuri hi 30-1G"

Short Description: 30MHz-1GHz

Start	Stop	Detector	Meas. Time	RBW	Transducer
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	3141-#1186




EMISSION LIMITATIONS - Radiated (Transmitter)
1GHz – 3GHz

§ 15.247 (c) (1)

CDMA1900+BT+WLAN

NOTE: The marked peak is CDMA 1900 carrier freq. @ 1880MHz and other two lower and higher peaks above the limit line are WLAN @ 2412MHz & BT @ 2480MHz respectively.

SWEEP TABLE:		"Spuri hi 1-3G"			
Short Description:		1-3GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
1.0 GHz	3.0 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)




EMISSION LIMITATIONS - Radiated (Transmitter)
3GHz – 18GHz

§ 15.247 (c) (1)

CDMA 1900+BT+WLAN

SWEEP TABLE:		"Spuri hi 3-18G"			
Short Description:		Spurious 3-18 GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
3.0 GHz	18.0 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)




EMISSION LIMITATIONS - Radiated (Transmitter)

§ 15.247 (c) (1)

18GHz – 26.5GHz

CDMA 1900+BT+WLAN

SWEEP TABLE:		"Spuri hi 18-26.5G"			
Short Description:		Spurious 18-26.5GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
18 GHz	26.5 GHz	MaxPeak	Coupled	1 MHz	#141 horn (dBi)



CONDUCTED EMISSIONS
CDMA850+BT+WLAN

§ 15.107/207


Technical specification: 15.107 / 15.207 (Revised as of August 20, 2002)

Limit

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

ANALYZER SETTINGS: RBW = 10KHz VBW = 10KHz



RECEIVER SPURIOUS RADIATION

§ 15.209

Limits

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

NOTE:


1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 3 and 26.5 GHz very short cable connections to the antenna was used to minimize the noise level.
2. All radios (BT, WLAN & CDMA) are set to idle/receive mode.
3. All measurements are done in peak mode unless specified with the plots.

RECEIVER SPURIOUS RADIATION

§ 15.209

30MHz – 1GHz**Antenna: vertical**

SWEEP TABLE:		"Spuri hi 30-1G"			
Short Description:		30MHz-1GHz			
Start	Stop	Detector	Meas. Time	RBW	Transducer
Frequency	Frequency			VBW	
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	3141-#1186




RECEIVER SPURIOUS RADIATION

§ 15.209

30MHz – 1GHz**Antenna: Horizontal**

SWEEP TABLE: "Spuri hi 30-1G"
Short Description: 30MHz-1GHz


Start	Stop	Detector	Meas. Time	RBW	VBW	Transducer
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz		3141-#1186



**RECEIVER SPURIOUS RADIATION
1GHz – 3GHz**

§ 15.209


SWEEP TABLE:		"Spuri hi 1-3G"			
Short Description:		Spurious 1-3GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
1.0 GHz	3.0 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)



**RECEIVER SPURIOUS RADIATION
3GHz – 18GHz**

§ 15.209


SWEEP TABLE:		"Spuri hi 3-18G"			
Short Description:		Spurious 3-18 GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
3.0 GHz	18.0 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)



RECEIVER SPURIOUS RADIATION
18GHz – 26.5GHz

§ 15.209

SWEEP TABLE:		"Spuri hi 18-26.5G"			
Short Description:		Spurious 18-26.5GHz			
Start	Stop	Detector	Meas.	RBW	Transducer
Frequency	Frequency	Time	Bandw.	VBW	
18.0 GHz	26.5 GHz	MaxPeak	Coupled	1 MHz	#326 horn (dBi)



TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	ESIB 40	Rohde & Schwarz	100107
02	Spectrum Analyzer	FSEM 30	Rohde & Schwarz	826880/010
03	Biconilog Antenna	3141	EMCO	0005-1186
04	Horn Antenna (700M-18GHz)	SAS-200/571	AH Systems	325
05	Horn Antenna (18-26.5GHz)	3160-09	EMCO	1240
06	2-3GHz Band reject filter	BRM50701	Microtronics	6
07	Pre-Amplifier	TS-ANA	Rohde & Schwarz	--
08	Pre-Amplifier	JS4-00102600	Miteq	00616

BLOCK DIAGRAMS
Radiated Testing

ANECHOIC CHAMBER

