



**AEGIS LABS INC.**



Modular Approval  
Test Report  
And Application for Grant of Equipment Authorization

Pertaining To:

<b>EUT</b>	<b>FCC ID:</b>
<b>Intel PRO/Wireless 2915ABG Network Connection, MN: WM3B2915ABG</b>	<b>PD9WM3B2915ABG</b>

<b>Configuration</b>
<b>802.11a / 802.11b / 802.11g with a set of Ethertronics Antennas</b>

*MEASUREMENTS PERFORMED IN ACCORDANCE WITH*

<b>Regulatory Standard(s)</b>
<b>47 CFR Part 15, Subpart C Section 15.247</b>
<p>Test Method: ANSI C63.4: 1992 American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz</p>



Certificate Number: 1111.01

**APPLICANT:**

Intel Corporation  
EC2-02 13280 Evening Creek Drive  
San Diego, California 92128

Contact(s): Mr. Robert Paxman

**PREPARED BY:**

Aegis Labs, Inc.  
22431 Antonio Parkway B160-417  
Rancho S. Margarita, CA 92688

Agent(s): Mr. Steve Kuiper  
Mr. Rick Candelas  
Mr. Johnny Candelas

Test Report #: INTEL-040412F  
Test Report Revision: None

	REPORT BODY	APPENDICES <i>A</i>	TOTAL PAGES
PAGES	18	73	91

The contents of this report shall not be reproduced except in full, without the written approval of Aegis Labs, Inc.

Page 1 of 18  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



# TABLE OF CONTENTS

SECTION	TITLE	PAGE
	<b>COVER SHEET</b> .....	<b>01</b>
	<b>TABLE OF CONTENTS</b> .....	<b>02</b>
<b>1.0</b>	<b>CERTIFICATION OF TEST DATA</b> .....	<b>03</b>
<b>2.0</b>	<b>SUMMARY OF TEST RESULTS</b> .....	<b>06</b>
<b>3.0</b>	<b>ADMINISTRATIVE DATA AND TEST DESCRIPTION</b> .....	<b>07</b>
<b>4.0</b>	<b>DESCRIPTION OF EUT</b> .....	<b>08</b>
4.1	EUT Description.....	08
4.1.1	Channel Number and Frequencies.....	09
4.2	EUT Configuration.....	10
4.3	List of EUT Sub-Assemblies and Host Equipment.....	11
4.4	I/O Cabling Diagram and Description.....	12
<b>5.0</b>	<b>TEST EQUIPMENT AND TEST SETUPS</b> .....	<b>13</b>
5.1	AC Power Line Conducted Emissions.....	13
5.2	Spurious Radiated Emissions.....	14
5.3	Conducted Emissions At The Antenna Port.....	14
5.4	Test and Measurement Equipment Used.....	15
<b>6.0</b>	<b>SAMPLE CALCULATIONS</b> .....	<b>16</b>
<b>7.0</b>	<b>MODIFICATIONS AND RECOMMENDATIONS</b> .....	<b>18</b>

## APPENDICES

<b>A</b>	Test Data
----------	-----------



AEGIS LABS INC.

## 1.0 CERTIFICATION OF TEST DATA

Aegis Labs, Inc. operates as both a Nevada and California Corporation with no organizational or financial relationship with any company, institution, or private individual.

Testing and engineering functions provided by Aegis Labs are furnished through the use of part-time, full-time or consulting engineers with the appropriate qualifications to carry out their duties. The intended purpose of this test report is to describe the measurement procedure and to determine whether the equipment under test "EUT" complies with both the conducted and radiated limits. Limits for emissions testing are described under Subpart C of Part 15 of the FCC rules.

The data, data evaluation and equipment configuration represented herein are a true and accurate representation of the Equipment Under Test (EUT) under the requirements specified in the emissions standard as described below. The test results contained in this report are only representative of the test sample tested as described in Section 3.0 of this report. Certification of the EUT is required as a prerequisite to marketing as defined in Part 2 of the FCC Rules.

**Prepared By:**

06/24/04

**Rick Candelas**  
**Staff Engineer**  
**Aegis Labs, Inc.**

**Date:**

**Report Approved By:**

06/24/04

**Steve J. Kuiper**  
**Quality Assurance Manager**  
**Aegis Labs, Inc.**

**Date:**

Page 3 of 18

Report Number: INTEL-040412F

FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

## 2.0 SUMMARY OF TEST RESULTS

The test results provided within this report, indicate that the EUT has been found to be in **COMPLIANCE** with the test specifications based upon the following RF compliance standards:

Pass/Fail determination is based upon the nominal values of the test data.

### *802.11a Mode (5725-5850 MHz)*

EMISSIONS STANDARD			
FCC Part 15 Section	Description	Results	Comments
15.247(a)(2)	The minimum 6dB bandwidth shall be at least 500 kHz.	PASSED	5745 MHz = 16.58 MHz 5785 MHz = 16.67 MHz 5825 MHz = 16.67 MHz
15.247(b)(1)	The maximum peak output power of the intentional radiator shall not exceed 1 watt.	PASSED	5745 MHz = 22.9 dBm = 194.98 mW 5785 MHz = 23.10 dBm = 204.17 mW 5825 MHz = 23.20 dBm = 208.93 mW
15.247(b)(4)	The intentional radiator shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines per Section 1.1307(b)(1).	PASSED	Refer to MPE Calculations Exhibit
15.247(c)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.	PASSED	See Data Sheets
15.247(c)	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.	PASSED	See Data Sheets
15.247(d)	The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	PASSED	5745 MHz = -10.50 dB 5785 MHz = -10.50 dB 5825 MHz = -9.83 dB
15.207	AC Conducted Emissions	PASSED	See Data Sheets
15.209	Radiated Emissions (30-1000 MHz)	PASSED	See Data Sheets



AEGIS LABS INC.

## 2.0 Summary of Test Results (Continued)

The test results provided within this report, indicate that the EUT has been found to be in **COMPLIANCE** with the test specifications based upon the following RF compliance standards:

Pass/Fail determination is based upon the nominal values of the test data.

### *802.11b Mode (2400-2483.5 MHz)*

EMISSIONS STANDARD			
FCC Part 15 Section	Description	Results	Comments
15.247(a)(2)	The minimum 6dB bandwidth shall be at least 500 kHz.	PASSED	2412 MHz = 7.75 MHz 2437 MHz = 7.83 MHz 2462 MHz = 7.75 MHz
15.247(b)(1)	The maximum peak output power of the intentional radiator shall not exceed 1 watt.	PASSED	2412 MHz = 17.40 dBm = 54.95 mW 2437 MHz = 18.95 dBm = 78.52 mW 2462 MHz = 19.20 dBm = 83.18 mW
15.247(b)(4)	The intentional radiator shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines per Section 1.1307(b)(1).	PASSED	Refer to MPE Calculations Exhibit
15.247(c)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.	PASSED	See Data Sheets
15.247(c)	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.	PASSED	See Data Sheets
15.247(d)	The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	PASSED	2412 MHz = -6.17 dB 2437 MHz = -6.67 dB 2462 MHz = -7.17 dB
15.207	AC Conducted Emissions	PASSED	See Data Sheets
15.209	Radiated Emissions (30-1000 MHz)	PASSED	See Data Sheets

Page 5 of 18

Report Number: INTEL-040412F

FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

## 2.0 Summary of Test Results (Continued)

The test results provided within this report, indicate that the EUT has been found to be in **COMPLIANCE** with the test specifications based upon the following RF compliance standards:

Pass/Fail determination is based upon the nominal values of the test data.

### *802.11g Mode (2400-2483.5 MHz)*

EMISSIONS STANDARD			
FCC Part 15 Section	Description	Results	Comments
15.247(a)(2)	The minimum 6dB bandwidth shall be at least 500 kHz.	PASSED	2412 MHz = 16.33 MHz 2437 MHz = 16.67 MHz 2462 MHz = 16.67 MHz
15.247(b)(1)	The maximum peak output power of the intentional radiator shall not exceed 1 watt.	PASSED	2412 MHz = 24.00 dBm = 251.19 mW 2437 MHz = 23.80 dBm = 239.88 mW 2462 MHz = 23.90 dBm = 245.47 mW
15.247(b)(4)	The intentional radiator shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines per Section 1.1307(b)(1).	PASSED	Refer to MPE Calculations Exhibit
15.247(c)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.	PASSED	See Data Sheets
15.247(c)	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.	PASSED	See Data Sheets
15.247(d)	The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	PASSED	2412 MHz = -11.33 dB 2437 MHz = -12.67 dB 2462 MHz = -11.17 dB
15.207	AC Conducted Emissions	PASSED	See Data Sheets
15.209	Radiated Emissions (30-1000 MHz)	PASSED	See Data Sheets

Page 6 of 18

Report Number: INTEL-040412F

FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

### 3.0 ADMINISTRATIVE DATA AND TEST DESCRIPTION

<b>DEVICE TESTED:</b>	ITE Type: Intel PRO/Wireless 2915ABG Network Connection Model Number(s): WM3B2915ABG Serial Number: 26E5FE224ABC51962011 FCC ID: PD9WM3B2915ABG
<b>TEST DATE(S):</b>	June 6-10, 2004
<b>DATE EUT RECEIVED:</b>	June 4, 2004
<b>ORIGIN OF TEST SAMPLE(S):</b>	Pre-Production Unit
<b>RESPONSIBLE PARTY:</b>	Intel Corporation EC2-02 13280 Evening Creek Drive San Diego, California 92128
<b>CLIENT CONTACT:</b>	Mr. Robert Paxman
<b>MANUFACTURER:</b>	Intel Corporation
<b>TEST LOCATION:</b>	Aegis Labs, Inc. 32231 Trabuco Creek Road Trabuco Canyon, CA 92678 Conducted Site #2 Radiated Site #2
<b>A2LA CERTIFICATE:</b>	1111.01, Valid through February 28, 2006
<b>PURPOSE OF TEST:</b>	To demonstrate compliance with the relevant standards described in Section 2.0 of this report.
<b>TEST(S) PERFORMED:</b>	Refer to Table in Section 2.0 of this report.

All calibration vendors were responsible for certifying Aegis Labs, Inc. test equipment as per the manufacturer's specifications and that the equipment is calibrated using instruments and standards where the accuracy is traceable to the National Institute of Standards and Technology (NIST). Calibration of all test equipment conforms to ANSI/NCSL Z540-1 and ISO 10012-1 and/or ISO/IEC Guide 17025 compliance (Additionally, other pertinent test equipment will carry MIL-STD-45662A). All calibration documents are on file with Aegis Labs, Inc., with copies provided upon request.

Page 7 of 18  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

## 4.0 DESCRIPTION OF EUT

### 4.1 EUT Description

<b>Equipment Under Test (EUT)</b>	
<b>Trade Name:</b>	Intel PRO/Wireless 2915ABG Network Connection
<b>Model Number:</b>	WM3B2915ABG
<b>Frequency Range:</b>	802.11a = 5725 – 5850 MHz 802.11b/g = 2400 – 2483.5 MHz
<b>Type of Transmission:</b>	Direct Sequence Spread Spectrum
<b>Transfer Rate:</b>	1/5.5/11 Mbps for 802.11b mode 6/36/54 Mbps for 802.11g and 802.11a modes
<b>Number of Channels:</b>	802.11a mode (5725-5850 MHz) = 5 802.11b mode (2400-2483.5 MHz) = 11 802.11g mode (2400-2483.5 MHz) = 11
<b>Modulation Type:</b>	DBPSK, DQPSK, CCK, OFDM
<b>Antenna Type:</b>	Hirose U.FL-R-SMT mates with cable connector U.FL-LP-066
<b>Antenna Gain (See Note 2):</b>	Ethertronics Antenna @ 5 GHz = 5.00 dBi Ethertronics Antenna @ 2.4 GHz = 3.00 dBi
<b>Transmit Output Power:</b>	23 dBm (Typical) for 802.11a mode 19 dBm (Typical) for 802.11b mode 24 dBm (Typical) for 802.11g mode Please see Appendix A (Data Sheets) for actual output power.
<b>Power Supply:</b>	3.3VDC from computer MPCIE slot.
<b>Number of External Test Ports Exercised:</b>	2 Antenna Ports (1 Main & 1 Auxiliary)

The Intel PRO/Wireless 2915ABG Network Connection is an embedded 2.4 and 5 GHz Wireless Local Area Network Mini-PCI adapter. The Mini-PCI Type 3B form factor is designed for notebook computer systems where overall thickness must be kept to an absolute minimum and connect to antennas internal to a notebook computer. It is capable of a data rate of up to 52 Mbps.

**NOTE 1:** For a more detailed description, please refer to the manufacture's specifications or User's Manual.

**NOTE 2:** The EUT was tested with a set of antennas (Ethertronics). (Refer to the antenna specifications exhibits).

Page 8 of 18  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG





#### 4.1.1 Channel Number and Frequencies

802.11a Mode		802.11b Mode		802.11g Mode	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	1	2412	1	2412
153	5765	2	2417	2	2417
157	5785	3	2422	3	2422
161	5805	4	2427	4	2427
165	5825	5	2432	5	2432
		6	2437	6	2437
		7	2442	7	2442
		8	2447	8	2447
		9	2452	9	2452
		10	2457	10	2457
		11	2462	11	2462



AEGIS LABS INC.

## 4.2 EUT Configuration

The EUT was tested installed in the Mini-PCI slot of the Hewlett Packard host computer as a modular device using a PCI extender board to extend the EUT outside the computer chassis. The EUT was then connected to a set of antennas via its Main and AUX antenna ports. Data for a set of Ethertronics antennas can be found in Appendix A (Data Sheets)

For conducted emissions at the AC mains port and radiated emissions, the Hewlett Packard host computer was connected to a Zoom modem, Hewlett Packard printer, Dell monitor, Hewlett Packard keyboard, and Hewlett Packard mouse via its serial, parallel, video, keyboard, and mouse ports respectively.

The low, middle, and high channels were tested in 802.11a, b, & g modes. Also, the EUT was tested once transmitting from the MAIN antenna port and once transmitting from the AUX antenna port. The EUT was placed in either continuous transmit or continuous receive mode by a program provided by the manufacturer (*CRTU Version 3.2.11.0000*).



AEGIS LABS INC.

#### 4.3 List of EUT, Sub-Assemblies, and Host Equipment


<b>LIST OF EUT AND SUB-ASSEMBLIES</b>			
<b>Equipment Name</b>	<b>Manufacturer</b>	<b>Model Number</b>	<b>Serial Number</b>
Intel PRO/Wireless 2915ABG Network Connection	Intel Corporation	WM3B2915ABG	26E5FE224AB C51962011
<b>EUT Sub-Assemblies</b>			
Main Multi Band Antenna	Ethertronics	MPCI01001	N/A
Auxiliary Multi Band Antenna	Ethertronics	MPCI01001	N/A

<b>HOST EQUIPMENT LIST</b>			
<b>Equipment Name</b>	<b>Manufacturer</b>	<b>Model Number</b>	<b>Serial Number</b>
Computer	Hewlett Packard	Pavillion a300n	MXK3391864
LCD Monitor	Dell	E151FPp	CN-06R644-47804-34R- LATL
Keyboard	Hewlett Packard	5183	BF33339165
Mouse	Hewlett Packard	M042KC	30870136

NOTE: All the power cords of the above support equipment are standard non-shielded, 1.8 meters long.



#### 4.4 I/O Cabling Diagram and Description



- Cable 1: This is a 6-foot braid and foil shielded round cable connecting the Hewlett Packard host computer with the Zoom modem. It has metallic DB-9 type connector at the computer end and a metallic DB-25 type connector at the modem end. The cable is bundled to a length of one meter and the shield of the cable is grounded to the chassis of both devices via the connector shells.
- Cable 2: This is a 6-foot braid and foil shielded round cable connecting the Hewlett Packard host computer with the Dell LCD monitor. It has metallic DB-15 type connector at the computer end and is hardwired to the monitor. The cable is bundled to a length of one meter and the shield of the cable is grounded to the chassis of both devices via the connector shells.
- Cable 3: This is a 6-foot braid and foil shielded round cable connecting the Hewlett Packard host computer to the Hewlett Packard printer. It has a metallic DB-25 type connector at the computer end and a metallic centronics type connector at the printer end. The cable is bundled to a length of one meter and the shield of the cable is grounded to the chassis of both devices via the connector shells.
- Cable 4: This is a 6-foot braid and foil shielded round cable connecting the Hewlett Packard host computer to the Hewlett Packard keyboard. It has a metallic 6-pin mini din type connector at the computer end and is hardwired to the keyboard. The shield of the cable is grounded to the chassis of the computer via the connector shell.
- Cable 5: This is a 6-foot braid and foil shielded round cable connecting the Hewlett Packard host computer to the Hewlett Packard mouse. It has a metallic 6-pin mini din type connector at the computer end and is hardwired to the mouse. The shield of the cable is grounded to the chassis of the computer via the connector shell.



AEGIS LABS INC.

## 5.0 TEST EQUIPMENT AND TEST SETUPS

The test equipment settings and functions are selected using the guidance of ANSI C63.4-1992. All test equipment setups and operations during conducted and radiated emissions testing are in accordance with this reference document.

### 5.1 AC Power Line Conducted Emissions

During conducted emissions measurements, a spectrum analyzer was used as the measuring instrument along with a preselector and quasi-peak detector. A 10 dB attenuation pad was used for the protection of the spectrum analyzer input stage. The conducted emissions from the EUT in the frequency range from 150 kHz to 30 MHz were captured for graphical display through the use of automated LABVIEW EMI measurement software. All graphical readings were measured in the “Peak” mode only to reduce testing time. Upon completion of the graphical scan, the test lab personnel performed the conducted measurement scan manually using the spectrum analyzer front panel keys. All peak measurements coming within 3 dB of the limit line were “Averaged” and/or “Quasi-Peaked” and denoted appropriately in the EXCEL spreadsheet.

The Equipment Under Test (EUT) was configured as a system with peripherals connected, so that at least one interface port of each type is connected to one external peripheral when tested for conducted emissions according to ANSI C63.4: 1992. Excess power cord length was wrapped in a bundle 30 to 40 centimeters in length near the center of the cord. The EUT was tested in a tabletop configuration.

The emission readings for Line 1 and Line 2 are highlighted on the data sheets in Appendix A. The graphical scans only reflect peak readings while the tabulated data sheets reflect peak, average, and/or quasi-peak readings which ever applies.



AEGIS LABS INC.

## 5.2 Spurious Radiated Emissions

A spectrum analyzer was used as the measuring instrumentation along with a preselector and quasi-peak-detector. The pre-amplifiers were used to increase the sensitivity of the instrument. The spectrum analyzer was used in the peak detector mode with the “max-hold” feature activated and in Positive Peak mode. In this mode, the spectrum analyzer records the highest measured reading over all the sweeps. The quasi-peak detector was used only for those readings, which are marked accordingly in the data sheet. The effective measurement bandwidth used for the radiated emissions test was 120 kHz for (30 MHz- 1000 MHz). The spectrum analyzer operated such that the modulation of the signal was filtered out to set the analyzer in linear mode. For testing beyond 1000 MHz a spectrum analyzer capable of taking reading above 1000 MHz was connected to the high frequency amplifier, where these measurement readings were taken with the transducer placed at a 3-meter test distance from the EUT.

The Open Area Test Sites (OATS) was used for radiated emission testing. These test sites are designed according to ANSI C63.4: 1992 and ANSI C63.7: 1992 guidelines. The Measurements were conducted in accordance with ANSI C63.4: 1992 and ANSI C63.7: 1992 requirements.

Broadband biconical, log periodic, and horn antennas were used as transducers during the measurement reading phase. The frequency spans were wide (30 MHz-88 MHz, 88 MHz- 216 MHz, 216 MHz- 300 MHz, and 300 MHz- 1000 MHz). After 1000 MHz the horn antenna was used to measure emissions. The emission readings in both horizontal and vertical polarities are highlighted on the data sheets in Appendix A.

## 5.3 Conducted Emissions at the Antenna Port

A spectrum analyzer or power meter was used as the measuring instrumentation along with an attenuator and/or filter connected to the EUT antenna port. The attenuator and filters are used to ensure that the front end of the measurement instrument is not overloaded by the fundamental transmission. . The instruments recorded the measured readings with the bandwidths (video and resolution) set in accordance with the FCC Rules and regulations.

For the power out measurements in 802.11b and 802.11g modes a peak power meter was used along with a peak power sensor with a wide enough bandwidth to capture the entire fundamental transmission. For 802.11a mode a spectrum analyzer with “Channel Power Measurement” function was used to measure the peak output power.

The measured readings are on the data sheets in Appendix A.



AEGIS LABS INC.

## 5.4 Test and Measurement Equipment Used

TEST EQUIPMENT USED					
Equipment Name	Manufacturer	Model Number	Serial Number	Calibration Due Date	Calibration Cycle
EMI Receiver - RF Section	Hewlett Packard	85462A	3325A00137	03/29/05	1 Year
EMI Receiver – RF Filter Section	Hewlett Packard	85460A	3330A00138	03/29/05	1 Year
Attenuator - 5W-10dB	Pasternack	PE7014-10	N/A	11/03/04	1 Year
LISN (EUT)	FCC	FCC-LISN-50-25-2	9931	02/06/05	1 Year
LISN (Access)	Com-Power	LI-200	12019	01/25/05	1 Year
LISN (Access)	Com-Power	LI-200	12018	01/25/05	1 Year
Spectrum Analyzer	Agilent	8564EC	4046A00387	02/06/06	2 Years
Preamplifier	Miteq	JS42-01001800-25-10P	815980 & 884968 & 885090	12/09/04	2 Years
2400-2483.5 MHz Notch Filter	Micro-Tronics	BRM50702-02	003	04/21/06	2 Years
5725-5850 MHz Notch Filter	Microwave Circuits, Inc.	N0257881	3173-01	06/27/05	2 Years
Antenna - Biconical	EMCO	3110	9108-1421	02/11/05	1 Year
Antenna - Log Periodic	EMCO	3148	4947	02/11/05	1 Year
1-18 GHz Antenna - Horn	Com-Power	AH-118	10069	12/09/04	2 Years
18-26.5 GHz Preamplified Antenna – Horn	Custom Microwave	H042	001	11/04/04	1 Year
Power Meter	Anritsu	ML2487A	6K00001785	04/05/05	2 Years
Wide Bandwidth Sensor	Anritsu	MA2491A	31193	04/05/05	2 Years
Temperature/Humidity Monitor	Dickson	TH550	7255185	01/18/05	1 Year

Page 15 of 18  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



## 6.0 SAMPLE CALCULATIONS

If a preamplifier is used during the Radiated Emissions Testing, it is required that the amplifier gain be subtracted from the Spectrum Analyzer (Meter) Reading. In addition, a correction factor for the antenna, cable and a distance factor, if any, must be applied to the Meter Reading before a true field strength reading can be obtained. In the Automatic Mode of A.R.M.S. measurements, these considerations are automatically presented as a part of the printout. In the case of manual measurements and for greater efficiency and convenience, usage of the calibration correction factors in the Appendices is necessary to calculate the Corrected Meter Reading. These correlation factors for each meter reading, shall be modified to reflect these correlation factors at each frequency value so that the meter readings can be compared directly to the modified specification limit. This modified specification limit is referred to as the "Corrected Meter Reading Limit" (CML).

The equation shall be derived in the following manner:

$$\text{Corrected Meter Reading} = \text{Meter Reading} + F + C - G - D$$

Where, F = Antenna Factor  
C = Cable Factor  
G = Amplifier Gain  
D = Distance Factor

Therefore, the equation for determining the Corrected Meter Reading Limit (CML) is:

$$\text{CML} = \text{Specification Limit} - F - C + G + D$$

For the manual mode of measurement, a table of corrected meter reading limits shall be used to permit immediate comparison of the meter reading to determine if the measured emission amplitude exceeded the specification limit at that specific frequency. There shall be two calculation sheets done, one for three meter and one for ten-meter measurement distances, where applicable. The correction factors for the antenna and the amplifier gain are attached in the Appendices.





AEGIS LABS INC.

## 6.0 Sample Calculations (Continued)

### Peak Transmit Power Output:

A correction factor for the cable must be applied to the Conducted Power before a true power reading can be obtained. This is referred to as the “Corrected Power” (CP).

The equation shall be derived in the following manner:

$$\text{Corrected Power Reading} = \text{Conducted Power Reading} + C$$

Where, C = Cable Factor

The conducted power is taken in units of dBm. To obtain units of mW the following equation is used:

$$\text{mW} = 10^{(\text{dBm}/10)}$$



AEGIS LABS INC.

## 7.0 MODIFICATIONS AND RECOMMENDATIONS

No modifications were made to the EUT.

*Page 18 of 18*  
*Report Number: INTEL-040412F*  
*FCC ID: PD9WM3B2915ABG*



AEGIS LABS INC.

## **APPENDIX A**

### ***TEST DATA***

*Page 1 of 73 (Appendix A)*  
*Report Number: INTEL-040412F*  
*FCC ID: PD9WM3B2915ABG*



AEGIS LABS INC.

## AC POWER LINE CONDUCTED EMISSIONS TEST RESULTS

<b>CLIENT:</b>	Intel Corporation	<b>DATE:</b>	06/11/04
<b>EUT:</b>	Intel PRO/Wireless 2915ABG Network Connection	<b>PROJECT NUMBER:</b>	INTEL-040412-149
<b>MODEL NUMBER:</b>	WM3B2915ABG	<b>TEST ENGINEER:</b>	JC
<b>SERIAL NUMBER:</b>	26E5FE224ABC51962011	<b>SITE #:</b>	2
<b>CONFIGURATION:</b>	Tested installed in the Hewlett Packard host computer's mini PCI slot.	<b>TEMPERATURE:</b>	19 C
		<b>HUMIDITY:</b>	63% RH
		<b>TIME:</b>	11:00 AM

<b>Standard:</b>	FCC CFR 47, Part 15.207
<b>Description:</b>	AC Power Line Conducted Emissions
<b>Results:</b>	Passes the conducted limits by -4.75@ 0.4947 MHz

Conducted Limits		
Frequency (MHz)	Quasi-Peak Limit (dBuV)	Average Limit (dBuV)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

NOTE: During preliminary scans, there wasn't any difference which mode, channel, or data rate was used with the EUT; therefore only 802.11b mode at Channel 1 with a data rate of 1 Mbps was used for final testing. Also, the scan was only done with the Ethertronics set of antennas.


Page 2 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

AC Power Line Conducted Emissions Test Results (Continued)

CONDUCTED EMISSIONS – LINE 1						
Freq. (MHz)	Meter Reading (dBuV)	Detector (PK/QP/AV)	Average Limit (dBuV)	Average Delta(dB)	Quasi-Peak Limit (dBuV)	Quasi-Peak Delta(dB)
0.1653	49.90	PK	55.56	-5.66	65.56	-15.66
0.2490	42.30	PK	53.17	-10.87	63.17	-20.87
0.4014	42.10	PK	48.82	-6.72	58.82	-16.72
1.0872	39.30	PK	46.00	-6.70	56.00	-16.70
1.8600	38.80	PK	46.00	-7.20	56.00	-17.20
14.8400	40.50	PK	50.00	-9.50	60.00	-19.50




Page 3 of 73 (Appendix A)  
 Report Number: INTEL-040412F  
 FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

### AC Power Line Conducted Emissions Test Results (Continued)

CONDUCTED EMISSIONS - LINE 2						
Freq. (MHz)	Meter Reading (dBuV)	Detector (PK/QP/AV)	Average Limit (dBuV)	Average Delta(dB)	Quasi-Peak Limit (dBuV)	Quasi-Peak Delta(dB)
0.1653	50.20	PK	55.56	-5.36	65.56	-15.36
0.2493	42.20	PK	53.16	-10.96	63.16	-20.96
0.3999	41.90	PK	48.86	-6.96	58.86	-16.96
0.4947	41.40	PK	46.15	-4.75	56.15	-14.75
1.8600	39.10	PK	46.00	-6.90	56.00	-16.90
15.2400	39.60	PK	50.00	-10.40	60.00	-20.40



Page 4 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

## SPURIOUS RADIATED EMISSIONS TEST RESULTS

<b>CLIENT:</b>	Intel Corporation	<b>DATE:</b>	06/10/04
<b>EUT:</b>	Intel PRO/Wireless 2915ABG Network Connection	<b>PROJECT NUMBER:</b>	INTEL-040412-147
<b>MODEL NUMBER:</b>	WM3B2915ABG	<b>TEST ENGINEER:</b>	JC
<b>SERIAL NUMBER:</b>	26E5FE224ABC51962011	<b>SITE #:</b>	2
<b>CONFIGURATION:</b>	Tested installed in the Hewlett Packard host computer's mini PCI slot.	<b>TEMPERATURE:</b>	17 C
		<b>HUMIDITY:</b>	57% RH
		<b>TIME:</b>	9:30 AM

<b>Standard:</b>	FCC Pt. 15.209
<b>Description:</b>	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in Sec. 15.209.
<b>Results:</b>	Passes the radiated limits by -1.17@ 96.01 MHz (Vertical antenna polarization)

Radiated Limits	
Frequency (MHz)	Quasi-Peak Limit (dBuV)
30-88	40
88-216	43.52
216-960	46.02
960-1000	54

NOTE: During preliminary scans, there wasn't any difference which mode, channel, or data rate was used with the EUT; therefore only 802.11b mode at Channel 1 with a data rate of 1 Mbps was used for final testing. Also, the scan was only done with the Ethertronics set of antennas.

Page 5 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

### Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Horizontal Antenna Polarization												
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	10 Meter Distance Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +/- FAIL
33.38	38.10	400	270			34.42	0.97	17.88	10.46	32.99	40.00	-7.01
66.62	44.20	350	270			34.40	1.33	7.14	10.46	28.74	40.00	-11.26
85.95	48.50	400	135			34.41	1.56	7.57	10.46	33.68	40.00	-6.32
96.01	53.40	400	90	51.75	Q	34.41	1.66	9.38	10.46	38.84	43.50	-4.66
99.59	51.30	400	270	50.81	Q	34.41	1.70	10.03	10.46	38.58	43.50	-4.92
133.35	37.60	350	180			34.34	1.95	14.43	10.46	30.10	43.50	-13.40
166.50	40.20	400	270			34.34	2.24	15.70	10.46	34.25	43.50	-9.25
200.26	35.80	400	270			34.31	2.40	17.00	10.46	31.36	43.50	-12.14
233.10	37.60	400	270			34.24	2.63	17.50	10.46	33.95	46.00	-12.05
267.05	40.20	350	90			34.21	2.84	18.59	10.46	37.88	46.00	-8.12
299.82	43.30	300	180			34.14	3.00	19.70	10.46	42.31	46.00	-3.69
329.37	40.90	250	135			34.11	3.18	14.99	10.46	35.42	46.00	-10.58
336.08	43.60	300	90			34.10	3.22	15.06	10.46	38.24	46.00	-7.76
343.30	41.60	300	90			34.09	3.26	15.13	10.46	36.36	46.00	-9.64
357.98	42.20	300	45			34.07	3.33	15.15	10.46	37.07	46.00	-8.93
366.49	49.90	300	45	48.17	Q	34.06	3.37	15.10	10.46	43.04	46.00	-2.96
384.08	48.70	200	225	47.63	Q	34.04	3.44	15.10	10.46	42.59	46.00	-3.41
430.06	39.40	200	270			33.96	3.62	16.22	10.46	35.74	46.00	-10.26
500.07	43.30	200	45			33.86	4.00	18.80	10.46	42.70	46.00	-3.30

NOTE: The measurements were taken at 10 meters and extrapolated to 3 meters.





AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

**RADIATED EMISSIONS - Vertical Antenna Polarization**

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	10 Meter Distance Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
33.34	38.50	100	315			34.42	0.97	17.46	10.46	32.97	40.00	-7.03
66.66	50.40	100	45			34.40	1.33	7.37	10.46	35.16	40.00	-4.84
85.95	53.00	100	315	52.82	Q	34.41	1.56	7.89	10.46	38.32	40.00	-1.68
96.01	53.70	100	270	52.00	Q	34.41	1.66	9.10	10.46	38.81	43.50	-4.69
99.49	53.30	100	270	51.81	Q	34.41	1.69	9.45	10.46	39.00	43.50	-4.50
133.55	48.60	100	45	47.39	Q	34.34	1.95	13.10	10.46	38.56	43.50	-4.94
166.70	40.50	100	90			34.34	2.24	15.40	10.46	34.26	43.50	-9.24
200.27	40.50	100	0			34.31	2.40	17.11	10.46	36.16	43.50	-7.34
232.57	36.10	100	315			34.24	2.63	18.19	10.46	33.14	46.00	-12.86
267.03	43.80	100	0			34.21	2.84	19.24	10.46	42.13	46.00	-3.87
299.82	42.50	100	315			34.14	3.00	20.59	10.46	42.41	46.00	-3.59
329.37	37.50	100	270			34.11	3.18	15.61	10.46	32.64	46.00	-13.36
336.06	43.80	100	0			34.10	3.22	15.54	10.46	38.91	46.00	-7.09
366.76	47.20	100	45			34.06	3.37	15.33	10.46	42.30	46.00	-3.70
384.01	44.20	100	45			34.04	3.44	15.66	10.46	39.72	46.00	-6.28
432.13	40.60	100	180			33.96	3.63	16.72	10.46	37.45	46.00	-8.55
500.09	41.50	100	90			33.86	4.00	18.70	10.46	40.80	46.00	-5.20

NOTE: The measurements were taken at 10 meters and extrapolated to 3 meters.



AEGIS LABS INC.

### Spurious Radiated Emissions Test Results (Continued)

<b>CLIENT:</b>	Intel Corporation	<b>DATE:</b>	06/03/04
<b>EUT:</b>	Intel PRO/Wireless 2915ABG Network Connection	<b>PROJECT NUMBER:</b>	INTEL-040412
<b>MODEL NUMBER:</b>	WM3B2915ABG	<b>TEST ENGINEER:</b>	JC
<b>SERIAL NUMBER:</b>	26E5FE224ABC51962011	<b>SITE #:</b>	2
<b>CONFIGURATION:</b>	Tested installed in the Hewlett Packard host computer's mini PCI slot in <b>802.11a (5725-5850 MHz) mode with the Ethertronics antennas.</b>	<b>TEMPERATURE:</b>	32 C
		<b>HUMIDITY:</b>	37% RH
		<b>TIME:</b>	4:30 PM

<b>Standard:</b>	FCC CFR 47, Part 15.247(c)
<b>Description:</b>	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.
<b>Results:</b>	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	< -20 dBc

Page 8 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



Spurious Radiated Emissions Test Results (Continued)

*Fundamental Measurements in 802.11a mode (5725-5850 MHz)*  
*Channels 149, 157, & 169*  
*Continuous TX at MAIN Antenna port with Ethertronics Antennas*  
*Aegis Labs, Inc. File #: INTEL-040412-136*

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
5745.00	62.67	100	225				5.25	34.85	102.76		
5745.00				52.37	A		5.25	34.85	92.46		
5785.00	63.00	100	225				5.27	34.87	103.14		
5785.00				52.69	A		5.27	34.87	92.83		
5825.00	63.17	100	225				5.30	34.90	103.37		
5825.00				52.99	A		5.30	34.90	93.19		

<b>RADIATED EMISSIONS – Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
5745.00	66.83	100	180				5.25	34.85	106.92		
5745.00				56.35	A		5.25	34.85	96.44		
5785.00	67.00	100	135				5.27	34.87	107.14		
5785.00				56.39	A		5.27	34.87	96.53		
5825.00	66.33	100	135				5.30	34.90	106.53		
5825.00				56.08	A		5.30	34.90	96.28		



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

**Band Edge Field Strength Measurements in 802.11a mode (5725-5850 MHz)**  
**Channels 149, 157, & 169**  
**Continuous TX at MAIN Antenna port with Ethertronics Antennas**  
**Aegis Labs, Inc. File #: INTEL-040412-136**

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>	<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>	
5725.00	36.33	100	225				5.23	34.84	76.40	82.76	-6.37
5850.00	31.50	100	225				5.32	34.91	71.73	83.37	-11.64



<b>RADIATED EMISSIONS – Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>	<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>	
5725.00	43.33	100	180				5.23	34.84	83.40	86.92	-3.53
5850.00	34.00	100	135				5.32	34.91	74.23	86.53	-12.30



AEGIS LABS inc.

## Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)





Page 11 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



### Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)





Spurious Radiated Emissions Test Results (Continued)

*Spurious Emissions Measurements in 802.11a mode (5725-5850 MHz)  
Channels 149, 157, & 169  
Continuous TX at MAIN Antenna port with Ethertronics Antennas  
Aegis Labs, Inc. File #: INTEL-040412-138*

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +/-FAIL</i>
<b>EUT in Continuous Transmit Mode on Channel 149 (5.745 GHz)</b>											
3830.00	55.17	100	225			43.17	4.18	31.16	47.34	74.00	-26.66
3830.00				50.41	A	43.17	4.18	31.16	42.58	54.00	-11.42
7660.00	53.67	100	135			43.62	6.27	40.05	56.37	74.00	-17.63
7660.00				47.19	A	43.62	6.27	40.05	49.89	54.00	-4.11
11490.00	51.00	100	135			43.50	7.64	41.18	56.32	74.00	-17.68
11490.00				39.59	A	43.50	7.64	41.18	44.91	54.00	-9.09
15319.89	51.00	100	180			43.39	8.80	41.49	57.90	68.00	-10.10
<b>EUT in Continuous Transmit Mode on Channel 157 (5.785 GHz)</b>											
3856.66	56.17	100	135			43.17	4.21	31.23	48.43	74.00	-25.57
3856.66				51.32	A	43.17	4.21	31.23	43.58	54.00	-10.42
7713.33	54.33	100	135			43.60	6.29	40.20	57.22	74.00	-16.78
7713.33				48.04	A	43.60	6.29	40.20	50.93	54.00	-3.07
11569.98	51.00	100	135			43.48	7.66	41.38	56.57	74.00	-17.43
11569.98				39.60	A	43.48	7.66	41.38	45.17	54.00	-8.83
15426.58	49.83	100	180			43.35	8.80	41.56	56.84	74.00	-17.16
15426.58				38.73		43.35	8.80	41.56	45.74	54.00	-8.26
<b>EUT in Continuous Transmit Mode on Channel 165 (5.825 GHz)</b>											
3883.34	57.50	100	135			43.17	4.23	31.30	49.85	74.00	-24.15
3883.34				53.96	A	43.17	4.23	31.30	46.31	54.00	-7.69
7766.66	54.67	100	135			43.58	6.32	40.35	57.75	68.00	-10.25
11650.00	50.33	100	135			43.45	7.69	41.59	56.16	74.00	-17.84
11650.00				38.75	A	43.45	7.69	41.59	44.58	54.00	-9.42
15533.23	50.17	100	180			43.35	8.82	41.71	57.35	74.00	-16.65
15533.23				39.01	A	43.35	8.82	41.71	46.19	54.00	-7.81



Spurious Radiated Emissions Test Results (Continued)

<b>RADIATED EMISSIONS - Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
<b>EUT in Continuous Transmit Mode on Channel 149 (5.745 GHz)</b>											
3830.00	57.67	100	135			43.17	4.18	31.09	49.78	74.00	-24.22
3830.00				54.17	A	43.17	4.18	31.09	46.28	54.00	-7.72
7660.00	51.00	100	135			43.62	6.27	40.11	53.77	74.00	-20.23
7660.00				41.78	A	43.62	6.27	40.11	44.55	54.00	-9.45
11490.00	50.67	100	135			43.50	7.64	41.66	56.47	74.00	-17.53
11490.00				39.70	A	43.50	7.64	41.66	45.50	54.00	-8.50
<b>EUT in Continuous Transmit Mode on Channel 157 (5.785 GHz)</b>											
3856.66	60.33	100	180			43.17	4.21	31.14	52.51	74.00	-21.49
3856.66				57.71	A	43.17	4.21	31.14	49.89	54.00	-4.11
7713.33	52.17	100	135			43.60	6.29	40.28	55.15	74.00	-18.85
7713.33				43.90	A	43.60	6.29	40.28	46.88	54.00	-7.12
11569.98	50.17	100	135			43.48	7.66	41.81	56.17	74.00	-17.83
11569.98				39.22	A	43.48	7.66	41.81	45.22	54.00	-8.78
<b>EUT in Continuous Transmit Mode on Channel 165 (5.825 GHz)</b>											
3883.33	62.33	100	135			43.17	4.23	31.19	54.58	74.00	-19.42
3883.33				60.22	A	43.17	4.23	31.19	52.47	54.00	-1.53
7766.66	53.33	100	135			43.58	6.32	40.45	56.52	68.00	-11.48
11650.00	50.00	100	135			43.45	7.69	41.94	56.18	74.00	-17.82
11650.00				38.44	A	43.45	7.69	41.94	44.62	54.00	-9.38





AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

*Spurious Emissions Measurements in 802.11a mode (5725-5850 MHz)  
Channels 149, 157, & 169  
Continuous RX at MAIN Antenna port with Ethertronics Antennas  
Aegis Labs, Inc. File #: INTEL-040412-138*

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
<b>EUT in Continuous Receive Mode on Channel 149 (5.745 GHz)</b>											
3829.97	52.67	100	135			43.17	4.18	31.16	44.84	80.00	-35.16
3829.97				46.35	A	43.17	4.18	31.16	38.52	60.00	-21.48
7659.91	53.17	100	135			43.62	6.27	40.05	55.87	80.00	-24.13
7659.91				45.84	A	43.62	6.27	40.05	48.54	60.00	-11.46
11489.92	50.00	100	135			43.50	7.64	41.18	55.32	80.00	-24.68
11489.92				38.44	A	43.50	7.64	41.18	43.76	60.00	-16.24
<b>EUT in Continuous Receive Mode on Channel 157 (5.785 GHz)</b>											
3856.62	53.33	100	135			43.17	4.21	31.23	45.59	80.00	-34.41
3856.62				46.64	A	43.17	4.21	31.23	38.90	60.00	-21.10
7713.32	53.83	125	135			43.60	6.29	40.20	56.72	80.00	-23.28
7713.32				46.79	A	43.60	6.29	40.20	49.68	60.00	-10.32
11569.92	50.00	150	135			43.48	7.66	41.38	55.57	80.00	-24.43
11569.92				39.11	A	43.48	7.66	41.38	44.68	60.00	-15.32
<b>EUT in Continuous Receive Mode on Channel 165 (5.825 GHz)</b>											
3883.34	52.83	100	135			43.17	4.23	31.30	45.18	80.00	-34.82
3883.34				45.78	A	43.17	4.23	31.30	38.13	60.00	-21.87
7766.62	53.17	125	135			43.58	6.32	40.35	56.25	80.00	-23.75
7766.62				46.50	A	43.58	6.32	40.35	49.58	60.00	-10.42
11649.94	49.83	100	135			43.45	7.69	41.59	55.66	80.00	-24.34
11649.94				39.79	A	43.45	7.69	41.59	45.62	60.00	-14.38



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

<b>RADIATED EMISSIONS - Vertical Antenna Polarization</b>											
<i>Freq.</i> (MHz)	<i>Meter</i> <i>Reading</i> (dBuV)	<i>Antenna</i> <i>Height</i> (cm)	<i>Azimuth</i> (degrees)	<i>Quasi pk or</i> <i>AVG (dBuV)</i>		<i>Preamp</i> <i>Factor</i> (dB)	<i>Cable</i> <i>Factor</i> (dB)	<i>Ant.</i> <i>Factor</i> (dB)	<i>Corrected</i> <i>Reading</i> (dBuV)	<i>Limits</i> (dBuV)	<i>Diff (dB)</i> +=FAIL
<b>EUT in Continuous Receive Mode on Channel 149 (5.745 GHz)</b>											
3830.01	51.50	100	135			43.17	4.18	31.09	43.61	80.00	-36.39
3830.01				42.29	A	43.17	4.18	31.09	34.40	60.00	-25.60
7660.02	51.17	100	135			43.62	6.27	40.11	53.94	80.00	-26.06
7660.02				41.06	A	43.62	6.27	40.11	43.83	60.00	-16.17
11489.96	50.50	100	135			43.50	7.64	41.66	56.30	80.00	-23.70
11489.96				40.07	A	43.50	7.64	41.66	45.87	60.00	-14.13
<b>EUT in Continuous Receive Mode on Channel 157 (5.785 GHz)</b>											
3856.65	51.67	100	135			43.17	4.21	31.14	43.85	80.00	-36.15
3856.65				43.01	A	43.17	4.21	31.14	35.19	60.00	-24.81
7713.29	51.33	125	135			43.60	6.29	40.28	54.31	80.00	-25.69
7713.29				42.68	A	43.60	6.29	40.28	45.66	60.00	-14.34
11569.91	50.83	100	135			43.48	7.66	41.81	56.83	80.00	-23.17
11569.91				40.98	A	43.48	7.66	41.81	46.98	60.00	-13.02
<b>EUT in Continuous Receive Mode on Channel 165 (5.825 GHz)</b>											
3883.35	50.67	100	135			43.17	4.23	31.19	42.92	80.00	-37.08
3883.35				41.65	A	43.17	4.23	31.19	33.90	60.00	-26.10
7766.63	50.50	100	135			43.58	6.32	40.45	53.69	80.00	-26.31
7766.63				40.89	A	43.58	6.32	40.45	44.08	60.00	-15.92
11649.97	50.00	125	135			43.45	7.69	41.94	56.18	80.00	-23.82
11649.97				39.96	A	43.45	7.69	41.94	46.14	60.00	-13.86



AEGIS LABS INC.

### Spurious Radiated Emissions Test Results (Continued)

<b>CLIENT:</b>	Intel Corporation	<b>DATE:</b>	06/03/04
<b>EUT:</b>	Intel PRO/Wireless 2915ABG Network Connection	<b>PROJECT NUMBER:</b>	INTEL-040412
<b>MODEL NUMBER:</b>	WM3B2915ABG	<b>TEST ENGINEER:</b>	JC
<b>SERIAL NUMBER:</b>	26E5FE224ABC51962011	<b>SITE #:</b>	2
<b>CONFIGURATION:</b>	Tested installed in the Hewlett Packard host computer's mini PCI slot in <b>802.11b mode (2400-2483.5 MHz with the Ethertronics antennas.</b>	<b>TEMPERATURE:</b>	32 C
		<b>HUMIDITY:</b>	37% RH
		<b>TIME:</b>	4:30 PM

<b>Standard:</b>	FCC CFR 47, Part 15.247(c)
<b>Description:</b>	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.
<b>Results:</b>	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	< -20 dBc

Page 17 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



Spurious Radiated Emissions Test Results (Continued)

*Fundamental Measurements in 802.11b mode (2400-2483.5 MHz)*  
*Channels 1, 6, & 11*  
*Continuous TX at MAIN Antenna port with Ethertronics Antennas*  
*Aegis Labs, Inc. File #: INTEL-040412-136*

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
2412.00	76.67	125	225				3.30	31.11	111.08		
2412.00				73.01	A		3.30	31.11	107.42		
2437.00	78.00	100	225				3.32	31.05	112.37		
2437.00				74.50	A		3.32	31.05	108.87		
2462.00	78.67	100	225				3.34	30.99	113.00		
2462.00				74.65	A		3.34	30.99	108.98		

<b>RADIATED EMISSIONS – Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
2412.00	74.67	200	225				3.30	31.24	109.21		
2412.00				70.89	A		3.30	31.24	105.43		
2437.00	74.50	200	225				3.32	31.20	109.02		
2437.00				71.73	A		3.32	31.20	106.25		
2462.00	74.50	200	225				3.34	31.16	109.00		
2462.00				71.29	A		3.34	31.16	105.79		



Spurious Radiated Emissions Test Results (Continued)

**Band Edge Field Strength Measurements in 802.11b mode (2400-2483.5 MHz)**  
**Channels 1, 6, & 11**  
**Continuous TX at MAIN Antenna port with Ethertronics Antennas**  
**Aegis Labs, Inc. File #: INTEL-040412-136**

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
2390.00									56.58	74.00	-17.42
2390.00									44.76	54.00	-9.24
2386.80									58.25	74.00	-15.75
2386.80									46.26	54.00	-7.74
2400.00	42.17	125	225				3.29	31.14	76.60	91.08	-14.48
2483.50									59.50	74.00	-14.50
2483.50									49.48	54.00	-4.52
2489.00									61.83	74.00	-12.17
2489.00									50.65	54.00	-3.35



<b>RADIATED EMISSIONS - Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
2390.00									54.71	74.00	-19.29
2390.00									42.77	54.00	-11.23
2386.80									56.38	74.00	-17.62
2386.80									44.27	54.00	-9.73
2400.00	40.50	200	225				3.29	31.26	75.05	89.21	-14.16
2483.50									55.50	74.00	-18.50
2483.50									46.29	54.00	-7.71
2489.00									57.83	74.00	-16.17
2489.00									47.46	54.00	-6.54



AEGIS LABS INC.

### Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)





Page 20 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



### Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)





Spurious Radiated Emissions Test Results (Continued)

*Spurious Emissions Measurements in 802.11b mode (2400-2483.5 MHz)  
Channels 1, 6, & 11  
Continuous TX at MAIN Antenna port with Ethertronics Antennas  
Aegis Labs, Inc. File #: INTEL-040412-137*

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
<b>EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)</b>											
2312.00	31.67	100	225			9.54	3.23	31.35	56.71	74.00	-17.29
2312.00				17.98	A	9.54	3.23	31.35	43.02	54.00	-10.98
<b>EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)</b>											
2336.00	32.17	100	225			9.54	3.25	31.29	57.17	74.00	-16.83
2336.00				19.28	A	9.54	3.25	31.29	44.28	54.00	-9.72
<b>EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)</b>											
2358.66	32.00	100	225			9.54	3.26	31.24	56.96	74.00	-17.04
2358.66				16.96	A	9.54	3.26	31.24	41.92	54.00	-12.08
<b>RADIATED EMISSIONS - Vertical Antenna Polarization</b>											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
<b>EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)</b>											
2312.00	30.83	100	225			9.54	3.23	31.40	55.92	74.00	-18.08
2312.00				16.76	A	9.54	3.23	31.40	41.85	54.00	-12.15
<b>EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)</b>											
2336.00	31.67	100	225			9.54	3.25	31.36	56.74	74.00	-17.26
2336.00				16.22	A	9.54	3.25	31.36	41.29	54.00	-12.71
<b>EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)</b>											
2358.66	30.83	100	225			9.54	3.26	31.33	55.88	74.00	-18.12
2358.66				15.10	A	9.54	3.26	31.33	40.15	54.00	-13.85

NOTE: These spurious emissions measurements were taken without a preamp at a distance on 1 meter to avoid saturating the preamp and analyzer because the signals were close to the fundamental frequency. The readings were extrapolated to 1 meter.





Spurious Radiated Emissions Test Results (Continued)

*Spurious Emissions Measurements in 802.11b mode (2400-2483.5 MHz)  
 Channels 1, 6, & 11  
 Continuous TX at MAIN Antenna port with Ethertronics Antennas  
 Aegis Labs, Inc. File #: INTEL-040412-138*

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
<b>EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)</b>											
3216.01	53.50	100	225			43.07	3.89	30.24	44.56	91.08	-46.52
4824.00	56.33	100	135			43.27	4.73	34.53	52.32	74.00	-21.68
4824.00				52.24	A	43.27	4.73	34.53	48.23	54.00	-5.77
6431.97	58.00	100	135			43.82	5.73	36.64	56.56	91.08	-34.52
9648.01	52.67	100	135			43.22	6.95	38.88	55.28	91.08	-35.80
12864.03	49.83	100	225			43.83	7.95	43.86	57.82	91.08	-33.26
<b>EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)</b>											
3249.32	52.83	100	225			43.08	3.91	30.25	43.90	92.37	-48.47
4873.99	59.50	100	135			43.29	4.77	34.72	55.70	74.00	-18.30
4873.99				56.64	A	43.29	4.77	34.72	52.84	54.00	-1.16
6498.69	62.00	100	135			43.84	5.78	36.90	60.83	92.37	-31.54
9747.96	54.33	100	135			43.25	6.99	39.00	57.06	92.37	-35.31
12997.37	49.83	100	225			43.83	8.02	44.29	58.31	92.37	-34.06
<b>EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)</b>											
3282.69	52.00	100	225			43.10	3.91	30.26	43.07	93.00	-49.93
4924.00	55.00	150	135			43.30	4.81	34.91	51.41	74.00	-22.59
4924.00				48.96	A	43.30	4.81	34.91	45.37	54.00	-8.63
6565.34	60.83	100	135			43.84	5.83	37.32	60.14	93.00	-32.86
9848.01	52.67	100	135			43.29	7.03	39.12	55.53	93.00	-37.47
13130.67	50.17	100	225			43.70	8.07	44.25	58.79	93.00	-34.21



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

<b>RADIATED EMISSIONS - Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
<b>EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)</b>											
3216.00	51.83	100	135			43.07	3.89	30.44	43.09	89.21	-46.12
4823.96	57.00	100	225			43.27	4.73	34.53	52.99	74.00	-21.01
4823.96				52.63	A	43.27	4.73	34.53	48.62	54.00	-5.38
6431.95	56.50	100	135			43.82	5.73	36.64	55.06	89.21	-34.15
9647.97	52.83	100	135			43.22	6.95	38.97	55.53	89.21	-33.68
12864.01	49.50	100	135			43.83	7.95	44.23	57.85	89.21	-31.36
<b>EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)</b>											
3249.32	49.67	100	135			43.08	3.91	30.45	40.94	89.02	-48.08
4874.01	58.50	100	225			43.29	4.77	34.72	54.70	74.00	-19.30
4874.01				55.23	A	43.29	4.77	34.72	51.43	54.00	-2.57
6498.66	58.33	100	135			43.84	5.78	36.89	57.16	89.02	-31.86
9748.04	54.83	100	135			43.25	6.99	39.15	57.71	89.02	-31.31
12997.35	49.83	100	135			43.83	8.02	44.49	58.51	89.02	-30.51
<b>EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)</b>											
3282.66	50.33	100	135			43.10	3.91	30.46	41.60	89.00	-47.40
4924.00	54.17	100	225			43.30	4.81	34.91	50.58	74.00	-23.42
4924.00				49.54	A	43.30	4.81	34.91	45.95	54.00	-8.05
6565.32	56.50	100	135			43.84	5.83	37.38	55.87	89.00	-33.13
9847.96	51.00	100	135			43.29	7.03	39.33	54.07	89.00	-34.93
13130.63	49.83	100	135			43.70	8.07	44.45	58.65	89.00	-30.35



Spurious Radiated Emissions Test Results (Continued)

*Spurious Emissions Measurements in in802.11b mode (2400-2483.5 MHz)  
 Channels 1, 6, & 11  
 Continuous RX at MAIN Antenna port with Ethertronics Antennas  
 Aegis Labs, Inc. File #: INTEL-040412-138*

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
<b>EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)</b>											
3216.02	53.17	100	225			43.07	3.89	30.24	44.23	80.00	-35.77
3216.02				47.67	A	43.07	3.89	30.24	38.73	60.00	-21.27
6432.00	58.50	100	135			43.82	5.73	36.64	57.06	80.00	-22.94
6432.00				56.10	A	43.82	5.73	36.64	54.66	60.00	-5.34
9648.03	50.83	100	135			43.22	6.95	38.88	53.44	80.00	-26.56
9648.03				40.19	A	43.22	6.95	38.88	42.80	60.00	-17.20
<b>EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)</b>											
3249.32	52.67	100	225			43.08	3.91	30.25	43.74	80.00	-36.26
3249.32				47.59	A	43.08	3.91	30.25	38.66	60.00	-21.34
6498.70	60.17	100	135			43.84	5.78	36.90	59.00	80.00	-21.00
6498.70				57.63	A	43.84	5.78	36.90	56.46	60.00	-3.54
9747.99	51.00	100	135			43.25	6.99	39.00	53.73	80.00	-26.27
9747.99				40.24	A	43.25	6.99	39.00	42.97	60.00	-17.03
<b>EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)</b>											
3282.66	53.00	100	225			43.10	3.91	30.26	44.07	80.00	-35.93
3282.66				47.15	A	43.10	3.91	30.26	38.22	60.00	-21.78
6565.32	60.67	100	135			43.84	5.83	37.32	59.98	80.00	-20.02
6565.32				58.56	A	43.84	5.83	37.32	57.87	60.00	-2.13
9848.01	50.67	100	135			43.29	7.03	39.12	53.53	80.00	-26.47
9848.01				39.59	A	43.29	7.03	39.12	42.45	60.00	-17.55



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

<b>RADIATED EMISSIONS - Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
<b>EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)</b>											
3216.00	50.50	150	225			43.07	3.89	30.44	41.76	80.00	-38.24
3216.00				43.45	A	43.07	3.89	30.44	34.71	60.00	-25.29
6432.03	55.67	100	135			43.82	5.73	36.64	54.23	80.00	-25.77
6432.03				51.46	A	43.82	5.73	36.64	50.02	60.00	-9.98
9648.02	50.33	125	135			43.22	6.95	38.97	53.03	80.00	-26.97
9648.02				39.39	A	43.22	6.95	38.97	42.09	60.00	-17.91
<b>EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)</b>											
3249.32	49.33	125	225			43.08	3.91	30.45	40.60	80.00	-39.40
3249.32				39.93	A	43.08	3.91	30.45	31.20	60.00	-28.80
6498.67	58.00	100	135			43.84	5.78	36.89	56.83	80.00	-23.17
6498.67				54.78	A	43.84	5.78	36.89	53.61	60.00	-6.39
9747.96	50.83	125	135			43.25	6.99	39.15	53.71	80.00	-26.29
9747.96				40.54	A	43.25	6.99	39.15	43.42	60.00	-16.58
<b>EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)</b>											
3282.67	50.67	125	225			43.10	3.91	30.46	41.94	80.00	-38.06
3282.67				41.40	A	43.10	3.91	30.46	32.67	60.00	-27.33
6565.37	57.33	100	135			43.84	5.83	37.38	56.70	80.00	-23.30
6565.37				54.15	A	43.84	5.83	37.38	53.52	60.00	-6.48
9847.98	50.50	125	135			43.29	7.03	39.33	53.57	80.00	-26.43
9847.98				39.50	A	43.29	7.03	39.33	42.57	60.00	-17.43



AEGIS LABS INC.

### Spurious Radiated Emissions Test Results (Continued)

<b>CLIENT:</b>	Intel Corporation	<b>DATE:</b>	06/03/04
<b>EUT:</b>	Intel PRO/Wireless 2915ABG Network Connection	<b>PROJECT NUMBER:</b>	INTEL-040412
<b>MODEL NUMBER:</b>	WM3B2915ABG	<b>TEST ENGINEER:</b>	JC
<b>SERIAL NUMBER:</b>	26E5FE224ABC51962011	<b>SITE #:</b>	2
<b>CONFIGURATION:</b>	Tested installed in the Hewlett Packard host computer's mini PCI slot in <b>802.11g mode (2400-2483.5 MHz with the Ethertronics antennas.</b>	<b>TEMPERATURE:</b>	32 C
		<b>HUMIDITY:</b>	37% RH
		<b>TIME:</b>	4:30 PM

<b>Standard:</b>	FCC CFR 47, Part 15.247(c)
<b>Description:</b>	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.
<b>Results:</b>	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	< -20 dBc

Page 27 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



Spurious Radiated Emissions Test Results (Continued)

*Fundamental Measurements in 802.11g mode (2400-2483.5 MHz)  
Channels 1, 6, & 11  
Continuous TX at MAIN Antenna port with Ethertronics Antennas  
Aegis Labs, Inc. File #: INTEL-040412-136*

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
2412.00	78.17	100	225				3.30	31.11	112.58		
2412.00				68.08	A		3.30	31.11	102.49		
2437.00	79.17	100	225				3.32	31.05	113.54		
2437.00				68.86	A		3.32	31.05	103.23		
2462.00	78.17	100	225				3.34	30.99	112.50		
2462.00				67.92	A		3.34	30.99	102.25		

<b>RADIATED EMISSIONS – Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
2412.00	76.67	200	225				3.30	31.24	111.21		
2412.00				65.72	A		3.30	31.24	100.26		
2437.00	76.67	200	225				3.32	31.20	111.19		
2437.00				66.35	A		3.32	31.20	100.87		
2462.00	74.83	200	225				3.34	31.16	109.33		
2462.00				64.25	A		3.34	31.16	98.75		



Spurious Radiated Emissions Test Results (Continued)

*Band Edge Field Strength Measurements in 802.11g mode (2400-2483.5 MHz)  
 Channels 1, 6, & 11  
 Continuous TX at MAIN Antenna port with Ethertronics Antennas  
 Aegis Labs, Inc. File #: INTEL-040412-136*



<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
2390.00									66.41	74.00	-7.59
2390.00									51.32	54.00	-2.68
2400.00	54.17	100	225				3.29	31.14	88.60	92.58	-3.98
2483.50									69.33	74.00	-4.67
2483.50									52.59	54.00	-1.41

<b>RADIATED EMISSIONS – Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
2390.00									65.04	74.00	-8.96
2390.00									49.09	54.00	-4.91
2400.00	51.33	200	225				3.29	31.26	85.88	91.21	-5.33
2483.50									66.16	74.00	-7.84
2483.50									49.09	54.00	-4.91



### Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)







AEGIS LABS INC.

### Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)

<i>Test Date</i>	<i>Data</i>	<i>Test Eng.</i>
06/03/04	2.462 GHz band edge <b>PEAK DELTA</b> (INTEL-040412-139c25)	JC
<p>*ATTEN 30dB    ΔMKR 43.17dB  RL 20.0dBm    10dB/    -26.0MHz</p> <p>CENTER 2.4835GHz    SPAN 100.0MHz  *RBW 1.0MHz    *VBW 1.0MHz    SWP 50.0ms</p>		
<i>Test Date</i>	<i>Data</i>	<i>Test Eng.</i>
06/03/04	2.462 GHz band edge <b>AVERAGE DELTA</b> (INTEL-040412-139c26)	JC
<p>*ATTEN 30dB    ΔMKR 49.66dB  RL 20.0dBm    10dB/    -23.2MHz</p> <p>CENTER 2.4835GHz    SPAN 100.0MHz  *RBW 1.0MHz    *VBW 10Hz    SWP 37.0sec</p>		

Page 31 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



Spurious Radiated Emissions Test Results (Continued)

*Spurious Emissions Measurements in 802.11g mode (2400-2483.5 MHz)  
Channels 1, 6, & 11  
Continuous TX at MAIN Antenna port with Ethertronics Antennas  
Aegis Labs, Inc. File #: INTEL-040412-137*

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>1 Meter Distance Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
<b>EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)</b>											
2312.00	33.33	100	225			9.54	3.23	31.35	58.37	74.00	-15.63
2312.00				23.32	A	9.54	3.23	31.35	48.36	54.00	-5.64
<b>EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)</b>											
2336.00	34.33	100	225			9.54	3.25	31.29	59.33	74.00	-14.67
2336.00				25.35	A	9.54	3.25	31.29	50.35	54.00	-3.65
<b>EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)</b>											
2358.68	33.17	100	225			9.54	3.26	31.24	58.13	74.00	-15.87
2358.68				22.64	A	9.54	3.26	31.24	47.60	54.00	-6.40
<b>RADIATED EMISSIONS - Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>1 Meter Distance Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
<b>EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)</b>											
2312.00	32.50	100	225			9.54	3.23	31.40	57.59	74.00	-16.41
2312.00				20.24	A	9.54	3.23	31.40	45.33	54.00	-8.67
<b>EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)</b>											
2336.00	32.83	100	225			9.54	3.25	31.36	57.90	74.00	-16.10
2336.00				20.92	A	9.54	3.25	31.36	45.99	54.00	-8.01
<b>EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)</b>											
2358.68	32.17	100	225			9.54	3.26	31.33	57.22	74.00	-16.78
2358.68				18.79	A	9.54	3.26	31.33	43.84	54.00	-10.16

NOTE: These spurious emissions measurements were taken without a preamp at a distance on 1 meter to avoid saturating the preamp and analyzer because the signals were close to the fundamental frequency. The readings were extrapolated to 1 meter.



Spurious Radiated Emissions Test Results (Continued)

*Spurious Emissions Measurements in 802.11g mode (2400-2483.5 MHz)  
Channels 1, 6, & 11  
Continuous TX at MAIN Antenna port with Ethertronics Antennas  
Aegis Labs, Inc. File #: INTEL-040412-138*

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamplifier Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +/- FAIL</i>
<b>EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)</b>											
3216.00	52.17	100	225			43.07	3.89	30.24	43.23	92.58	-49.35
4824.20	53.83	100	135			43.27	4.73	34.53	49.83	74.00	-24.17
4824.20				42.39	A	43.27	4.73	34.53	38.39	54.00	-15.61
6432.05	58.50	100	135			43.82	5.73	36.64	57.06	92.58	-35.52
9647.97	50.83	100	135			43.22	6.95	38.88	53.44	92.58	-39.14
12864.05	50.17	100	135			43.83	7.95	43.86	58.16	92.58	-34.42
<b>EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)</b>											
3249.37	53.67	100	225			43.08	3.91	30.25	44.74	93.54	-48.80
4874.06	54.00	100	135			43.29	4.77	34.72	50.20	74.00	-23.80
4874.06				42.44	A	43.29	4.77	34.72	38.64	54.00	-15.36
6498.69	62.00	100	135			43.84	5.78	36.90	60.83	93.54	-32.71
9748.09	50.83	100	135			43.25	6.99	39.00	53.56	93.54	-39.98
12997.35	49.67	100	135			43.83	8.02	44.29	58.15	93.54	-35.39
<b>EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)</b>											
3282.68	52.67	100	225			43.10	3.91	30.26	43.74	92.83	-49.09
4923.82	52.33	100	135			43.30	4.81	34.91	48.74	74.00	-25.26
4923.82				41.40	A	43.30	4.81	34.91	37.81	54.00	-16.19
6565.42	61.33	100	135			43.84	5.83	37.32	60.64	92.83	-32.19
9847.97	50.17	100	135			43.29	7.03	39.12	53.03	92.83	-39.80
13130.70	49.83	100	135			43.70	8.07	44.25	58.45	92.83	-34.38



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

<b>RADIATED EMISSIONS - Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
<b>EUT in Continuous Transmit Mode on Channel 1 (2.412 GHz)</b>											
3216.01	50.33	100	135			43.07	3.89	30.44	41.59	91.21	-49.62
4823.97	55.67	100	225			43.27	4.73	34.53	51.66	74.00	-22.34
4823.97				42.57	A	43.27	4.73	34.53	38.56	54.00	-15.44
6431.99	55.83	100	135			43.82	5.73	36.64	54.39	91.21	-36.82
9648.08	51.00	100	135			43.22	6.95	38.97	53.70	91.21	-37.51
12863.98	50.17	100	135			43.83	7.95	44.23	58.52	91.21	-32.69
<b>EUT in Continuous Transmit Mode on Channel 6 (2.437 GHz)</b>											
3249.35	51.67	100	135			43.08	3.91	30.45	42.94	91.19	-48.25
4874.03	53.00	100	225			43.29	4.77	34.72	49.20	74.00	-24.80
4874.03				40.99	A	43.29	4.77	34.72	37.19	54.00	-16.81
6498.67	58.17	100	135			43.84	5.78	36.89	57.00	91.19	-34.19
9748.00	51.17	100	135			43.25	6.99	39.15	54.05	91.19	-37.14
12997.35	50.00	100	135			43.83	8.02	44.49	58.68	91.19	-32.51
<b>EUT in Continuous Transmit Mode on Channel 11 (2.462 GHz)</b>											
3282.65	50.83	100	135			43.10	3.91	30.46	42.10	90.33	-48.23
4924.01	51.67	100	135			43.30	4.81	34.91	48.08	74.00	-25.92
4924.01				40.68	A	43.30	4.81	34.91	37.09	54.00	-16.91
6565.34	56.33	100	135			43.84	5.83	37.38	55.70	90.33	-34.63
9848.03	50.50	100	135			43.29	7.03	39.33	53.57	90.33	-36.76
13130.62	49.67	100	135			43.70	8.07	44.45	58.49	90.33	-31.84



Spurious Radiated Emissions Test Results (Continued)

*Spurious Emissions Measurements in 802.11g mode (2400-2483.5 MHz)  
Channels 1, 6, & 11  
Continuous RX at MAIN Antenna port with Ethertronics Antennas  
Aegis Labs, Inc. File #: INTEL-040412-138*

<b>RADIATED EMISSIONS - Horizontal Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
<b>EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)</b>											
3215.99	53.00	100	225			43.07	3.89	30.24	44.06	80.00	-35.94
3215.99				47.01	A	43.07	3.89	30.24	38.07	60.00	-21.93
6431.98	59.33	100	135			43.82	5.73	36.64	57.89	80.00	-22.11
6431.98				56.44	A	43.82	5.73	36.64	55.00	60.00	-5.00
9647.99	51.00	100	135			43.22	6.95	38.88	53.61	80.00	-26.39
9647.99				40.02	A	43.22	6.95	38.88	42.63	60.00	-17.37
<b>EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)</b>											
3249.32	52.50	100	225			43.08	3.91	30.25	43.57	80.00	-36.43
3249.32				45.84	A	43.08	3.91	30.25	36.91	60.00	-23.09
6498.67	60.83	100	135			43.84	5.78	36.89	59.66	80.00	-20.34
6498.67				58.52	A	43.84	5.78	36.89	57.35	60.00	-2.65
9748.03	50.17	100	135			43.25	6.99	39.00	52.90	80.00	-27.10
9748.03				39.32	A	43.25	6.99	39.00	42.05	60.00	-17.95
<b>EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)</b>											
3282.66	52.67	100	225			43.10	3.91	30.26	43.74	80.00	-36.26
3282.66				45.99	A	43.10	3.91	30.26	37.06	60.00	-22.94
6565.32	60.33	100	135			43.84	5.83	37.32	59.64	80.00	-20.36
6565.32				58.20	A	43.84	5.83	37.32	57.51	60.00	-2.49
9848.03	50.67	100	135			43.29	7.03	39.12	53.53	80.00	-26.47
9848.03				39.86	A	43.29	7.03	39.12	42.72	60.00	-17.28



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

<b>RADIATED EMISSIONS - Vertical Antenna Polarization</b>											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Preamp Factor (dB)</i>	<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
<b>EUT in Continuous Receive Mode on Channel 1 (2.412 GHz)</b>											
3216.00	50.83	150	225			43.07	3.89	30.44	42.09	80.00	-37.91
3216.00				43.21	A	43.07	3.89	30.44	34.47	60.00	-25.53
6432.00	55.83	100	135			43.82	5.73	36.64	54.39	80.00	-25.61
6432.00				52.01	A	43.82	5.73	36.64	50.57	60.00	-9.43
9648.00	50.50	125	135			43.22	6.95	38.97	53.20	80.00	-26.80
9648.00				39.44	A	43.22	6.95	38.97	42.14	60.00	-17.86
<b>EUT in Continuous Receive Mode on Channel 6 (2.437 GHz)</b>											
3249.33	50.33	100	225			43.08	3.91	30.45	41.60	80.00	-38.40
3249.33				41.48	A	43.08	3.91	30.45	32.75	60.00	-27.25
6498.69	58.00	100	135			43.84	5.78	36.90	56.83	80.00	-23.17
6498.69				54.04	A	43.84	5.78	36.90	52.87	60.00	-7.13
9748.03	50.67	125	135			43.25	6.99	39.15	53.55	80.00	-26.45
9748.03				39.58	A	43.25	6.99	39.15	42.46	60.00	-17.54
<b>EUT in Continuous Receive Mode on Channel 11 (2.462 GHz)</b>											
3282.67	49.83	125	225			43.10	3.91	30.46	41.10	80.00	-38.90
3282.67				40.38	A	43.10	3.91	30.46	31.65	60.00	-28.35
6565.34	57.00	100	135			43.84	5.83	37.38	56.37	80.00	-23.63
6565.34				54.19	A	43.84	5.83	37.38	53.56	60.00	-6.44
9848.04	50.83	125	135			43.29	7.03	39.33	53.90	80.00	-26.10
9848.04				39.73	A	43.29	7.03	39.33	42.80	60.00	-17.20



AEGIS LABS INC.

## PEAK TRANSMIT POWER

<b>CLIENT:</b>	Intel Corporation	<b>DATE:</b>	06/03/04
<b>EUT:</b>	Intel PRO/Wireless 2915ABG Network Connection	<b>PROJECT NUMBER:</b>	INTEL-040412-135
<b>MODEL NUMBER:</b>	WM3B2915ABG	<b>TEST ENGINEER:</b>	JC
<b>SERIAL NUMBER:</b>	26E5FE224ABC51962011	<b>SITE #:</b>	2
<b>CONFIGURATION:</b>	Tested installed in the Hewlett Packard host computer's mini PCI slot.	<b>TEMPERATURE:</b>	31 C
		<b>HUMIDITY:</b>	33% RH
		<b>TIME:</b>	3:30 PM

<b>Standard:</b>	FCC CFR 47, Part 15.247(b)(1)
<b>Description:</b>	The maximum peak output power of the intentional radiator shall not exceed 1 watt.
<b>Results:</b>	See Data Sheet

Peak Transmit Power Limits	
Frequency (MHz)	Output Power (W)
5725-5850	1
2412-2462	1

Page 37 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

### Peak Transmit Power (Continued)

Mode	Channel	Frequency (MHz)	Rate (Mbps)	Average Power (dBm)	Average Power (mW)	Peak Power (dBm)	Peak Power (mW)
802.11a	149	5745	6	17.10	51.29	22.90	194.98
802.11a	157	5785	6	17.05	50.70	23.10	204.17
802.11a	165	5825	6	17.15	51.88	23.20	208.93
802.11b	1	2412	1	15.05	31.99	17.40	54.95
802.11b	6	2437	1	16.80	47.86	18.95	78.52
802.11b	11	2462	1	17.10	51.29	19.20	83.18
802.11g	1	2412	6	15.40	34.67	24.00	251.19
802.11g	6	2437	6	15.30	33.88	23.80	239.88
802.11g	11	2462	6	15.35	34.28	23.90	245.47

NOTE: The output power measurement is conducted.





AEGIS LABS INC.

## 6 dB EMISSIONS BANDWIDTH

<b>CLIENT:</b>	Intel Corporation	<b>DATE:</b>	06/09/04
<b>EUT:</b>	Intel PRO/Wireless 2915ABG Network Connection	<b>PROJECT NUMBER:</b>	INTEL-040412
<b>MODEL NUMBER:</b>	WM3B2915ABG	<b>TEST ENGINEER:</b>	JC
<b>SERIAL NUMBER:</b>	26E5FE224ABC51962011	<b>SITE #:</b>	2
<b>CONFIGURATION:</b>	Tested installed in the Hewlett Packard host computer's mini PCI slot.	<b>TEMPERATURE:</b>	22 C
		<b>HUMIDITY:</b>	50% RH
		<b>TIME:</b>	9:50 AM

<b>Standard:</b>	FCC CFR 47, Part 15.247(a)(2)
<b>Description:</b>	The minimum 6 dB bandwidth shall be at least 500 kHz.
<b>Results:</b>	See Data Sheets



Page 39 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

6 dB Emissions Bandwidth (Continued)

802.11a Mode






AEGIS LABS INC.

### 6 dB Emissions Bandwidth (Continued)

#### 802.11a Mode





AEGIS LABS INC.

### 6 dB Emissions Bandwidth (Continued)

#### 802.11b Mode


Test Date	Data	Test Eng.
06/09/04	2.412 GHz (INTEL-040412-140a1)	JC
<p>*ATTEN 30dB                    ΔMKR 0dB RL 20.0dBm                    10dB/                    7.75MHz</p> <p>CENTER 2.41200GHz                    SPAN 50.00MHz *RBW 100kHz                    *VBW 300kHz                    SWP 50.0ms</p>		
Test Date	Data	Test Eng.
06/09/04	2.437 GHz (INTEL-040412-140a2)	JC
<p>*ATTEN 30dB                    ΔMKR -.17dB RL 20.0dBm                    10dB/                    7.83MHz</p> <p>CENTER 2.43700GHz                    SPAN 50.00MHz *RBW 100kHz                    *VBW 300kHz                    SWP 50.0ms</p>		



AEGIS LABS INC.

### 6 dB Emissions Bandwidth (Continued)

#### 802.11b Mode







AEGIS LABS INC.

### 6 dB Emissions Bandwidth (Continued)

#### 802.11g Mode




Page 44 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

### 6 dB Emissions Bandwidth (Continued)

#### 802.11g Mode





AEGIS LABS INC.

## PEAK POWER SPECTRAL DENSITY

<b>CLIENT:</b>	Intel Corporation	<b>DATE:</b>	06/09/04
<b>EUT:</b>	Intel PRO/Wireless 2915ABG Network Connection	<b>PROJECT NUMBER:</b>	INTEL-040412
<b>MODEL NUMBER:</b>	WM3B2915ABG	<b>TEST ENGINEER:</b>	JC
<b>SERIAL NUMBER:</b>	26E5FE224ABC51962011	<b>SITE #:</b>	2
<b>CONFIGURATION:</b>	Tested installed in the Hewlett Packard host computer's mini PCI slot.	<b>TEMPERATURE:</b>	22 C
		<b>HUMIDITY:</b>	50% RH
		<b>TIME:</b>	9:30 AM

<b>Standard:</b>	FCC CFR 47, Part 15.247(d)
<b>Description:</b>	The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
<b>Results:</b>	See Data Sheets

Peak Power Spectral Density Limits	
Frequency (MHz)	Limit (dBm)
5725-5850	8
2412-2462	8

Page 46 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG







AEGIS LABS INC.

### Peak Power Spectral Density (Continued)

**802.11a Mode**




Page 47 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

### Peak Power Spectral Density (Continued)

#### 802.11a Mode





AEGIS LABS INC.

### Peak Power Spectral Density (Continued)

#### 802.11b Mode


Test Date	Data	Test Eng.
06/09/04	2.412 GHz (INTEL-040412-140c1)	JC
<p>*ATTEN 20dB                      MKR -6.17dBm RL 10.0dBm                      10dB/                      2.412505GHz</p> <p>CENTER 2.412000GHz                      SPAN 1.500MHz *RBW 3.0kHz                      *VBW 3.0kHz                      *SWP 500sec</p>		
Test Date	Data	Test Eng.
06/09/04	2.437 GHz (INTEL-040412-140c2)	JC
<p>*ATTEN 20dB                      MKR -6.67dBm RL 10.0dBm                      10dB/                      2.436505GHz</p> <p>CENTER 2.437000GHz                      SPAN 1.500MHz *RBW 3.0kHz                      *VBW 3.0kHz                      *SWP 500sec</p>		



AEGIS LABS inc.

Peak Power Spectral Density (Continued)



802.11b Mode





Peak Power Spectral Density (Continued)


802.11g Mode





Peak Power Spectral Density (Continued)

802.11g Mode





AEGIS LABS INC.

## CONDUCTED OUT OF BAND EMISSIONS

<b>CLIENT:</b>	Intel Corporation	<b>DATE:</b>	06/09/04
<b>EUT:</b>	Intel PRO/Wireless 2915ABG Network Connection	<b>PROJECT NUMBER:</b>	INTEL-040412
<b>MODEL NUMBER:</b>	WM3B2915ABG	<b>TEST ENGINEER:</b>	JC
<b>SERIAL NUMBER:</b>	26E5FE224ABC51962011	<b>SITE #:</b>	2
<b>CONFIGURATION:</b>	Tested installed in the Hewlett Packard host computer's mini PCI slot.	<b>TEMPERATURE:</b>	20 C
		<b>HUMIDITY:</b>	60% RH
		<b>TIME:</b>	12:00 PM

<b>Standard:</b>	FCC CFR 47, Part 15.247(c)
<b>Description:</b>	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

Page 53 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11a Mode

Test Date	Data	Test Eng.
06/09/04	5.745 GHz (INTEL-040412-146d01)	JC
<p>*ATTEN 20dB                      MKR -65.00dBm  RL 10.0dBm                      10dB/                      846.4MHz</p> <p>START 30.0MHz                      STOP 1.0000GHz  *RBW 100kHz                      *VBW 300kHz                      SWP 540ms</p>		
Test Date	Data	Test Eng.
06/09/04	5.745 GHz (INTEL-040412-146d02)	JC
<p>*ATTEN 20dB                      MKR -44.17dBm  RL 10.0dBm                      10dB/                      3.827GHz</p> <p>START 1.000GHz                      STOP 5.000GHz  *RBW 100kHz                      *VBW 300kHz                      SWP 2.20sec</p>		







AEGIS LABS INC.

### Conducted Out Of Band Emissions (Continued)

#### 802.11a Mode

<i>Test Date</i>	<i>Data</i>	<i>Test Eng.</i>
06/09/04	5.745 GHz (INTEL-040412-146d03)	JC
<p>*ATTEN 20dB                                  MKR -38.33dBm RL 10.0dBm                                  10dB/                                  5.500GHz</p>  <p>START 5.000GHz                                  STOP 10.000GHz *RBW 100kHz                                  *VBW 300kHz                                  SWP 2.80sec</p>		
<i>Test Date</i>	<i>Data</i>	<i>Test Eng.</i>
06/09/04	5.745 GHz (INTEL-040412-146d04)	JC
<p>*ATTEN 20dB                                  MKR -54.17dBm RL 10.0dBm                                  10dB/                                  11.48GHz</p>  <p>START 10.00GHz                                  STOP 20.00GHz *RBW 100kHz                                  *VBW 300kHz                                  SWP 5.50sec</p>		



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11a Mode

Test Date	Data	Test Eng.
06/09/04	5.745 GHz (INTEL-040412-146d05)	JC
<p>*ATTEN 20dB                                    MKR -52.50dBm            RL 10.0dBm                                10dB/                                36.57GHz</p> <p>START 20.00GHz                                STOP 40.00GHz            *RBW 100kHz                                *VBW 300kHz                                SWP 11.0sec</p>		
Test Date	Data	Test Eng.
06/09/04	5.785 GHz (INTEL-040412-146d06)	JC
<p>*ATTEN 20dB                                    MKR -65.50dBm            RL 10.0dBm                                10dB/                                377.6MHz</p> <p>START 30.0MHz                                    STOP 1.0000GHz            *RBW 100kHz                                *VBW 300kHz                                SWP 540ms</p>		



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11a Mode



Test Date	Data	Test Eng.
06/09/04	5.785 GHz (INTEL-040412-146d07)	JC
<p>*ATTEN 20dB                      MKR -41.67dBm RL 10.0dBm                      10dB/                      3.853GHz</p> <p>START 1.000GHz                      STOP 5.000GHz *RBW 100kHz                      *VBW 300kHz                      SWP 2.20sec</p>		
Test Date	Data	Test Eng.
06/09/04	5.785 GHz (INTEL-040412-146d08)	JC
<p>*ATTEN 20dB                      MKR -42.83dBm RL 10.0dBm                      10dB/                      5.542GHz</p> <p>START 5.000GHz                      STOP 10.000GHz *RBW 100kHz                      *VBW 300kHz                      SWP 2.80sec</p>		



AEGIS LABS INC.

### Conducted Out Of Band Emissions (Continued)

#### 802.11a Mode







AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)



802.11a Mode





Conducted Out Of Band Emissions (Continued)

802.11a Mode


Test Date	Data	Test Eng.
06/09/04	5.825 GHz (INTEL-040412-146d13)	JC
<p>*ATTEN 20dB                      MKR -41.83dBm RL 10.0dBm                      10dB/                      5.500GHz</p>  <p>START 5.000GHz                      STOP 10.000GHz *RBW 100kHz                      *VBW 300kHz                      SWP 2.80sec</p>		
Test Date	Data	Test Eng.
06/09/04	5.825 GHz (INTEL-040412-146d14)	JC
<p>*ATTEN 20dB                      MKR -55.67dBm RL 10.0dBm                      10dB/                      11.63GHz</p>  <p>START 10.00GHz                      STOP 20.00GHz *RBW 100kHz                      *VBW 300kHz                      SWP 5.50sec</p>		



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11a Mode







AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode



Page 62 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG







AEGIS LABS INC.

### Conducted Out Of Band Emissions (Continued)

#### 802.11b Mode



Page 63 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG




AEGIS LABS INC.


Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
06/09/04	2.437 GHz (INTEL-040412-140d05)	JC



Test Date	Data	Test Eng.
06/09/04	2.437 GHz (INTEL-040412-140d06)	JC





Page 64 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode





Page 65 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

### Conducted Out Of Band Emissions (Continued)

#### 802.11b Mode





Page 66 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode





Page 67 of 73 (Appendix A)  
 Report Number: INTEL-040412F  
 FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode







AEGIS LABS INC.

### Conducted Out Of Band Emissions (Continued)

#### 802.11g Mode





Page 69 of 73 (Appendix A)  
 Report Number: INTEL-040412F  
 FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

**802.11g Mode**



Page 70 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG







AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode





Page 71 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode



Page 72 of 73 (Appendix A)  
Report Number: INTEL-040412F  
FCC ID: PD9WM3B2915ABG



AEGIS LABS INC.

### Conducted Out Of Band Emissions (Continued)

#### 802.11g Mode

