

## MPE Analysis Report

The Equipment-Under-Test (EUT) PULSE 2 is an All-In-One Compact Wireless Streaming Music System. The EUT contains both WLAN (WiFi) and Bluetooth modules. The Bluetooth module has Bluetooth 4.0 BLE and Bluetooth 3.0 features. The EUT can accept analog audio signal, digital audio signal and wireless audio signal via Bluetooth devices. An iOS/Android apps Bluesound installed in Smartphone can act as the remote control of the EUT. The EUT has internal power amplifiers and loudspeaker. It is powered by 100-240VAC.

### WiFi Module

Antenna Type: Internal, Integral

Antenna Gain: 2dBi

Operating mode	Nominal Conducted Power	Production Tolerance	Modulation Type
802.11b	12.86 dBm	+/- 3dB	DSSS
802.11g	11.88 dBm	+/- 3dB	OFDM
802.11n (HT20)	9.56 dBm	+/- 3dB	mcs0
802.11n (HT40)	6.96 dBm	+/- 3dB	mcs0

### Bluetooth Module

Antenna Type: Internal, Integral

Antenna Gain: 2dBi

Operating mode	Nominal Conducted	Production Tolerance	Modulation Type
Bluetooth 4.0 BLE	6.84 dBm	+/- 3dB	GFSK

Operating mode	Nominal Radiated Field Strength	Production Tolerance	Modulation Type
Bluetooth 3.0	98.8 dB $\mu$ V/m at 3m	+/- 3dB	GFSK

## INTERTEK TESTING SERVICE

---

For Maximum Permissible Exposure (MPE) evaluation of the PULSE 2, the maximum power density at 20 cm from this mobile transmitter shall be less than the General Population / Uncontrolled MPE limit in OET Bulletin 65.

1) For the WLAN (WiFi), maximum conducted power measured within its production tolerance was 16.68dBm (maximum). The antenna gain is 2 dBi = 1.58 (num gain) and the maximum source-based time-averaging duty factor is 100%. From these data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

$$\text{The conducted power} = 15.86\text{dBm} \quad (38.55\text{mW})$$

$$\begin{aligned} \text{The radiated (EIRP) source-based time-averaging output power (with antenna gain)} \\ &= (38.55 * 1 * 1.58) \text{ mW} \\ &= 60.9 \text{ mW} \end{aligned}$$

$$\begin{aligned} \text{The power density at 20 cm from the antenna} \\ &= \text{EIRP} / 4\pi R^2 \\ &= 0.012 \text{ mW cm}^{-2} \end{aligned}$$

2) For the Bluetooth 4.0 BLE, maximum conducted power measured within its production tolerance was 9.98dBm (maximum). The antenna gain is 2 dBi = 1.58 (num gain) and the maximum source-based time-averaging duty factor is 100%. From these data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

$$\text{The conducted power} = 9.84\text{dBm} \quad (9.64\text{mW})$$

$$\begin{aligned} \text{The radiated (EIRP) source-based time-averaging output power (with antenna gain)} \\ &= (9.64 * 1 * 1.58) \text{ mW} \\ &= 15.2 \text{ mW} \end{aligned}$$

$$\begin{aligned} \text{The power density at 20 cm from the antenna} \\ &= \text{EIRP} / 4\pi R^2 \\ &= 0.003 \text{ mW cm}^{-2} \end{aligned}$$

3) For the Bluetooth 3.0, maximum field strength measured within its production tolerance (FS) was 101.8 dB $\mu$ V/m (maximum). The distance (D) between the antenna and the equipment under test (EUT) was 3 meters. And the maximum source-based time-averaging duty factor is 100%. From these data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

$$\text{The radiated power} = (\text{FS} * \text{D})^2 / 30 = 4.5 \text{ mW}$$

$$\begin{aligned} \text{The radiated (EIRP) source-based time-averaging output power} \\ &= (4.5 * 1) \text{ mW} \\ &= 4.5 \text{ mW} \end{aligned}$$

$$\begin{aligned} \text{The power density at 20 cm from the antenna} \\ &= \text{EIRP} / 4\pi R^2 \\ &= 0.0009 \text{ mW cm}^{-2} \end{aligned}$$

In the frequency range of 1,500 - 100,000MHz, the MPE limit is 1.0 mWcm<sup>-2</sup> for general population and uncontrolled exposure. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structures and body of the user or nearby persons. The following RF exposure statement is proposed to be included in the user manual:

**“ FCC RF Radiation Exposure Statement**

**Caution: To maintain compliance with the FCC’s RF exposure guidelines, place the product at least 20cm from nearby persons.”**

In addition, for this product with multiple transmitter and antenna (Bluetooth and WiFi), the requirement of Simultaneous Transmission evaluation has also been considered and has complied with the following conditions of the worse case;

$$MPE1/Limit1 + MPE2/Limit2 \leq 1$$

Thus,

$$\begin{array}{l} 0.012 / 1 + 0.003 / 1 \\ \text{WiFi} \quad \quad \text{Bluetooth 4.0 BLE} \end{array} = 0.015 \leq 1$$

It is concluded that no Simultaneous Transmission evaluation is required.