

TEST REPORT

Report No.: HK09061564-1

Clarion (M) Sdn Bhd

Application
For
Certification
(Original Grant)
(FCC ID: Q2ZFZ709)
(IC: 419D-FZ709)

Transceiver

Prepared and Checked by:



Norton Yuen/sl
Lead Engineer

Approved by:



Ho Wai Kin, Ben
Senior Supervisor
Date: Aug 04, 2009

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

INTERTEK TESTING SERVICES

GENERAL INFORMATION

Clarion (M) Sdn Bhd
BRAND NAME: Clarion, MODEL: FZ709

FCC ID: Q2ZFZ709
IC: 419D-FZ709

Grantee:	Clarion (M) Sdn Bhd
Grantee Address:	Phase 3, FIZ, 11400 Bayan Lepas, Malaysia.
Contact Person:	Mr. Tomonori Kume
Tel:	604 614 8400
Fax:	604 641 4324
e-mail:	tomonori_kume@clarion.com.my
Manufacturer:	Clarion (M) Sdn Bhd
Manufacturer Address:	Phase 3, FIZ, 11400 Bayan Lepas, Malaysia.
Brand Name:	Clarion
Model:	FZ709
Type of EUT:	Transceiver
Description of EUT:	Car Stereo with FM/USB/MP3/Bluetooth/ Hands Free combination
Serial Number:	N/A
FCC ID / IC:	Q2ZFZ709 / 419D-FZ709
Date of Sample Submitted:	June 30, 2009
Date of Test:	July 15, 2009
Report No.:	HK09061564-1
Report Date:	Aug 04, 2009
Environmental Conidtions:	Temperature: +10 to 40°C Humidity: 10 to 90%

INTERTEK TESTING SERVICES

SUMMARY OF TEST RESULT

Clarion (M) Sdn Bhd
BRAND NAME: Clarion, MODEL: FZ709

FCC ID: Q2ZFZ709
IC: 419D-FZ709

TEST SPECIFICATION	REFERENCE	RESULTS
Maximum Peak Output Power	15.247(b), (c) / RSS-210 A8.4	N/A
Hopping Channel Carrier Frequencies Separation	15.247(e) / RSS-210 A8.1	N/A
20dB Bandwidth of the Hopping Channel	15.247(a) / RSS-210 A8.1	N/A
Number of Hopping Frequencies	15.247(e) / RSS-210 A8.1	N/A
Average Time of Occupancy of Hopping Frequency	15.247(e) / RSS-210 A8.1	N/A
Antenn Conducted Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
Radiated Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
Transmitter Power Line Conducted Emissions	15.207 / RSS-Gen 7.2.2	N/A
Transmitter Field Strength	15.227 / RSS-310 3.8	N/A
Transmitter Field Strength	15.229 / RSS-210 A2.7	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(a) / RSS-210 A1.1.1	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(e) / RSS-210 A1.1.5	N/A
Transmitter Field Strength and Bandwidth Requirement	15.239 / RSS-210 A2.8	N/A
Transmitter Field Strength and Bandwidth Requirement	15.249 / RSS-210 A2.9	Pass
Transmitter Field Strength and Bandwidth Requirement	15.235 / RSS-310 3.9	N/A
Receiver Radiated Emissions	RSS-210 2.7	Pass
Digital Device Conducted Emissions	15.107 / ICES-003	N/A

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

INTERTEK TESTING SERVICES

Table of Contents

1.0	<u>General Description</u>	1
1.1	Product Description	1
1.2	Related Submittal(s) Grants.....	1
1.3	Test Methodology.....	1
1.4	Test Facility	1
2.0	<u>System Test Configuration</u>	2
2.1	Justification	2
2.2	EUT Exercising Software.....	2
2.3	Special Accessories	2
2.4	Equipment Modification	2
2.5	Measurement Uncertainty.....	2
2.6	Support Equipment List and Description	3
3.0	<u>Emission Results</u>	3
3.1	Field Strength Calculation.....	3
3.2	Radiated Emission Configuration Photograph.....	4
3.3	Radiated Emission Data	4
4.0	<u>Equipment Photographs</u>	11
5.0	<u>Product Labelling</u>	11
6.0	<u>Technical Specifications</u>	11
7.0	<u>Instruction Manual</u>	11
8.0	<u>Miscellaneous Information</u>	11
8.1	Measured Bandwidth / RF Output Signal	11
8.2	Discussion Pulse Desensitivity	12
8.3	Calculation of Average Factor.....	12
8.4	Emissions Test Procedures	12
9.0	<u>Confidentiality Request</u>	14
10.0	<u>Equipment List</u>	14

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The Equipment Under Test (EUT) is a Car Audio System with Bluetooth operating at 2402 - 2480 MHz. The EUT is powered by 12.0VDC. The EUT can read USB flash drive, iPod and has an AM/FM receiver. The EUT also has a Bluetooth function which allows mobile phone and music player connection.

Antenna Type : Internal, Integral

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

This is a single application for certification of a transceiver.

1.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.4 (2003). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC and IC.

INTERTEK TESTING SERVICES

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2003).

The device was powered from 12.0VDC.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

USB flash drive and microphone are used during the test.

2.4 Equipment Modification

Any modifications installed previous to testing by Clarion (M) Sdn Bhd will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

INTERTEK TESTING SERVICES

2.6 Support Equipment List and Description

1. 12VDC Power Supply
2. Agilent Bluetooth Tester (E1852A)

3.0 **Emission Results**

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where FS = Field Strength in dB μ V/m
 RA = Receiver Amplitude (including preamplifier) in dB μ V
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB
 AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where FS = Field Strength in dB μ V/m
 RR = RA - AG - AV in dB μ V
 LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$\begin{aligned} RA &= 52.0 \text{ dB}\mu\text{V/m} & RR &= 18.0 \text{ dB}\mu\text{V} \\ AF &= 7.4 \text{ dB} & LF &= 9.0 \text{ dB} \\ CF &= 1.6 \text{ dB} \\ AG &= 29.0 \text{ dB} \\ AV &= 5.0 \text{ dB} \\ FS &= RR + LF \\ FS &= 18 + 9 = 27 \text{ dB}\mu\text{V/m} \end{aligned}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 4804.000 MHz (Tx)
2402.000 MHz (Rx)

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 20.4 dB (Tx)
13.1 dB (Rx)

INTERTEK TESTING SERVICES

Applicant: Clarion (M) Sdn Bhd

Date of Test: July 15, 2009

Model: FZ709

Worst-Case Operating Mode: Bluetooth (Tx)

Table 1

Radiated Emissions

Channel 0

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
V	2402.000	96.6	33	29.4	43.9	49.1	94.0	-44.9
V	4804.000	51.7	33	34.9	43.9	9.7	54.0	-44.3
H	7206.000	45.5	33	37.9	43.9	6.5	54.0	-47.5
H	9608.000	42.8	33	40.4	43.9	6.3	54.0	-47.7
H	12010.000	42.1	33	40.5	43.9	5.7	54.0	-48.3
H	14412.000	42.2	33	40.0	43.9	5.3	54.0	-48.7

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
V	2402.000	96.6	33	29.4	93.0	114.0	-21.0
V	4804.000	51.7	33	34.9	53.6	74.0	-20.4
H	7206.000	45.5	33	37.9	50.4	74.0	-23.6
H	9608.000	42.8	33	40.4	50.2	74.0	-23.8
H	12010.000	42.1	33	40.5	49.6	74.0	-24.4
H	14412.000	42.2	33	40.0	49.2	74.0	-24.8

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

Report No.: HK09061564-1

FCC ID: Q2ZFZ709

IC: 419D-FZ709

INTERTEK TESTING SERVICES

Applicant: Clarion (M) Sdn Bhd

Date of Test: July 15, 2009

Model: FZ709

Worst-Case Operating Mode: Bluetooth (Tx)

Table 2

Radiated Emissions

Channel 38

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
V	2440.000	96.4	33	29.4	43.9	48.9	94.0	-45.1
V	4880.000	51.5	33	34.9	43.9	9.5	54.0	-44.5
H	7320.000	45.7	33	37.9	43.9	6.7	54.0	-47.3
H	9760.000	42.8	33	40.4	43.9	6.3	54.0	-47.7
H	12200.000	42.3	33	40.5	43.9	5.9	54.0	-48.1
H	14640.000	44.2	33	38.4	43.9	5.7	54.0	-48.3

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
V	2440.000	96.4	33	29.4	92.8	114.0	-21.2
V	4880.000	51.5	33	34.9	53.4	74.0	-20.6
H	7320.000	45.7	33	37.9	50.6	74.0	-23.4
H	9760.000	42.8	33	40.4	50.2	74.0	-23.8
H	12200.000	42.3	33	40.5	49.8	74.0	-24.2
H	14640.000	44.2	33	38.4	49.6	74.0	-24.4

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

Report No.: HK09061564-1

FCC ID: Q2ZFZ709

IC: 419D-FZ709

INTERTEK TESTING SERVICES

Applicant: Clarion (M) Sdn Bhd

Date of Test: July 15, 2009

Model: FZ709

Worst-Case Operating Mode: Bluetooth (Tx)

Table 3

Radiated Emissions

Channel 78

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Average Factor (-dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
V	2480.000	96.0	33	29.4	43.9	48.5	94.0	-45.5
V	4960.000	51.3	33	34.9	43.9	9.3	54.0	-44.7
H	7440.000	45.3	33	37.9	43.9	6.3	54.0	-47.7
H	9920.000	42.6	33	40.4	43.9	6.1	54.0	-47.9
H	12400.000	41.9	33	40.5	43.9	5.5	54.0	-48.5
H	14880.000	43.8	33	38.4	43.9	5.3	54.0	-48.7

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
V	2480.000	96.0	33	29.4	92.4	114.0	-21.6
V	4960.000	51.3	33	34.9	53.2	74.0	-20.8
H	7440.000	45.3	33	37.9	50.2	74.0	-23.8
H	9920.000	42.6	33	40.4	50.0	74.0	-24.0
H	12400.000	41.9	33	40.5	49.4	74.0	-24.6
H	14880.000	43.8	33	38.4	49.2	74.0	-24.8

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

Report No.: HK09061564-1

FCC ID: Q2ZFZ709

IC: 419D-FZ709

INTERTEK TESTING SERVICES

Applicant: Clarion (M) Sdn Bhd

Date of Test: July 15, 2009

Model: FZ709

Worst-Case Operating Mode: Bluetooth (Rx)

Table 4

Radiated Emissions

Channel 0

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	1201.000	43.8	33	29.4	40.2	54.0	-13.8
V	2402.000	39.0	33	34.9	40.9	54.0	-13.1
H	3603.000	35.1	33	37.9	40.0	54.0	-14.0
H	4804.000	32.4	33	40.4	39.8	54.0	-14.2
H	6005.000	31.9	33	40.5	39.4	54.0	-14.6
H	7206.000	33.6	33	38.4	39.0	54.0	-15.0

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: Clarion (M) Sdn Bhd

Date of Test: July 15, 2009

Model: FZ709

Worst-Case Operating Mode: Bluetooth (Rx)

Table 5

Radiated Emissions

Channel 38

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	1220.000	43.8	33	29.4	40.2	54.0	-13.8
V	2440.000	38.9	33	34.9	40.8	54.0	-13.2
H	3660.000	35.1	33	37.9	40.0	54.0	-14.0
H	4880.000	32.4	33	40.4	39.8	54.0	-14.2
H	6100.000	31.9	33	40.5	39.4	54.0	-14.6
H	7320.000	33.6	33	38.4	39.0	54.0	-15.0

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: Clarion (M) Sdn Bhd

Date of Test: July 15, 2009

Model: FZ709

Worst-Case Operating Mode: Bluetooth (Rx)

Table 6

Radiated Emissions

Channel 78

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-amp Gain (dB)	Antenna Factor (dB)	Calculated at 3m (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
V	1240.000	44.2	33	29.4	40.6	54.0	-13.4
V	2480.000	38.9	33	34.9	40.8	54.0	-13.2
H	3720.000	35.5	33	37.9	40.4	54.0	-13.6
H	4960.000	32.2	33	40.4	39.6	54.0	-14.4
H	6200.000	31.9	33	40.5	39.4	54.0	-14.6
H	7440.000	33.1	33	38.4	38.5	54.0	-15.5

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

4.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 Product Labelling

For electronics filing, the FCC ID and IC label artwork and the label location are saved with filename: label.pdf.

6.0 Technical Specifications

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States and Canada.

8.0 Miscellaneous Information

The miscellaneous information includes details of the test procedure and measured bandwidth / calculation of factor such as pulse desensitization and averaging factor (calculation and timing diagram).

8.1 Measured Bandwidth

For electronic filing, the plot shows the fundamental emission when modulated is saved With filename: be.pdf. From the plot, the field strength of any emissions outside of the specified frequency band is attenuated to the general radiated emission limits in Section 15.209. It fulfills the requirement of 15.249(d).

Peak Measurement

Bandedge compliance is determined by applying marker-delta method, i.e. (bandedge Plot A and Plot B).

INTERTEK TESTING SERVICES

Resultant field strength = Fundamental emissions (peak value) – data from the plot A
= 93.00dB μ V/m – 36.36dB μ V/m
= 56.64dB μ V/m

Resultant field strength = Fundamental emissions (peak value) – delta from the plot A - Average Factor
= 93.00dB μ V/m – 36.36dB μ V/m – 43.90dB μ V/m
= 12.74dB μ V/m

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74dB μ V/m (Peak Limit) and 54dB μ V/m (Average Limit).

8.2 Discussion Pulse Desensitvity

Pulse desnesitivity is not applicable for this device. The effective period (Teff) is approximately 625 μ s for a ditital “1” bit which illustrated on technical specification, with a resolution bandwidth (3dB) of 1MHz, so the pulse densensitivity factor is 0dB.

8.3 Calculation of Average Factor

Based on the Bluetooth Specification Version 2.0 + EDR, transmitter ON time is independent of the packet type (DH1, DH3 and DH5) and packet length (single-slot and multi-slot). The maximum transmitter ON time for the Bluetooth is 625 μ s.

Each TX and RX time slot is 625 μ s in length. A TDD scheme is used where master and slave alternately transmit. For one period for a pseudo-random hopping through all 79 RF channels, it takes: 79 x (0.625 x 2) ms = 98.75ms.

Therefore,

$$\begin{aligned}\text{Average Factor (AF) of Bluetooth in dB} &= 20\log_{10}(0.625/98.75)\text{dB} \\ &= 20\log_{10}(0.00633) \text{ dB} \\ &= -43.9 \text{ dB}\end{aligned}$$

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 2003. A typical or an unmodulated CW signal at the operating frequency of the EUT has been supplied to the EUT for all measurements. Such a signal is supplied by a signal generator and an

INTERTEK TESTING SERVICES

antenna in close proximity to the EUT. The signal level is sufficient to stabilize the local oscillator of the EUT.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

8.4 Emissions Test Procedures (cont'd)

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 - 2003.

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

INTERTEK TESTING SERVICES

9.0 Confidentiality Request

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

10.0 Equipment List

1) Radiated Emissions Test

Equipment	EMI Test Receiver	Biconical Antenna	Log Periodic Antenna
Registration No.	EW-0014	EW-0954	EW-0446
Manufacturer	R&S	EMCO	EMCO
Model No.	ESVS30	3104C	3146
Calibration Date	Jun. 01, 2009	Sep. 30, 2008	Oct. 02, 2008
Calibration Due Date	Jun. 01, 2010	Mar. 30, 2010	Apr. 02, 2010