

DATE: 11 November 2003

I.T.L. (PRODUCT TESTING) LTD.

EMC Test

for

Bluesoft Inc.

Equipment under test:

AeroScout™ Tag

(For Transmitter Section)

BWH2000-02

Approved by: _____

I. Raz, EMC Laboratory Manager

This report must not be reproduced, except in full, without the written permission of I.T.L. (Product Testing) Ltd.

This report relates only to items tested.

12. Transmitted Power Density

[In accordance with section 15.247(d)]

12.1 Test procedure

The E.U.T. antenna terminal was connected to the spectrum analyzer through an appropriate coaxial cable. The spectrum analyzer was set to 3 kHz resolution BW, 10 kHz video BW and sweep time of 1 second for each 3 kHz “window”. The spectrum peaks were located at each of the 3 operating frequencies.




Figure 60 —2412 MHz

12:51:46 NOV 11, 2003

ACTV DET: PEAK
 MEAS DET: PEAK QP AVG
 MKR 2.4419828 GHz
 -12.58 dBm




Figure 61 —2442 MHz

13:05:35 NOV 11, 2003

ACTV DET: PEAK
 MEAS DET: PEAK QP AVG
 MKR 2.4619828 GHz
 -12.74 dBm




Figure 62 —2462 MHz

12.2 Results table

E.U.T. Description: AeroScout™ TAG
 Model No.: BWH2000-02
 Serial Number: 110-1000-4101
 Specification: F.C.C. Part 15, Subpart C (15.247)

Operation Frequency (MHz)	Reading (dBm)	Final Result (dBm)	Specification (dBm)	Margin (dB)	Cable Attenuation (dB)
2412	-12.9	-9.5	8.0	-17.5	3.4
2442	-12.6	-9.2	8.0	-17.2	3.4
2462	-12.7	-9.3	8.0	-17.3	3.4

Figure 1 Test Equipment Used

JUDGEMENT: Passed by 17.2 dB

TEST PERSONNEL:

Tester Signature:  Date: 11.11.03
 Typed/Printed Name: Y. Mordukhovitch

1.1 Test Equipment Used.

Transmitted Power Density

Instrument	Manufacture	Model	Serial Number	Calibration	
				Last Calibr.	Period
Spectrum Analyzer	HP	8542E	3411A00102	31.01.03	1 year

Figure 2 Test Equipment Used