



Date: 3 January 2022

To: Federal Communications Commission

Subject: LMA Cover Letter

This letter introduces AeroScout's request to approve its module model: TAG-2200B, FCC ID: Q3HTAGB1200 according to FCC Limited Modular Approval procedure, and to demonstrate the means to control the module as required by the LMA procedure.

The TAG-2200B BLE Asset Tag is a component of AeroScout's BLE Platform. The tag supports BLE 5.0 and is easily and quickly activated using its pushbutton.

This model is not sold separately, nor it is installed in any unit other than AeroScout's products. The module is currently used in the following hosts:

TAG2200B-F, WGB-TAG-1000-XYZ, WGB-TAG-2ABC-XYZ

Due to the above mentioned and the fact that AeroScout has full control on the sales and installation of the module, complete compliance with FCC LMA is assured.

Thank you,

Signature:

A handwritten signature in blue ink, appearing to read "Reuven Amsalem".

Reuven Amsalem
VP HW R&D



As per § 15.212 Modular transmitters: Single modular transmitters must meet the following requirements to obtain a modular transmitter approval.

Requirement	Not Maintained	Maintained
(1) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	X	
(2) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.		X
(3) The modular transmitter must have its own power supply regulation.		X
(4) The modular transmitter must comply with the antenna and transmission system requirements of §§15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a “unique” antenna coupler (at all connections between the module and the antenna, including the cable). The “professional installation” provision of §15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.		X

Requirement	Not Maintained	Maintained
(5) The modular transmitter must be tested in a stand-alone configuration, <i>i.e.</i> , the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in §15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see §15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see §15.31(i)).		X
(6) The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number.		X
(7) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.		X
(8) The modular transmitter must comply with any applicable RF exposure requirements in its final configuration.		X