

Company: Radwin Ltd

Test of: AP0158770 Wireless Module

To: FCC CFR 47 Part 15 Subpart E 15.407
Industry Canada RSS-247 Issue 1

Report No.: RDWN39-U3a MPE Rev A

MPE TEST REPORT



MPE TEST REPORT

FROM



Test of: Radwin Ltd. AP0158770
to

To: FCC CFR 47 Part 15 Subpart E 15.407
Industry Canada RSS-247 Issue 1

Test Report Serial No.: RDWN39-U3a MPE Rev A

This report supersedes: NONE

Applicant: Radwin
27 Habarzel Street
Tel Aviv 69710
Israel

Product Function: 5 GHz Wireless Module

Issue Date: 7th December 2015

This Test Report is Issued Under the Authority of:

MiCOM Labs, Inc.
575 Boulder Court
Pleasanton California 94566
USA
Phone: +1 (925) 462-0304
Fax: +1 (925) 462-0306
www.micomlabs.com



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory



1. MAXIMUM PERMISSABLE EXPOSURE

Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm²) = EIRP/(4*π*d²)

EIRP = P * G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm²

Worst case results for each antenna type 5725-5850 MHz

Antenna Model	Type	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance @ 1mW/cm ² Limit (cm)	Minimum Distance (cm)
RW-9401-5002	Shark Fin Monopole	11.5*	14.13	24.44	278.0	17.7	20.0
RW-9061-5002	Sector Dual Pole 60 Deg	15.5*	35.48	20.41	109.9	17.6	20.0
RW-9622-5001	Flat Panel Dual Pole External	28*	630.96	29.91	979.5	221.8	221.8
RW-9732-4958	Dual Pole Dish	31*	1258.93	29.91	979.5	313.3	313.3
AM0156430	Integrated Smart Flat Panel	20.5	112.2	29.91	979.5	93.5	93.5

* Gain includes 1 dB feeder loss for external antennas

Note: for mobile or fixed location transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.



Title: Radwin Ltd. AP0158770
To: FCC CFR 47 Part 15 Subpart E 15.407
Serial #: RDWN39-U3 Rev A
Issue Date: 7th December 2015
Page: 4 of 5

Specification
Maximum Permissible Exposure Limits

FCC §1.1310 Limit = 1mW / cm² from 1.310 Table 1

RSS-Gen §3.2 In addition to RSS-Gen, the requirements in Radio Standards Specification RSS-102 shall be met.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court
Pleasanton, California 94566, USA
Tel: +1 (925) 462 0304
Fax: +1 (925) 462 0306
www.micomlabs.com